

7260




Box mode #2 – summary

- Required memory speed: 1x 16-bit DDR4-2133
 - High-temperature refresh supported
- Features:
 - Single1920x1080p60/60i decode
 - MTG support
 - UHD display (through up-scaling) and SD display
 - Main only (no PIP)
 - No multi-PIP
 - No HDMI input
 - No transcoding



Possible video routings





Source limitations

- For each source, you may toggle between any of the provided options.
 - Only one option enabled at a given time.
- Decode 0
 - 1920x1080p60/60i 10-bit HEVC / VP9
 - 1920x1080p60/60i 8-bit AVC / MPEG2
 - MTG supported

- Graphics 0 (UHD)
 - 1080p60 32-bit ARGB
- Graphics 1 (SD)
 - 480p60 or 576p50 32-bit ARGB



HARDWARE RESOURCE MAPPING

Decoder	MFD	Hardware
Decode 0	MFD0	HVD0



Window limitations

- Window 0 (MAIN / UHD)
 - Up to full-screen display (smooth scaling)
 - 1080i60 de-interlacing
- Window 1 (MAIN / SD)
 - Up to full-screen display (smooth scaling)



Display and encode limitations

- Display 0 (UHD)
 - 1920x1080p60
 - 3840x2160p60 (through up-scaling)

