


BOX MODE #4

7439 Bx



- **Required memory speed: 2x 32-bit DDR3-2133**
 - No high-temperature refresh support
- **Features:**
 - 3840x2160p60 10-bit decode for MAIN
 - UHD + SD display
 - Dual independent transcoding from 1080p50 HEVC / 1080p25 AVC to 1080p25
 - Source cannot come from display decoder
 - No PIP support
 - No Multi-PIP support
 - No HDMI input support

POSSIBLE VIDEO ROUTINGS



- **For each source, you may toggle between any of the provided options.**
 - Only one option enabled at a given time.
- **Decode 0**
 - 3840x2160p60 10-bit HEVC
 - 3840x2160p60 8-bit VP9
 - 1920x1080p60 8-bit AVC / MPEG
- **Decode 1 (Transcode)**
 - 1920x1080p50 10-bit HEVC
 - 1920x1080p50 8-bit VP9
 - 1920x1080p25 / 50i 8-bit AVC / MPEG
- **Decode 2 (Transcode)**
 - 1920x1080p50 10-bit HEVC
 - 1920x1080p50 8-bit VP9
 - 1920x1080p25 / 50i 8-bit AVC / MPEG
- **Graphics 0 (UHD)**
 - 1080p60 32-bit ARGB
- **Graphics 1 (SD)**
 - 480p60 32-bit ARGB
 - 576p50 32-bit ARGB

Decoder	MFD	Usage	Hardware
Decode 0	MFD0	Display	HVD0
Decode 1	MFD2	Transcode 0	HVD1
Decode 2	MFD3	Transcode 1	HVD1

- **Window 0 (MAIN / UHD)**

- Up to full-screen display (smooth scaling)
- 10-bit support / 1080i60 10-bit de-interlacing

- **Window 1 (MAIN / SD)**

- Up to full-screen display (smooth scaling)

- **Window 2 (Transcode)**

- Full-screen display
- 1080i50 8-bit de-interlacing

- **Window 3 (Transcode)**

- Full-screen display
- 1080i50 8-bit de-interlacing

- **Display 0 (UHD)**

- 3840x2160p60

- **Display 1 (SD)**

- 480i60
- 576i50

- **Encode 0**

- 1080p25 8-bit AVC

- **Encode 1**

- 1080p25 8-bit AVC