

72603




Box mode #3 – summary

- Required memory speed: 1x 32-bit DDR3-1866 or 32-bit DDR4-2133
 - 1x 32-bit DDR4-2400 recommended (for additional headroom)
 - No high-temperature refresh
- Features:
 - Dual 1920x1080p60/60i decode
 - UHD display (through up-scaling)
 - Independent SD display supported (graphics only no video)
 - Main + PIP
 - No multi-PIP
 - No HDMI input
 - No transcoding



Possible video routings





Source limitations

- Decode 0
 - 1920x1080p60/60i 10-bit HEVC / VP9
 - 1920x1080p60/60i 8-bit AVC
 - 1920x1080p30/60i 8-bit MPEG2
 - MTG support
- Decode 1
 - 1920x1080p60/60i 10-bit HEVC / VP9
 - 1920x1080p60/60i 8-bit AVC
 - 1920x1080p30/60i 8-bit MPEG2
 - MTG support

- Graphics 0 (UHD)
 - 1080p60 32-bit ARGB
- Graphics 1 (SD)
 - 480p60 or 576p50 32-bit ARGB



HARDWARE RESOURCE MAPPING

Decoder	MFD	Hardware
Decode 0	MFD0	HVD0
Decode 1	MFD1	HVD0



Window limitations

- Window 0 (MAIN / UHD)
 - Up to full-screen display (smooth scaling)
 - 1080i60 de-interlacing
- Window 1 (PIP / UHD)
 - Up to full-screen display (smooth scaling)
 - No de-interlacing.



Display and encode limitations

- Display 0 (UHD)
 - 1920x1080p60
 - 3840x2160p60 (through up-scaling)
- Display 1 (SD)
 - **-** 480i60

