

BOX MODE #24

7439 Bx


BOX MODE #24 – SUMMARY



- Required memory speed: 2x 32-bit DDR3-2133
 - No high-temperature refresh
- Features:
 - Four 1080p30/60i decodes
 - Two can be fed into the video network
 - Two can be used by the graphics path
 - Two 1080p30/60i encodes
 - Each with 1080p60 graphics
 - No UHD or SD display (headless)
 - No HDMI input

POSSIBLE VIDEO ROUTINGS





SOURCE LIMITATIONS



- For each source, you may toggle between any of the provided options.
 - Only one option enabled at a given time.
- Decode 0
 - 1080p30/60i 10-bit HEVC
 - 1080p30/60i 8-bit VP9 / AVC / MPEG2
 - MTG disabled
- Decode 1
 - 1080p30/60i 10-bit HEVC
 - 1080p30/60i 8-bit VP9 / AVC / MPEG2
 - MTG disabled

Decode 2

- 1080p30/60i 10-bit HEVC
- 1080p30/60i 8-bit VP9 / AVC / MPEG2
- Cannot be fed into the video network
- Decode 3
 - 1080p30/60i 10-bit HEVC
 - 1080p30/60i 8-bit VP9 / AVC / MPEG2
 - Cannot be fed into the video network
- Graphics 0
 - 1080p60 32-bit ARGB
- Graphics 1
 - 1080p60 32-bit ARGB

HARDWARE RESOURCE MAPPING



Decoder	MFD	Hardware
Decode 0	MFD0	HVD0
Decode 1	MFD1	HVD0
Decode 2	-	HVD1
Decode 3	-	HVD1

WINDOW LIMITATIONS



- Window 0 (MAIN / Encode 0)
 - Full-screen display only
 - 1080i60 de-interlacing
- Window 1 (MAIN / Encode 1)
 - Full-screen display only
 - 1080i60 de-interlacing

DISPLAY AND ENCODE LIMITATIONS



- Encode 0
 - 1080p30/60i
- Encode 1
 - 1080p30/60i