TPI IoT API 0.1.0 OAS 3.1

/openapi.json

default

GET /health Health

POST /readings Create Reading

GET /devices/{dev_id}/readings Readings

Parameters | Try it out

Name	Description
dev_id • required string (path)	dev_id pattern: ^[a-z0-9-]{1,32}$
since integer (query)	Default value : 0 0 minimum: 0
limit integer (query)	Default value : 10 10 maximum: 100 minimum: 1
min_temp number | (number | null) (query)	min_temp

Responses

Code	Description	Links
200	Successful Response Media type application/json Controls Accept header. Example Value | Schema	No links

```
[
  {
    "dev": "njkdc177x08-m6zqs8",
    "seq": 0,
    "ts": 1600000001,
    "temp": -40,
```

Responses

Code	Description	Links
200	Successful Response Media type: application/json Controls Accept header. **Example Value** Schema	*No links*
422	Validation Error Media type: application/json **Example Value** Schema	*No links*

```
[
  {
    "dev": "njkdc177x08-m6zqs8",
    "seq": 0,
    "ts": 1600000001,
    "temp": -40,
    "hum": 100
  }
]
```

```
{
  "detail": [
    {
      "loc": [
        "string",
        0
      ],
      "msg": "string",
      "type": "string",
      "input": "string",
      "ctx": {}
    }
  ]
}
```

GET /devices Devices