MIL-W-8005E
27 September 1965

SUPERSEDING
MIL-W-8005D
1 August 1962

MILITARY SPECIFICATION

WHEELS AND HUBS, FOR INDUSTRIAL PNEUMATIC TIRES

This specification has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers wheels and hubs, with or without tires and tubes as specified. The hubs covered herein are of the cantilever or fork mounting type. Sizes of wheels, hubs, tires, and tubes are as follows: (See applicable MS standard and 6.2.)

(a) Cantilever mounting

Sizes	3.50-6	7.50-10
	4.00-8	9.00-10
	6.00-9	

(b) Fork mounting

Sizes	3.50-6	6.00-9
	4.00-8	7.50-10

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

QQ-P-416	-	Plating, Cadmium (Electrodeposited)
QQ-Z-325	-	Zinc Plating (Electro-Deposited)

FSC 2530

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

TT-C-490	-	Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
TT-E-489	-	Enamel; Gloss, Synthetic (For Exterior and Interior Surfaces).
TT-P-636	-	Primer Coating, Synthetic, Wood and Ferrous Metal.
TT-P-666	-	Paint; Primer, Zinc Yellow, For Aluminum and Magnesium Surfaces.
ZZ-T-410	-	Tires and Tubes (Inner), Pneumatic, Industrial.
PPP-B-576	-	Box, Wood, Cleated, Veneer, Paper Overlaid.
PPP-B-585	-	Boxes, Wood, Wirebound.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Box, Fiberboard.
PPP-T-60	-	Tape; Pressure Sensitive Adhesive, Waterproof - For Packaging and Sealing.

Military

MIL-P-116	-	Preservation, Methods Of.
MIL-B-121	-	Barrier Material, Greaseproofed, Flexible (Waterproofed).
MIL-E-5272	-	Environmental Testing, Aeronautical And Associated Equipment, General Specification For.
MIL-C-5541	-	Chemical Films For Aluminum And Aluminum Alloys.
MIL-A-8625		Anodic Coatings, For Aluminum and Aluminum Alloys.
MIL-B-10547	-	Liners, Case, Waterproof.

STANDARDS

Federal

595	-	Colors

Military

MIL-STD-105	-	Sampling Procedures and Tables For Inspection By Attributes.
MIL-STD-129	-	Marking For Shipment And Storage.
MIL-STD-130	-	Identification Marking of U. S. Military Property.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

MIL-STD-1186	-	Cushioning, Anchoring, Bracing, Blocking, And Waterproofing, With Appropriate Test Methods.
MS24322	-	Wheel & Hub Assemblies.
MS24323	-	Wheel for 3.50-6 Tire.
MS24324	-	Wheel for 4.00-8 Tire.
MS24325	-	Wheel for 6.00-9 Tire.
MS24326	-	Wheel for 7.50-10 & 9.00-10 Tires.
MS24327		Hub-Cantilever Mounting for 3.50-6 & 4.00-8 Wheels.
MS24328	-	Hub-Cantilever Mounting for 6.00-9, 7.50-10, & 9.00-10 Wheels.
MS24329	-	Hub-Fork Mounting for 3.50-6 & 4.00-8 Wheels.
MS24330	-	Hub-Fork Mounting for 6.00-9 & 7.50-10 Wheels.

(*Copies of specifications*, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS
Handbook H28 - Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C.)

TIRE AND RIM ASSOCIATION, INCORPORATED
Tire and Rim Yearbook

(Copies of the TRA Yearbook may be obtained from the Tire and Rim Association, Inc., 2001 First National Tower, Akron 8, Ohio.)

OFFICIAL CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules

(Application for copies of the above publication should be addressed to the Official Classification Committee, 1 Park Avenue at 33rd Street, New York 16, N.Y.)

AMERICAN TRUCKING ASSOCIATION
National Motor Freight Classification Rules and Container Specifications

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

(Application for copies of the above publication should be addressed to the American Trucking Association, 1424 16th Street, N.W., Washington D.C.)

3. REQUIREMENTS

3.1 General requirements.- Wheel and hub assemblies shall conform to the standards specified on MS 24322. Where the requirements of MS 24322 and this specification conflict, the requirements of this specification shall govern.

3.2 Standard parts.- MS Standard parts shall be used wherever they are suitable for the purpose, and shall be identified by their part numbers. Commercial utility parts such as screws, nuts, bolts, cotter pins, et cetera, may be used, provided they have suitable properties and are replaceable by MS Standard parts without alternation. In applications for which no suitable corresponding MS part is in effect on date of invitation for bids, commercial parts may be used provided they conform to the requirements of this specification.

3.3 Materials.-

3.3.1 Protective treatment.- When materials are used in the construction of the wheels and hubs that are subject to deterioration when exposed to climatic and environmental conditions likely to occur during service usage, they shall be protected against such deterioration in a manner that will in no way prevent compliance with the performance requirements of this specification. The use of any protective coating that will crack, chip, or scale with age or extremes of climatic and environmental conditions shall be avoided.

3.3.2 Metals.- Metals shall be of the corrosion-resistant type or shall be suitably protected to resist corrosion during normal service life.

3.4 Design.- The wheels and hubs shall be designed as running gear on equipment items which must be towed or moved by hand on paved areas, pierced plank areas, unpaved roads, and unimproved level terrain, whether such areas are dry, wet, or covered with up to 6 inches of snow or 4 inches of mud.

3.5 Construction.- Wheel and hub assemblies shall be constructed so that no parts will work loose in service and shall be built to withstand the requirements specified herein.

3.5.1 Wheels.- The wheels shall be of the split-rim type, with all the necessary bolts, lockwashers, and nuts required for assembly of the two halves as shown on MS24323, MS24324, MS24325, or MS24326, as applicable. The wheel halves shall be of steel or aluminum alloy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

3.5.2 Hubs. A hub shall consist of all the parts shown on MS24327, MS24328, MS24329, and MS24330, as applicable, including all bolts, nuts, and lockwashers for attaching the wheel to the hub. All dimensions, tolerances, and parts such as grease seals and hubcaps which are not specified in detail shall meet the requirements specified in 3.6. Axles are not a part of the wheels and hubs covered by this specification.

3.5.2.1 Bearing removal. Slots or other provisions shall be provided inside the hubs to facilitate the removal of bearing cups.

3.6 Performance. The wheels and hubs shall be capable of operation when subjected to the following environmental conditions:

(a.) A temperature of from -65° to $+125^{\circ}F$.

(b.) A relative humidity of 95 $\pm$ 5 per cent at a temperature of $125^{\circ}F \pm 5^{\circ}F$.

(c.) Exposure to airborne sand and dust particles encountered in normal and desert operation.

(d.) Exposure to atmosphere containing salt-laden moisture.

3.7 Attachment bolts. Hub-to-wheel attachment bolts shall be of the sizes shown on the standards specified in 3.5.2 and shall be ribbed-neck carriage bolts. The length of the ribbed part of the bolt shall be from the head to within 1/16 inch of extending through the flange of the hub. The bolts shall be capable of being pressed out to allow for attachment of a brake mechanism to the hub body.

3.8 Seals. Seals for the hub as shown on the standards specified in 3.5.2 shall be standard grease seals of the molded, synthetic-rubber type. The seals shall provide adequate protection for the wheel bearings under the conditions specified herein.

3.9 Brake drum pilot. Each cantilever mounting hub shall be provided with a brake drum pilot surface on the hub flange as shown on MS24327 and MS24328.

3.10 Tires and tubes. All industrial pneumatic-type tires and tubes furnished with the wheels shall conform to ZZ-T-410, except tire size 7.50-10 shall be 10-ply rating. Tires size 9.00-10 shall be used only with ferrous metal hubs and wheels. All tires shall have a free-rolling tread design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

3.10.1 Ply rating. The ply rating shall be as specified on MS24322.

3.10.2 Flaps. Unless otherwise specified, all 10-ply rating tires shall be equipped with flaps.

3.10.3 Valve stems. The valve stem on the tube furnished with the 3.50-6 tire shall conform to Standard TR 87. The valve stem on the tube furnished with the 4.00-8 tire shall conform to Standard TR 13 or TR 87. The valve stem on the tubes furnished with the 6.00-9 and 7.50-10 tires shall conform to Standard TR 135. The valve stem on the tube furnished with the 9.00-10 tire shall conform to Standard TR 150. These standards are listed in the Tire and Rim Association Year Book.

3.11 Utility parts. MS utility parts shall conform to the material requirements specified on the applicable standards. Commercial utility parts used in lieu of MS parts shall also conform to the material requirements of the standards.

3.12 Interchangeability. All parts having the same MS part number shall be directly and completely interchangeable with each other with respect to installation and performance.

3.13 Screw threads. Unless otherwise specified on the applicable standards, all screw threads shall conform to Handbook H28.

3.14 Finishes and protective coating.

3.14.1 Color. Unless otherwise specified (see 6.2), wheels and hubs shall be finished in yellow, color 13538 of FED-STD-595.

3.14.2 Ferrous-metal wheels, hubs, and hubcaps. Ferrous-metal wheels, hubs, and hubcaps shall be finished as follows prior to assembly. Bearing cup bores shall not be finished.

Treatment:	Type I, TT-C-490
Primer:	0.75-1.25 mils thick, TT-P-636
Enamel:	0.75-1.25 mils thick, TT-E-489

3.14.3 Aluminum alloy wheels, hubs, and hubcaps. Aluminum alloy wheels, hubs, and hubcaps shall be finished as follows prior to assembly. Bearing cup bores shall not be finished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

TABLE I

INDUSTRIAL TIRE LOADS AND INFLATION PRESSURES FOR DESIGN AND SERVICE

(Based on recommendations of the Tire and Rim Association, Inc.)

Loads specified apply to both ferrous metal and aluminum alloy wheels.

Tire Size (TRA)	Ply Rating	Valve Hole Location	TRA Rim Contour No.	Tire O.D. (Approx in.)	ON PAVED ROAD 5 MPH Load Lbs	5 MPH Infl. PSI	10 MPH Load Lbs	10 MPH Infl. PSI	OFF ROAD 5 MPH Load Lbs	5 MPH Infl. PSI	10 MPH Load Lbs	10 MPH Infl. PSI
3.50-6	4	Center	3-1/4 I	13	590	80	490	75	295	65	220	30
4.00-8	6	Center	3-3/4 I	16	1090	100	950	100	570	85	370	30
6.00-9	10	9/16 Inch Offset	4.00 E	21	2290	100	1990	100	1175	95	780	30
7.50-10	10	1 Inch Offset	5.50 F	25	3520	95	2860	85	1620	75	1230	30
9.00-10	10	1 Inch Offset	5.50 F	28	4270	80	3580	75	2000	65	1655	30

* Ferrous wheels and hubs only -

TRA- Tire & Rim Association Standards: These tire sizes are included in ZZ-T-410, except the size 7.50-10, 10-ply rating.

NOTES:

a. Seventy-five percent, or less, of specified load ratings should be used during initial design.

b. No tire smaller than size 6.00-9 should be used as the main wheels for equipment to be used in unpaved areas. The use of sizes 3.50-6 and 4.00-8 should be limited to auxiliary wheels or landing gear for this type of equipment.

c. All tires should have a free-rolling tread design, nondirectional type, with multiple ribs.

d. Worst conditions of use, not average conditions, should be used in tire selection.

e. For given conditions of use, loads below the maximum specified permit use of lower inflation pressures and hence affords an increase in flotation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

Treatment: MIL-C-5541 or MIL-A-8625

Primer: 0.40-0.60 mils thick, TT-P-666

Enamel: 0.75-1.25 mils thick, TT-E-489

3.14.4 Bearings, grease seals, and enclosed parts. The bearings, grease seals, and enclosed parts and surfaces of the hub shall not be painted. The outside surface of the seals shall be painted or plated in accordance with the applicable finishes specified above.

3.14.5 Utility parts. Utility parts shall be cadmium plated in accordance with QQ-P-416, type I, class 3, or zinc-plated in accordance with QQ-Z-325, type II, class 3, and shall not be painted over. Wheel mounting bolts shall be masked or otherwise protected during painting of the hubs.

3.15 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130. The identification data shall be applied to both wheel halves and hub body either by stamping, casting, or molding of letters which shall be plainly visible after protective finishes have been applied and shall consist of the following:

Specification MIL-W-8005
Size_____
MS Part No._____
Mfr's. Name or Trademark_____ _____.

3.16 Workmanship. The wheels and hubs shall be fabricated and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from defects, burrs, and sharp edges; accuracy of dimensions; provision of adequate fillet radii or relieved corners where not specifically required; correct marking of parts; soundness of casting or welding; thoroughness of painting; proper alignment of parts; and freedom from strain.

3.16.1 Rim surface. The surface of the rim between bead seats shall be free of defects which would be injurious to the inner tube.

3.16.2 Flanges. The hub face and mating wheel faces shall be smooth and free from defects.

3.16.3 Register. The register bore of the wheel and register diameter of the hub shall be concentric and free from defects. The least clearance between these surfaces shall be maintained as is consistent with the applicable figures and the production method used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of tests. The inspection and testing of wheels and hubs shall be classified as follows:

a. Preproduction sample tests: Preproduction sample tests are those tests accomplished on samples in accordance with section 4.3 to determine conformance with the requirements specified herein.

b. Acceptance tests: Acceptance tests are those tests accomplished on wheels and hubs produced for delivery under the contract or purchase order.

4.3 Preproduction sample tests.

4.3.1 Preproduction test samples. Unless otherwise specified in the contract or purchase order, preproduction test samples shall consist of two wheel and hub assemblies containing the MS component or components to be supplied under this specification. Hubs shall be tested using the largest applicable wheel in accordance with Table I. Samples shall be marked with identification data as specified in 3.15. Acceptance of the preproduction test samples shall not constitute a waiver by the Government of its rights under the provisions of the contract or purchase order.

4.3.2 Preproduction sample tests shall consist of the acceptance tests and the following tests:

4.3.2.1 Environmental tests. Wheels and hubs shall be subjected to the following tests conducted in accordance with the specified procedures of MIL-E-5272. If axles are removed from the hub, the grease seal bore shall be covered with a suitable closure.

4.3.2.1.1 High temperature. The high temperature test shall be conducted in accordance with Procedure I, except the temperature shall be 125°F. At the conclusion of this test and with the temperature maintained, the wheels and hubs shall meet the test specified in 4.3.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Low temperature. The low temperature test shall be conducted in accordance with Procedure I. At the conclusion of this test and with the temperature maintained, the wheels and hubs shall be subjected 20 times to an instantaneously applied load of one-half the applicable amount specified in 4.3.2.3, distributed along an axle 4 feet between wheel centers. This load shall be dropped a distance of 3 inches.

4.3.2.2 Wheel burst test. Wheels, mounted with tires and tubes, shall not be deformed when the tires and tubes are subjected to the following pressures:

Size		Inflation pressure PSI
3.50-6	4-ply	140
4.00-8	6-ply	175
6.00-9	10-ply	175
7.50-10	10-ply	175
9.00-10	10-ply	175

4.3.2.3 Static load test. Wheels with tires and tubes installed and mounted to hubs of corresponding size shall be tested on dry smooth concrete with the following concentrated static loads. On cantilever type hubs, one wheel and hub shall be mounted on each end of a rigid axle 4 feet long between wheel centers. The load shall be applied simultaneously to each end of the axle 4 inches in from the centerlines of the wheels. For fork-type hubs, the hub shall be mounted in a rigid fork mount similar to that utilized in normal operation so that an equal portion of the load is applied to each side of the centerline of the wheel simultaneously.

Wheel Size	Tire Inflation PSI	Pounds at Each Wheel
3.50-6	80	2,500
4.00-8	100	5,000
6.00-9	100	6,250
7.50-10	95	10,000
9.00-10	80	10,000

4.3.2.4 Towing test. With an overrated load capacity of 10 percent at 5 mph (see Table I), the wheel and hub assemblies shall be mounted to a trailer and towed over a concrete pavement in a circular path having a 35-foot radius as measured to the outside wheels of the trailer, or mounted to a towing simulator and subjected to a comparable test. The trailer shall make 5 complete circles clockwise and 5 complete circles counterclockwise at a speed of 15 mph. At the conclusion of the test, the wheel and hub assemblies shall be inspected for permanent deformation or other damage. Permanent deformation or other damage to the component being tested shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

4.4 Acceptance tests. Acceptance tests shall consist of the individual tests and sampling tests.

4.4.1 Individual tests. Each wheel and each hub shall be inspected to determine compliance with the requirements specified herein with respect to materials, workmanship, and marking.

4.4.2 Sampling plan and test.

4.4.2.1 Lot by lot inspection. Lot by lot inspection shall be performed by the supplier in accordance with the following procedures.

4.4.2.2 Inspection lot formation. A lot shall consist of all wheels and hubs from an identifiable production period, not to exceed 500 wheels or 500 hubs in number.

4.4.2.3 Sampling inspection.

4.4.2.3.1 Visual and dimensional inspection. Sampling shall be in accordance with standard MIL-STD-105, using single sampling. The classification of defects and Acceptable Quality Level (AQL) shall be as listed below.

Characteristic number	Characteristic	Method of inspection
	Major AQL 1% Defective	
101	Wheel Dimensions (see 3.5)-----	SME
102	Parts Missing-----------	Visual
103	Component Dimensions (see 3.2)--	SME
104	Seals, Leakage-----------	Visual
105	Tire Dimensions (see Table & 3.10)--	SME
106	Interchangeability (see 3.12)---	SIE
107	Threads (see 3.13)-----------	SIE
	Minor AQL 4% Defective	
201	Weight-----------	SME
202	Protective coating 3.3.1-------	Visual
203	Paint (wrong color) 3.14.1------	Visual

4.4.2.3.2 Unclassified characteristics. All defects having no bearing on function, safety, interchangeability or life, but which are considered departures from good workmanship, will be noted in writing. Workmanship deficiencies falling within this category and recurring in five consecutive lots, or in ten lots or more within a thirty day period, will be added to the minor characteristics with no increase in AQLs.

4.4.3 Dimensional check. The wheels and hubs shall be dimensionally checked to determine conformance with the applicable standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

4.5 Inspection of preparation for delivery.

4.5.1 Sampling for packaging and packing. Sampling for lot by lot examination and testing of packaging and packing of wheels and hubs shall be conducted.

4.5.1.1 Lot formation. A lot shall consist of all packs prepared for shipment in accordance with one level (see 5.1) from an identifiable production period from one manufacturer.

4.5.1.2 Sampling for lot by lot examination. Lot by lot examination shall be conducted at the contractor's manufacturing facility. Sampling shall be in accordance with Standard MIL-STD-105.

4.5.1.3 Sampling for lot by lot testing. For packaging and packing Levels A and B (see 6.2), one complete package and one complete pack from each lot shall be selected for lot by lot testing as specified in 4.5.3.1 and 4.5.3.2.

4.5.2 Examination inspection for packaging and packing.

4.5.2.1 Acceptable quality level. Each sample selected in accordance with 4.5.1.3 shall be examined for conformance to the following acceptable quality levels (AQLs) on the basis of percent defective.

Major	1%	AQL
Minor	2.1%	AQL

4.5.2.2 Classification of defects for preparation for delivery.

Category	Major 1% AQL	Method of inspection
101	Parts improperly cleaned----------	Visual
102	Improper preservation----------	Visual
103	Excess cube----------	Visual
104	Wrap improperly sealed----------	Visual
105	Improper interior container----------	Visual
106	Improper exterior container----------	Visual
107	Interior container improperly sealed--	Visual
108	Illegible marking----------	Visual
109	Incorrect marking----------	Visual
	Minor 2.5% AQL	
201	Improper strapping and blocking-------	Visual
202	Improper wrap----------	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

4.5.3 Packaging and packing tests.

4.5.3.1 Packaging test. Packaging samples selected shall be subjected to tests and examination of tests as specified for selected sub method 1A of Table III of Specification MIL-P-116 and referenced paragraphs thereto.

4.5.3.2 Packing test. Packs selected in 4.5.1.3 shall be subjected to the packing tests and examination tests as specified in standard MIL-STD-1186. Level B packs shall receive the same tests, except the height of drop test shall be 75 percent of the height of the drop specified in MIL-STD-1186.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging shall be Level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning and Drying shall be in accordance with the applicable process of specification MIL-P-116.

5.1.1.2 Preservation. Bearings and interior bearing surfaces of hubs shall be coated with type P-11 preservative in accordance with specification MIL-P-116. Barrier material conforming to type 2, grade A, class 2, specification MIL-B-121 shall be used to cover hub openings and shall be secured with tape conforming to class 3 of specification PPP-T-60. Each hub assembly and wheel and hub assembly shall be preserved in accordance with Method 1A8 of specification MIL-P-116. Each wheel assembly shall be preserved in accordance with method III, specification MIL-P-116.

5.1.1.3 Packaging. Each hub, wheel, or hub and wheel assembly shall be completely assembled for packaging. When tires are required, they shall be mounted and inflated to 2/3 the applicable pressure. The preserved assemblies shall be packaged one each in a unit container conforming to type CF, class domestic, in accordance with specification PPP-B-636.

5.1.2 Level C. Wheels and hubs shall be preserved and packaged in accordance with manufacturer's commercial practice.

5.2 Packing shall be Level A, B, or C as specified (see 6.2).

5.2.1 Level A. Wheels and hubs shall be packed in containers meeting PPP-B-[illegible]5 (class 2), PPP-B-601 (overseas type), PPP-B-621 (class 2), or PPP-B-576 (overseas type). The contents shall be cushioned, blocked, and braced in accordance with MIL-STD-1186. As far as practical, exterior

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

containers shall be of uniform shape and size, be of minimum cube and tare consistent with the protection required, and contain identical quantities. Containers shall be closed and strapped in accordance with the applicable container specification or appendix thereto. Containers shall be provided with a case liner conforming to MIL-L-10547 and shall be sealed in accordance with the appendix thereto.

5.2.2 Level B. Wheels and hubs shall be packed in containers meeting, PPP-B-585 (class 1), PPP-B-601 (domestic type), PPP-B-621 (class 1), or PPP-B-576 (domestic type). The contents shall be cushioned, blocked, and braced in accordance with MIL-STD-1186. Exterior containers shall be of minimum cube and tare consistent with the protection required. As far as practical, exterior containers shall be of uniform shape and size and contain identical quantities. Containers shall be closed and strapped in accordance with the applicable container specification or appendix thereto.

5.2.3 Level C. Packages which require over-packing for acceptance by the carrier shall be packed in exterior-type shipping containers in a manner that will insure safe transportation at the lowest rate to the point of delivery. Containers shall meet Uniform Freight Classification or rules and regulations of other common carriers as applicable to the mode of transportation.

5.3 Marking. Interior and exterior containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Wheels and hubs covered by this specification are intended for use as standard components of mobile equipment used by the Armed Services under all extremes of climatic and environmental conditions.

6.1.1 Caster mounts. Where wheels and hubs are to be used as components of single-or dual-tired pneumatic casters, cantilever mounting should be required in the detail specification to facilitate wheel removal.

6.1.2 Fork mounts. Fork mounting of wheels and hubs will be used only when specified by the procuring activity. Testing to determine the adequacy of the fork mounted type hub and wheel assembly should be conducted in conjunction with first article testing of the end item for each specific application.

6.2 Ordering data. Procurement documents should specify the following:

(a) Number, title and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

(b) Applicable MS part number, which covers size, whether wheels or hubs, or both, are to be procured, whether tires and tubes are required with wheels, and whether cantilever- or fork-mounting type hub is required. (see 1.1).

(c) Required inflation pressure of tires (see Table I).

(d) Color, if other than yellow (see 3.14.1).

(e) Level of preservation and packaging required (see 5.1).

(f) Level of packing required (see 5.2).

6.4 Tire selection criteria. TRA Yearbook should be used as a guide for the selection of tire sizes for use on a specific item of mobile equipment, subject to the following:

6.4.1 Conditions. Select for the worst expected conditions of use; generally, off-road, 10-mph conditions.

6.4.2 Rating. To assure adequate flotation, use no more than 75 percent of the maximum tire ratings in initial design.

6.4.3 Tire sizes. Use tire size 6.00-9, or larger, where equipment items must be mobile over pierced plank and level unpaved surfaces. (Size 600-9, 6-ply rating tires may be used in lieu of 6.00-9, 10-ply rating tires where use of this rule results in underloading of tires). Use tire sizes 3.50-6 and 4.00-8 as landing gear wheels for two-wheel trailers and similar items, or where the equipment item is light in weight and will be moved only over paved surfaces.

Custodians:
Army - MO
Navy - YD
Air Force - 84

Reviewer activities:
Air Force - 85

Preparing activity:
Air Force - 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1426 REPLACES NAVSHIPS FORM 1336, WHICH IS OBSOLETE PLATE NO. 15413

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T09:48Z
Check the source to verify that this is the current version before use.