INCH-POUND

O-D-1435B
June 30, 1992
SUPERSEDING
O-D-1435A
August 25, 1971

FEDERAL SPECIFICATION

SANITIZER, PHENOLIC TYPE, CONCENTRATE

This specification is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers a phenolic type sanitizer for use after dissolving in water. The sanitizer is in flake or granular form and is packaged in a laminated plastic/foil pouch.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-B-636 - Boxes, Shipping, Fiberboard

Federal Standards:

FED-STD-101 - Test Procedures For Packaging Materials

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5019 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 6840

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Single copies of this specification, and other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Auburn, WA.)

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications:

MIL-L-35078 - Loads, Unit: Preparation Of Semiperishable Substance Items: Clothing, Personal Equipment And Equipage: General Specification For

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipping and Storage
MIL-STD-147 - Palletized Unit Loads

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Federal Regulations:

40 CFR Part 152 - Federal Insecticide, Fungicide, and Rodenticide Act

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

Document shall be examined for foreign particles visible to the naked eye. T

American Society for Testing and Materials (ASTM)

D 882 - Plastic Sheeting, Thin, Tensile Properties of
D 3951 - Packaging, Commercial
F 372 - Water Vapor Transmission of Flexible Barrier Materials Using Infrared Detection Technique

(Application for copies should be addressed to the American Society of Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

Munsell Book of Color

(Application for copies should be addressed to the Munsell Color Company, Inc., 2441 N. Calvert Street, Baltimore, MD 21218.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

American National Standards Institute (ANSI)

ANSI Z 358.1 - Eyewash and Shower Equipment, Emergency - 5 Oct. 1989

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, NY 10018.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Laboratory report approval. Unless otherwise specified (see 6.2) at the time of submission of a bid, the bidder shall submit to the contracting officer a certified copy of a current year laboratory report covering the quality and grade of materials which he proposes to deliver. The laboratory report shall contain test data which demonstrates that the sanitizer concentrate which the bidder proposes to deliver has been tested in accordance with section 4 and found to comply with the requirements of this specification. Any of the following types of reports will be satisfactory for this requirement:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

a. An independent of commercial laboratory report.
b. The prospective supplier's own laboratory report.
c. A Government laboratory report from a contract.

The purpose of the above requirement is to assist the Government in determining the capability of bidders to conform to all the requirements of this specification. The submission of an acceptable report under this requirement shall not be construed as relieving a bidder from subsequently meeting all requirements of this specification on all deliveries.

3.3 Composition and form. The sanitizer shall be in flake or granular form and shall be a uniform composition of the following ingredients when tested as specified in 4.4.4.

	Percent by weight
Sodium-o-phenylphenate, tetrahydrate	97.0 minimum
Inert ingredients	3.0 maximum
Total.....	100.0

3.4 Solubility. The sanitizer shall be completely soluble in distilled water when tested as specified in 4.4.4.

3.5 Heavy metals. The sanitizer shall show no evidence of the presence of heavy metals when tested as specified in 4.4.4.

3.6 Solubility. The pH of a solution of the sanitizer (5g/L of water) shall be not less than 10.5 and not greater than 11.0 when tested as specified in 4.4.4.

3.7 Color. The color shall be within the following Munsell value limits:

Light limit	Hue number 12.5 Reddish yellow - red Hue symbol 2.5 yr 9/2
Heavy (dark) limit	Hue number 12.5 Reddish yellow - red Hue symbol 2.5 yr 8/2

3.8 Workmanship. The sanitizer shall be clean, uniform, free of foreign matter and shall conform to the quality and grade of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure that all products or supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the current contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3 and shall be tested as specified in 4.4.4.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of reference documents unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.2 End item visual examination. The sanitizer in pouches shall be examined for the defects listed below. The lot size shall be expressed in units of filled pouches. The sample unit for this examination shall be one filled pouch. The inspection level shall be S-4 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

Examine	Defects
Materials	Pouch not constructed with specified laminated barrier material (see 5.1.1).
Construction	Seams and closures not completely heat sealed throughout. Seals not uniform construction.
Workmanship	Evidence of weak or unsound seams. Tears, cuts, splits, cracks, blisters, abraded areas or holes (including pin holes). Contents not clean and uniform, presence of foreign matter, not flaked or granular.
Markings	Markings pertaining to the applicable information and instructions for end item use, missing, illegible or do not conform to legend specified. Label does not contain EPA Registration and Establishment numbers.
Color (contents)	Not as specified.

4.4.3 Net weight examination. The filled pouches shall be examined for net weight. Any pouch not conforming to the contents weight requirement in 5.1.1 shall be classified as a defect. The lot size shall be expressed in units of filled pouches. The sample unit shall be one filled pouch. The inspection level shall be S-2 and the AQL, expressed as percent defective, shall be 2.5.

4.4.4 End item testing. The end items shall be tested for the characteristics specified in table I. The lot size shall be expressed in units of pouches (or packaging material expressed in equivalent number of pouches). The sample unit for testing shall be 10 pouches (or the equivalent amount of packaging material) randomly selected throughout the lot. The number of sample units to be drawn shall be as indicated below. The lot shall be unacceptable if one or more sample units fail to meet any test requirement specified.

Lot size (pouches)	Sample units
800 or less	2
801 up to and including 22,000	3
22,001 or more	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

TABLE I. End item tests

Characterisitc	Requirement paragraph	Test method	Average number determination per sample unit	Results reported as Pass or fail	Results reported as numerically to nearest
Composition and form	3.3	4.5.1	2	--	0.1 percent
Solubility	3.4	4.5.2	1	X	---
Heavy metals	3.5	4.5.3	1	X	---
pH	3.6	4.5.4	2	--	0.1 pH
Pouch construction	5.1.1	1/			
Water vapor transmission rate	5.1.1	4.5.5	3	--	0.01g/100sq. in/24 hr.
Seam (heat sealed) strength	5.1.1	4.5.6	5	--	0.01 lbs/in.
Leakage test	5.1.1	4.5.7	2	X	---

1/ Unless otherwise specified, a certificate of compliance is required and will be acceptable for the requirements stated.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

Content	Number of pouches per shipping container more or less than required

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Analytical method for sodium o-phenylphenate.

4.5.1.1 Apparatus.

4.5.1.1.1 Gas chromatograph: Hewlett-Packard Model 5790A, or equivalent, equipped with a flame ionization detector, available from Hewlett-Packard, 39550 Orchard Hill Drive, Novi, MI 48050.

4.5.1.1.2 Computing integrator: HP 3392A, or equivalent, available from Hewlett-Packard.

4.5.1.1.3 Capillary column: 50 m X 0.32 mm ID fused silica, coated with SE-54 (5% phenylmethylsilicone) liquid phase, 1-micron film thickness, available from Quadrex Corporation, New Haven, CT 06525.

4.5.1.1.4 Syringe, 10 microliter: Hamilton 701 N, or equivalent, available from Fisher Scientific Company, 2400 James Savage Road, Midland, MI 48640.

4.5.1.1.5 Pipets: 10 and 20 mL, available from Fisher Scientific Company.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:16Z
Check the source to verify that this is the current version before use.

4.5.1.1.6 Analytical balance, capable of measuring 0.1 mg: Mettler AE163, or Equivalent, available from Mettler Instrument Corp., Princeton-Hightstown Road, Hightstown, NJ 08520.

4.5.1.1.7 Oxygen removal system: General Electric Go-Getter, or equivalent, available from The Anspec Company, Inc., 122 Enterprise Drive, Ann Arbor, MI 48107.

4.5.1.2 Reagents.

4.5.1.2.1 Diphenyl oxide (99.9%) and sodium-o-phenylphenate: available from The Sample Coordinator, The Dow Chemical Company, 779 Building, Midland, MI 48667.

4.5.1.2.2 o-Phenylphenol (99.7%): available from Specialty Chemicals TS&D, The Dow Chemical Company, 2040 Building, Midland, MI 48674.

4.5.1.2.3 Heptane (99.7%), and hydrochloric acid (1 N): available from Fisher Scientific Company.

4.5.1.3 Chromatographic conditions.

Instrument:	HP 5790 GC/FID; HP 3392A Integrator
Column	50 m X 0.32 mm ID, SE-54, 1-um film thickness, fused silica capillary
Temperatures:	
Injector:	300°C
Detector:	300°C
Oven:	200°C (Isothermal)
Flows:	
Carries:	2 mL/min (helium)
Split:	60 mL/min
Make-up:	22 mL/min (nitrogen)
Hydrogen:	25 mL/min
Air:	250 mL/min
Sample size:	1 uL
Range:	10
Attenuation:	1

An efficient oxygen scavenging system such as the General Electric Go-Getter should be used with the helium supply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

4.5.1.4 Preparation of internal standard solution.

Weigh 12.6 g of the internal standard diphenyl oxide (DPO) to the nearest 0.1 mg into a 10-dram vial. Transfer the DPO quantitatively to a 500-mL volumetric flask and dilute to volume with heptane solvent. Shake the solution to ensure complete solution of the DPO in the heptane.

4.5.1.5 Preparation of calibration standard.

Weigh 0.64 g to the nearest 0.1 mg of o-phenylphenol into a 10-dram Vial. Add 10.0 mL of 1 N hydrochloric acid and 20 mL of internal standard solution (see 4.5.1.4) by means of pipets. Mix the resulting solution for 10 minutes on a mechanical shaker. Allow the layers to separate.

4.5.1.5.1 Calibration.

Inject 1 microliter of the heptane (top) layer in the gas chromatograph and analyze according to the conditions described in 4.5.1.3. Repeat the procedure at least twice and determine the response factor for o-phenylphenol (OPP) according to the following equation:

$$RF = \frac{(A)\ (D)}{(B)\ (C)}$$

Where: RF = response factor for sodium-o-phenylphenate
A = area of internal standard
B = g of internal standard
C = area of sodium-o-phenylphenate
D = g of OPP multiplied by 1.129 to calculate as sodium-o-phenylphenate

4.5.1.6 Preparation of sample.

Weigh 1.0 ± 0.1 g (to the nearest 0.1 mg) of sample containing sodium-o-phenylphenate into a 10-dram vial. Pipette 10 mL of 1 N hydrochloric acid and 20 mL of internal standard solution. Mix the solution for 10 minutes on a mechanical shaker. Allow the layers to separate.

4.5.1.6.1 Procedure.

Inject 1 microliter of the heptane (top) layer into the gas chromatograph and analyze according to the conditions in 4.5.1.3.

4.5.1.6.2 Calculations.

$$\text{Percent Sodium-o-Phenylphenate} = \frac{RF\ (C)\ (B)}{(D)\ (A)} \times 100$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

Where: RF = response factor of sodium-o-phenylphenate
A = area of internal standard
B = g of internal standard
C = area of o-phenylphenate
D = g of sodium-o-phenylphenate

4.5.1.7 Precautions for safety.

4.5.1.7.1 Sodium-o-phenylphenate may cause burns and severe eye injury. Wear chemical workers' goggles and impervious gloves to prevent eye and skin contact.

4.5.1.7.2 Prolonged or repeated contact with diphenyl oxide may cause irritation of skin and/or respiratory system. In case of contact, wash with plenty of water and contact appropriate personnel.

4.5.1.7.3 Prolonged or repeated contact with o-phenylphenol may cause irritation of eye and respiratory system. To prevent exposure, samples should only be handled in a well ventilated area.

4.5.1.7.4 Hydrochloric acid and acetic acid are toxic and corrosive materials. Wear chemical workers' goggles and gloves to prevent eye and skin contact. A full length face shield should be worn in addition to the chemical workers' goggles if the danger of splashing exists. An apron or other appropriate impermeable outer garmet and foot covers may be needed, depending on the conditions of use.

4.5.1.7.5 Heptane, methanol and Karl Fischer reagent are flammable solvents. Work in a well ventilated area away from any source of ignition. An emergency eyewash and deluge shower should be easily accessible in the area of use. If the eyewash is of the plumbed type, it must be capable of delivering at least 0.4 gallons per minute for at least 15 minutes. If the eyewash is of the personal or portable type, it must comply with the provisions of the American National Standards Institute publication Z 358.1-1981.

4.5.1.7.6 Each analyst should be aquainted with potential hazards of the reagents, products, and solvents before commencing laboratory work. SOURCES OF INFORMATION INCLUDE: MATERIAL SAFETY DATA SHEETS, LITERATURE, AND OTHER RELATED DATA. Safety information should be requested from the supplier. Disposal of reagents, reactants and solvents must be in compliance with local, state, and federal laws and regulations.

4.5.2 Solubility test. Weigh out 5.000 g sample of the finished product within 1 milligram and transfer to a 1500 mL beaker (Corning No. 1000 or equivalent) containing 1000 mL of distilled water at 20°C. Stir vigorously with glass stirring rod for 10 seconds every 30 seconds for 5 minutes. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

product shall be completely soluble and free of any undissolved matter after the 5-minute period. Save this solution for use in 4.5.3 and 4.5.4.

4.5.3 Heavy metals, qualitative test. A 0.4 to 0.5 g sample of the finished product shall be transferred into a 100 mL Kjeldahl flask (Corning No. 5420 or equivalent). Add 15 mL of reagent grade concentrated nitric acid, several boiling chips and boil in a fume hood for 1 hour using the usual precautions for handling the nitric acid mixture. Use safety-shield, and wear goggles and rubber gloves as a precautionary measure. Let flask and contents cool a little, then add 30 mL of distilled water and boil for 30 to 40 minutes. Cool flask and contents under tap water. Transfer a 10 mL sample to a beaker and neutralize with 5N sodium hydroxide solution 1/ to pH 6 to 7, using a glass electrode equipped pH meter (Beckman Model G or equivalent). To a 16 X 150 mm test tube, add 8.0 mL of distilled water, 1.0 mL of phosphate buffer pH 7.2 2/, 1.0 mL of the neutralized sample of the finished product solution as prepared above, and 0.5 mL of diphenylthiocarbazone solution 3/, shaking after each addition. Prepare a blank sample with distilled water and a standard sample containing 10 micrograms of Mercury 4/ for comparison with the neutralized sample of the finished product when carrying out the analysis. The solutions will be yellow to amber color in the absence of heavy metal. If heavy metal is present a pink to purple color develops which will precipitate on standing. Let sample stand for 6 hours and inspect for a colored precipitate in the bottom of the test tubes.

1/ Sodium hydroxide solution (5N): Dissolve 20 g of reagent grade NaOH in distilled water and make up to 100 mL.

2/ Phosphate buffer solution: Dissolve 34 g of reagent grade potassium dihydrogen phosphate (KH_2PO_4) in 500 mL of distilled water. Add approximately 175 mL of 1N NaOH to pH 7.2 and then dilute to 1 liter.

3/ Diphenylthiocarbazone solution: Dissolve 50 mg of diphenylthiocarbazone (Eastman No. 3092 or equivalent) in reagent grade ethyl alcohol (95% or 100%) and make up to 50 mL.

4/ Mercuric chloride solution: Dissolve 1.345 g reagent grade mercuric chloride ($HgCl_2$) in distilled water and make up to 1 liter. Prepare a 1 to 100 dilution or this stock solution which will contain 10 micrograms of mercury per mL.

4.5.4 pH test. Check pH of solution prepared in 4.5.2 with an electrometric pH meter (Beckman Model G or equivalent) equipped with special glass electrode corrected for sodium error, standardizing the instrument at pH 11.00 with a standard buffer solution (prepared from Certified Colemen Buffer Tablets pH 11.00 or equivalent). The pH of the solution shall be determined at 20°C (68°F).

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:16Z
Check the source to verify that this is the currentversion before use.

4.5.5 Water vapor transmission rate (WVTR) examination. The WVTR for barrier material shall be tested in accordance with ASTM F 372 (see 4.4.4) for conformance to WVTR requirements in 5.1.1.

4.5.6 Seam strength test. Seam strength shall be tested in accordance with ASTM D 882 for conformance to seam strength requirements in 5.1.1 (see 4.4.4).

4.5.7 Leakage test. Filled and sealed pouch shall be tested for leaks in accordance with the hot water technique of Method 5009 of FED-STD-101 for conformance to leakage requirements in 5.1.1 (see 4.4.4). Bubbles which may appear on the surface of the pouch, but are not released at a slowly decreasing rate, are not to be construed as an indication of failure. A steady stream of recurring succession of bubbles from any surface or seam shall be considered a failure. Upon completion of the test, the pouches shall be thoroughly dried to prior packing.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A. Eight ounces of sanitizer shall be filled in a flat style notched pouch having approximate inside dimensions of 5-1/2 inches by 8-1/2 inches. The pouch shall be constructed of barrier material consisting of a lamination (from inside to outside) of 0.0015 inch polyethylene by 0.00035 inch aluminum foil by 0.001 inch polyethylene by 25 pound basis weight paper with 2 pound basis weight per ream (24 X 36 - 500) lacquer coating. The water vapor transmission rate (WVTR) shall not exceed 0.20 gram per hundred square inches in 24 hours when tested in accordance with 4.4.4. The closure shall be heat sealed. All four heat seals of pouch shall be 3/16 to 1/4 inch width, uniform and smooth (without wrinkles or foreign matter) and shall have a breaking strength of not less than 7 pounds per inch of width when tested in accordance with 4.4.4. The filled pouch shall not leak when tested in accordance with 4.4.4.

5.2 Packing. Packing shall be level A, B or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Twelve pouches of sanitizer, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC-L, grade V2s of PPP-B-636. Inside dimensions of the box shall be approximately 12 inches in length, 9 inches in width, and 4-1/2 inches in depth. Each box shall be closed, waterproofed, and reinforced in accordance with the appendix of PPP-B-636. Boxes shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Twelve pouches of sanitizer, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC-L, variety SW or SF, class domestic, grade 275 of PPP-B-636. Inside dimensions of the box shall be approximately 12 inches in length, 9 inches in width, and 4-1/2 inches in depth. Each box shall be closed in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant shipping container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636.

5.2.3 Commercial packing. Sanitizer, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), sanitizer packed as specified in 5.2.2. or 5.2.3 shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 104 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract of purchase order, unit packs, shipping containers, and unit loads shall be marked in accordance with MIL-STD-129, FED-STD-123, or ASTM D 3951, as applicable.

5.4.1 Information and warning labels. The outside of each pouch and shipping container shall be marked with Environmental Protection Agency (EPA) approved warning labels as shown on figures 1 and 2. The EPA registration number "40510-5" shown on figure 1 has been assigned to the Natick Research, Development, and Engineering Center, Natick, MA 01760-5020 in accordance with the Federal Insecticide, Fungicide, and Rodenticide Act. The contractor shall use the EPA establishment number assigned to the manufacturing plant in accordance with the Federal Insecticide, Fungicide, and Rodenticide Act.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The sanitizer is intended to be used in sanitizing latrine buckets and their contents and in everyday housekeeping for floors, walls, sinks, shower stalls, urinals, toilet bowls, garbage cans and garbage platforms.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:16Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. When laboratory report is required (see 3.2).
c. When a first article sample is required (see 3.1, 4.3 and 6.3).
d. Level of packing (see 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Cross-reference. The "A" revision of this specification covered two forms of disinfectant, a liquid (type I) and a solid (type II). The liquid form (type I) is replaced by A-A-1438. The solid sanitizer covered by this specification replaces the type II.

6.5 Subject term (key words) listing.

Cleaning
Disinfectant
Garbage cans
Latrine bucket
Shower stalls
Toilet
Urinal

MILITARY INTERESTS:

Custodians

Army - GL
Air Force - 68

Review activities:

Army - MD
Navy - MS

CIVIL AGENCY COORDINATING ACTIVITIES:

DOG
GSA - FSS
HEW - FDA, NIH
NASA - JFK
PO
VA

PREPARING ACTIVITY:

Army - GL

(Project 6840-1006)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

SANITIZER, PHENOLIC TYPE, CONCENTRATE FED. SPEC. O-D-1435B

For sanitizing latrine; buckets, urinals, toilet bowls, walls, shower stalls garbage cans and garbage platforms

(8 oz. net quantity in 2 quarts of water for latrine buckets.)

(8 oz. net quantity in 4 gallons of water for toilet bowls, floors, etc.)

ACTIVE INGREDIENTS:
Sodium ortho-Phenyiphenate, Tetrahydrate.....97%
Inert Ingredients.....3%

KEEP OUT OF REACH OF CHILDREN

DANGER

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS AND FIRST AID

Name of Mfg & Address Lot No. Date

Contract No.

EPA Reg. No. 40510-5 EPA Est. No.

Inspection Test Date

NET CONTENTS.....8 OZ.

FIGURE 1. FRONT PANEL.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:16Z
Check the source to verify that this is the currentversion before use.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING

1. For housekeeping sanitation--Dissolve contents of one pouch (8 oz.) in a scrub bucket and add four gallons of water, proportionately less for smaller amounts of water. Preferably, use without soap as a rinse for best sanitation.

2. For bacteriostatic odor control in field latrine buckets -- Dissolve contents of one pouch (8 oz.) in two quarts of water. After contents are thoroughly dissolved, pour one quart of resulting solution into each latrine bucket (14-quart capacity). Empty each bucket when it becomes half full.

3. Make fresh solutions for each use.

STORAGE AND DISPOSAL

- Do not contaminate water, food, or feed by storage or disposal.
- Storage: Keep package tightly closed when not in use.
- Pesticide disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
- Container disposal: Completely empty bag into application equipment. Then dispose of empty bag in a sanitary landfill or by incineration, or, if allowed by State and local authorities, by burning. If burned, stay out of smoke.

KEEP OUT OF REACH OF CHILDREN

DANGER

PRECAUTIONARY STATEMENTS
Hazards to Humans and Domestic Animals

CORROSIVE TO SKIN • INJURIOUS TO EYES
IRRITATING DUST • HARMFUL IF SWALLOWED

Do Not Get in Eyes, on Skin, or on Clothing
Avoid Breathing Dusts • Wear Goggles or Face Shield and Rubber Gloves when Handling
Wash Thoroughly after Handling

Statements of Practical Treatment

•In case of eye contact, immediately wash eyes with flowing water for 15 minutes. Call a physician.
•In case of skin contact immediately flush skin with plenty of water for at least 15 minutes and get medical attention if irritation persists. Remove contaminated clothing and shoes. Wash clothing before reuse. Destroy contaminated shoes.
•If swallowed, induce vomiting immediately by giving two glasses of water and sticking finger down throat. Call a physician. Do not induce vomiting or give anything by mouth to an unconscious person.
•Anyone experiencing noticeable ill effects from breathing the dust of this material should be removed to fresh air.

Environmental Hazard

Do not discharge into lakes, streams, or public waters unless in accordance with an NPDES permit. For guidance, contact your regional office of the EPA.

In case of an emergency endangering life or property involving this product, call collect
517-636-4400

NOTICE
Do Not Ship or Store with Food, Feeds, Drugs or Clothing

FIGURE 2. BACK PANEL.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	O-D-1435B	1992 June 30

3. DOCUMENT TITLE

SANITIZER, PHENOLIC TYPE, CONCENTRATE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

[redacted]

7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. NAME

U.S. Army Natick RD&E Center

b. TELEPHONE (Include Area Code)
(1) Commercial: 508-651-4532
(2) AUTOVON/DSN: 256-4532

c. ADDRESS (Include Zip Code)
Commander, U.S. Army Natick RD&E Center
ATTN: STRNC-IRT
Natick, MA 01760-5019

IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:
Defense Quality and Standardization Office
5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466
Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T11:16Z
Check the source to verify that this is the current version before use.