S-F-700F
March 29, 1985
SUPERSEDING
S-F-700E
December 17, 1977

FEDERAL SPECIFICATION

FRYERS, DEEP-FAT (GAS, HEAVY DUTY)

This specification is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers commercial, heavy-duty, floor and mounted gas heated, deep-fat fryers.

1.2 Classification. Fryers shall be of the following types, sizes, and classes, as specified (see 6.2).

Type I	- Floor mounted.
Size 1	- Deleted (see 6.5).
Size 2	- 60 pounds production capacity (min.). 1/
Size 3	- 90 pounds production capacity (min.).
Size 4	- 110 pounds production capacity (min.)
Model A	- Deleted (see 6.5).
Type II	- Deleted (see 6.5).
Size 1	- Deleted (see 6.5).
Size 2	- Deleted (see 6.5).
Grade A	- Deleted (see 6.5).
Grade B	- Deleted (see 6.5).

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

Class 1 - Without automatic fry basket lowering and raising mechanism.

Class 2 - With automatic fry basket lowering and raising mechanism.

1/ Production capacity is expressed as the quantity of raw potatoes (prepared for french frying) that can be properly processed per hour.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Standard:

FED-STD-123 - Marking for Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Single copies of this specification, other Federal specifications, standards, and commercial item descriptions required by activities outside the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Houston, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specification:

MIL-R-11337 - Ranges, Packaging and Packing Of

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the currentversion before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-129 - Marking for Shipment and Storage

(Copies of Military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

American Gas Association (A.G.A.)

Directory of Certified Appliances and Accessories

(Application for copies should be addressed to the American Gas Association, 8501 East Pleasant Valley Road, Cleveland, OH 44131.)

American National Standards Institute (ANSI)

No. C 73 - Dimension of Caps, Plugs, and Receptacles

No. Z 21.41 - Quick Disconnect Device for Use With Gas Fuel

No. Z 21.45 - Flexible Connectors of Other Than All-Metal Construction for Gas Appliances

No. Z 21.18 - Gas Appliance Pressure Regulators

No. Z 83.13 - Standard for, Gas Food Service Equipment Deep Fat Fryers

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

American Society for Testing and Materials (ASTM)

A 167 - Stainless and Heat Resisting Chromium-Nickel Steel Plate, Sheet, and Strip

A 176 - Stainless and Heat Resisting Chromium Steel Plate, Sheet, and Strip

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

National Sanitation Foundation (NSF)

No. 4 - Commercial Cooking and Hot Food Storage Equipment Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The fryer shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product with any added features needed to comply with the requirements of this specification. Standard or modified commercial products furnished in accordance with this specification shall be identifiable by all regular manufacturer's or commercial service organizations servicing the brand involved. Service organizations shall be capable of providing complete parts and repair services on models furnished to the Government consistent with their normal commercial practices.

3.2 Codes and standards. The deep fat fryers shall conform to the applicable requirements of National Sanitation Foundation (NSF) Standard No. 4 and American National Standards Institute (ANSI) Standard No's. Z 83.13, Z 21.41 and Z 21.45 and C 73, as applicable.

3.3 Compliance. Prior to commencing production the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the fryer he proposes to furnish under this specification meets the applicable requirements of NSF Standard No. 4 and ANSI Standard No's. Z 83.13, Z 21.41 and Z 21.45 and C 73, as follows:

3.3.1 NSF. Acceptable evidence of meeting the requirements of NSF shall be one of the following:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF Seal on the finished fryer.

(2) A certification for the fryer issued by NSF under their special one-time contract evaluation/certification service.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the current version before use.

(3) A test report, acceptable to the Contracting Officer with the advice of the Army Surgeon General from an independent testing laboratory, indicating that the deep-fat fryer has been tested and conforms to NSF.

3.3.2 ANSI. Acceptable evidence of meeting the applicable requirements of Z 83.13, Z 21.41 and Z 21.45 shall be a photostatic copy of the A.G.A. Appliance Certificate; a listing of the fryers and quick disconnect devices and connectors in the A.G.A. Directory of Certified Appliances and Accessories; or a certified test report from a recognized, independent testing laboratory acceptable to the Government stating that the fryers have been tested and conform to Z 83.13, Z 21.41 and Z 21.45 and C 73, when applicable.

3.4 Materials (see 6.3) and components. Materials and components shall be as specified herein. Materials not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial gas deep fat fryers provided the completed item complies with all provisions of this specification.

3.4.1 Stainless steel plates, sheets and strips. Stainless steel plates, sheets and strips shall conform to type 302 or type 304 of ASTM A 167; or any type in the 400 series of ASTM A 176.

3.5 Design and construction. Type I fryer shall be of the enclosed cabinet design for floor use. All fryers shall be provided with a back splash guard. The cabinet front shall be provided with door(s). The cabinet exterior surfaces, back and sides, shall have no protrusion(s) i.e., receptacle or connections. Fryers shall be provided with legs. Class 2 fryers shall be provided with power "ON-OFF" switch. Class 1 fryers shall be without automatic fry basket lowering and raising mechanism. Class 2 fryers shall be provided with automatic fry basket lowering and raising mechanism. The minimum gas consumption shall be as specified in table I. Fryer dimensions excluding back splash shall be as specified in table II.

TABLE I. Gas consumption rate

Types	Fryer size	British Thermal Units (Btu) Minimum
I	2	90,000
I	3	110,000
I	4	125,000

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the currentversion before use.

TABLE II. Overall exterior dimensions (inches) excluding back splash

Fryers	Size 2	Size 3	Size 4
Height (from floor to top of cooking vessel)			
Type I	34 to 37-1/2	34 to 37-1/2	34 to 37-1/2
Width (maximum)			
Type I	20	21	21-1/2
Depth (maximum)			
Type I	38	38	38

3.5.1 Cabinet. The fryer shall have an enclosed cabinet designed for floor use equipped with adjustable stainless steel legs. The cabinet front and door(s) shall be stainless steel with the remaining sides and back finished in accordance with the standard manufacturers practice. The cabinet shall be provided with a shelf or may be provided with other means at the bottom to accommodate the fat-draining vessel. The shelf shall be fabricated from the same material as the cabinet. The cabinet front shall be provided with door(s), or when specified (see 6.2), the cabinet shall be provided with an open front. The shelf shall be constructed to support the fat-draining vessel when filled with the specified amount of fat.

3.5.2 Production capacity. The type I, sizes 2, 3, and 4 fryers shall be capable of french-frying at least 60, 90, and 110 pounds of raw potatoes per hour, respectively. Capacity shall be determined by the following equation:

$$P = \frac{R}{Ec}$$

Where P = potato production capacity in pounds per hour,
R = actual input rate in British Thermal Units (Btu) per hour,
Ec = energy consumption, which shall be the average of at least two complete tests as specified in the "Cooking Performance" paragraphs of ANSI Standard No. Z 83.13.

The production capacity of type I, sizes 2, 3, and 4 fryers shall be not more than 20 percent greater than the specified production capacity. When tested as specified in 4.4.2, the production capacity shall be as specified above.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the currentversion before use.

3.5.3 Vessels.

3.5.3.1 Cooking. Cooking vessels shall be fabricated of carbon steel or stainless steel. The carbon steel cooking vessel shall be nickel plated except that no copper plating shall be used prior to nickel plating. The cooking vessel for the type I, sizes 2, 3, and 4 fryers shall be nonremovable and shall be provided with drain facilities as specified in 3.5.3.3.

3.5.3.2 Fat draining. The fat draining vessel shall be fabricated of stainless steel. Handles or a rim for carrying and pouring the hot fat shall be provided. The volumetric capacity shall be not less than 35 percent of the normal operating cooking vessel volumetric capacity for type I, sizes 2, 3, and 4 fryers, when tested in accordance with 4.4.3.

3.5.3.3 Drains. The drain for the type I, sizes 2, 3, and 4 fryers shall consist of a hand operated valve. Means for opening and closing the hand operated valve shall not interfere with the removal of the fat draining vessel. The drain outlet shall be located so that the fat draining vessel will catch all fat without spillage and can be easily removed without disturbing the drain.

3.5.4 Baskets. Unless otherwise specified (see 6.2), each class 1 fryer shall be equipped with one large and two small metal baskets. The class 2 fryers shall be equipped with two small metal baskets. The metal baskets shall be fabricated of carbon steel or stainless steel wire, or expanded metal. The small baskets shall be 1/2 the size of the large baskets. Openings in the wire baskets shall be approximately 1/4 inch square. Diamond-shaped openings of the expanded-metal baskets shall have a short dimension between 3/16 and 5/16 inch. After fabrication, the carbon steel baskets shall be tin plated, and then retinned by the hot-dip method or may be nickel plated with the exception that no copper plating shall be used prior to nickel plating. The large basket shall be compatible with the fryer and shall be smaller than the frying area. The two small baskets shall be suitable for simultaneous use in the fryer. The large basket, supplied with the type I, sizes 3 and 4 fryers, shall have two loop-type handles on each side or one loop-type handle opposite the fry basket handle. Basket supports or other suitable device shall be furnished to permit draining the grease from the cooked food in the basket or baskets, into the cooking vessel without spilling grease over the sides.

3.5.5 Cover. Each fryer shall be equipped with a removable cover with handle suitable for covering the cooking vessel fabricated of the same material and finish as the cooking vessel (3.5.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

3.5.6 Automatic fry basket. Class 2 fryers shall be provided with two automatic fry basket lowering and raising mechanisms, each capable of independently and automatically lowering a small fry basket into the cooking vessel and raising the fry basket at completion of the cooking cycle. The fry baskets when not in the cooking mode shall be in the raised position. Each automatic fry basket mechanism shall work independently of the other and shall consist of an adjustable timer and activating cooking cycle switch. Each adjustable timer shall have a time range from 1 to 15 minutes for selecting desired cooking time and an integral push button cycling switch that electrically activates the automatic fry basket mechanism. It shall not be necessary to reset the timer after each cooking cycle. When the preset time cycle is complete, the fry basket shall automatically raise and remain in the raised position until the push button is activated again. Fryer controls, switches, moving parts and electrical circuits shall operate through a complete cooking cycle without malfunction, binding, or excessive looseness when tested as specified in 4.4.5. A complete cooking cycle is defined as the lowering of the fry basket into the cooking vessel and remaining there until the time cycle is complete then elevating the fry basket to the raised position.

3.5.7 Fuel system. The fuel system, including burners, shall be designed to efficiently burn natural or liquified petroleum gas (LPG) with appropriate conversion.

3.5.7.1 Natural gas. The unit shall be furnished to operate on natural gas. Main burners shall be provided with fixed orifices with orifice hoods or spuds that can be interchanged. The orifice hoods or spuds installed for natural gas shall be unpainted brass. An automatic pilot including a 100 percent shutoff shall be provided on each unit.

3.5.7.2 LPG. The contractor shall furnish black color-coded orifice hoods or spuds to convert the unit to operate on LPG. The contractor shall also furnish complete instructions for conversions to operate on LPG.

3.5.7.3 Accessories. A pressure regulator for natural gas conforming to Z 21.18 shall be furnished with each unit. The unit shall be furnished with a connector conforming to Z 21.45 and a quick disconnect conforming to Z 21.41. Means shall be provided to secure the metal flexible connector to the back of the unit when it is disconnected from the supply line. The connector length shall be 36 inches.

3.5.7.4 Automatic ignition. All burners shall be equipped with a means for automatic ignition of gas. An automatic pilot device, complete shutoff type, shall be supplied on each fryer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

3.5.8 Thermostat. Each deep-fat fryer shall be equipped with a variable thermostat, ranging from 200°/275° to 375°/400°F.

3.5.8.1 Overtemperature thermostat. A second or overtemperature thermostat shall be installed in the temperature control system to shut off the entire gas system when the fat temperature reaches a high limit of 430°-460°F. This thermostat shall be nonadjustable, manual resetting type and shall require relighting the pilot burner and manual resetting before operation can be resumed.

3.5.9 Electrical characteristics. Unless otherwise specified (see 6.2), class 2 fryers shall be designed for operation on a nominal 120-volt, 60 Hertz (Hz), system. The class 2 fryers shall be supplied with a 6 foot long power cord with a NEMA 5-15 plug.

3.5.10 Signal light. Each class 2 fryer shall be supplied with a timer(s) and a minimum of one temperature indicating signal light. The signal light shall operate on nominal 120-volt, 60 (Hz) system and shall indicate whether fryer burners are in operation. The timer(s) and signal light shall be mounted in a visible location on the front of the fryer.

3.5.11 Operation. Fryers shall not leak gas; and burners, controls and moving parts shall operate and perform as intended when tested as specified in 4.4.4.

3.6 Finish. All fryers shall be finished to conform to NSF standard No. 4.

3.7 Marking.

3.7.1 Identification plate. Each fryer shall have a corrosion-resistant metal nameplate permanently and legibly marked with the manufacturer's model and serial number and with the manufacturer's name or trademark, of such known character as to be readily identifiable to the manufacturer. The nameplate shall be permanently fastened to the outside front surface in an accessible location, or may be permanently fastened to the inside surface of the door. In addition, such information as required by ANSI Standard No. Z 83.13 shall also appear on this plate.

3.7.2 User's instruction plate. Each fryer shall bear a corrosion-resistant metal user's instruction plate, minimum thickness 0.020 inch, permanently fastened to the outside front or may be permanently fastened to the inside surface of the door. The plate shall be of sufficient overall size to contain the following information etched, embossed, or die stamped thereon in legible characters:

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the currentversion before use.

DEEP FAT FRYER

USER'S INSTRUCTIONS

1. If provided with drain valve, close valve tightly before filling cooking vessel to proper level with oil or fat.

S-F-700F

2. Turn on gas, light pilot, set thermostat for fat temperature desired, and heat for about 15 minutes before starting to cook food. Do not turn on the gas burner unless the heating surfaces are covered with fat or oil.

3. After food is fried, drain basket by hanging it on basket support.

4. Turn off gas immediately when through using fryer.

5. Do not allow burned crumbs to accumulate.

6. Do not let grease accumulate and harden on frame and body of cooking vessel.

7. Before fat is returned to cooking vessel, it shall be filtered.

8. Remove fat and all residue from cooking vessel using scraper or soft brush if necessary, then wash with hot soapy or detergent water, rinsed with clear hot water and dry thoroughly.

9. Clean cooking vessel at least once each week. Fill vessel with solution of mild washing compound, bring to boil, and let stand for several hours. Refill with clear water and boil again. Add 2 ounces of vinegar to the final cold-water rinse to neutralize any trace of alkalinity remaining from compound. Stir, drain, rinse, and wipe vessel with soft cloth.

10. Clean exterior of fryer with detergent solution or grease solvent.

11. Cover cooking vessel when not in use.

12. Do not bend flexible metal connector to less than 2-1/2 inch radius.

The above instructions shall be in characters not less than 3/32 inch high except the words "DEEP FAT FRYER" shall be in characters not less than 3/16 inch high; "USERS INSTRUCTIONS" shall be in characters not less than 1/8 inch high.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:19Z
Check the source to verify that this is the current version before use.

3.8 Workmanship. All components and assemblies of the fryer shall be free from dirt and other harmful extraneous material, burrs, slivers, rough die, tool and grind marks, dents and cracks. Castings, molded parts, and stampings, if used, shall be free of sand, fins, pits, blow holes and sprues. External surfaces shall be free from sharp edges and corners.

3.8.1 Metal fabrication. Metal used in the fabrication of the fryer shall be free from kinks. Forming and shearing shall not cause damage to the metal and shall be done neatly and accurately. Corners shall be square and true and all bends of a major nature shall be made with dies or fixtures to insure uniformity of size and shape.

3.8.2 Welding. The surface of parts to be welded shall be free from rust, scale, paint, grease and other foreign matter. Welds shall be smooth and free of cracks, burn holes, undercuts or incompleted fusion. All scale and flux shall be removed from the finished weld area.

3.8.3 Fastening devices. Threaded fastener and rivet holes shall be accurately punched or drilled and shall have burrs removed. Threaded fasteners shall not be broken, cracked or stripped and shall be securely torqued. Rivets shall fill the hole completely and the heads shall be in full contact with the surface of the member and concentric with the hole.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, the components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

4.2.2 End item visual examination. The end item shall be examined for the defects listed in table III. The lot size shall be expressed in units of fryers. The sample unit shall be one fryer. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE III End item visual defects

Examine	Defect	Classification Major	Minor
Standard product	Item not in accordance with manufacturers standard product except for changes necessary to comply with specification requirements	X	
Finish	Not as specified		X
Design, construction and workmanship (general)	Part or component missing	X	
grind marks	Any rough or sharp edges, burrs, slivers, or scratches; rough die or	X	
	Any component fractured, buckled, bent, punctured, malformed, or damaged	X	
	Component not readily accessible for servicing where required		X
	Functioning component that does not operate as intended	X	
	Protrusion on cabinet exterior surface	X	
	Material not as specified	X	
Drain	Drain handle interferes with draining vessel	X	
Flexible metal (gas line)	Not type specified	X	
	Means to secure hose when disconnected from supply line not provided	X	
Connector	Not provided	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

TABLE III End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Welding	Welds broken, porous, cracked, incomplete, or not ground smooth and polished	X	
	Any burn holes or material deformed	X	
	Scale or flux deposits not removed	X	
Controls	Not as specified, not accessible from front	X	
Hand valve for non-removable vessel (as applicable)	Interferes with removal of fat receiving vessel	X	
Identification markings	Missing, incomplete, not legible		X
Instruction markings	Missing, incomplete, not legible	X	
	Not as specified type or size, not affixed in prescribed manner		X

4.2.3 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of fryers. The sample unit shall be one complete fryer. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.2.4 End item testing.

4.2.4.1 Initial production unit testing. The initial production unit shall be tested as specified in 4.4.1, 4.4.2, 4.4.3, and 4.4.4. Any failure shall be cause for rejection of the fryer, for necessary design and construction changes, and for repetition of the above testing on the next produced fryer. The process shall be repeated until a fryer successfully passes the tests.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the current version before use.

4.2.4.2 Operational testing. The end items shall be tested as specified in 4.4.1, 4.4.4, and 4.4.5 (when applicable). The lot size shall be expressed in units of fryers. The sample unit shall be one fryer. The inspection level shall be S-4 and the AQL, expressed in units of defects per hundred units, shall be 4.0.

4.2.5 Packaging inspection. The inspection shall be in accordance with the quality assurance provisions of MIL-R-11337.

4.3 Certification examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.4 Methods of inspection.

4.4.1 Preparation for testing. The completely assembled fryer shall be connected to a gas supply of known Btu value. Class 2 fryers shall be operated using the electrical characteristics specified in 3.5.9. The cooking vessel shall be filled with the normal quantity of hydrogenated vegetable oil and the burner shall be ignited and tested as follows:

4.4.2 Production capacity test. The fryer shall be tested in accordance with ANSI No. Z 83.13 to determine conformance with potato production specified in 3.5.2. Any nonconformance with the specified requirements shall constitute failure of this test.

4.4.3 Volumetric test for vessels. All cooking vessels and fat draining vessels shall be filled with water, and the volumetric capacity observed to determine compliance with 3.5.3.2. Any noncompliance with the specified requirements shall constitute failure of this test.

4.4.4 Operational test. The fryer shall be operated at a temperature of 375°F through one cycle and tested for gas leaks and proper operation of burners, burner controls, and moving parts to determine compliance with the requirements specified in 3.5.11. Any noncompliance with the specified requirements shall constitute failure of this test.

4.4.5 Automatic fry basket test (class 2 only). With the class 2 fryer connected to a rated power source, operate each automatic fry basket mechanism through two complete cooking cycles for each of the following adjustable timer settings: 1,5,10, and 15 minutes. Operation shall be checked to determine compliance with 3.5.6. Any noncompliance with the performance requirements of 3.5.6 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:19Z
Check the source to verify that this is the currentversion before use.

5. PREPARATION FOR DELIVERY

5.1 Levels A, B, and C. Fryers shall be preserved, packaged, and packed for each level of protection in accordance with the applicable requirements of MIL-R-11337 (see 6.2).

5.2 Marking.

5.2.1 Civil agencies. In addition to any special marking required by the contract or purchase order, interior packages and shipping containers shall be marked in accordance with FED-STD-123.

5.2.2 Military agencies. In addition to any special marking required by the contract or purchase order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The fryers are intended for use in kitchens or galleys for deep fat frying food products.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a. Title, number, and date of this specification.
b. Type, size and class of fryer required (see 1.2).
c. Number and size of baskets, if other than specified (see 3.5.4).
d. Electrical current use, if other than specified (see 3.5.9).
e. Selection of applicable levels of preservation, packaging, and packing (see 5.1).

6.3 Recycled material. It is encourage that recycled material be used when practical as long as it meets the requirements of the specification (see 3.4).

6.4 Changes from the previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.5 Deletions. Model A, type II, sizes 1 and 2, grades A and B have been deleted since they are no longer required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review activities

Army - MD
Navy - MS, SA
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITIES

GSA - FSS
VA - OSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0690

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

NSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in ıbmitting comments and suggestions for improvements. All users of military standardization documents are invited to provide ıggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and ıailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was ɔo rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the roblems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an cknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being onsidered.

IOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of pecification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization ɔ waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

)EPARTMENT OF THE ARMY
my Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

)FFICIAL BUSINESS
'ENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
S-F-700F	Fryers, Deep Fat (Gas, Heavy Duty)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.