U-S-560B
April 28, 1972
SUPERSEDING
Int. Fed. Spec. U-S-00560A(GSA-FSS)
September 16, 1971

FEDERAL SPECIFICATION

SODIUM CHLORIDE TABLETS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers sodium chloride tablets for human ingestion in the prevention of heat cramps.

1.2 Classification. Sodium chloride tablets covered by this specification shall be of the following types, as specified (see 6.1).

Type I. Plain.
Type II. Impregnated.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

TT-C-495 - Coating, Exterior For Tinned Food Cans.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-676 - Boxes, Setup.
PPP-C-186 - Containers, Packaging and Packing for Drugs, Chemicals, and Pharmaceuticals.

Federal Standards:

Fed. Test Methods Std. No. 101 - Preservation, Packaging and Packing Materials, Test Procedures.
Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).
Fed. Std. No. 140 - Tablets (for Medicinal Purposes).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 6505

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

Military Specifications:

MIL-P-116 - Preservation, Methods of.
MIL-L-10547 - Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109 - Quality Assurance Terms and Definitions.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-668 - Sanitary Standards for Food Plants.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

21 CFR 1 - Federal Food, Drug, and Cosmetic Act.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

U.S. Department of Agriculture:

C&MS Visual Aid - 1 - Visual Aids for Inspection of Metal Containers.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

American Pharmaceutical Association:

National Formulary (N.F.).

(Application for copies should be addressed to the Mack Publishing Company, Easton, PA 18042.)

Association of Official Analytical Chemists:

Official Methods of Analysis, Eleventh Edition, 1970.

(Application for copies should be addressed to the Association of Official Analytica Chemists, P.O. Box 540, Benjamin Franklin Station, Washington, DC 20044.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

U.S. Pharmacopeial Convention, Inc.:

Pharmacopeia of the United States (U.S.P.).

(Application for copies should be addressed to the Mack Publishing Company, Easton PA 18042.)

3. REQUIREMENTS

3.1 Type I.

3.1.1 Material. The bulk salt component of the tablets shall be sodium chloride U.S.P. The tablets shall contain not more than 0.2 percent moisture. The tablets shall contain no potassium iodide and no drier (see 3.4).

3.1.2 Disintegrating agent. The disintegrating agent shall be cornstarch and shall be added in an amount not greater than 1 percent.

3.1.3 Disintegration time. Each tablet shall disintegrate within 2 minutes, when tested as specified in 4.3.2.

3.2 Type II.

3.2.1 Type II, sodium chloride tablets shall be uncoated tablets containing 0.648 gram (gm.) ± 0.03 gm. of sodium chloride. The bulk salt component of the tablets shall be sodium chloride U.S.P. The tablets shall contain not more than 0.2 percent moisture. The tablets shall contain no potassium iodide and no drier. The tablets shall be made by combining salt with nontoxic materials which meet the requirements of the Federal Food, Drug, and Cosmetic Act. The materials shall result in the formulation of a membraneous structure, controlling the dissolving rate of the tablets. All ingredients used in the manufacture of the tablets shall comply with the tests, standards, and requirements of the U.S.P. or N.F.

3.2.2 Dissolving time. Not more than 60 percent by weight of the tablet shall dissolve in 25 minutes and not less than 50 percent shall dissolve in 45 minutes when tested as specified in 4.3.2. Not less than 90 percent of the tablet shall dissolve in 180 minutes after immersion. The total disintegration time shall be not less than 70 minutes.

3.2.3 Color. If colored, the color used shall be a U.S. Certified color.

3.3 Dimensions. Each tablet shall be 13/32 inch in diameter and 0.20 inch in thickness.

3.4 Weight. Each tablet shall weigh 0.648 gm. ± 5 percent when tested in accordance with the U.S.P. Weight Variation Test for Tablets.

3.5 Storage stability. The tablets shall not disintegrate, block (stick together), or stain the container when tested as specified in 4.3.3.

3.6 Workmanship. The tablets and their containers shall be free from defects which detract from their appearance or may impair their usefulness.

3.7 Other requirements.

3.7.1 Civil agencies. The finished product shall be of high quality and shall be prepared in accordance with good commercial practice under sanitary conditions.

3.7.2 Military agencies. The product shall be processed in establishments meeting the requirements of MIL-STD-668. The product shall be prepared and processed with minimum delay between the various stages in production. The establishment shall meet the requirements of the solicitations regarding the suitability of the manufacturing plant.

3.8 All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Sampling for inspection. Unless otherwise specified in the procurement document (see 6.1), sampling shall be in accordance with MIL-STD-105.

4.2 Inspection.

4.2.1 General. Samples shall be carefully inspected for defects in material, workmanship, dimension, finish, and other applicable requirements.

4.2.2 Plant quality control. The passing as satisfactory of any detail of processin or materials shall not relieve the contractor of responsibility for faulty workmanship or materials which may be discovered at any time prior to final acceptance.

4.2.3 Final inspection. Unless otherwise specified (see 6.1), final inspection shall be made after delivery to the initial point of domestic destination.

4.2.4 Definitions. MIL-STD-109 or Fed. Std. No. 140 shall apply for definitions of quality assurance terms used herein. For Defense Personnel Support Center procurements the definitions of Fed. Std. No. 140, paragraph S4-2 and S4.3 shall apply. Otherwise, MIL-STD-109 is valid.

4.2.5 Pre-acceptance inspection (plant sanitation inspection).

4.2.5.1 Civil agencies. Inspection of plants producing the product shall be conducted upon request of the contracting officer to the appropriate Government inspection agency. Award of contracts shall be limited to establishments known to maintain proper sanitary conditions or which have received prior sanitary approval recommended by the inspection agency.

4.2.5.2 Military agencies. For Defense Personnel Support Center procurements, plants not complying with housekeeping provisions of the solicitation and contract are not acceptable.

4.2.6 Acceptance inspection. Inspection required and determination of acceptability shall be in accordance with housekeeping provisions set forth in MIL-STD-105, except where otherwise indicated.

4.2.7 Inspection of components (examination and testing). Quality assurance provisions for components and materials shall be in accordance with 4.2.7.1 and subsidiary specifications to the extent applicable, except that this specification shall govern in the event of conflict.

4.2.7.1 Testing of components. Testing of components described in this specificatio shall be in accordance with table I. Testing of components and inprocess testing and examination of tablets shall be in accordance with all subparagraphs of S6.6 of Fed. Std. No. 140.

TABLE I. Testing of components

Component	Sample unit	Lot size expressed in	Inspection level	Characteristics	Results reported	Test reference and requirement para.
Salt (component of type II tablets)	1 pound	Pounds	S-2	Moisture	Nearest 0.01 percent	3.2.1 4.3.1
				Sodium chloride	Nearest 0.1 pound/ percent	4.3.1
Cans	1 can	Cans	S-2	Tin plate 1/	Nearest 0.0 pound base box 1/	5.1.2.3

1/ Can coating, when required, shall be in accordance with the applicable subsidiary specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

4.2.8 Inprocess inspection. Inprocess examination shall be performed during the manufacture of sodium chloride tablets to ascertain compliance with 3.1.1, 3.1.2, and 3.2.1 as concerns kinds and amount of ingredients used in the manufacture of sodium chloride tablets, as applicable to the type being procured. Record of formulation shall be maintained reflecting the kinds and amounts of ingredients being utilized in the manufacture of the sodium chloride tablets. Nonconformance with requirements as may be determined by actual inprocess examination or as indicated by a review of formulation records, shall be cause for rejection of the involved product.

4.2.9 Examination of the end item. Classification of defects found during examination shall be in accordance with tables II through VI and 4.2.9.1 and 4.2.9.2. The inspection levels, sample units, expression of lot sizes and the acceptable quality levels (AQLs) for the above tables shall be as shown below. AQLs shall be expressed in defects per hundred units. Examination of the end item shall be in accordance with Fed. Std. No. 140, paragraph S6.9 including all subparagraph thereto.

TABLE II. Examination of the end item

Table	Inspection level	Sample unit	Lot size expressed in	AQL Major	AQL Minor
III	I	1 Unit package	Unit Package	1.5	4.0
IV	S-2	1 tablet from a unit package	Unit package	1.5	---
V	S-2	1 Shipping container	Shipping container	---	2.5
VI	S-2	1 Unit package	Unit package	1.5	4.0
VII	S-2	1 Shipping container	Shipping container	2.5	4.0

TABLE III. External examination of can 1/

Categories Major	Minor	Defects	Defects applicable to cans 1/	Defects applicable to commercial containers (level C)
151		Not type, style, or size specified	X	X
152		False or improper seam.	X	
153		Improperly closed.	X	X
154		Cable cut.	X	X
155		Pitted rust 2/.	X	
156		Severe dent.	X	
	201	Moderate dent.	X	
	202	Excessive amount of flux on ends or sides. 3/	X	
	203	Not clean. 4/	X	X
157		Pry out seal of can with screw closure, missing, insecure, or punctured.	X	
158		Snap on cap of can insecure.	X	
159		Objectionable odor.		X
160		Nomenclature missing, incorrect, or illegible.		X
	204	Labeling information other than nomenclature missing, incorrect, or illegible.		X

1/ Classification of can defects shall be in accordance with USDA - C&MS Visual Aid-1.
2/ Rust that can be removed by wiping with a soft cloth will not be considered as pitted rust.
3/ Traces of flux at edges of soldered areas, normally encountered in can manufacturing, but not enough to cause corrosion, will not be considered excessive.
4/ Can showing a very thin film of grease which is discernible to the touch, but not readily discernible visually, are considered to be clean.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

TABLE IV. Examination for net weight

Category	Defect
Major:	
151	Weight of tablet not as specified (including tolerance).

TABLE V. Examination of count of cans and arrangement of cans

Category	Defect
Minor:	
201	Number of tablets not as specified. 1/

1/ The average of the determinations shall be not less than required count.

TABLE VI. Examination of product 1/ 2/, and interior of can

Category		Defect
Major	Minor	
151		Moist.
152		Not clean.
153		Objectionable odor or taste.
154		Tablet not size specified.
	201	Broken tablet (tablet weighs less than eight grains).
	202	Tablet not smooth.
155		Inside of can rusted, not completely enameled, or enamel easily abraded with fingernail. 3/

1/ Examine 10 tablets from a sample unit. Acceptability of the lot will be determined by the total number of defective tablets from the total sample of tablets for the require AQL.
2/ Presence of foreign material (i.e., glass, stones, wood, etc.) in any sample unit shal be cause for rejection of entire lot.
3/ If necessary, cut can open to make determination.

4.2.9.1 Examination of can coating. When exterior of can is required to be in accordance with TT-C-495, examination of can coating shall be in accordance with that specification.

4.2.9.2 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing, and marking comply with the requirements in sectio 5. Defects shall be scored in accordance with table VII. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot.

TABLE VII. Classification of preparation for delivery defects

Category		Defect
Major	Minor	
151		Container not as specified.
	201	Markings omitted; incorrect; illegible; improper size, location, sequence, or method of application.
	202	Any component missing or damaged.
152		Case liner not furnished on level A packing.
	203	Quantity in intermediate packages and shipping containers not as specified.
153		Weight limit of shipping container exceeded.
154		Partitions not furnished in fiberboard boxes when required.
	204	Inadequate application of components such as incomplete closure of container flaps, loose strapping, or distortion of container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

4.2.10 Sampling procedures and acceptance criteria for testing of finished product. The finished product shall be tested for sodium chloride, moisture content, storage stability, and disintegration and dissolving time, to determine compliance with the applicable requirements of 3.1.1, 3.1.3, 3.2.1, 3.2.2, and 3.5. Tests shall be performed in accordance with the applicable subparagraphs of 4.3. Test results shall be reported to the nearest unit or decimal as specified for the specific requirement. Sampling of each lot for tests required shall be in accordance with level S-1 from the lot size expressed in terms of the applicable unit package. Requirements shall be applicable to the sample unit, except that the storage stability test shall be performed on a composite of 50 tablets selected from the sample unit packages, which represent the lot. The acceptance number of each test shall be zero. The sample shall be placed in noncrushable moisture-proof containers. Sampling procedures and acceptance criteria for testing of finished tablets shall be in accordance with Fed. Std. No. 140, paragraph S6.8, including all subparagraphs thereto.

4.2.11 Standby test samples. The Government reserves the right to withdraw and hold standby test samples of components or finished product or both (quantity of which shall be not more than twice that of the original Government sample) for inspection purposes. These samples, if not used, will be returned to the vendor.

4.3 Tests. Test procedures and controls which differ from those specified herein, may be used by the contractor if they provide a quality assurance equivalent to that specified. If the Government inspection activity determines that such procedures and controls do not provide, as a minimum, such quality assurance, the contractor will use the test procedures set forth herein. In case of dispute as to test results, the test methods specified herein will govern. Alternate test procedures shall not be acceptable.

4.3.1 Chemical analyses. Chemical analyses, when required by the purchaser in the examination or testing of samples and deliveries under this specification, shall be made in accordance with the following methods from Official Methods of Analysis; Eleventh Edition 1970.

Test	Method of analysis	
	Source	Method
Moisture	Chapter: Waters, Minerals and Salt. Section: Salt.	Moisture
Sodium chloride	Chapter: Waters, Minerals and Salt. Section: Mineral Waters.	Chloride (calculate sodium chloride)

NOTE: Assay requirements for Defense Personnel Support Center procurement shall be based upon the metric system.

4.3.2 Disintegration and dissolving time. Disintegration and dissolving time shall be determined in accordance with 4.3.2.1 and 4.3.2.2, as applicable.

4.3.2.1 Type I, plain. Place a salt tablet in a beaker containing 50 milliliters (ml.) of distilled water at 70° ± 2°F. Note the time for the tablet to disintegrate completely.

4.3.2.2 Type II, impregnated. Six tablets shall be tested. If 1 or 2 tablets fail to meet the requirements of 3.2.2, repeat the test on twelve additional tablets. Not less than 16 tablets of the total 18 tablets shall comply, when tested as follows: Dissolving time shall be determined by suspending a weighed tablet on a 10-mesh screen at the 80 ml. mark level in 100 ml. of distilled water at 70° ± 2°F., using a 100 ml. cylinder. The tablet in separate tests shall be removed from the solution at 25-, 45-, 70-, and 180-minute intervals and the salt in the solution shall be determined as specified in 4.3.1, or by an alternate electrical conductivity method.

4.3.3 Storage stability. Fifty tablets shall be placed in a covered weighing bottle (approximately 50 ml.). The weighing bottle with tablets shall then be placed in an oven maintained at 160° ± 2°F. for 3 days. After this period, the tablets and container shall be removed from the oven, cooled to room temperature, and the tablets and container examined.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.1). Cans, bottles, and dispensing units shall comply with the requirements in PPP-C-186, paragraph 3.2 and subparagraphs thereunder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

5.1.1 Unit of issue. The unit of issue shall be as shown in table VIII, column 1.

TABLE VIII. Packing and packing requirements

Unit of issue	Unit Packaging Para. No.	Intermediate packaging Quantity	Intermediate packaging Para. No.	Shipping container Quantity	Shipping container Para. No. 1/
Col. 1	Col. 2	Col. 3	Col. 4	Col. 5	Col. 6
100's Bottle	5.1.2.1	24	5.1.2.1.2	96	5.2.2.2
200's Hermetically sealed	5.1.2.2	Not required		48	5.2.2.1.1
500's Can	5.1.2.3 & 5.1.3	Not required		24	5.2.2.1
500's Dispenser	5.1.2.4	12	5.1.2.4.2	48	5.2.2.2
1000's Bottle	5.1.2.1	12	5.1.2.1.2	24	5.2.2.2
1000's Dispenser	5.1.2.4	6	5.1.2.4.2	24	5.2.2.2
1500's Dispenser	5.1.2.4	6	5.1.2.4.2	24	5.2.2.2

1/ Level A packing requirements are included in paragraph 5.2.1.

5.1.2 Level A.

5.1.2.1 Bottles. The number of tablets specified (100 or 1000) shall be packaged in a bottle complying with PPP-C-186, group A, class 1, type e, style 2, grade 1, closure A, B, or F, seal A or B.

5.1.2.1.1 Packaging of bottles. At the option of the supplier, each bottle may be packaged as specified in 5.2.5 or PPP-C-186.

5.1.2.1.2 Intermediate packaging of bottles. The number of bottles indicated in table VIII, column 3, shall be intermediate packaged in a fiberboard box conforming to PPP-B-636, double-faced A or C flute, minimum grade 200, class domestic. Carton design shall include partitions. Partitions shall be full or shoulder height, half-slotted style, fabricated of the same material as the carton. The partitions shall form a cell for each container. Partitions shall not be required when packaging specified in 5.1.2.1.1 is furnished.

5.1.2.2 Hermetically sealed packages. Fifty tablets shall be packaged in one continuous strip of laminated aluminum foil wherein each individual tablet is hermetically sealed. The aluminum foil shall be not less than 0.7 mil.(0.0007 inch) thick, shall be olive drab in color and nonreflecting on the outside surfaces. The layers of the aluminum foil shall not separate in handling, storage, use, or testing as specified. Splicing in any portion of the strip is not permitted. Each tablet shall be hermetically sealed within its own pocket (cell). Each pocket (cell) shall be of the minimum size necessary to protect the tablet and meet specified tests, but in no event shall exceed 1-3/8 inches by 1-3/8 inches, overall, including the heat sealed area. Each pocket shall be separated from its adjoining pocket by a single row of perforations to enable its removal from the strip easily and without disturbing the heat-seals of the pocket removed or the heat-seals of adjoining pockets in the strip. On the other hand, the perforations shall not rupture when the strip is folded at the perforations. Each pocket of the aluminum foil strip shall be capable of passing the test in 4.4.3.1 and 4.4.3.1.1, and, for test results in 4.4.3.2 and 4.4.3.4 of MIL-P-116. The required test techniques are paragraph 6.2 and all subparagraphs and paragraph 6.6 and all subparagraphs, with the exception of subparagraph 6.6.2 of referenced Method 241 of Fed. Test Method Standard No. 101.

5.1.2.2.1 Unit packaging of hermetically sealed packages. Four strips of 50 tablets each shall be rolled into a single, four-segment roll of 200 tablets, and packaged in a carton of appropriate size and design to accomodate the roll. The carton shall be constructed in accordance with PPP-B-566, or PPP-B-676, except that commercial colors are acceptable. Closure of carton shall be adequate to prevent accidental opening.

5.1.2.3 Cans. Five-hundred tablets shall be packaged in a square, rectangular, or round metal can having soldered side seams and compound-lined double-seamed ends. The top shall be fitted with a screw-neck opening, approximately 1-1/4 inches in diameter. The closure shall consist of a pry-out inner seal and a curled-edge, knurled screw cap fitted with a paper flange opening. Alternatively, the top of the can shall be fitted

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

with a paper flange opening. Alternatively, the top of the can shall be fitted with a stepped flange opening and closed with a curled-edge, compound-lined, snap-on cap, or a double friction top with an overseal. The cans shall be made throughout from not less than commercial 0.50 pound per base box electrolytic tin plate. The cans shall be coated on the inside with an enamel suitable for the product and overall outside with a coating conforming to MIL-C-10506, type I or II, as specified (see 6.1).

5.1.2.4 Dispenser container. The number of tablets specified (500, 1000, or 1500) shall be packaged in a plastic or 3-ply cardboard dispenser of the type designed to dispense one tablet at a time. Cardboard containers shall have rust-proof metal ends. Dispensers shall be complete with wall bracket and sufficient screws.

5.1.2.4.1 Packaging of dispenser containers. At the option of the supplier, each dispenser container may be packaged as specified in 5.2.5 of PPP-C-186.

5.1.2.4.2 Intermediate packaging of dispenser containers. Twelve dispenser containers, each containing 500 tablets, shall be intermediate packaged in a fiberboard box conforming to PPP-B-636, double-faced A or C flute, minimum grade 200, a filler pad between the top and bottom layer; partitions are not necessary. Carton design for 1000's and 1500's size dispensers shall include partitions. Partitions shall be full or shoulder height, half-slotted style, fabricated of the same material as the carton. The partitions shall form a cell for each container. Partitions shall not be required when packaging specified in 5.1.2.4.2 is furnished. Six dispenser containers each containing 1000 or 1500 tablets, shall be intermediate packaged in a fiberboard box conforming to PPP-B-636, double faced, A or C flute, minimum grade 200.

5.1.3 Level B. Unit packaging shall be as specified for level A, except that paragraph 5.1.2.3 is modified to permit a can with a commercial exterior coating when level B is specified. When specified, 500 or 1500 (as specified, see 6.2) salt tablets shall be packaged in chipboard cartons.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 Level A. Containers described in 5.2.2 as level B shipping containers shall be packed in an exterior container designed for type 2 load and constructed in accordance with PPP-B-585, style 3, for class 3 use; PPP-B-601, table II, using type III, class 1 plywood; or PPP-B-621, table III. The number of items in the shipping container will be governed by the weight limitation for the particular box being used. Each box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraph of the appendix thereto. Strapping, when required, shall be in accordance with the appendix of the applicable box specification. (NOTE: Strapping shall not be required for shipments forwarded to a receiving activity within the continental limits of the United States for storage and redistribution.)

5.2.2 Level B.

5.2.2.1 Items in unit packages (except hermetically sealed). The number of unit packages indicated in table VIII, column 5, packaged as specified in 5.1, shall be packed in a fiberboard box conforming to PPP-B-636, double-faced, A or C flute, grade not less than 200. Carton design shall include partitions. Partitions shall be full or shoulder height, half-slotted style, fabricated of the same material as the carton. The partitions shall form an individual, snug-fitting cell for each container. Partitions shall not be required when unit packages specified in 5.1.2.1.1 and 5.1.2.4.1 or in intermediate containers are furnished.

5.2.2.1.1 Hermetically sealed packages. The number of hermetically sealed packages indicated in table VIII, column 5, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic, grade not less than 200.

5.2.2.2 Items in intermediate packages. The number of unit packages indicated in table VIII, column 5, intermediate packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard box conforming to PPP-B-636, class domestic, grade not less than 200.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Sodium chloride tablets, packaged as specified in 5.1, shall be packed to assure carrier acceptance and safe delivery at destination at lowest rates, in containers complying with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.2.4 Packing variation permitted. If the required number of units to be shipped is less than the number of units specified to be overpacked in an exterior container , the number of units ordered shall be packed in the kind of container specified for the applicable level of packing.

5.3 Marking.

5.3.1 Civil agencies.

5.3.1.1 Unit packages. Any commercial labeling that complies with the Federal Food, Drug and Cosmetic Act, is acceptable.

5.3.1.2 Shipping containers. Shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies.

5.3.2.1 Hermetically sealed packages. Each individual pocket shall be permanently and legibly marked in black with the following information:

(a) SALT TABLETS.
(b) SODIUM CHLORIDE TABLETS.
(c) 0.648 gm (10 gr).
(d) Lot No._____
(e) Name and address of the manufacturer.

The labeling shall appear in the center of the pocket but shall not extend into the heat-sealed area. Repeat information may be stamped across the perforations of the pocket, provided it does not impair the legibility of the centrally positioned pocket label. The above marking shall comply with the test specified in 4.3.3 of PPP-C-186.

5.3.2.1.1 Unit packages of hermetically sealed packages. Each unit box containing a single roll, consisting of four strips of 50 tablets each shall be marked with the following information:

(a) The item identification designated as SODIUM CHLORIDE TABLETS, IMPREGNATED (when applicable).
(b) The synonym SALT TABLETS.
(c) The weight per tablet expressed as "0.648 gm (10 gr.)".
(d) Stock number.
(e) Lot or control number.
(f) Name and address of the manufacturer. When the manufacturer is not the contractor the name and address of the contractor shall also appear. When both names are placed on the label, the following designation shall precede the names: "MFR" for the manufacturer "CONTR" for the contractor.
(g) The unit of issue and quantity designated as "1 BOX (4 strips of 50 tablets)".
(h) Date of manufacture.

NOTE: Labeling shall be in accordance with the requirements of the Federal Food, Drug, and Cosmetic Act applied to intermediate and unit containers.

5.3.2.2 Cans, bottles, and dispensers. Each can, bottle, and dispenser container shall be marked with the following information:

(a) The item identification designated as SODIUM CHLORIDE TABLFTS IMPREGNATED.
(b) The synonym SALT TABLETS, IMPREGNATED (when applicable).
(c) The weight per tablet expressed as "0.648 gm (10 gr)".
(d) The number of tablets in the container.
(e) Stock number.
(f) Lot or control number.
(g) Name and address of the manufacturer. When the manufacturer is not the contractor, the name and address of the contractor shall also appear. When both names are placed on the label, the following designation shall precede the names: "MFR" for manufacturer and "CONTR" for contractor.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:20Z
Check the source to verify that this is the current version before use.

(h) Date of manufacture.
(i) The statement "Take one or two tablets with a drink of water. Use four to six times daily, as needed. Swallow whole".

5.3.2.2.1 Unit packages of bottles and dispensers. When bottles and dispenser containers are packaged as specified in 5.1.2.1.1 and 5.1.2.4.1, each unit package shall bear the same markings as specified in 5.3.2.2.

5.3.2.3 Intermediate packages. Each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Lot (control) number, contract or purchase order number, and name of the contractor shall be shown.

5.3.2.4 Exterior containers. Exterior containers shall be marked in accordance with MIL-STD-129. Date of manufacture shall be shown in lieu of date packed. Lot (control) number shall be shown.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and quantity of tablet desired (see 1.1 and 5.1.3).
(c) Sampling for inspection, if other than MIL-STD-105 (see 4.1.1).
(d) If final inspection made is other than after delivery to the initial point of domestic destination (see 4.2.3).
(e) Level of packaging and packing required (see 5.1 and 5.2).
(f) Type of exterior can coating required (see 5.1.2.3).
(g) Type of unit package desired (see table VIII).
(h) Quantity in unit package (see table VIII).

MILITARY CUSTODIANS:

Army-GL
Navy-SA
Air Force-67

Review activities:

Army-GL
Navy-MC,SA
Air Force-67
DSA-DPSC

User activities:

Army-67
DSA-DPSC

Preparing activity:

GSA-FSS

Coordinating activities:

GSA-FSS
HEW-FDA
VA-DMS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 15 cents each.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:20Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:20Z
Check the source to verify that this is the current version before use.