V–M–81b
DECEMBER 15, 1948
SUPERSEDING
Fed. Spec. V-M-81a
August 29, 1939

FEDERAL SPECIFICATION

MATTRESSES; COTTON (FELTED)

This specification was approved by the Director, Bureau of Federal Supply, for the use of all departments and establishments of the Government.

1. CLASSIFICATION

1.1 Types.—Felted cotton mattresses covered by this specification shall be of the following types, as specified:

Type I.—With plain box edge.

Type II.—With rolled box edge.

Type III.—With plain edge, not boxed.

1.2 Grades. — Felted cotton mattresses covered by this specification shall be of the following grades, as specified:

Grade A.—All cotton felt.

Grade B.—75 percent linters and 25 percent cotton felt.

Grade C.—60 percent linters and 40 percent cotton felt.

Grade D.—All linters felt.

1.3 Sizes.—The mattresses shall be furnished in the sizes shown in table I or other sizes, as specified. (See 3.8.)

2. APPLICABLE SPECIFICATIONS AND OTHER PUBLICATIONS

2.1 Specifications. — The following Federal Specifications, of the issues in effect on date of invitation for bids, form a part of this specification:

V–T–276—Thread; Cotton.

UU–P–271—Paper; Kraft, Wrapping, Waterproofed.

CCC–D–771—Duck; Cotton, Plied-Yarns (Army, Numbered, and Tent-Duck).

CCC–T–191—Textiles: General Specifications, Test Methods.

CCC–T–351—Ticking; Mattress and Pillow.

DDD–S–751—Stitches; Seams; and Stitching.

LLL–B–631—Boxes; Fiber, Corrugated (for Domestic Shipment).

LLL–B–636—Boxes; Fiber, Solid (for Domestic Shipment).

2.2 Other publications. — The following U. S. Department of Agriculture publications, of the issues in effect on date of invitations for bids, form a part of this specification:

The Development and Use of Standards for Grade, Color, and Character of American Cotton Linters.

Miscellaneous Publication No. 310—The Classification of Cotton.

(Copies of Federal specifications and the Federal Specifications Index may be obtained upon application, accompanied by postal note, money order, coupon, or cash, to the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Prices may be obtained from the Superintendent of Documents.)

(Copies of U. S. Department of Agriculture publications may be obtained upon application to the U. S. Department of Agriculture, Cotton Branch, Production and Marketing Administration, Washington 25, D. C.)

2.3 Specifications and publications applicable only to individual departments are listed in section 7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials.

3.1.1 *Linters.*—Linters shall be new (not previously used), shall conform to United States standard grade No. 2-high for grade B mattresses, and to United States standard grade No. 3-middle for grade C and grade D mattresses. (See U. S. Department of Agriculture pamphlet, "Development and Use of Standards for Grade, Color, and Character of American Cotton Linters.")

3.1.2 *Cotton.*—The cotton shall be new (not previously used), shall have a staple length of not more than $\frac{13}{16}$ inch nor less than ½ inch, and shall be not lower in grade than any of the following United States standard grades for cotton: No. 7 or Low Middling, No. 7 or Low Middling Spotted, No. 4 or Strict Middling Gray (see U. S. Department of Agriculture Miscellaneous Publication No. 310). The use of re-ginned cotton shall be permitted provided the re-ginned cotton is equivalent in grade to United States standard grades for cotton: No. 7 or Low Middling, No. 7 or Low Middling Spotted, or No. 4 or Strict Middling Gray. Tinged or stained cotton shall not be used.

3.1.3 *Felt.*—The felt shall be thoroughly dusted and well garnetted so as to produce unbroken laminated sheets of interlaced garnetted felt.

3.1.3.1 *Grade A.*—Felt for grade A mattresses shall be 100 percent cotton conforming to the requirements of paragraph 3.1.2.

3.1.3.2 *Grade B.*—Felt for grade B mattresses shall be made of a blend of not more than 75 percent of United States standard grade No. 2-high or better linters as specified in 3.1.1 and not less than 25 percent cotton conforming to the requirements of 3.1.2.

3.1.3.3 *Grade C.*—Felt for grade C mattresses shall be made of a blend of not more than 60 percent United States standard grade No. 3-middle linters or better as specified in 3.1.1 and not less than 40 percent cotton conforming to the requirements of 3.1.2.

3.1.3.4 *Grade D.*—Felt for grade D mattresses shall be made from linters not lower in grade than United States standard grade No. 3-middle or better as specified in 3.1.1, with the addition of cotton, if desired, not lower in grade than that specified in 3.1.2.

3.1.4 *Ticking.*—Ticking shall be of the following materials, as specified in the invitation for bids:

(1) Ticking conforming to Federal Specification CCC–T–351, type II, except that widths shall be as provided in 3.2 hereof, or as specified in the invitation for bids.

(2) Cotton duck conforming to Federal Specification CCC–D–771, type III, commercially designated 8-ounce weight on basis of 28½ inch width (10 to 11 ounces per square yard).

3.1.5 *Thread, sewing.*—The thread shall be unbleached cotton thread conforming to Federal Specification V–T–276, type IA1, 3-cord, ticket No. 30.

3.1.6 *Twine (for hand stitching of side, end, and roll-edge).*—The twine shall be waxed cotton twine having a breaking strength of not less than 20 pounds, single strand test.

3.1.7 *Tufting twine or tape.*—Cotton or flax tufting twine having a breaking strength of not less than 32 pounds or a single ⅝-inch tape having a breaking strength of not less than 50 pounds shall be used.

3.2 Mattress case.—The top and bottom sections of the mattress case ticking shall each be made up of not more than two longitudinal pieces, properly matched and sewn together. Cross seams shall be prohibited. The blue stripe of ticking conforming to type II of Federal Specification CCC–T–351 shall run lengthwise of the mattress case. The distance between the seams forming the box edge shall be $2 \pm \frac{1}{2}$ inches less than the thickness of the mattress when measured as described in 4.4. The box edge, if separate, shall be formed of not more than four sep-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

arate pieces. When more than one piece is used in constructing the box edge, the pieces shall be of such length that all joining seams shall be at a corner of the mattress and the pattern shall be properly matched. On type I and type III mattresses, corners shall be of the square box type. Corners on type II mattresses shall be slightly rounded to permit the use of a roll edge machine.

3.3 Stitches and seams. — The following stitch and seam types shall conform to the requirements of Federal Specification DDD–S–751.

3.3.1 *Stitches.*—All machine stitching for seaming the ticking shall be made with stitch type 301 or 401 using 30/3 cord unbleached cotton thread with not less than 10 stitches per inch.

3.3.2 *Seams.*—The ticking shall be seamed with seam type LSb–2 or SSa–1. The closing end shall be seamed with seam type SSc–1.

3.4 Distribution of felt.—From 80 to 90 percent of the felt batts shall be distributed in layers of unbroken laminated sheets to produce uniform thickness. The remainder shall be uniformly and equally distributed over the middle one-third of the length of each face and the full width of the mattress to provide crowning.

3.5 Tufting. — Mattresses shall be well tufted on both sides with twine (see 3.1.7), tape, tying tufts, or tape with a corrosion-resistant metal locking strip, securely fastened to each end. The tying tufts shall be drawn through both sides of the mattress and knotted. Tufts shall be drawn on both sides to a length not more than the thickness of the mattress, when measured as described in 4.4, minus 2 inches. In passing through the ticking the up-and-down twine or tape shall be sufficiently far apart to hold securely and avoid ripping and tearing of the intervening ticking. (Eyelets or cotton tufts will be cause for rejection.) Tufts shall be given diamond spacing and shall be not more than 8 inches apart.

3.6 Labels.—Each mattress shall have a label attached to conform to the legal requirements of the state in which the mattress is manufactured. Each mattress also shall have a contractor's cloth label to comply with the requirements of each procurement agency.

3.7 Standard samples.—When so specified, the finished mattresses shall conform in quality, workmanship, and appearance to the standard samples established by the procurement agency concerned.

3.8 Sizes.—Unless otherwise specified, dimensions and weights shall conform to the requirements in table I for each size. Other sizes, when required, shall be of the length, width, thickness, and weight stated in the invitation for bids, within the tolerances given in table I.

TABLE I.—*Sizes*

Size number	1	2	3	4	5	6	7	8	9	10	11	12
Width, ± ½ inch ..... inches	26	27	30	31	33	34	36	36	38	39	53	54
Length, ± ½ inch ..... "	76	73	76	78	75	76	78	84	75	78	75	78
Thickness, approx ..... "	3	4	4	4	6	4	4	4½	6	4½	6	4½
Weight, minimum ..... pounds	14	28	25	23	39	38	38	37	47	38	66	52

3.9 Hand stitching (side and end).

3.9.1 *Two-row finishing stitches.*—Type I mattresses shall have not less than the number of stitches given in table II. When sizes not tabulated are specified, the number of stitches shall be interpolated from table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

TABLE II.—*Number of hand stitches*

Size number	1	2	3	4	5	6	7	8	9	10	11	12
Stitches per single row, minimum:												
On each side	(1)	47	49	51	49	49	51	55	49	51	49	51
On each end	(1)	20	21	22	23	24	26	26	27	28	38	38

(1) Type II mattresses only.

3.9.2 *Roll edge stitching (type II mattresses).*—Roll edges shall be stitched with not less than two stitches to every 4 inches.

3.10 Workmanship.—Workmanship shall be first class in every respect. The use of oil in the fabrication of felt will not be permitted. The cotton felt shall be distributed in layers throughout the mattresses so as to produce a uniform thickness except for crowning and tufts, and side stitches shall be evenly spaced and drawn. The finished mattresses shall be free from defects affecting their appearance or which may impair their serviceability.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Sampling of finished mattresses.—Unless otherwise specified, one mattress of each type, grade, and size offered for delivery shall be taken at random for inspection and tests. (See 7.2.4.)

4.1.1 *Sampling of components.*—Samples of thread, stitching twine, and tufting twine or tape representative of the lot of mattresses offered for delivery shall be taken for inspection and tests to determine compliance with 3.1.5, 3.1.6, and 3.1.7.

4.2 Factory inspection.—Unless otherwise specified, raw materials in process of manufacture and the finished mattresses may be subject to preliminary factory inspection at the point of production. Final inspection of the finished mattresses shall be made either at the point of production or at a point of delivery, as designated by the procuring agency. The contractor shall inspect all finished mattresses prior to delivery for final inspection. (See 7.2.5.)

4.3 Felt.—Unless otherwise specified, the cotton and/or linters shall be examined for compliance with 3.1.3 through 3.1.3.4 by classifiers licensed by the U. S. Department of Agriculture; or representative samples, each weighing not less than ½ pound, of the cotton and/or linters and of the felt may be forwarded to the administrative office concerned at Washington, D. C., where inspection by the proper board of the U. S. Department of Agriculture will be obtained. The opinion of this board as to the true grade or quality will be final.

4.3.1 *New cotton.*—In cases of dispute as to whether or not felt contains new cotton, a sample shall be examined under an ultra-violet light as follows:

A sample approximately 5 x 5 x 1 inch of the garnetted felt shall be prepared in such a manner as to expose a fresh surface. Comparison specimens of known history shall be similarly prepared. These shall include new unused cotton felt (less than 2 years old), old unused cotton felt (preferably more than 5 years old), and old used cotton felt (taken from used mattresses over 5 years old). The inspection sample and comparison specimens shall be exposed in a dark room for at least 5 minutes to ultra-violet radiation within the range of 3300 to 3900 Angstrom units (see 6.5). The distance between the specimens and light filter shall be 3 to 5 inches. After irradiation, the fluorescence of the specimens shall be observed and compared. New unused cotton felt exhibits a uniform, purplish fluorescence over the entire surface with no background color evident. In old unused cotton, the surface fluorescence tends to diminish and a yellowish or ivory background predominates. Old used felt presents a somewhat

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

stronger yellow background and may exhibit strong spotty fluorescence indicative of staining or contamination.

4.4 Measurement of thickness.—Thickness shall be taken as the average of measurements taken at each of the four corners of a mattress, made by determining the free height under the corner of an 18-inch square wood panel weighing 4 pounds and resting on the mattress, with two edges over the adjacent edges of the mattress.

4.5 Measurement of length and width.—Length and width shall be taken as the average of three measurements in each direction. Before measuring, mattresses shall be shaken out after removal from cartons or bales, and laid in a flat position.

4.6 Tufting twine or tape.—The strength of the tufting twine or tape shall be determined on a motor-driven machine equipped with grips of the drum type not less than 1 inch in diameter. The distance between the centers of the drums at the start of test shall be 10 ± ¼ inches. The rate of travel of the leading drum shall be 12 ± 2 inches per minute.

5. PREPARATION FOR DELIVERY

5.1 Packing.

5.1.1 *For domestic shipment.*—Unless otherwise specified, mattresses shall be bundled in noncompressed bales or packed individually in corrugated or solid fiberboard boxes as follows:

5.1.1.1 *Bales.*—Unless otherwise specified, three mattresses, full-length, shall be wrapped together in waterproof paper conforming to the requirements of Federal Specification UU–P–271, type C. Mattresses shall be so wrapped that the paper will overlap all edges not less than 5 inches. All seams and overlaps shall be securely sealed by means of a water-resistant tape or adhesive. The closure shall have a water resistance equal to that of the body material. The wrapped bundle shall be further secured by tying with 2-ply twisted jute, sisal, or other suitable cord, having a tensile strength of not less than 288 pounds. The cord shall be applied in one length so as to divide the length of the bundle into four equal segments and the width into two equal segments. A secure knot shall be made at each crossover of the cord. The completed bundle shall be covered with not less than 40-inch 2.55-yard-per-pound Osnaburg tubular cloth. Each end shall be evenly gathered and shall be closed by means of two 15-gage wire ties placed as close to the bale as possible. The ear thus formed shall be not less than 3 inches in length.

5.1.1.2 *Boxes.*—Corrugated or solid fiberboard boxes shall conform to the requirements of Federal Specifications LLL–B–631 and LLL–B–636, respectively, except that the style shall be that known commercially as FOL (full overlapped) and the board shall have a minimum bursting strength of 200 pounds. Boxes shall be sealed by application of suitable adhesive to the entire contact area of the outer flaps.

5.1.2 *For overseas shipment.*—Unless otherwise specified, mattresses shall be baled as specified in 5.1.1.1.

5.2 Marking.—Each box or bale shall be plainly marked on each end with the name of the article, the type, the grade, the size, and the quantity contained therein as defined by the contract or order under which shipment is made, the name of the contractor, the name of the manufacturer, and the number of the contract or order. All bales shall be plainly marked "Use no hooks."

6. NOTES

6.1 Purchasers should exercise any desired options offered herein and should specify type, grade, and size required. (See 1.1, 1.2, 1.3, 3.1.4, 3.7, 3.8, 4.1, 4.2, 4.3, and 5.1.)

6.2 It is believed that this specification adequately describes the characteristics necessary to secure the desired material and that normally no samples will be necessary

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

prior to award to determine compliance with this specification. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids, and the particular purpose to be served by the bid sample should be definitely stated, the specification to apply in all other respects.

6.3 The following table lists the sizes used by the various agencies of the Federal Government and the respective bed sizes and types of beds for which they are intended.

TABLE III

Size No. (see table I)	Bed size—spring width x length, head to foot (inside)	Type of bed	Using agencies
	Inches		
1	26 x 76	Folding canvas cots	Army-Navy Medical Departments
2	27 x 73	Hospital train bunks and cabinet beds	Army-Navy Medical Depts. & Federal Prisons
3	30 x 76	Small hospital beds	Federal Prisons
4	31 x 78	Bedsteads and pack beds	Army & Veterans Hospitals
5	33 x 75	Dormitory beds	Department of Interior
6	34 x 76	Hospital beds	Army-Navy Medical Departments
7	36 x 78	Standard hospital beds	Veterans Hospitals and Interior Dept.
8	36 x 84	Hospital beds (extra tall)	Veterans Hospital
9	38 x 75	Domestic and Officers' beds	Interior Dept. & Bu. Yds. & Docks
10	39 x 78	Nurses' beds	Veterans Hospitals
11	53 x 75	Domestic and Officers' beds	Interior Dept. & Bu. Yds. & Docks
12	54 x 78	Housekeepers' quarters	Veterans Hospitals

6.4 Federal specifications do not include all types, classes, grades, sizes, etc., of the commodities indicated by the titles of the specifications, or which are commercially available, but are intended to cover the types, etc., which are suitable for Federal Government requirements.

6.5 The Hanovia Analytic Model Quartz Lamp equipped with a No. 6527c filter will fulfill the ultra-violet radiation requirements specified in 4.3.1. This apparatus may be obtained from the Hanovia Chemical and Manufacturing Company, Newark, New Jersey.

Patent notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

7. DEPARTMENTAL REQUIREMENTS

7.1 The following specifications and other publications, of the issues in effect on date of invitation for bids, and special requirements, form a part of this specification for purchases made under this specification by the respective departments.

7.2 Army.

7.2.1 *Applicable specifications.*

Federal specifications:

UU–P–268—Paper; Kraft, Wrapping.

CCC–B–811—Burlap; Jute.

CCC–O–721—Osnaburg; cotton.

LLL–B–636—Boxes; Fiber, Solid (for Domestic Shipment).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

Joint Army-Navy Specification:

JAN–P–125 — Packaging and Packing for Overseas Shipment—Barrier-Materials, Waterproof, Flexible.

U. S. Army Specifications:

100–1—Bailing of Clothing and Equipage.

100–2—Standard Specification for Marking Shipments by Contractors.

Quartermaster Corps Tentative Specification:

OQMG No. 106—Strapping, Steel, Nailless Type, Flat and Round Steel Wire, for Boxes, Crates and Bales.

(Copies of specifications required for Army purchases may be obtained upon application to the procuring agency. Both the title and identifying symbol or number should be stipulated when requesting copies.)

7.2.2 *Packing.*

7.2.2.1 *For domestic shipment.*—Mattresses may be packed in either noncompressed bales or in boxes conforming to the following requirements.

7.2.2.1.1 *Bales.*

7.2.2.1.1.1 *Wrapping.*—Three mattresses shall be stacked flat with edges flush and neatly wrapped together in not less than three thicknesses of No. 2 kraft paper having a combined basis weight of 200 pounds, with no sheet weighing less than 60 pounds per ream (24 x 36 — 500) and conforming to Federal Specification UU–P–268; the wrapping shall consist of not more than two pieces with the edges overlapping not less than 5 inches, and the seam at the center of the side of the package. Ends of the package shall be neatly folded with not less than 10 inches overlap and securely taped with 60-pound basis-weight gummed kraft paper tape, not less than 3 inches wide. The completed package shall be further secured by tying with two-ply twisted jute, sisal, or other suitable cord having a tensile strength of not less than 288 pounds. Twine shall be applied in one piece dividing the length of the package into four equal segments and the width into two equal segments. Nonslip knots shall be made at each cross-over of the cord.

7.2.2.1.1.2 *Bags.*—Alternatively, three mattresses shall be stacked flat with edges flush and packed in a prefabricated paper bag made of not less than three thicknesses of No. 2 kraft paper having a combined basis weight of 200 pounds, with no sheet weighing less than 60 pounds. The bags shall be fabricated, sealed and closed to conform to the requirements outlined in the Consolidated Freight Classification No. 18, Supplement No. 7, package 12-F. Each package shall be tied with twine as specified for the wrapped mattresses in 7.2.2.1.1.1.

7.2.2.1.2 *Boxes.*—Three mattresses shall be packed in a snug fitting fiberboard box made in conformance with the requirements of Federal Specification LLL–B–636, style FOL. The opening shall be on the ends or the smallest panel of the box. All flaps shall be securely sealed with a good quality adhesive applied throughout the entire area of contact between the flaps. Each box shall be reinforced with three flat steel straps ⅜" x .015" conforming to the requirements of Quartermaster Corps Tentative Specification OQMG No. 106.

7.2.2.2 *For overseas shipment.*—Mattresses shall be packed for overseas shipment to comply with one of the following methods as specified in 7.2.2.2.1 or 7.2.2.2.2 or 7.2.2.2.3.

7.2.2.2.1 Three mattresses shall be stacked flat with edges flush and neatly wrapped together in a No. 2 kraft paper having a basis weight of not less than 45 pounds per ream (24 x 36 — 500), conforming to Federal Specification UU–P–268, grade B, except that the paper shall be creped to have not less than 15 percent stretch in each direction. The wrapped mattresses shall then be protected with an additional wrap of waterproof barrier material type B-2, conforming to the requirements of Joint Army-Navy Specification JAN–P–125. The wrapped mattresses shall be protected for shipment by a cloth covering material of cotton osnaburg not less than 7

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

ounces to the square yard conforming to Federal Specification CCC–0–721, or jute burlap, 40-inch, 10 ounces per linear yard, conforming to Federal Specification CCC–B–811. Covering material shall be applied by one of the following methods:

(a) Bias sewn tubing shall be made which will fit the wrapped bundle of three mattresses snugly. Enough material shall be allowed at each end of the bundle so that the tubing may be pulled tight around all sides of the bundle and secured by either wire ties or sewing. Bundles may be sealed with one end presewn flat, seam to be 1 inch from the edge of the pre-cut cloth tubing and the other end to be closed with two wire ties.

(b) Cloth covering material may be handsewn to form a snug fitting outer wrap for each bundle of three mattresses and shall be overlapped at the seams not less than 3 inches.

Cloth covering material shall be sewn to form tubing in accordance with instructions outlined in paragraph G-1b of U. S. Army Specification 100–1. Closure of the bundles shall comply with paragraphs C–1f, C–1g and E–3a(1) or E–3a(2) of U. S. Army Specification 100–1.

7.2.2.2.2 Three mattresses may be wrapped together in waterproof barrier material similar to type B–2 of Joint Army-Navy Specification JAN–P–125, except that the material shall consist of 1 ply of 40-pound paper, 40 pounds of asphalt, and a ply of 60-pound paper with the 60-pound ply placed next to the mattresses. The barrier material shall meet the bleeding test requirements outlined in paragraph F–4d of Joint Army-Navy Specification JAN–P–125. When this material is used an inner wrap of plain kraft paper may be omitted. Each pack shall then be protected with cloth covering material as specified in 7.2.2.2.1.

7.2.2.2.3 Three mattresses may be packed in a laminated asphalt paper and cloth tubing barrier material conforming to the requirements outlined in Joint Army-Navy Specification JAN–P–125, type G–2c or G–3c, except that the inner ply of paper shall be 40 pounds basis weight (24 x 36 — 500) instead of 30 pounds as specified. The barrier material shall meet the bleeding test requirements outlined in paragraph F–4d of Joint Army-Navy Specifications JAN–P–125. When this material is used, an inner wrap of plain kraft paper may be omitted.

7.2.3 *Marking.*—Bales or boxes shall be marked in accordance with requirements of U. S. Army Specification 100–2, except that the service color marking shall not be applied for domestic shipment.

7.2.3.1 *For domestic shipment.*—Bales for domestic shipment (not containing waterproof barrier material), in addition to the regular marking, shall have a domestic shipment code "DOMPK" immediately following the stock number or nomenclature as illustrated in the following example:

Stock No.
"DOMPK"
Nomenclature
Quantity Size
Weight Cube

7.2.3.2 *For overseas shipment.*—Bales for overseas shipment (containing waterproof barrier material) shall be marked in accordance with the requirements of U. S. Army Specification 100–2, with the service color marking applied for the Army in Quartermaster Green. No other identification will be necessary.

7.2.4 *Sampling.* — Samples of any materials, components, etc., not furnished by the United States, entering into the manufacture of the articles covered herein, shall be selected from time to time by the Government inspector and carefully examined and tested to determine if they are in accordance with this specification.

7.2.5 *Inspection.*—Inspection may be made throughout the entire process of manufacture. The passing as satisfactory of any detail of construction or materials shall not relieve the contractor of responsibility for faulty workmanship or material which may

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

be discovered at any time prior to final acceptance. Final inspection of the finished articles shall be made either at the point of production or at the point of delivery as designated in the contract or purchase order of the procuring agency. In case of factory inspection, every facility shall be afforded inspectors by the manufacturer for the prosecution of their work.

7.3 Navy.

7.3.1 *Applicable specifications and other publications.*

Navy Department Specification:

General Specifications for Inspection of Material.

Bureau of Supplies & Accounts Publication:

Navy Shipment Marking Handbook.

(Copies of Federal specifications required for Navy purchases, Navy Department specifications, and the Navy Shipment Marking Handbook may be obtained without cost upon application to the Bureau of Supplies and Accounts, Navy Department, Washington 25, D. C., except that Naval activities should make application to the Supply Officer in Command, Naval Supply Depot, Norfolk 11, Va. When requesting specifications, refer to both title and number (or symbol).)

7.3.2 *Marking.*—In addition to any special marking required by the contract or order, marking of interior packages and shipping containers shall be in accordance with the Navy Shipment Marking Handbook.

7.4 Marine Corps.—Before quantity production is begun, a finished mattress (or pad, as applicable) together with a 2-yard sample of the cotton felt and a 2-yard sample of the ticking shall be submitted to the Depot Quartermaster, Marine Corps Depot of Supplies, 1100 South Broad Street, Philadelphia 46, Pa., for approval.

This specification is a part of Section IV, Part 5, of the Federal Standard Stock Catalog.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.