V-P-356E
September 23, 1986
SUPERSEDING
V-P-356D
September 27, 1968

FEDERAL SPECIFICATION

PILLOWS, BED, (FEATHER)

This specification is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers feather-filled bed pillows.

1.2 Classification.

1.2.1 Types, classes, and sizes. The pillows shall be of the following types and classes and in sizes as specified in table II (see 6.2):

Type I	- Landfowl feathers (crushed)
Type Ia	- Landfowl feathers (crushed) - chemically modified
Type II	- Duck feathers
Type III	- Goose feathers
Type IV	- Landfowl feathers (crushed) - chemically modified
Class 1	- White ticking
Class 2	- Blue and white striped ticking

2. APPLICABLE DOCUMENTS

2.1 Government publications. The following documents of the issues in effect on the date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7210

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

Federal Specifications

C-F-158	- Feathers, Landfowl; (Whole) and (Crushed)
C-F-160	- Feathers, Waterfowl; and Down, Waterfowl
V-T-276	- Thread, Cotton
CCC-C-436	- Cloth, Ticking Twill, Cotton
DDD-L-20	- Label: for Clothing, Equipage, and Tentage, (General Use)
PPP-B-636	- Boxes, Shipping, Fiberboard

Federal Standards

FED-STD-123	- Marking for Shipment (Civil Agencies)
FED-STD-191	- Textile Test Methods
FED-STD-751	- Stitches, Seams, and Stitchings

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards, and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Single copies of this specification and other Federal specifications and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available without charge from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX; Denver, CO; San Francisco, CA; Los Angeles, CA; and Seattle, WA.)

(Federal Government activities may obtain copies of Federal standardization documents and the Index of Federal Specifications, Standards, and Commercial Item Descriptions from established distribution points in their agencies.)

Military Specifications

MIL-L-35078	- Load Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-F-43612	- Feathers, Landfowl; (Whole and Crushed); Tan-O-Quil QM Treated

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

Military Standards

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Unit Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets

(Copies of military specifications and standards required by contractors in connection with specific procurement functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless a specific issue is specified, the issue in effect on the date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Guide samples. Samples, when furnished, are solely for guidance and information to the contractor (see 6.3). Variations from this specification may appear in the sample, in which case this specification shall govern.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.3 Materials.

3.3.1 Ticking. The cotton ticking shall conform to type I, class 1, style a or b (see 6.2) of CCC-C-436.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

3.3.2 Feathers. The feathers shall conform to the requirements for the respective types as established in the applicable specification referenced in table I.

TABLE I. Feather requirements

Pillow type	Feather type	Specification reference
I (Crushed, landfowl)	III	C-F-158
Ia (Crushed, landfowl, chemically modified)	I	MIL-F-43612
II (Waterfowl, medium filling power)	I, grade B	C-F-160
III (Waterfowl, high filling power)	I, grade A	C-F-160
IV (Crushed, landfowl, chemically modified)	I	MIL-F-43612

3.3.3 Thread. The thread utilized in the fabrication of the pillows shall be ticket No. 30, 3 ply, type IA1 (unbleached) or type IA2 (white), conforming to V-T-276 except that the looper thread shall be ticket No. 50 when the 401 stitch is used.

3.4 Sizes and weights. The pillows shall be rectangular in shape and shall conform to the finished dimensions and weights as specified in table II for the respective types and sizes (see 6.2).

TABLE II. Pillow sizes and weights

Type	Size	Width 1/ (in)	Length 1/ (in)	Total weight Minimum lb	Total weight Minimum oz	Total weight Maximum lb	Total weight Maximum oz	Weight of feathers Minimum lb	Weight of feathers Minimum oz	Weight of feathers Maximum lb	Weight of feathers Maximum oz
I	1	17	24	2	10	2	14	2	4	2	8
I	2	18	30	3	7	3	11	3	0	3	4
I	3	21	28	3	12	4	0	3	4	3	8
Ia	1	17	24	2	4	2	8	1	14	2	2
II and III	2	18	30	2	15	3	3	2	8	2	12

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

TABLE II. Pillow sizes and weights - Continued

Type	Size	Width 1/ (in)	Length 1/ (in)	Total weight Minimum lb	Total weight Minimum oz	Total weight Maximum lb	Total weight Maximum oz	Weight of feathers Minimum lb	Weight of feathers Minimum oz	Weight of feathers Maximum lb	Weight of feathers Maximum oz
II and III	3	21	28	3	2	3	6	2	10	2	14
IV	4	20	26	2	13	3	3	2	6	2	10

1/ Length and width of filled and closed pillow shall be measured from end of seam to end of seam. This shall be accomplished after placement of the pillow on a flat level surface, the pillow surfaces smoothened, and the seam lines straightened so that they are extended to the fullest in natural direction in which the measurement is to be taken. A tolerance of -0 and + 1/2 inch will be allowed on the specified dimensions.

3.5 Construction. Pillows shall be made of one piece of ticking with the stripes, when specified (see 6.2), in the widthwise direction (shorter dimension) of the pillow. The case shall be seamed inside-out, leaving approximately 6 inches of one end open. The end opening shall be seamed after turning the case right side out and filling the pillow. Stitching shall be not less than 1/4 inch from the edges of the material except that stitching on final closure shall be not less than 1/8 inch from the edge. One end of the identification, instruction and size labels shall be securely stitched into the closing seam or the seam opposite the closing seam of the pillow. When a separate state label is legally required by the state in which the pillow is manufactured, the state label shall be securely stitched adjacent to and in the same seam as the identification label.

3.5.1 Stitches, seams, and stitchings. Stitches, seams, and stitchings shall conform to the requirements of FED-STD-751. All stitches except closing seam shall be stitch type 301 or type 401. The closing seam shall be stitch type 301. Stitches shall be not less than 8 and not more than 10 stitches per inch. All seams, except closing seam, shall be seam type SSa-1. The closing seam shall be seam SSc-1. Ends of all stitching produced with type 301 stitch, when not caught in other seams or stitching, shall be backtacked not less than 1/4 inch. Both ends of all seams and stitching produced with 401 stitch type, when not caught in other seams or stitching, shall have a 1/2-inch minimum chain extending beyond each end. Thread breaks (all stitch types) shall be secured by stitching back of the break not less than 1 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

Skipped stitches or thread breaks (401 stitch type) may be repaired by using type 301 stitch. Seam allowances shall be maintained with seams properly sewn so that no raw edges, run-offs, twists, pleats, puckers, or open seams will result.

3.6 Labels.

3.6.1 State labeling requirements. When required, each pillow shall have a label attached to conform with the legal requirements of the state in which it is manufactured. When allowed under state law, the information required under state regulations may be combined in the identification and size labels.

3.6.2 Identification and size label. Each pillow shall have a combination identification and size label (or space on a combination label) not less than 2 inches wide by 1 1/2 inches high, containing the following information printed with minimum 10-point (approximately 1/8 inch) bold letters and numerals:

Nomenclature
Type, size
Stock number
Contract number and date
Contractor's registration number
Manufacturer's name (when other than contractor)

For military identification, the printed information shall be as specified above except that the contractor's name as stated in the contract shall be substituted for the contractor's registration number. The labels shall conform to the requirements of type VI, class 9 of DDD-L-20 and shall show fair or better fastness to accelerated laundering when tested as specified therein.

3.6.3 Instruction label. Each pillow shall have an instruction label conforming to type VI, class 3, of DDD-L-20 (see 3.6.2 and 3.6.4). The end item is intended to be laundered. The content shall be as follows:

CARE INSTRUCTIONS

Launder and dry by Formula G
of FM 10-17

Tumble dry at 160°-180°F
for 60 minutes

3.6.4 Combination labels. The identification, size, and instruction labels may be combined into one combination label.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. The pillows shall conform to the quality and grade of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels (AQL).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.2.1, 4.4.2.2, 4.4.2.2.1, 4.4.2.2.2, and 4.4.2.3. The presence of any defect shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

4.4 Quality conformation inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 In-process inspection.

4.4.1.1 Visual examination of cases. Examination of unfilled ticking cases shall be made for the defects listed in table III. The lot shall be expressed in units of unfilled ticking cases. The sample unit for this examination shall be one ticking case, inside out. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

TABLE III. Case inner seam defects

Examine	Defect
Construction and workmanship	Not stitch type specified
	Seams, except closing seams, not seam type SSa-1
	Less than 8 stitches per inch
	More than 10 stitches per inch
	Any open seam
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur.
	Stitching less than 1/4 inch from edge of material
	Loose tension resulting in a loose seam
	Tight tension (stitches break when normal pull tension is applied)
	Stitching irregular or uneven, resulting in badly twisted, pleated, or bulging edges
	Ends of seams produced with 301 stitch type (when not caught in other seams or stitching) backtacked less than 1/4 inch
	Ends of seams produced with 401 stitch type (when not caught in other seams or stitching) not having chain extending beyond each end, or having chain extending less than 1/2 inch beyond each end
	Any thread break not backstitched a minimum of 1 inch
	Stripes, if applicable, not in widthwise direction

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

4.4.1.2 Determination of weight of ticking cases. A determination for average weight of ticking cases shall be made for each lot (for use in calculating the weight of feathers in the finished pillows, see 4.4.2.2). The average case weight shall be taken as the average weight obtained from weighing not less than 100 cases in the lot.

4.4.2 End item examination. The completed pillows shall be examined as specified in 4.4.2.1, 4.4.2.2, and 4.4.2.3. The lot shall be expressed in units of completely fabricated pillows. The sample unit shall be one completely fabricated pillow.

4.4.2.1 End item visual examination. The end item shall be examined for the defects in table IV. (The qualification "clearly visible" here indicated shall be based on a normal inspection distance of approximately 3 feet.) The lot size shall be expressed in units of pillows. The sample unit shall be one pillow. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 1.5 for major defects and 4.0 for total (major and minor combined) defects.

TABLE IV. End item visual defects

Examine	Defect	Classification	
		Major	Minor
Quality of material	Hole, cut, tear, or any mend	X	
	Any smash	X	
	Abrasion mark; tender or weak place	X	
	Broken or missing yarns, two or more contiguous	X	
	Crack, clearly visible	X	
	Slub, more than three times the thickness of normal yarns		X
Cleanness	Any spot, stain, or streak clearly visible		X
	Untrimmed thread ends on exterior of pillow, feathers not removed throughout outside of pillow		X
	Offensive or objectionable odor	X	

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:21Z
Check the source to verify that this is the current version before use.

TABLE IV. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Construction and workmanship	Loose tension resulting in loose seam	X	
	Tight tension (stitches break when normal pull tension is applied)	X	
	Ends of seams produced with 301 stitch type (when not caught in other seams or stitching) backtacked less than 1/4 inch		X
	Stitching irregular or uneven, resulting in badly twisted, pleated, or bulging edges	X	
	Any thread break not backstitched a minimum of 1 inch		X
	Any open seam	X	
	Closing seam not SSc-1	X	
	NOTE: A seam shall be classified as open when one or more stitches are broken, or when two or more consecutive skipped or run-off stitches occur.		
	Wrong seam or stitch type:		
	- seriously affecting serviceability	X	
	- affecting serviceability but not seriously		X
	Raw edge over 1/2 inch in length	X	
	Raw edge over 1/4 inch up to and including 1/2 inch in length		X
	NOTE: Raw edge not securely caught in stitching shall be classified as open seam.		
	Two or more stitches per inch less or more than required	X	
	One stitch per inch less or more than required		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

TABLE IV. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Construction and workmanship - continued	Covering spliced or not fabricated of one piece of material	X	
	Row of closure stitching less than 1/8 inch from edge		X
Label or labels	Missing, incorrect, illegible, or not securely attached		X

4.4.2.2 Examination for weights. Weights, as required in 4.4.1.2, 4.4.2.2.1, and 4.4.2.2.2 shall be determined, recorded, and calculated to the nearest 1 ounce. In the event of dispute, the samples shall be conditioned to constant weight (± 0.25 ounce) under standard conditions as defined in FED-STD-191, and the results obtained on the conditioned samples shall be considered final.

4.4.2.2.1 Total weight. Determination shall be made of the weight of the finished pillow. Any total weight that is not within the range of the applicable minimum and maximum weight requirements as shown in table II shall be classified as a defect with respect to total weight. The inspection level shall be level S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.4.2.2.2 Weight of feathers. Determination shall be made of the weight of feathers contained in the finished pillow, calculated as the total weight of the pillow minus the average weight of the ticking case as determined in 4.4.1.2. Any weight of feathers that is not within the range of the applicable minimum and maximum weight requirements as shown in table II shall be classified as a defect with respect to weight of feathers. The inspection level shall be level S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:21Z
Check the source to verify that this is the current version before use.

4.4.2.3 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified in table II. Dimensions shall be along seams, from end of seam to end of seam. Any dimensions that is not within the specified tolerances for dimensions listed in table II shall be classified as a defect with respect to dimensions. The lot shall be expressed in units of pillows. The sample unit shall be one pillow. The inspection level shall be level S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.4.3 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than specified

4.4.4 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

Examine	Defect
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Each pillow shall be inserted in a snug-fitting, clear polyethylene film bag of 0.00125-inch thickness (± 20 percent tolerance). The identification label attached to each pillow shall be positioned so that the printed information can be easily read. The bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and to the formed edges of the bag. The final closure of the bag shall be heat sealed with the heat seal made as close as possible to the open end. Open vents of approximately 1 inch at each side of the closure or a 1/2-inch hole in each of the opposite corners of the bag shall be provided for the escape of excess air. Alternatively, the final closure of the bag shall be accomplished by folding over and securing the open end to the bag body with pressure-sensitive tape.

5.1.2 Commercial. Pillows shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Ten pillows of like description, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style FTC, grade V2s of PPP-B-636. Level A unit packs shall be packed flat, two in length and five in depth, within a shipping container. Inside dimensions of each shipping container shall be 36 inches in length, 24 inches in width, and the depth dependent upon the compression applied to the pillows. Each shipping container shall be closed, waterproofed, and reinforced with strapping or tape banding in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Ten pillows of like description, preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style FTC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, two in length and five in depth, within a shipping container. Inside dimensions of each shipping container shall be 36 inches in length, 24 inches in width, and the depth dependent upon the compression applied to pillows. Each shipping container shall be closed and reinforced with strapping in accordance with the appendix of PPP-B-636, except that the strapping shall be applied three girthwise and one lengthwise.

5.2.2.1 Weather-resistant shipping container. When specified (see 6.2), the shipping container shall be grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of PPP-B-636.

5.2.3 Commercial packing. Pillows, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), pillows, packed as specified in 5.2.2 and 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 89 in accordance with appendix of MIL-STD-147.

5.4 Marking.

5.4.1 Civil agencies. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with FED-STD-123.

5.4.2 Military requirements. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The pillows are primarily intended for use by the United States Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

a. Title, number, and date of this specification.
b. Type, class, and size of pillows required (see 1.2, 3.3.1, 3.4, and 6.5).
c. When a first article is required (see 3.2, 4.3, and 6.4).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 Standard sample. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.5 Medical or nonmedical use. Department of Defense procurement for nonmedical use is restricted to type I or type Ia pillows in size 1 or type IV in size 4, and for medical use to type II, size 2.

6.6 Civil agency procurement. When level B packaging is specified for civil agency procurement, the requirements in 5.1.1 will apply.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Air Force - 84
DLA - CT

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7210-0271

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
V-P-356E	Pillows, Bed, (Feather)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:21Z
Check the source to verify that this is the current version before use.