MILITARY SPECIFICATION

PRIMER, STAB, M45
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of primer designated as Primer, Stab, M45.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 —Preservation, Methods of.

MIL-A-2550 — Ammunition and Special Weapons; General Specification for.

MIL-P-12059 — Powder. Sulfurless Meal.

MIL-I-45607 —Inspection Equipment, Supply and Maintenance of.

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).

MIL-STD-109 — Quality Assurance Terms and Definitions.

MIL-STD-650 — Explosives: Sampling, Inspection and Testing.

MIL-STD-1235— Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ORDNANCE CORPS

7548099 — Box, Packing, Ammunition for Detonators.

7548103 — Box, Set-up, Packing, Ammunition, Outer for Small Explosive Components.

7548104 — Box, Set-up, Packing, Ammunition, Inner for Small Explosive Components.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:30Z
Check the source to verify that this is the currentversion before use.

9207643 — Primer, Stab, M45.

PUBLICATIONS

ORDNANCE CORPS

IEL–9207643 — Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Primer. The primers shall comply with all requirements specified on Drawing (dwg. 9207643), and with all requirements specified in applicable specifications.

3.3 Moisture content of sulfurless meal powder. The moisture content of the sulfurless meal powder used in loading the primers shall not exceed the amount specified in Specification MIL–P–12059 when determined as specified in 4.3.1.

3.4 Moisture content of primer mixture. The moisture content of the primer mixture used in loading the primers shall not exceed 0.30 percent when tested as specified in 4.3.2.1.

3.5 Functioning.

3.5.1 *Sensitivity.* The primers shall function on the first attempt and shall cause perforation of the aluminum disc to a diameter of not less than 0.250 inch (in.) when tested as specified in 4.3.3.1.

3.5.2 *Waterproofness.* The primers shall be waterproof as evidenced by normal functioning after being immersed under a minimum (min.) of 2 in. of water for a min. of 48 hours when tested as specified in 4.3.3.2.

3.6 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL–STD–109 in order to define terms used herein. The provisions of Specification MIL–A–2550 shall apply.

4.1.1 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all of the quality assurance provisions specified within this specification.

(b) Number of units of product inspected.

(c) Results obtained, by defect code, for all inspections performed.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:30Z
Check the source to verify that this is the currentversion before use.

(d) Drawing, specification number and date, together with an identification and date of changes.

(e) Statement of findings on the primer mixture and associated ingredients and a certificate of conformance on all material purchased by the contractor when such material is controlled by Government specification referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted will be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions.

4.2.1 *Lot formation.* A lot shall consist of primers produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification, and process changes not affecting safety, performance or fit, as determined by the Government, shall not necessitate changing the lot interfix number. Lots shall be submitted for inspection in accordance with Standard MIL–STD–105 (or Standard MIL–STD–1235 when applicable). Each lot shall contain:

(a) Parts of one lot interfix number from one manufacturer.

(b) Primer mixture from one batch or blending of batches which results in homogeneity of all primer mixture used in loading the entire primer lot.

(c) Sulfurless meal powder from one lot from one manufacturer.

4.2.2 *Examination.* Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL–STD–105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Standard MIL–STD–1235 may be used, for defects other than critical, if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the current version before use.

4.2.2.1 Assembly prior to loading (see dwg. 9207643).

Categories	Defects	Method of inspection	Code No. (see 6.2)
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Coating compound or lacquer on exposed surface of disc	Visual	01001
102.	Coating of metal components incomplete or inadequate	Visual	01002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6)	Visual	01003

4.2.2.2 Assembly (see dwg. 9207643).

Categories	Defects	Method of inspection	Code No.
Critical:			
1.	Cup cracked or split	Visual	02001
Major:	AQL 1.00 percent		
101.	Total length	Gage	02002
102.	Diameter	Gage	02003
103.	Disc loose, punctured or torn	Visual	02004
104.	Color of lacquer incorrect on either end	Visual	02005
105.	Crimp not full 360 degrees	Visual	02006
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship, (see 3.6)	Visual	02007

4.2.2.3 Box, set-up, inner (see dwg. 7548104).

Categories	Defects	Method of inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Box damaged	Visual	03001
102.	Number of primers incorrect	Visual	03002
Minor:	AQL 1.00 percent		
201.	Marking misleading or unidentifiable	Visual	03003
202.	Any packing material missing	Visual	03004

4.2.2.4 Box, set-up, outer (see dwg. 7548103).

Categories	Defects	Method of inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Number of inner set-up boxes incorrect	Visual	04001
102.	Sealing strip torn, badly wrinkled, incomplete or otherwise fails to seal the box completely	Visual	04002
Minor:	AQL 1.50 percent		
201.	Box torn, cut or punctured	Visual	04003
202.	Marking misleading or unidentifiable	Visual	04004
203.	Contents move when box is shaken	Manual	04005

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:30Z
Check the source to verify that this is the current version before use.

4.2.2.5 Sealed barrier bag (see dwg. 7548103).

Categories	Defects	Method of inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Seal missing, incomplete or incorrectly located	Visual	05001
102.	Bag punctured, torn or cut	Visual	05002
Minor: None defined			

4.2.2.6 Box, packing, ammunition for detonators see dwg. 7548099).

Categories	Defects	Method of inspection	Code No.
Critical: None defined			
Major:	AQL 0.65 percent		
101.	Box damaged	Visual	06001
102.	Nailing inadequate	Visual	06002
103.	Strapping missing or loose	Visual	06003
104.	Marking incomplete, misleading or unidentifiable	Visual	06004
Minor: None defined			

4.2.3 Testing.

4.2.3.1 *Moisture content of sulfurless meal powder (see 3.3.)—Major defect—Code No. 06001.* The moisture content of the sulfurless meal powder shall be determined for each lot at the time of loading. A sample, in sufficient quantity to perform the test specified in 4.3.1, shall be selected and tested as specified in 4.3.1. If the moisture content is in excess of the percentage specified and loading has not begun, the lot of sulfurless meal powder shall be rejected. If loading has begun, action on the unloaded sulfurless meal powder shall be as specified above and all primers loaded with the questionable sulfurless meal powder shall be rejected.

4.2.3.2 Primer mixture.

4.2.3.2.1 *Moisture content (see 3.4)— Major defect—Code No. 07001.* The moisture content of the primer mixture shall be determined for each batch or blend of batches at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.3.2.1, shall be selected and tested as specified in 4.3.2.1. If the moisture content is in excess of the percentage specified and loading has not begun, the batch or blend of batches of primer mixture shall be rejected. If loading has begun, action on the unloaded primer mixture shall be as specified above and all primers loaded with the questionable primer mixture shall be rejected.

4.2.3.2.2 *Composition (see dwg. 9207643) —Major defect—Code No. 08001.* The composition of the primer mixture shall be determined for each batch or blend of batches at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.3.2.2, shall be selected and tested as specified in 4.3.2.2. If the composition of the primer mixture fails to conform to the requirements specified on the applicable drawing and if loading has not begun, the batch or blend of batches of primer mixture shall be rejected. If loading has begun, action on the unloaded primer mixture shall be as specified above and all primers loaded with the questionable primer mixture shall be rejected.

4.2.3.3 Functioning.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

4.2.3.3.1 *Sensitivity (see 3.5.1)—Major defect—Code No. 09001.* A sample of 315 primers shall be selected at random from each lot. If 3 or more primers fail to comply with the requirement specified, the lot shall be rejected. If one or two defectives are found, a second sample of 315 primers shall be selected at random and tested. If in the combined first and second sample a total of 4 or more defectives are found, the lot shall be rejected. The test shall be performed as specified in 4.3.3.1 using test equipment as specified in 4.2.4.

4.2.3.3.2 *Waterproofness (see 3.5.2)—Major defect—Code No. 09002.* A sample of 25 primers shall be selected at random from each lot. If one or more primers fail to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.3.3.2 using test equipment as specified in 4.2.4.

4.2.3.4 *Heat seal test of sealed bag (see dwg. 7548103) Major defect — Code No. 05003.* Sampling, acceptance criteria and test procedures for this test shall be as specified in Specification MIL–P–116.

4.2.4 *Inspection Equipment.* Index of Inspection Equipment Number IEL–9207643 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 *Government rights to documentation.* Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement. manufacture, testing evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 *Supply and maintenance.* Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL–I–45607.

4.2.4.3 *Government use of contractor's inspection and test equipment.* The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of it's accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures.

4.3.1 *Moisture content of sulfurless meal powder.* The moisture content of the sulfurless meal powder shall be determined as specified in Specification MIL–P–12059.

4.3.2 Primer mixture.

4.3.2.1 *Moisture content of primer mixture.* An accurately weighed 0.7 gram portion of the sample shall be dried to constant weight in an oven, maintained at 60 degrees C. plus or minus 5 degrees C., or in a desiccator, containing calcium chloride. The loss in weight shall be calculated as the percentage of moisture.

4.3.2.2 Composition.

4.3.2.2.1 Potassium chlorate.

4.3.2.2.1.1 Preparation of solutions.

4.3.2.2.1.1.1 *Solution Number 1.* To approximately 800 ml. distilled water, in a one liter amber glass reagent bottle, 400 grams (gm.) of potassium thiocyanate shall be addded. The bottle shall be sealed with a rubber stopper and the reagent bottle and con-

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the currentversion before use.

tents shaken until the solid material is dissolved. To this solution 1.0 gm. of lead thiocyanate, 1.0 gm. of antimony sulfide and 1.0 gm. of lead azide shall be added. The bottle shall again be stoppered and the reagent bottle and contents vigorously shaken for several minutes, and then allowed to stand overnight. Portions of the saturated solution shall be filtered before using.

4.3.2.2.1.1.2 *Solution Number 2.* To approximately 400 ml. of distilled water, in a one-half liter amber glass reagent bottle, 1.0 gm. of lead thiocyanate, 1.0 gm. of antimony sulfide and 1.0 gm. of lead azide shall be added. The bottle shall be sealed with a rubber stopper and the reagent bottle and contents vigorously shaken for several minutes and then allowed to stand overnight. Portions of the saturated solution shall be filtered before using.

4.3.2.2.1.2 *Procedure.* A portion of approximately 1.0 gm. of the sample shall be accurately weighed directly into a tared 30 ml. sintered glass crucible of medium porosity. From a burette 3.0 ml. of Solution Number 1 shall be added to the crucible. The solution shall be swirled for exactly one minute, taking care not to spill any liquid; aspirated with suction and the bottom of the crucible wiped dry, using tissue paper. The washing shall be continued, using one more 3.0 ml. portion, two 2.0 ml. and two 1.0 ml. portions, making a total of 12.0 ml. The crucible shall be removed and the bottom of the crucible, the funnel, the adapter and the suction flask washed with water. The test tube shall be placed in the flask and the stem of the filtering funnel inserted into the test tube. The crucible and contents shall be washed with one 1.0 ml. portion of Solution Number 1 as above, and aspirated with suction, catching the filtrate in the test tube. The test tube shall be removed, 1.0 ml. of distilled water added and the chlorate ion, determined as follows.

The tube shall be inclined at an angle of about 45 degrees and from a dropper about 0.5 ml. of a solution containing 1.0 gm. of diphenylamine in 100 gm. of concentrated sulfuric acid shall be run down the side of the tube, so that there will be two distinct layers. If an appreciable amount of chlorate ion is present, a distinct blue ring will be visible at the border of the two layers. On shaking the tube, the ring disappears, but the contents assume a blue coloration, which lasts several seconds, depending on the amount of chlorate ion present. If only a trace of chlorate ion is present the blue ring may not form, but upon shaking the test tube, a slight bluish coloration will appear momentarily throughout the solution, lasting only a fraction of a second. If a definite blue ring forms, the washing shall be repeated as before using one 1.0 ml. portion of Solution Number 1, and finally a 0.5 ml. portion of the same solution, as needed, depending on the outcome of the tests for the chlorate ion. (Usually a total of 14.0 or 14.5 ml. of Solution Number 1 is sufficient.) After complete removal of potassium chlorate the inside of the crucible shall be washed with 1.0 ml. of Solution Number 2 and aspirated immediately. The bottom of the crucible shall be wiped dry with tissue paper and dried in an oven at 80 degrees C. plus or minus 1 degree C. for 30 minutes, cooled in a desiccator and weighed. The percentage of potassium chlorate shall be calculated as follows:

$$\text{Potassium Chlorate, percent} = \frac{100B}{W(1-M)}$$

where:

B = loss in weight of contents of crucible, grams.

W = weight of sample, grams.

$M = \dfrac{\text{percent moisture}}{100}$

4.3.2.2.2 Antimony sulfide.

4.3.2.2.2.1 *Preparation of solution of Ferric ammonium sulfate.* To approximately 120

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:30Z
Check the source to verify that this is the current version before use.

ml. of distilled water, in a one-half liter reagent bottle, 125 gm. of ferric ammonium sulfate shall be added. The bottle shall be stoppered and shaken vigorously for several minutes and then allowed to stand overnigh. Portions of the saturated solution shall be filtered before using.

4.3.2.2.2.2 *Procedure.* A portion of approximately 1 gm. of the sample shall be accurately weighed directly into a tared 30 ml. sintered glass crucible of medium porosity. Five ml. of one percent nitric acid shall be added and the crucible constantly swirled for one minute in order to dissolve all the ingredients of the powder except antimony sulfide. Care shall be taken not to spill any liquid. The mixture shall be filtered by applying suction employing a vacuum flask. The crucible shall be removed from the adapter and the bottom wiped dry with tissue paper. The operations of washing, using 5.0 ml. of one percent nitric acid each time and swirling for exactly one minute shall be repeated. After a total of 40 ml. of one percent nitric acid has been used, the crucible shall be removed and the bottom of it washed with water. The funnel, the funnel adapter and the vacuum flask shall be washed with water; the filtrate and washings shall be discarded. About 1 ml. of a saturated solution of ferric ammonium sulfate shall be placed in the flask. The contents of the crucible shall be treated as before with 5.0 ml. of one percent nitric acid and filtered by means of suction into the flask. If the liquid in the flask turns red, due to the presence of the thiocyanate ion in the filtrate, the washing of the contents in the crucible shall be repeated with additional 5.0 ml. portions of one percent nitric acid until a negative test for the sulfocyanate ion is affected. (Usually a total of 50 ml. is sufficient.) The crucible and contents shall be rinsed with alcohol and then with ether, and then aspirated until the odor of ether is no longer detectable. The crucible and contents shall be dried in an oven at 80 degrees C. plus or minus 1 degree C. for 30 minutes, cooled in a desiccator and weighed. The percentage of antimony sulfide shall be calculated as follows:

$$\text{Antimony sulfide, percent} = \frac{100A}{B}$$

where:

A = weight of residue in the crucible.

B = weight of sample on a moisture-free basis.

4.3.2.2.3 *Lead azide.* The lead azide content shall be determined using the (Eudiometer) method and apparatus in MIL–STD–650 Method No. 407.1.

4.3.2.2.4 *Lead thiocyanate.* The percentage of lead thiocyanate in the sample shall be calculated on a moisture-free basis by subtracting from 100 the sum of the percentages of potassium chlorate, antimony sulfide and lead azide.

4.3.3 Functioning.

4.3.3.1 *Sensitivity.* The primer shall be assembled to the applicable test fixture specified in 4.2.4 so that the firing pin will strike the sensitive end of the primer. A steel ball $^{13}/_{16}$ inch in diameter and weighing 3.95 ounces maximum, shall be dropped of the firing pin to function the primer, from a height of 3 inches, maximum. The height of drop shall be measured as the height from the top of the firing pin to the bottom of the ball. A primer that fails to fire or fails to create a hole in the alumimum disc of the required size shall be classed defective.

4.3.3.2 *Waterproofness.* The primers shall be submerged in water maintained at a temperature of 70 degrees F. plus or minus 10 degrees at the required depth for the time specified and immediately upon removal from water subjected to the sensitivity test specified in 4.3.3.1. A primer that fails to fire or

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

fails to create a hole in the aluminum disc of the required size shall be classed defective.

5. PREPARATION FOR DELIVERY.

5.1 Preservation and packaging.

5.1.1 *Level C.* The primers shall be preserved and packaged in accordance with dwg. 7548104.

5.1.2 *Intermediate packaging.* The primers shall be packaged in accordance with dwg. 7548103.

5.2 Packing.

5.2.1 *Level C.* The containers shall be packed in accordance with dwg. 7548099.

5.3 Marking.

5.3.1 Unit, intermediate and exterior containers shall be marked in accordance with dwgs. 7548104, 7548103, and 7548099.

5.4 Data cards. Data card information shall be prepared for each lot in accordance with the procedure specified in Specification MIL–A–2550.

6. NOTES

6.1 Ordering data. Procurement documents shall specify title, number and date of this specification.

6.2 Inspection code numbers. The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 Inspection equipment lists. Inspection equipment lists indicate the availability of inspection equipment designs by showing in the number column of the list of inspection equipment (00 Form 1242–3) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 *Inspection equipment list codes.* The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designated in the IEL by the following codes:

CDAF	— Contractor's design responsibility on Army format in accordance with MIL–D–45608.
CDCF	— Contractor's design responsibility on contractor format.
AD	— Army design.
ADMU	— Army design, mandatory for use.
CE	— Commercial equipment.
SCD	— Specification control drawing.

6.3.3 *Army designs.* Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

inspection equipment. Army designs fall into two basic classifications, mandatory and nonmandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with nonmandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 *Specification control drawing.* Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagramatic, or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 *Commercial equipment.* Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 *Contractor designs.* Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL D–45608, and in addition, contain the detail and information specified above. Final approved contractor designs identified as CDCF shall be suitable for microfilming. They must be nonproducible diazo or electrostatic prints of top quality full size with black line on white background and shall provide a legible print produced via the 35mm microfilm process. Contractor shall submit one copy of the final approved design as a rolled set or flat set.

6.3.7 *Submission of contractor designs.* Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA–ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 **Check test for possible deterioration.** The following test is designed to prevent the loading of primers which have deteriorated, into a major ammunition item. The test shall be performed on primers from each lot which

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

have been stored under normal conditions for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the primers are loaded does not require that the check test be performed, the contracting officer should insert a provision for the performance of the check test in that contract. The contracting officer will arrange for the contractor to be reimbursed for expenses incurred in the performance of the check test for possible deterioration.

6.4.1 *Sensitivity.* A sample of 315 primers shall be selected at random from each lot. If 4 or more primers fail to comply with the requirement specified, the lot shall be rejected. If more than one defective is found, a second sample of 315 shall be selected at random and tested. If in the combined first and second sample a total of 5 or more defectives are found, the lot shall be rejected. The test shall be performed as specified in 4.3.5.1 using test equipment as specified in 4.2.4.

6.5 **Supersession data.** This specification supersedes in part, Specification *MIL-P-14100* (Ord) dated 27 June 1955, for Primers, Stab Type, Loading, Assembling and Packing.

Custodian:

Army—MU

Preparing activity:

Army—MU

Project No. 1375-A915

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.