INCH-POUND

MIL-P-71136(AR)
12 October 1992

MILITARY SPECIFICATION

PROCESS SPECIFICATION, AMMUNITION, 25MM, PACKAGING, PACKING AND MARKING

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the packaging, packing and marking of 25mm ammunition for use in the M242 gun. (See 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation. (See 6.2).

SPECIFICATIONS

MILITARY

MIL-A-48078 -Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-414 -Sampling Procedures and Tables for Inspections by Variables for Percent Defectives

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

MIL-STD-810 -Environmental Test Methods and Engineering Guidelines

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12929427 -Packing and Marking for Container, Ammo, PA125, for Linked 25MM Ammunition

12013695 -Characteristics, Link Belt, 25mm, M28

U.S. ARMY MATERIAL COMMAND

19-48-4232/ 17-20PM1007 Unitized Procedures for Boxed Ammunition and Components Packed in Metal or Plastic Boxes on 4-way Entry Pallets

CODE OF FEDERAL REGULATIONS

Title 49 -Transportation, Parts 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify "49 CFR 100-199 (latest revision)").

(Copies of other Government documents, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the document cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Components. The linked ammunition and container shall comply with all requirements specified on Drawing (Dwg.) 12929427, Dwg. 12013695 and associated drawings and with all requirements specified in applicable specifications and standards.

3.2 Pull. The belt of 15 cartridges shall be subjected to a load of 600 ± 50 Newtons without fracture or separation. The test shall be performed as specified in 4.5.1.

3.3 Free hinging. Linked ammunition shall hinge and fold over without binding, kinking, separating or any interference. The test shall be performed as specified in 4.5.2.

3.4 Airtightness. The loaded container shall hold, without leakage, an internal air pressure differential of three pound per square inch (psig). The test shall be conducted in accordance with 4.5.3.

3.5 First Article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.6 Workmanship. The links and cartridges shall be assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter. All components of the container shall be free of cracks, dents, sharp edges, burrs, grease, rust, and gouges. The cleaning method used shall not be injurious to the links, cartridges or container, nor shall they be contaminated by the cleaning agents. Exterior surface coating on all parts shall be continuous except for a few light scratches not exposing base material. All required marking and stamping shall be neat and sharply defined. The separator assembly and endplates shall be free of burrs and cracks and will conform to individual quality assurance provisions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsiblity for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of any defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection (4.3).

b. Quality Conformance Inspection (See 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
M791, M792, M793 M794, M910 or M919 as applicable	12929427	30 Belts (450 Cartridges)
Container, Ammunition	12929427	15

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

4.3.2 Inspections to be performed. First Article materiel shall be tested in accordance with Table I. Any test samples may be subjected, by the Government, to any or all of the examinations and tests specified herein, in the contract or on the applicable drawings.

4.3.3 Rejection. If any component or assembly fails to comply with the requirements, the First Article sample shall be rejected. The Government reserves the right to terminate its inspection upon the failure of an item of materiel to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new First Article quantity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-P-71136(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Packing and Marking for Container, Ammo, PA125 For Linked 25mm, Ammunition	1 OF 1	12929427
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Packing and Marking for Container, Ammo, PA125 for Linked 25MM Ammunition			
	Examination for defects	30 Belts 1/	3.1,3.2 3.3,3.6	4.4.2.1
	Examination for defects	15 Containers 2/	3.1,3.4, 3.6	4.4.2.2

NOTES: 1/ Fifteen (15) cartridges per belt
2/ The fifteen (15) containers shall be loaded with the thirty (30) belts from the first article after the belts successfully pass the first article inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product. All material submitted for inspection in accordance with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

4.4.1.1 Lot identification. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II using the inspection levels stated in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

TABLE II. Attributes sampling inspection

Lot Size	Inspection Levels I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150000 to 500000	1250	500	200	125	50	13
500001 and over	1250	500	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluating (see 6.9). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as do whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program plan or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-P-71136(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Characteristics, Link Belt 25mm, M28	1 OF 1	12013695
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101.	Height from base of cartridge to forward tab, max.	Level II	3.1	Gage
102.	Dimple not engaged in cartridge case groove, two places	100%	3.1	Visual
103.	Pull	100%	3.2	4.5.1
104.	Free hinging	100%	3.3	4.5.2
105.	One (1) or more deformed links	Level II	3.1	Visual
Minor:				
201.	One (1) or more cartridges missing from belt	Level IV	3.1	Visual
202.	Evidence of poor workmanship	Level V	3.6	Visual

NOTES:

Above examinations and tests performed on belted cartridges (15 cartridges per belt).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.2	Packing and Marking for Container, Ammo, PA125 For Linked 25mm, Ammunition		12929427
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical:				
1.	Marking misleading, unidentifiable or missing	100%	3.6, 5.2.1	Visual
Major				
101.	Belts (2) assembled to Separator Assembly improperly 1/	Level II	3.1	Visual
102.	Restraining plates (2) assembled to belts and separator assembly improperly 1/	Level II	3.1	Visual
103.	Filler pads, top & bottom missing damaged or improperly assembled to ammo stack within container (2 places) 1/	Level II	3.1	Visual
104.	Gasket loose, missing, damaged or improperly installed to container cover assembly 1/	100%	3.1	Visual
105.	Excessive effort required to close cover assembly to body assembly (2 places) 1/	100%	3.1	Visual/ Manual

NOTES: Above examinations and tests performed on belted cartridges (15 cartridges per belt).
1/ Prior to assembly of security seal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Packing and Marking for Container, Ammo, PA125 For Linked 25mm, Ammunition	2 OF 2	12929427
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Major				
106.	Container not properly closed	100%	3.1	Visual
107.	Security seal missing or missing or improperly assembled (2 places)	100%	3.1	Visual
108.	Lot number incorrect, illegible or missing	100%	3.1	Visual
109.	Airtightness	100%	3.4	4.5.3
MINOR:				
201.	Spring loaded handles not under tension (3 places)	Level IV	3.1	Visual/ Manual
202.	Evidence of poor workmanship	Level V	3.6	Visual

NOTES: Above examinations and tests performed on belted cartridges (15 cartridges per belt).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. The tests listed shall be performed on each lot in compliance with the test methods and procedures specified by 4.6. For acceptance, the results of each test shall apply with the applicable requirements.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.4.5 Variable Inspection Plan. A variables inspection plan from MIL-STD-414, Table 3-3 shall be used to determine lot acceptability, applying the method calculation as shown in example B-3. Failure of the sample to meet the acceptablity criterion shall be the cause of rejection of the lot.

4.5 Method of inspection.

4.5.1 Pull. One end of the belt shall be attached to a suitable hook on a horizontal table and the load specified in 3.2 applied to the other end. Observation shall be made for compliance with the requirements. Links that fail as a result of this test shall be dismantled and scrapped and the cartridges visually inspected for damage prior to rebelting.

4.5.2 Free hinging. Each belt shall be laid out horizontally to its full length with the open side of the links up. One end shall be drawn back upon the remainder of the belt until the belt is returned to its original (open side of links up) position. Observation shall be made for compliance with the applicable specification requirement.

4.5.3 Airtightness. The loaded container shall be immersed in water in a vacuum vessel. (a wetting agent may be used to minimize air bubbles clinging to the exterior surface of the container.) The pressure in the vacuum vessel shall be lowered to cause a minimum three (3) psi pressure differential on the container. Observation for leakage of air from the container shall be made for minimum of 30 seconds after reduction of pressure. A steady stream of five or more bubbles from any single surface, joint, or gasket junction shall be evidence of a defective container and a cause for rejection. Note, more vacuum may be required if the lowest part of the container has a significant amount of water head. The alternate airtightness test

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

shall be in accordance with MIL-STD-810, Method 5123, procedure I - basic leakage (temperature and water head shall cause a minimum 3 psi pressure differential). The container shall be dried externally and examined for internal wetness. Wetness shall be cause for rejection.

5. PACKAGING

5.1 Preservation and packaging. Not Applicable.

5.2 Packing.

5.2.1 Level A. The belted cartridges shall be packed in accordance with Dwg. 12929427.

5.3 Marking. Marking shall be in accordance with Dwg. 12929427 and Code of Federal Regulations, Title 49 Parts 100-199.

5.4 Unitized loads. The belted cartridges, packed in accordance with 5.2.1, shall be unitized in accordance with Dwg. 19-48-4232/17-20PM1007.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but not mandatory.)

6.1 Intended use. The belted 25mm ammunition covered by this specification is intended for use in the 25mm M242 Automatic Gun.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. Place of inspection, if not place of manufacture.

c. Issue of DoDISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).

d. When first article is required (see 3.6).

e. Requirements for quality conformance inspection sampling plan.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

6.3 Submission of contractor inspection equipment designs for approval. Submit two copies of designs as required to: Commander, U.S. Army AMCCOM, ATTN: SMCAR-QAF-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423, in the contract.

6.4 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a first article sample, a first production item, or a standard production item from the contractor's current inventory and the number of items to be tested as specified in 4.3. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should be provided that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has bidders offering such product, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Intermediate point inspection. The classification of defects identifies the defect characteristics (among other things) for acceptance inspection. It may be necessary to modify the sequence of inspection stations to best suit the manufacturing process. Inspection for characteristics which will be hidden or altered by subsequent processing operations (including unrelated operations) should be scheduled to prevent premature acceptance or rejection, which could be detrimental to the attainment of optimum product quality in the end item.

6.7 Definition of terms.

6.7.1 Deformed link. A link whose shape or dimensions or both have been mutilated or altered by processing to the extent that it is unsuitable for its intended use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

6.8 Subject term (keyword) listing.

M790 Series Ammunition
M242 Gun

6.9 Submission of alternative inspection provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AE30)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-71366	921012

3. DOCUMENT TITLE: PROCESS SPECIFICATION, AMMUNITION, 25MM, PACKAGING, PACKING, AND MARKING

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:23Z
Check the source to verify that this is the current version before use.