MILITARY STANDARD

ELECTRONIC EQUIPMENT PARTS
SELECTED STANDARDS
MICROCIRCUITS AND SEMICONDUCTORS

TO ALL HOLDERS OF MIL-STD-242G(NAVY), PART 5:

1. THE FOLLOWING PAGES OF MIL-STD-242G(NAVY), PART 5 HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	31 August 1981	(Reprint without change)	
vi	15 October 1985	vi	12 April 1985
114	15 October 1985	114	12 April 1985
116.1	15 October 1985	116.1	12 April 1985
116.2	12 April 1985	(Reprint without change)	
120	15 October 1985	NONE	----
301.1	15 October 1985	301.1	10 February 1983
301.2	15 October 1985	301.2	10 February 1983
310	15 October 1985	310	31 August 1981
311	15 October 1985	311	10 February 1983
312	15 October 1985	312	12 April 1985
313	31 August 1981	(Reprint without change)	
314	15 October 1985	314	12 April 1985
315	15 October 1985	315	12 April 1985
316	10 February 1983	(Reprint without change)	
317	15 October 1985	317	31 August 1981
318	15 October 1985	318	31 August 1981
319	31 August 1981	(Reprint without change)	
320	31 August 1981	(Reprint without change)	
321	15 October 1985	NONE	----

2. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

3. HOLDERS OF MIL-STD-242G(NAVY), PART 5, WILL VERIFY THAT PAGE CHANGES AND ADDITIONS INDICATED ABOVE HAVE BEEN ENTERED. THIS NOTICE PAGE WILL BE RETAINED AS A CHECK SHEET. THIS ISSUANCE, TOGETHER WITH APPENDED PAGES, IS A SEPARATE PUBLICATION. EACH NOTICE IS TO BE RETAINED BY STOCKING POINTS UNTIL THE MILITARY STANDARD IS COMPLETELY REVISED OR CANCELLED.

Review activity:
Navy - AS, SH, OS

User activities:
Navy - MC

Preparing activity:
Navy-EC

(Project NO 59GP-N055)

FSC 59GP

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

d. DEVICE CLASS. THE DEVICE CLASS IS DESIGNATD BY A SINGLE LETTER INDENTIFYING THE PRODUCT ASSURANCE LEVEL (B IS THE MINIMUM ACCEPTANCE LEVEL).

e. CASE OUTLINE. THE CASE OUTLINE IS DESIGNATED BY A SINGLE LETTER ASSIGNED TO EACH OUTLINE WITHIN EACH DETAIL SPECIFICATION.

f. LEAD FINISH. THE LEAD FINISH IS DESIGNATED BY A SINGLE LETTER AS FOLLOWS:

FINISH LETTER	LEAD FRAME MATERIAL AND FINISH
A	TYPES A OR B, WITH HOT SOLDER DIP
B	TYPES A OR B, WITH ACID TIN PLATE
C	TYPES A OR B, WITH GOLD PLATE
X	TYPES A OR B, WITH FINISHES A, B OR C

NOTES

1. THE LIST FOR MICROCIRCUITS DOES NOT SPECIFY THE FINAL TWO ELEMENTS OF THE PART NUMBER (PARAGRAPHS 5-1.e AND f.). ANY COMBINATION OF OUTLINE, AND LEAD FINISH IS APPROVED FOR USE. THE FINISH DESIGNATION "X" IS NOT MARKED ON THE MICROCIRCUIT OR ITS PACKAGING, BUT IS USED ONLY IN DRAWINGS, PARTS LISTS, PURCHASE ORDERS OR OTHER DOCUMENTS WHERE ANY OF THE LEAD FINISHES ARE CONSIDERED ACCEPTABLE AND INTERCHANGEABLE.

2. NO OUTLINE DRAWINGS ARE PROVIDED FOR MICROCIRCUITS BECAUSE THE PACKAGE CONFIGURATION IS INDICATED BY PART NUMBER. REFER TO THE DETAIL SPECIFICATION FOR COMPLETE CONFIGURATION INFORMATION.

Review activities:
Navy - AS, SH, OS

User activity:
Navy - MC

Preparing activity:
Navy - EC

(Project Number 59GP-N031-5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

TABLE OF CONTENTS

SUBJECT/SECTION	PAGE
100 MICROCIRCUITS	
112 DIGITAL, LPS-TTL	112.1 THRU 112.3
114 DIGITAL, CMOS	114
115 LINEAR	115.1 THRU 115.2
116 MEMORIES	116.1 THRU 116.2
117 MICROPROCESSORS	117
119 DIGITAL LPAS-TTL	119
120 DIGITAL ADVANCED L.P. SCHOTTKY, (ALSTTL)	120
200 SEMICONDUCTORS, DIODES	
201 SEMICONDUCTOR, INDEX (DIODES)	201.1 THRU 201.4
205 SEMICONDUCTOR OUTLINE DRAWINGS	205.1 THRU 205.29
210 VOLTAGE-VARIABLE CAPACITORS	210
211 GENERAL PURPOSE DIODES AND RECTIFIERS	211
212 VOLTAGE REFERENCE	212
213 VOLTAGE REGULATOR	213.1 THRU 213.4
214 CURRENT REGULATOR	214
215 SWITCHING AND FAST RECOVERY RECTIFIERS	215
216 TRANSIENT VOLTAGE SUPPRESSORS	216
217 LIGHT EMITTING	217
218 OPTICALLY COUPLED ISOLATORS	218
300 SEMICONDUCTORS, TRANSISTOR	
301 SEMICONDUCTOR, INDEX (TRANSISTORS)	301.1 THRU 301.2
310 DARLINGTON	310
311 THYRISTOR(SILICON CONTROLLED RECTIFIER)	311
312 FIELD EFFECT	312
313 UNIJUNCTION	313
314 DUAL	314
315 HIGH FREQUENCY	315
316 NPN, LOW POWER(PC $\langle$5 WATTS @ TA=25°C) GEN PURP & SWITCH	316
317 PNP, LOW POWER(PC $\langle$5 WATTS @ TA=25°C) GEN PURP & SWITCH	317
318 NPN, POWER TRANSISTOR (PC$\rangle$ 5 WATTS)	318
319 PNP, POWER TRANSISTOR (PC$\rangle$ 5 WATTS)	319
320 CHOPPER	320
321 MOS FET, POWER(N-CHANNEL)	321

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, CMOS MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
05451B--	ADDER	4-BIT	4008B
05501B--	BUFFER	HEX, INVERTER	4009A
05502B--		HEX, NON-INVERTING	4010A
05503B--		HEX, INVERTER	4049A
05554B--		HEX, NON-INVERTING	4050B
05651B--	COUNTER	DECADE COUNTER/DIVIDE	4017B
05652B--		PRESETTABLE DIVIDE BY N	4018B
05653B--		14-STAGE RIPPLE CARRY	4020B
05604B--		DIVIDE BY 8 COUNTER/DIVIDE	4022B
05655B--		7-STAGE BINARY COUNTER	4024B
05151B--	FLIP-FLOP	D-TYPE, DUAL, EDGE-TRIGGERED	4013B
05152B--		DUAL, J-K MASTER SLAVE	4027B
05051B--	GATE	QUAD, NAND, 2-INPUT	4011B
05052B--		DUAL, NAND, 4-INPUT	4012B
05053B--		TRIPLE, NAND, 3-INPUT	4023B
05201B--		DUAL, NOR, 3-INPUT, PLUS INVERTER	4000A
05252B--		NOR, QUAD, 2-INPUT	4001B
05253B--		NOR, DUAL, 4-INPUT	4002B
05254B--		TRIPLE, NOR, 3-INPUT	4025B
05351B--		DUAL COMPLEMENTARY PAIR PLUS INVERT	4007UB
05352B--		QUAD, AND-OR SELECT	4019B
05353B--		QUAD, EXCLUSIVE-OR	4030B
17001B--		QUAD, AND, 2-OUTPUT	4081B
17002B--		DUAL, AND, 4-INPUT	4082B
17003B--		TRIPLE, AND, 3-INPUT	4073B
17101B--		QUAD, OR, 2-INPUT	4071B
17102B--		DUAL, OR, 4-INPUT	4072B
17103B--		TRIPLE, OR, 3-INPUT	4075B
17201B--		DUAL, AND-OR-INVERT, 2-WIDE, 2-INPUT	4085B
17202B--		EXPANDABLE, AND-OR-INVERTER	4086B
17203B--		QUAD, EXCLUSIVE-OR	4070B
17204B--		QUAD, EXCLUSIVE-NOR	4077B
05701B--	SHIFT REGISTER	DUAL 4-STAGE, DUAL 5-STAGE, STATIC	4006A
05752B--		8-STAGE, SYN, PARALLEL OR SERIAL IN	4014B
05753B--		DUAL 4-STAGE, SER INPUT, PAR OUTPUT	4015B
05754B--		8-STAGE, ASYN	4021B
05705B--		64-STAGE STATIC	4031A

NOTE: USE CMOS SERIES B PARTS AS THEY BECOME QUALIFIED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, MEMORIES MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
20101B--	PROM	512-BIT, 64-WORDS/8-BITS/WORD OC, TTL	54186,HPROM 512 MCM5303
20301B--		1024-BIT(256 X4), OC, S-TTL	7610, 5300-1 82S126,93417
20302B--		1024-BIT(256 X4), TS, S-TTL	7611, 5301-1, 82S129,93427
20401B--		2048-BIT(512 X4), OC, S-TTL	7620,5303-1, 82S130,93436
20402B--		2048-BIT(512 X4), TS S-TTL	7621,5306-1 82S131,93446
20602B--		4096-BIT(1024 X4), TS, S-TTL	7643,5353-1, 82S137,93453
20701B--		256-BIT(32 X 8), OC, S-TTL	7602,5330, 82S23
20702B--		256-BIT(32 X 8), TS, S-TTL	7603, 5331, 82S123
20802B--		4096-BIY(512 X 8), TS, S-TTL	7641,5341-1,
20902B--		2048 X 4 PROM (FUSIBLE LINK,TS)	82S185
21004B--		2048 X 8 PROM (FUSIBLE LINK,TS)	93Z511 82S141,93448
20904B--		8192-BIT(1024 X 8), TS, S-TTL(LOW PWR)	7681,5381-1, 82S181,93451
20905B--		8192-BIT(1024 X 8), TS, S-TTL	82S2708, 93461
21002B--		16,384-BIT(2048 X 8), TS, S-TTL	76161, 53S1681 82S191,93Z511
23102B--	RAM	1024 X 1 STATIC RAM (60ns)	93425
23103B--		1024 X 1 STATIC RAM (70ns)	93L415
23104B--		1024 X 1 STATIC RAM (70 ns)	93L425
23108B--		1024 X 1 STATIC RAM (45ns)	82S115
23112B--		256 X 1 STATIC RAM LOW POWER(75 ns)	93L422
23113B--		1024 X 1 STATIC RAM LOW POWER(50 ns)	93L425A
23115B--		256 X 1 STATIC RAM LOW POWER(55 ns,TS)	93L422A
23801B--		4096 X 1 STATIC RAM(85ns)	2147
23803B--		4096 X 1 STATIC RAM(70ns)	2147H
23805B--		1024 X 4 STATIC RAM(55ns)	2147H-3

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, MEMORIES MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
23806B--	PALS	1024 X 4 STATIC RAM(70ns)	2148H
23807B--		1024 X 4 STATIC RAM(45ns)	2147H-2
24001B--		16384 X 1-BIT, TS, NMOS(200ns)	2117,4116
24002B--		16384 X 1-BIT, TS, NMOS(250ns)	2117,4116
24402B--		64K X 1 DYNAMIC RAM(2ms REFRESH,TS)	4564
50301B--		OCTAL 10-INPUT AND-OR GATE ARRAY	PAL-10H8
50303B--		QUAD 14-INPUT AND-OR GATE ARRAY	PAL-14H4
50306B--		10-INPUT 8-OUTPUT AND-OR-INVERT GATE	PAL-10L8

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

MICROCIRCUITS

DIGITAL, ADVANCED L.P.SCHOTTKY, TTL (ALSTTL) MIL-M-38510 QPL-38510

PART NO. JM38510/	FUNCTION	CIRCUIT	COMMERCIAL TYPE
38301	BUFFER	OCTAL INVERTING W/INVERTING CONTROL INPUTS	54ALS240
38302		OCTAL NONINVERTING W/COMPLEMENTARY CONTROL IN	54ALS241
38303		OCTAL NONINVERTING W/INVERTING CONTROL IN	54ALS244
37701	DECODER	3 TO 8 LINE	54ALS138
37001	GATE	QUAD, 2-INPUT NAND	54ALS00
37002		TRIPLE, 3-IN NAND	54ALS10
37003		DUAL, 4-IN NAND	54ALS20
37004		8-IN NAND	54ALS30
37005		13-IN NAND	54ALS133
37301		QUAD, 2-IN NOR	54ALS02
37302		TRIPLE, 3-IN NOR	54ALS27
37401		QUAD, 2-IN AND	54ALS08
37402		TRIPLE, 3-IN AND	54ALS11
37501		QUAD, 2-IN OR	54ALS32
38401	GATE BUFFER	QUAD, 2-IN NAND	54ALS1000 54ALS37
38402		QUAD 2-IN NOR	54ALS1002 54ALS28
38407		DUAL, 4-IN NAND	54ALS1020 54ALS40
38411		HEX NON INVERTING	54ALS1034
37006	INVERTER	HEX	54ALS04

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, INDEX (TRANSISTORS)

PART NUMBER MIL-S-19500	SLASH SHEET	OUTLINE DRAWING	PAGE NUMBER	PART NUMBER MIL-S-19500	SLASH SHEET	OUTLINE DRAWING	PAGE NUMBER
JANTX 2N683	108	TO208	311	JANTX 2N3030	419	TO18	311
JANTX 2N685	108	TO208	311	JANTX 2N3031	419	TO18	311
JANTX 2N687	108	TO208	311	JANTX 2N3032	419	TO18	311
JANTX 2N688	108	TO208	311	JANTX*2N3251A	323	TO18	317
JANTX 2N689	108	TO208	311	JANTX 2N3330##	378	TO72	312
JANTX 2N690	108	TO208	311	JANTX 2N3331##	378	TO72	312
JANTX*2N918?	301	TO72	315	JANTX*2N3375?	341	TO212	315
JANTX 2N1774A	168	TO64	311	JANTX*2N3421S	393	TO5	316
JANTX 2N1793	204	TO83	311	JANTX*2N3439	368	TO5	316
JANTX 2N1795	204	TO83	311	JANTX*2N3440	368	TO5	316
JANTX 2N1798	204	TO83	311	JANTX*2N3442	370	TO3	318
JANTX 2N1800	204	TO83	311	JANTX*2N3467	348	TO5	317
JANTX 2N1806	204	TO94	311	JANTX*2N3468	348	TO5	317
JANTX 2N1911	204	TO94	311	JANTX*2N3501	366	TO5	316
JANTX 2N1913	204	TO94	311	JANTX*2N3585	384	TO66	318
JANTX 2N1916	204	TO94	311	JANTX*2N3637	357	TO5	317
JANTX*2N2060	270	TO77	314	JANTX*2N3700S	391	TO18	316
JANTX 2N2151	277	TO111	318	JANTX*2N3716	408	TO3	318
JANTX*2N2219A	251	TO5	316	JANTX*2N3735	395	TO5	316
JANTX*2N2222A	255	TO18	316	JANTX*2N3737	395	TO46	316
JANTX*2N2323AS	276	TO5	311	JANTX*2N3739	402	TO66	318
JANTX*2N2324AS	276	TO5	311	JANTX*2N3741	441	TO66	319
JANTX*2N2326AS	276	TO5	311	JANTX*2N3743	397	TO39	317
JANTX*2N2328AS	276	TO5	311	JANTX*2N3764	396	TO46	317
JANTX*2N2329S	276	TO5	311	JANTX*2N3765	396	TO46	317
JANTX*2N2369A	317	TO18	316	JANTX*2N3767	518	TO66	318
JANTX*2N2432A	313	TO18	320	JANTX*2N3792	379	TO3	319
JANTX*2N2484	376	TO18	316	JANTX*2N3810	336	TO77	314
JANTX*2N2605	354	TO46	317	JANTX*2N3811	336	TO77	314
JANTX*2N2814	415	TO61	318	JANTX*2N3821#	375	TO72	312
JANTX*2N2857#	343	TO72	315	JANTX*2N3822#	375	TO72	312
JANTX*2N2880	315	TO111	318	JANTX*2N3823#	375	TO72	312
JANTX*2N2905A	290	TO5	317	JANTX*2N3866?	398	TO39	315
JANTX*2N2907A	291	TO18	317	JANTX*2N3868S	350	TO5	317
JANTX*2N2920	355	TO77	314	JANTX*2N3879	526	TO66	318
JANTX*2N2944A	382	TO46	320	JANTX*2N3960	399	TO18	316
JANTX*2N2945A	382	TO46	320	JANTX*2N3997	374	TO214†	318
JANTX*2N2946A	382	TO46	320	JANTX*2N4033	512	TO39	317
JANTX*2N3019S?	391	TO5	315	JANTX*2N4150S	394	TO5	316
JANTX*2N3019S	391	TO5	316	JANTX*2N4261	511	TO72	317
JANTX 2N3027	419	TO18	311	JANTX*2N4449	317	TO46	316
JANTX 2N3028	419	TO18	311	JANTX*2N4854**	421	TO77	314
JANTX 2N3029	419	TO18	311	JANTX*2N4856#	385	TO18	312
JANTX*2N3093	280	TO94	311	JANTX*2N4857#	385	TO18	312
JANTX*2N3095	280	TO94	311	JANTX*2N4858#	385	TO18	312
JANTX*2N3097	280	TO94	311	JANTX*2N4948	388	TO18	313

Supersedes page 301.1 of 10 February 1983

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, INDEX (TRANSISTORS CONTINUED)

PART NUMBER MIL-S-19500	SLASH SHEET	OUTLINE DRAWING	PAGE NUMBER	PART NUMBER MIL-S-19500	SLASH SHEET	OUTLINE DRAWING	PAGE NUMBER
JANTX*2N4957??	426	TO72	315				
JANTX*2N5004	534	TO59†	318	JANTX*2N6299	540	TO66	310
JANTX*2N5038	439	TO3	318	JANTX 2N6350?	472	TO33	310
JANTX*2N5039	439	TO3	318	JANTX 2N6351?	472	TO33	310
JANTX*2N5109?	453	TO39	315	JANTX 2N6352?	472	TO66	310
JANTX 2N5157	371	TO3	318	JANTX 2N6353?	472	TO66	310
JANTX*2N5114##	476	TO18	312	JANTX 2N6384?	523	TO3	310
JANTX*2N5115##	476	TO18	312	JANTX*2N6385?	523	TO3	310
JANTX*2N5116##	476	TO18	312	JANTX*2N6546	525	TO3	318
JANTX*2N5237	394	TO5	316	JANTX*2N6547	525	TO3	318
JANTX 2N5241	414	TO3	318	JANTX*2N6649??	527	TO3	310
JANTX*2N5250	380	TO114	318	JANTX 2N6650??	527	TO3	310
JANTX*2N5251	380	TO114	318	JANTX*2N6756	542	TO3	321
JANTX*2N5416S	485	TO5	317	JANTX*2N6758	542	TO3	321
JANTX*2N5545$$	430	TO71	312	JANTX*2N6760	542	TO3	321
JANTX*2N5546$$	430	TO71	312	JANTX*2N6762	542	TO3	321
JANTX*2N5664	455	TO66	318	JANTX*2N6764	543	TO3	321
JANTX*2N5665	455	TO66	318	JANTX*2N6766	543	TO3	321
JANTX*2N5666	455	TO5	316	JANTX*2N6768	543	TO3	321
JANTX*2N5667	455	TO5	316	JANTX*2N6770	543	TO3	321
JANTX*2N5684	466	TO3	319	JANTX*2N6782	556	TO39	321
JANTX*2N5685	464	TO3	318	JANTX*2N6784	556	TO39	321
JANTX*2N5686	464	TO3	318	JANTX*2N6786	556	TO39	321
JANTX*2N5794	495	TO77	314	JANTX*2N6788	555	TO39	321
JANTX*2N5796	495	TO77	314	JANTX*2N6790	555	TO39	321
JANTX*2N6033	528	TO3	318	JANTX*2N6792	555	TO39	321
JANTX*2N6052??	501	TO3	310	JANTX*2N6794	555	TO39	321
JANTX*2N6059?	502	TO3	310	JANTX*2N6796	557	TO39	321
JANTX*2N6137§	493	TO18	313	JANTX*2N6798	557	TO39	321
JANTX*2N6138§	493	TO18	313	JANTX*2N6800	557	TO39	321
JANTX*2N6284?	504	TO3	310	JANTX*2N6802	557	TO39	321
JANTX*2N6287??	505	TO3	310	JANTX*2N6300	539	TO66	310
JANTX*2N6298??	540	TO66	310	JANTX*2N6301?	539	TO66	310

*--JANTX AND/ OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
**--COMPLEMENTARY NPN/PNP
#--N-CHANNEL
##--P-CHANNEL
?--NPN
??--PNP
§--PROGRAMABLE UNIJUCTION
$--COLLECTOR COMMON TO STUD
$$--DUAL MATCHED N CHANNEL
†--COLLECTOR ISOLATED FROM CASE

Supersedes page 301.2 of 10 February of 1983

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

DARLINGTON MIL-S-19500 OPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT	IC	VBR				hFE	VCE	f	C	ton	toff
				MAX	EB1	EB2	CBO1	CEO	MIN / MAX	(SAT)				
			W	Adc	Vdc	Vdc	Vdc	Vdc		Vdc	MHz	PF	uS	uS
JANTX*2N6052##	501	TO3	150.0?	12	5.0		100	100	1000 10K	3.0	20	300	1.0	6.0
JANTX*2N6059#	502	TO3	150.0?	12	5.0		100	100	1000 10K	3.0	20	300	1.0	6.0
JANTX*2N6284#	504	TO3	175.0?	20	7.0		100	100	1250 18K	3.0	8	300	1.5	7.5
JANTX*2N6287##	505	TO3	175?	20	7.0		100	100	1250 18K	3.0	8	300	1.5	7.5
JANTX 2N6350#	472	TO33	1.0??	5	12.0	6.0	80		2000 10K	1.1	50	40	.5	1.2
JANTX 2N6351#	472	TO33	1.0??	5	12.0	6.0	150		1000 10K	2.5	50	40	.5	1.2
JANTX 2N6352#	472	TO66	2.0??	5	12.0	6.0	80		2000 10K	1.5	50	40	.5	1.2
JANTX 2N6353#	472	TO66	2.0??	5	12.0	6.0	150		1000 10K	2.5	50	40	.5	1.2
JANTX 2N6384#	523	TO3	100?	10	5.0		60	60	1000 20K	2.0	300	200	2.5	10
JANTX*2N6385#	523	TO3	100?	10	5.0		80	80	1000 20K	2.0	300	200	2.5	10
JANTX*2N6649##	527	TO3	85?	10	5.0		60	60	1000 20K	2.0	400	200	2.5	10
JANTX 2N6650##	527	TO3	85?	10	5.0		80	80	1000 20K	2.0	400	200	2.5	10
JANTX*2N6298##	540	TO66	32??	8	5.0		60	60	750 18K	2.0	25 350	200	2.0	8.0
JANTX*2N6299##	540	TO66	32??	8	5.0		80		750 18K	2.0	25 350	200	2.0	8.0
JANTX*2N6300#	539	TO66	32??	8	5.0		60	60	750 18K	2.0	25 350	200	2.0	8.0
JANTX*2N6301#	539	TO66	32??	8	5.0		80	80	750 18K	2.0	25 350	200	2.0	8.0

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
#--NPN.
##--PNP.
?--TC=25
??--TC=100

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTORS

THYRISTOR (SILICON CONTROLLED RECTIFIER) MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	IO A	VDRM V	ITSM a	IH mAdc	VGT Vdc	IGT mAdc	ton uS	toff uS	dv/dt V/us
JANTX 2N683	108	TO208	16.0	100	150	50	.25-3.0	80	5	30	25
JANTX 2N685	108	TO208	16.0	200	150	50	.25-3.0	80	5	30	25
JANTX 2N687	108	TO208	16.0	300	150	50	.25-3.0	80	5	30	25
JANTX 2N688	108	TO208	16.0	400	150	50	.25-3.0	80	5	30	25
JANTX 2N689	108	TO208	16.0	500	150	50	.25-3.0	80	5	30	25
JANTX 2N690	108	TO208	16.0	600	150	50	.25-3.0	80	5	30	25
JANTX 2N1777A	168	TO64	4.7	400	60	25	.20-2.0	15	5	30	5
JANTX 2N1793	204	TO83	50.0	100	1000	40	.25-3.0	70	15	40	20
JANTX 2N1795	204	TO83	50.0	200	1000	40	.25-3.0	70	15	40	20
JANTX 2N1798	204	TO83	50.0	400	1000	40	.25-3.0	70	15	40	20
JANTX 2N1800	204	TO83	50.0	600	1000	40	.25-3.0	70	15	40	20
JANTX 2N1806	204	TO94	50.0	600	1000	40	.25-3.0	70	15	40	20
JANTX 2N1911	204	TO94	50.0	100	1000	40	.25-3.0	70	15	40	20
JANTX 2N1913	204	TO94	50.0	200	1000	40	.25-3.0	70	15	40	20
JANTX 2N1916	204	TO94	50.0	400	1000	40	.25-3.0	70	15	40	20
JANTX*2N2323AS	276	TO5	0.22	50	15	2	.35-.8	0.20			.7
JANTX*2N2324AS	276	TO5	0.22	100	15	2	.35-.8	0.20			.7
JANTX*2N2326AS	276	TO5	0.22	200	15	2	.35-.8	0.20			.7
JANTX*2N2328AS	276	TO5	0.22	300	15	2	.35-.8	0.20			.7
JANTX*2N2329S	276	TO5	0.22	400	15	2	.35-.8	0.20			1.8
JANTX 2N3027	419	TO18	.175	30	8	5	.4-.8	0.20	0.2	2	30
JANTX 2N3028	419	TO18	.175	60	8	5	.4-.8	0.20	0.2	2	15
JANTX 2N3029	419	TO18	.175	100	8	5	.4-.8	0.20	0.2	2	10
JANTX 2N3030	419	TO18	.175	30	8	4	.44-.6	0.02	0.1	2	30
JANTX 2N3031	419	TO18	.175	60	8	4	.44-.6	0.02	0.1	2	15
JANTX 2N3032	419	TO18	.175	100	8	4	.44-.6	0.02	0.1	2	10
JANTX*2N3093	280	TO94	50	800	1000		3.0	70		40	20
JANTX*2N3095	280	TO94	50	1000	1000		3.0	70		40	20
JANTX*2N3097	280	TO94	50	1200	1000		3.0	70		40	20

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
**--BIDIRECTIONAL.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

FIELD EFFECT MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT TA=25°C mW	VDG Vdc	VDS Vdc	VGS Vdc	VGS (OFF) MIN / MAX Vdc	IG mAdc	IDSS MIN / MAX mAdc	yfs MIN / MAX umho	CISS PF
JANTX 2N3330##	378	TO72	300	20		20	- / 6	10	1 / 3	1000 / 2000	32
JANTX 2N3331##	378	TO72	300	20		20	- / 8	10	1 / 3	1000 / 2000	32
JANTX*2N3821#	375	TO72	300	50	50	50	- / 4	10	.5 / 25	150 / 4500	6
JANTX*2N3822#	375	TO72	300	50	50	50	- / 6	10 / 10	2. / 10	3000 / 6500	6
JANTX*2N3823#	375	TO72	300	30	30	30	- / 8	10	4. / 20	3500 / 6500	6
JANTX*2N4856#	385	TO18	360	40	40	40	4 / 10	50	50		18
JANTX*2N4857#	385	TO18	360	40	40	40	2 / 6	50	20 / 100		18
JANTX*2N4858#	385	TO18	360	40	40	40	0.8 / 4	50	8. / 80		18
JANTX*2N5114##	476	TO18	500	30	30	30	5 / 10	50	30 / 90		25
JANTX*2N5115##	476	TO18	500	30	30	30	3 / 6	50	15 / 60		25
JANTX*2N5116##	476	TO18	500	30	30	30	1.0 / 4	50	5 / 25		27
JANTX*2N5545$	430	TO71	250 / 400	50		50	0.5 / 4.5	30	.5 / 8.0	1500 / 6000	6
JANTX#2N5546$	430	TO71	250 / 400	50		50	0.5 / 4.5	30	.5 / 8.0	1500 / 6000	6

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
#--N CHANNEL
##--P CHANNEL
$--DUAL MATCHED N CHANNEL

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

UNIJUNCTION MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT mW	Ie mA(rms)	VB2E Vdc	RBBO MIN OHMS	RBBO MAX OHMS	n MIN	n MAX	IB2(MOD) MIN mAdc
JANTX*2N4948	388	TO18	360	50	30	4000	1200	.55	.82	12
JANTX*2N6137**	493	TO18	300	300	40					
JANTX*2N6138**	493	TO18	300	300	100					

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
**--PROGRAMABLE UNIJUNCTION

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

DUAL MIL-S-19500 QPL- 19500

TYPE PART NO.	SPEC	OUT DWG	PT		IC	VBR			hFE	hFE1 hFE2	VBE1 VBE2	Cobo	ft
			ONE mW	BOTH mW	mAdc	CBO Vdc	CEO Vdc	EBO Vdc	MIN / MAX		mVdc	(PF)	MHz MIN / MAX
JANTX*2N2060	270	TO77	540	600	500	100	60	7	30 90	.9-1.1	5	15	60 500
JANTX*2N2920	355	TO77	300	500	30	70	60	6	150	.9-1.1	3	5	60 400
JANTX*2N3810	336	TO77	500	600	50	60	60	5	150 450	.9-1.1	3	5	100 500
JANTX*2N3811	336	TO77	500	600	50	60	60	5	300 900	.9-1.1	3	5	100 500
JANTX*2N4854**	421	TO77	300	600	600	60	40	5	100 300			8	200 800
JANTX*2N5794	495	TO77	500	600	600	75	40	6	100 300	.9-1.1	5	8	200
JANTX*2N5796	496	TO77	500	600	600	60	60	5	100 300	.9-1.1	5	8	200

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
**--COMPLEMENTARY NPN/PNP

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

HIGH FREQUENCY MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT@ TA=25°C mW	POUT MIN/MAX W	PIN W	f W	n MHz	VBR CBO %	VBR CEO	VBR EBO	hFE@ MIN/MAX	IC mAdc	ft MHZ MIN/MAX
JANTX*2N918#	301	TO72	200	.030				30	15	3	20 200	3	600
JANTX*2N2857#	343	TO72	200					30	15	3	30 150	3	1000 1900
JANTX*2N3019S#	391	TO5	800					140	80	7	100 300	150	100 400
JANTX*2N3375#	341	TO212	2600	3 6	1.00	400	40	65	40	4	15 150	150	350
JANTX*2N3866A#	398	TO39	1000	1 2	.15	400	45	60	30	3.5	25 200	50	800 1500
JANTX*2N4957##	426	TO72	200					30	30	3	30 150	5	1200 3600
JANTX*2N5109#	453	TO39	1000					40	20	3	40 150	50	1200 2200

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
#--NPN
##--PNP

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

NPN,LOW POWER(PC<5 W AT TA=25°C) G.P. AND SWTICHING MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT TA= 25°C W	IC A	VBR CBO Vdc	VBR CEO Vdc	VBR EBO Vdc	VCE (SAT) MAX Vdc	VBE (SAT) MAX Vdc	hFE@IC MIN/MAX	hFE@IC mAdc	ft MIN/MAX MHz	Cobo PF	ton nS	toff nS
JANTX*2N2219A	251	TO5	.800	.800	75	50	6.0	.3	1.2	100 300	150	250 1200	8	35	300
JANTX*2N2222A	255	TO18	.500	.800	75	50	6.0	.3	1.2	100 300	150	250	8	35	300
JANTX*2N2369A	317	TO18	.360		40	15	4.5	.2	.7	40 120	10	300 1200	4	12	18
JANTX*2N2484	376	TO18	.360	.050	60	60	6	.3		250	1	60 210	5		
JANTX*2N3019S	391	TO5	.800	1	140	80	7	.2	1.1	50 200	100	100 400	12		
JANTX*2N3421S	393	TO5	1	3	125	80	8.0	.25	1.2	40 120	1000	40 160	150	300	1200
JANTX*2N3439	368	TO5	.800	1	450	350	7	.5	1.3	40 160	20	15 75	10	1K	10K
JANTX*2N3440	368	TO5	.800	1	300	250	7	.5	1.3	40 160	20	15 75	10	1K	10K
JANTX*2N3501	366	TO5	1	.300	150	150	6.0	.4	1.2	100 300	150	150 800	8	115	900
JANTX*2N3700	391	TO18	.500	1	140	80	7	.2	1.1	50 200	500	100 400	12		
JANTX*2N3735	395	TO5	1	1.5	75	50	5.0	.5	1.2	40 140	500	250 600	9	48	60
JANTX*2N3737	395	TO46	.500	1.5	75	50	5.0	.5	1.2	40 140	500	250 600	9	48	60
JANTX*2N3960	399	TO18	.400		20	12	4.5	.3	1	60 300	10	1300 2600	25		
JANTX*2N4150S	394	TO5	1.5	10	100	70	7	.60	1.5	40 120	5	15 75	350	550	2K
JANTX*2N4449	317	TO46	.300		40	15	4.5	.2	.85	40 120	10	500	4	12	18
JANTX*2N5237	394	TO5	1.5	10	150	120	7	.50	1.5	40 120	5	15 75	350	550	2K
JANTX*2N5666	455	TO5	1.2	5	250	200	6	.4	1.2	15	3	20 140	90	250	1.5K
JANTX*2N5667	455	TO5	1.2	5	400	300	6	.4	1.2	10	3	20 140	90	250	2K

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

PNP, LOW POWER (PC≤5 W AT TA=25°C) G.P. & SWITCHING MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT@ TA=25°C W	IC A	VBR CBO Vdc	VBR CEO Vdc	VBR EBO Vdc	VCE (SAT) MAX	VBE (SAT) MAX	hFE @ IC MIN/MAX	hFE @ IC A	ft MIN/MAX	Cobo PF	ton nS	toff nS
JANTX*2N2605	354	TO46	.400	.030	70	60	6	.5	.9	30 240	.010	30 240	6		
JANTX*2N2905A	290	TO5	.600	.600	60	60	5	.40	1.3	100 300	.030	200	8	45	200
JANTX*2N2907A	291	TO18	.400	.600	60	60	5	.40	1.3	100 300	.150	200	8		200
JANTX*2N3251A	323	TO18	.360	.200	60	60	5	.25	.9	100 300	.010	300 900	6	70	250
JANTX*2N3467	348	TO5	1	1	40	40	5	.60	1.2	40 120	.500	175 500	25	40	90
JANTX*2N3468	348	TO5	1	1	50	50	5	.60	1.2	25 75	500	150 500	25	40	90
JANTX*2N3637	357	TO5	1	1	175	175	5	.9	.9	100 300	050	200 850	10	400	600
JANTX*2N3743	397	TO39	1	.050	300	300	5	1.2	1.2	50 200	.030	40 160	15		
JANTX*2N3764	396	TO46	.500	1.5	40	40	5	.50	1.2	40 140	.50	180 600	15	43	115
JANTX*2N3765	396	TO46	.500	1.5	60	60	5	.50	1.2	40 140	.500	150 600	15	43	115
JANTX*2N3868S	350	TO5	1	3	60	60	4	.75	1.4	30 150	1.5	60 240	120	100	400
JANTX*2N4033	512	TO39	0.8	1	80	80	5	0.5	1.2	100 300	.100	150 600	10	40	210
JANTX*2N5416S	485	TO5	.75	1	350	300	6		1.5	30 120	.050	75 75	15	1	10
JANTX*2N4261	511	TO72	.200	.03	15	15	4.5	.15		30 150	.010	200	2.5	2.5	3.5

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

NPN,POWER TRANSISTOR(PC>5W) MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT@ IC TC=100°C W	A	V(BR) CBO Vdc	CEO Vdc	EBO Vdc	VCE (SAT) MAX	VBE (SAT) MAX	hFE @ IC MIN/MAX	A	ft MHZ MIN/MAX	Cobo PF	ton nS	toff nS
JANTX 2N2151	277	TO111	30	2	150	100	8	.1	1.2	20 60	1		160		
JANTX*2N2814	415	TO61	50	10	120	80	8	.5	1.2	40 120	5	15 70	350	.350	1.2
JANTX*2N2880	315	TO111	30	5	110	80	8	.25	1.2	40 120	1	20 120	150	.360	2.0
JANTX*2N3442	370	TO3	67	10	160	140	7	1.0		20 70	3				
JANTX*2N3585	384	TO66	20	2	500	300	6	.75	1.4	25 100	1	15 75	120	3	7
JANTX*2N3716	408	TO3	85.7	10	100	80	7	1.0	1.5	50 100	1	4 20	500	1.5	2.0
JANTX*2N3739	402	TO66	10	2	325	30	6	.75		40 200	.100	10 60	20	1.5	3.5
JANTX*2N3767	518	TO66	25.0	4	100	80	6	2.5	1.5	40 160	.500	10 80	50	.250	2.5
JANTX*2N3879	526	TO66	35	7	120	75	7	1.2		20 80	4			.44	1.2
JANTX*2N3997	374	TO214#	30	5	100	80	8	.25	1.2	80 240	1	40 120	150	.3	2.0
JANTX*2N5038	439	TO3	80	20	150	90	7	1.00		20	12	60 240	500	.5	2.0
JANTX*2N5039	439	TO3	80	20	125	75	7	1.00		20	10	60 240	500	.5	2.0
JANTX 2N5157	371	TO3	66.75	3.5	700	500	6	.80	1.5	30 90	1	2.5 12	250	.8	1.7
JANTX 2N5241	414	TO3	85.7	10.0	400	400	6	.70	1.5	15 35	2.5	2.5 12.5	500	.8	1.7
JANTX*2N5250	380	TO114	200	50.0	125	100	10	2.00	2.5	10 40	70.0	10.0 70.0		2.0	2
JANTX*2N5251	380	TO114	200	50.0	180	150	10	2.30	2.5	10 40	70.0	10.0 70.0		2.0	2
JANTX*2N5664	455	TO66	30	5	250	200	6	.4	1.2	15	3	20 140	90	.25	1.5
JANTX*2N5665	455	TO66	30	5	400	300	6	.4	1.2	10	3	20 140	90	.25	2.0
JANTX*2N5685	464	TO3	171	50.0	60	60	5	1.00	2.0	15 60	25.0	2.0 20.0	1200	1.5	3
JANTX*2N5686	464	TO3	171	50.0	80	80	5	1.00	2.0	15 60	25.0	2.0 20.0	1200	1.5	3
JANTX*2N6033	528	TO3	140	40	150	120	7	1.0		10 50	40			.5	2
JANTX*2N6546	525	TO3	100	15		300	9	1.5	1.6	12 60	5	6 30	500	1	4.7
JANTX*2N6547	525	TO3	100	15		450	9	1.5	1.6	12 60	5	6 30	500	1	4.7
JANTX*2N5004	534	TO59#	30	5	100	80	5.5	1.5	2.2	70 200	2.5	70	250	.5	1.5

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.
#--COLLECTOR ISOLATED FROM CASE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

PNP, POWER TRANSISTOR(PC>5W) MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT TC=100° W	IC A	VBR CBO Vdc	VBR CEO Vdc	VBR EBO Vdc	VCE (SAT) MAX	VBE (SAT) MAX	hFE @ IC MIN/MAX	hFE @ IC A	ft MIN/MAX	Cobo PF	ton uS	toff uS
JANTX*2N3741	441	TO66	14.25	4	80	80	7	.4		30 100	.250	25 250	100	.4	1
JANTX*2N3792	379	TO3	85.7	10	60	60	7	2.5	3.0	30 120	3	4 20	500	1.5	2
JANTX*2N5684	466	TO3	300	50	80	80	5	1.00	2.0	15 60	25	2 20	2K	1.5	3
JANTX*2N5005#	535	TO59	30	5	100	80	5.5	1.5	2.2	70 200	25	70	250	.5	1.5
JANTX*2N5683	466	TO3	171	50	60	60	5	1.0	2.0	15 60	25	2	2000	1.5	3

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.

#--ISOLATED CASE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTORS, TRANSISTOR

CHOPPER MIL-S-19500 QPL-19500

TYPE PART NO.	SPEC	OUT DWG	PT	VBR				hFE	hFE	VEC	Rec	ft	Cobo	Cibo
				CEO Vdc	CBO Vdc	EBO Vdc	ECO Vdc	MIN / MAX	INV	ofs mVdc	(ON) OHMS	MIN / MAX MHz	PF	PF
JANTX*2N2432A	313	TO18	300	45	45		18	80 400	3	.7	15	40 200	12	12
JANTX*2N2944A	382	TO46	400	10	15	15	10	100	50	.6	4	15 55	10	6
JANTX*2N2945A	382	TO46	400	20	25	25	20	70	30	1.0	6	10 55	10	6
JANTX*2N2946A	382	TO46	400	35	40	40	35	50	20	2.0	8			

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.

SEMICONDUCTOR, TRANSISTORS

MOS FET, POWER (N-CHANNEL) MIL-S-19500 QPL - 19500

TYPE PART NO.	SPEC	OUT DWG	PT @ TC=25°C W	VDS V	VGS V	ID TC=25°C A	IDM A(ph)	VGS(th) MIN / MAX	VGS(th) @ID mA	VDS(on) @VGS=10V MAX OHM	td (on) tr ns	td (off) tf ns	CISS pf.	gfs MIN / MAX
JANTX*2N6782	556	TO39	15	100	+20	3.50	14.0	2.0	0.5	0.6	15	25	60	1.0
								4.0			25	20	200	3.0
JANTX*2N6784				200		2.25	9.0			1.5	15	30		0.9
											20	20		2.7
JANTX*2N6786				400		1.25	5.5			3.6	15	35		0.7
											20	30		2.1
JANTX*2N6788	555	TO39	20	100	+20	6.00	24	2.0	1.0	.30	40	40	200	1.5
								4.0			70	70	600	4.5
JANTX*2N6790				200		3.50	14			.80	40	50		1.5
											50	50		4.5
JANTX*2N6792				400		2.00	10			1.80	40	60		1.0
											35	35		3.0
JANTX*2N6794				500		1.50	6.5			3.00	40	60		1.0
											30	30		3.0
JANTX*2N6796	557	TO39	25	100	+20	8.0	25	2.0	0.5	0.18	30	40	350	3.0
								4.0			75	45	900	9.0
JANTX*2N6798				200		5.5	12.5			0.4	30	50		2.5
											50	40		7.5
JANTX*2N6800				400		3.0	6.0			1.0	30	55		2.0
											35	35		6.0
JANTX*2N6802				500		2.5	5.0			1.5	30	50		1.5
											30	30		4.5
JANTX*2N6756	542	TO3	75	100	+20	14.0	56	2.0	1.0	0.18	30	40	350	4.0
								4.0			75	45	800	12
JANTX*2N6758				200		9.0	36			0.4	30	50		3.0
											50	40		9.0
JANTX*2N6760				400		5.5	22			1.0	30	55		3.0
											35	35		9.0
JANTX*2N6762				500		4.5	18			1.5	30	55		2.5
											30	30		7.5
JANTX*2N6764	543	TO3	150	100	+20	38	160	2.0	1.0	.055	35	125	1000	9.0
								4.0			100	100	3000	27
JANTX*2N6766				200		30	120			.085	35	125		9.0
											100	100		27
JANTX*2N6768				400		14	60			.300	35	150		8.0
											65	75		24
JANTX*2N6770				500		12	52			.400	35	150		8.0
											50	70		24

*--JANTX AND/OR JANTXV PARTS ARE APPROVED AND EITHER CAN BE USED.

☆U.S. GOVERNMENT PRINTING OFFICE: 1985—605-036/24787

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:46Z
Check the source to verify that this is the current version before use.