MIL-T-52932/1B
1 November 1983
SUPERSEDING
MIL-T-52932/1A
11 July 1980

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, SOLID TIRES; 4000-POUND CAPACITY, 144-INCH LIFT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the truck described herein shall consist of this document and the issue in effect of Specification MIL-T-52932B.

REQUIREMENTS

1. Capacity: 4000 pounds at 24 inches load center.
2. Collapsed mast height: 70 inches maximum.
3. Maximum fork height: 144 inches minimum.
4. Free lift height: 42 inches minimum.
5. Fork size: 1-13/16 inches maximum thickness X 5-1/16 inches maximum width X 42 inches long, plus 0 inch minus 1/2 inch.
6. Fork spacing: 10 inches to minimum 32 inches.
7. Tires: Drive 2; steer 2.
8. Overhead guard height: 83 inches maximum.
9. Right-angle turn dimension: 150 inches maximum. (Add 4 inches when side shift is used.)
10. Maximum travel speed: 8 mph minimum.
11. Upright tilt: 3 degrees, plus or minus 1/2 degree, forward; 6 degrees minimum rearward.
12. Underclearance beneath mast assembly: 3.25 inches minimum.
13. Acceleration: 22 feet in maximum 4 seconds.
    44 feet in maximum 6 seconds.
14. Cycle time: Average 3 minutes or less.

Custodians:
Army - ME
Air Force - 99
Navy - SA

Review activities:
Army - SM, MT
Navy - MC
DLA - CS

User activity:
Navy - SH

Preparing activity:
Army - ME

Project 3930-0529

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:40Z
Check the source to verify that this is the current version before use.