MIL-C-17596E
AMENDMENT-1
27 February 1984

MILITARY SPECIFICATION

COMPRESSORS, RECIPROCATING OR ROTARY POWER DRIVEN
(EMD), AIR, BASE MOUNTED, 10 HP TO 300 HP

This specification is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Paragraph 3.9, line 2: Delete "cable" and substitute "capable".

PAGE 5

Paragraph 3.9.3, line 2: Delete "symmetrical".

PAGE 7

Paragraph 3.10.4, line 4: Delete "15" and insert "10".

Paragraph 3.11.1, line 5: Delete "three" and substitute "two", and delete "(full load, one-half load, and no load)".

PAGE 13

4.1, line 11: Delete "a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4)."

Add: 4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

Add: 4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

Custodians:

Army - ME
Navy - YD
Air Force - 99

Preparing Activity:

Navy - YD

Project No. 4310-0166

Review Activity:

DLA - CS

User Activity:

Army - ER

FSC 4310

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:22Z
Check the source to verify that this is the current version before use.