INCH-POUND
MIL-C-17671F
11 May 1989
SUPERSEDING
MIL-C-17671E
23 September 1986
(See 6.8)

MILITARY SPECIFICATION

CANISTER, OXYGEN BREATHING APPARATUS, FOR TYPE A-4

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a canister for the type A-4 oxygen breathing apparatus (OBA).

1.2 Part number. The part number for the canister covered by this specification shall be M17671-1.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Naval Sea Systems Command, SEA 55Z3, Department of the Navy, Washington, DC 20362-5101 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4240
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

MILITARY
MIL-P-116 - Preservation, Methods of.

STANDARDS

FEDERAL
FED-STD-313 - Material Safety Data, Transportation Data and Disposal Data for Hazardous Materials Furnished to Government Activities.
FED-STD-595 - Colors.

MILITARY
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-147 - Palletized Unit Loads.
MIL-STD-171 - Finishing of Metal and Wood Surfaces.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWING

NAVAL SEA SYSTEMS COMMAND (NAVSEA)
803-5184258 - Oxygen Breathing Apparatus, Canister, Quick Starting.

(Application for copies should be addressed to the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

PUBLICATION

DEPARTMENT OF HEALTH AND HUMAN SERVICES, NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH (NIOSH)

85-114 - Pocket Guide to Chemical-Hazards

(Application for copies should be addressed to Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.4) in accordance with 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

3.2 Design and details. The design of the canister shall be in accordance with Drawing 803-5184258. The canister shall not utilize compressed gas as a source of breathable gas.

3.3 Markings. Markings on the canisters shall be in accordance with Drawing 803-5184258. A caution shall be imprinted on the canister label warning of the burn hazard when unprotected skin is exposed to the canister.

3.4 Canister performance.

3.4.1 Canister output. The canisters shall maintain breathable gas continuously without deliberate additional user action for a minimum of 30 or 60 minutes after initiation of the starting process (see 4.6.2.2). Breathable gas shall be defined as not less than 20.0 (dry atmosphere) volume percent oxygen. The breathable gas shall contain no impurity in excess of the exposure limit defined in NIOSH 85-114. The canister shall contain no impurities which will generate gas, smoke, or other products which will have any harmful physiological effect on personnel under any conditions of use. The average carbon dioxide volumetric content of the gas shall conform to the limits as specified (see 4.6.2.2.1). The gas temperature when measured as specified (see 4.6.2.2.3) shall be less than 115°F (46°C) dry bulb and 105°F (40°C) wet bulb.

3.4.1.1 Canister surface temperature. The external surface temperature of the canister, with the exception of the ignition components of the breathable gas starting process, shall not exceed 475°F (246°C) during the gas evolution process (see 4.6.2.3). The surface temperature of ignition components (such as the primer) shall not exceed 475°F after 5 minutes after the breathable gas starting process is initiated.

3.4.1.2 Moisture. The humidity content of the gas shall be sufficiently low to preclude condensation forming upon the OBA facepiece lens (fogging) and collection of liquid in the breathing bag and hoses (see 4.6.2.4). Fogging shall be defined as moisture which forms and obscures the wearer's vision and persists for more than 4 consecutive seconds.

3.4.2 Gasflow resistance. Prior to performance testing, the resistance of each fully assembled canister to gasflow shall be not greater than 0.72 inch (18 millimeters (mm)), of water column height when tested as specified (see 4.6.2.1).

3.5 Breathable gas starting process. The canister shall contain a breathable gas starting process which rapidly supplies breathable gas at the beginning of canister use.

3.5.1 Overall requirements. The starting process shall operate within an ambient temperature range of minus 22 to 212°F (minus 30 to 100°C) (see 4.6.3.1 and 4.6.3.2). The process shall supply a minimum of 0.088 cubic foot (2.5 liters (L)) of breathable gas at standard temperature and pressure (STP), 30.4 inches (760 mm) mercury, 32°F (0°C), in the first minute of operation and shall continue to evolve breathable gas until 0.334 cubic foot (9.5 L) of breathable gas at STP have been evolved within a maximum of 3.5 minutes. When the process is initiated at 212°F, it shall evolve 0.354 cubic foot of breathable gas at STP in not less than 45 seconds. Carbon monoxide generated from the starting process shall be less than 0.02 percent by volume (see 4.6.3.3).

Source: https://assist.dla.mil -- Downloaded: 202640-18T10:27Z
Check the source to verify that this is the currentversion before use.

3.5.2 Sparking. The breathable gas starting process shall be non-sparking (see 4.6.4).

3.5.3 Salt spray. The breathable gas starting process shall be resistant to salt water (see 4.6.5).

3.6 Weight. The fully assembled canister shall weigh not more than 75.4 ounces (2155 grams).

3.7 Color. The color of the canister shall be green, in accordance with color number 14110 or 14187 of FED-STD-595 and as specified on Drawing 803-5184258.

3.8 Finish. The finish for the canister shall be in accordance with finish number 22.9 of MIL-STD-171 and as specified on Drawing 803-5184258.

3.9 Identification. The bottom of each canister shall be permanently imprinted with the lot number and date of manufacture. A label with the contract number shall be applied to the canister.

3.10 Material safety data sheet (MSDS). The contracting activity shall be provided a material safety data sheet at the time of contract award. The MSDS shall be provided in accordance with the requirements of FED-STD-313. The MSDS shall be included with each shipment of the material covered by this specification (see 6.5).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of the manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. One hundred sample canisters shall be furnished for first article inspection when specified (see 6.4). If any sample fails any examination or test, it shall constitute failure of first article inspection (see 6.3).

4.3.1 For examinations and nondestructive test. Forty canisters shall be randomly selected from the 100 sample canisters, and subjected to the examinations and test in table I.

TABLE I. First article inspection (examinations and nondestructive test).

Examination or test	Requirement	Test	Number tested
Canister weight	3.6	4.6.1	40
Visual and dimensional examination	3.2, 3.3, 3.7, 3.8 and 3.9	4.5	40

4.3.2 For destructive tests. From the 100 representative canisters selected at random in 4.3, canisters will be selected for the tests specified in table II. The first five tests in table II may be accomplished concurrently.

TABLE II. First article inspection (destructive tests).

Test	Requirement	Test	Number tested
Resistance to gasflow	3.4.2	4.6.2.1	13
Duration	3.4.1	4.6.2.2.1	13
Performance purity	3.4.1	4.6.2.2.2	13
Temperature of canister produced gas	3.4.1	4.6.2.2.3	13
External surface temperature	3.4.1.1	4.6.2.3	13
Moisture	3.4.1.2	4.6.2.4	2
Breathable gas starting process			
Breathable gas evolution at minus 22°F (minus 30°C)	3.5.1	4.6.3.1	13
Breathable gas evolution at 212°F (100°C)	3.5.1	4.6.3.2	13
Purity	3.5.1	4.6.3.3	13
Canister sparking	3.5.2	4.6.4	13
Salt spray	3.5.3	4.6.5	13

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Quality conformance inspection shall consist of the visual and nondestructive examination specified in 4.4.1.1 and group A and D tests specified in tables III and IV. Group B and C tests are not applicable. Test specified in 4.6.4 and 4.6.2.2.2 need to be tested on only one random sample per lot and tests specified in 4.6.3.1 and 4.6.3.2 need only be conducted on two random samples per lot. Tests specified in 4.6.5 need be tested on only two canisters from every 20 lots to validate conformance to requirements.

TABLE III. Group A examinations and test.

Examinations and test	Requirement	Test
Canister weight	3.6	4.6.1
Visual and dimensional examination	3.2, 3.3, 3.7, 3.8 and 3.9	4.5

TABLE IV. Group D tests.

Test	Requirement	Test
External surface temperature	3.4.1.1	4.6.2.3
Temperature of canister produced gas	3.4.1	4.6.2.2.3
Canister sparking	3.5.2	4.6.4
Resistance to gasflow	3.4.2	4.6.2.1
Duration	3.4.1	4.6.2.2.1
Performance purity	3.4.1	4.6.2.2.2
Breathable gas starting process		
Breathable gas evolution at minus 22°F (minus 30°C)	3.5.1	4.6.3.1
Breathable gas evolution at 212°F (100°C)	3.5.1	4.6.3.2
Salt spray	3.5.3	4.6.5

4.4.1 Lot. A lot shall consist of all completed canisters produced under the same conditions and offered for inspection at one time with quantity not to exceed 3,200 canisters.

4.4.1.1 Sampling for examination. A random sample of assembled canisters shall be selected from each lot for the examination specified in table V. Sampling shall be in accordance with table VI for major defects and table VII for minor defects. If the number of nonconforming items in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected. Any item in the sample found to have one or more defects shall not be offered for delivery. If any item contains a critical defect, the entire lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

TABLE V. Classification of defects.

Categories	Defects
Critical:	
1	Evidence of oil, grease, or flammable substances.
Major:	
101	Breathable gas starting process defective or damaged.
102	Lot number, date of manufacture, or contract number missing.
103	Instruction markings missing, illegible, incorrect, or not as specified.
104	Identification and caution markings missing, illegible, incorrect, or not as specified.
105	Finish missing, incomplete, damaged, or not as specified.
106	Body and neck bent, cracked, or not as specified.
107	Fully assembled canister which is in excess of 75.4 ounces.
Minor:	
201	Tear-off cap defective, not secure on neck, or not as specified.
202	Color not as specified.
203	Workmanship not as required.

TABLE VI. Sampling plan for major defects.

Lot size	Sample size	Acceptance number
2 to 15	2	0
16 to 50	3	0
51 to 150	5	0
151 to 500	8	0
501 to 3200	13	0

TABLE VII. Sampling plan for minor defects.

Lot size	Sample size	Acceptance number
2 to 15	2	0
16 to 50	3	0
51 to 150	5	0
151 to 500	8	1
501 to 3200	13	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

4.4.1.2 Sampling for tests.

4.4.1.2.1 Sampling for group A examinations (nondestructive). Tests specified in table III shall be sampled as specified in 4.4.1.1 and table VI.

4.4.1.2.2 Sampling for group D tests (destructive). A random sample of assembled canisters shall be selected from each lot for the tests specified in table IV. Sampling shall be in accordance with table VI. If the number of non-conforming items in any sample exceeds the acceptance number for that sample, the lot represented by the sample shall be rejected. Tests specified in 4.6.2.2.2 and 4.6.4 need to be tested on only one random sample per lot. Tests specified in 4.6.3.1 and 4.6.3.2 need be conducted on only two random samples per lot. Tests specified in 4.6.5 need be tested on only two canisters from every 20 lots to validate conformance to requirements.

4.5 Examinations.

4.5.1 Visual. Sample canisters shall be visually examined for conformance to the requirements specified in 3.3, 3.7, 3.8 and 3.9.

4.5.2 Dimensions. Sample canisters shall be examined for conformance to the requirement specified in 3.2.

4.6 Tests.

4.6.1 Weight. Sample canisters shall be tested for weight to determine conformance to the requirement in 3.6.

4.6.2 Resistance to gasflow and performance tests.

4.6.2.1 Resistance to gasflow. Each sample canister selected shall be tested using a continuous gasflow of 22.5 gallons per minute (gal/min) (85 L per minute (L/min)). Resistance shall be measured within the first minute of gasflow through the canister. Each canister shall be tested for conformance to 3.4.2. A dry or inert gas test shall be used in making this determination.

4.6.2.2 Performance test. After the gasflow test, the canister performance test shall be conducted. For this test, the canister shall be properly installed in a type A-4 oxygen breathing apparatus that has had the facepiece removed from the point where the valve housing attaches to the corrugated breathing tubes. The ends of the corrugated breathing tubes shall be connected to an approved automatic breathing metabolic simulator (ABMS). An approved ABMS is defined as simulator based on the Penn State design developed for the United States Bureau of mines, and approved by the contracting officer. Test samples shall be taken at the "mouth" where the corrugated breathing tubes and the ABMS are connected. Two tests, a normal demand test, and a high demand test shall be used. Half the canisters shall be tested for a minimum of 60 minutes using the normal demand test, and the other half tested for a minimum of 30 minutes using the high demand test. The following metabolic parameters shall be used:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

Normal demand test:

		Work	Wait	Rest
(a)	Oxygen consumption rate	1.50	1.25	0.70 L/min
(b)	CO_2 production rate	1.30	1.05	0.60 L/min
(c)	Ventilation rate (sinusoidal)	42	32	26 L/min
(d)	Respiratory frequency	32	24	24 breaths/min
(e)	Exhaled humidity	80 percent saturated approximately		
(f)	Exhalation temperature	95°F (35°C)		

The test shall begin with work for 1 minute followed by wait for 1 minute. The preceding shall be repeated five times for a total of 10 minutes then followed by rest for 2 minutes. This 12-minute cycle shall be repeated for the remainder of the test.

High demand test:

(a)	Oxygen consumption rate	2.1 L/min
(b)	CO_2 production rate	1.8 L/min
(c)	Ventilation rate (sinusoidal)	50 L/min
(d)	Respiratory frequency	25 breaths/min
(e)	Exhaled humidity	80 percent saturated approximately
(f)	Exhalation temperature	95°F (35°C)

The above parameters (for both tests) shall be maintained continuously through the test. All parameters have a tolerance of plus or minus 5 percent (except exhalation temperature, which is plus 5°F, minus 0°F), of these values over one test, with 1 minute or less variations acceptable. The oxygen and carbon dioxide rate volume represents displacement at operating conditions. The canister performance shall meet the requirements of 4.6.2.2.1 through 4.6.2.2.3.

4.6.2.2.1 Duration. Both carbon dioxide volume content of the gas inhaled by the ABMS and airflow resistance of the ABMS "mouth" shall be monitored and recorded continuously during the performance tests. The sensing unit used for resistance monitoring shall have a 90 percent fullscale response within 10 milliseconds and accuracy of plus or minus 0.5 percent full scale. The following limits shall not be exceeded during the minimum duration of each test:

Average carbon dioxide volume content during test	1.5 percent
*Instantaneous carbon dioxide volume content	5 percent
**Increase in peak inhalation airflow resistance	5 cm of water
**Increase in peak exhalation airflow resistance	10 cm of water

*Average over any 30-second interval
**Increase is relative to the initial value measured in the third minute of the test.

Sample canisters shall conform to the requirements of 3.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

4.6.2.2.2 Performance purity. The test samples of the canister output shall be monitored for purity as specified in 3.4.1. The test samples shall be taken within the first minute of the performance test cycle and shall continue to be drawn at 10-minute intervals until completion of the test cycle as specified in 4.6.2.2.1. Samples shall conform to the requirements of 3.4.1.

4.6.2.2.3 Temperature. At the point where the test samples are taken, the temperature of the canister output shall be monitored and recorded continuously to determine conformance to 3.4.1.

4.6.2.3 Canister external surface temperature. The external surface temperature of the canister shall conform to 3.4.1.1 at any point during the gas evolution process. Test samples shall be taken at contact points around the body of the canister as follows: on the bottom, near the oxygen starting process; on the top, at two points equally distant from the neck; on the concave face, at two distinct points along the vertical center line separated by 4 inches (10.16 centimeters (cm)) and on the convex faces, at two distinct points along the vertical centerline separated by 4 inches.

4.6.2.4 Moisture. To demonstrate conformance to 3.4.1.2, the canister shall be installed in a type A-4 oxygen breathing apparatus. After the apparatus has been completely donned by the wearer it shall be activated. The following work shall then be performed at normal room temperature 70 ± 5°F (21 ± 3°C) by a person weighing a minimum of 180 pounds.

(a) Using a box 8.5 inches high, step up onto it and down at the rate of 30 times per minute for 1 minute.
(b) Rest for 1 minute.
(c) Repeat (a) and (b) for 60 minutes.

4.6.3 Breathable gas starting process. The breathable gas starting process shall be tested by installing the canister in the ABMS to conduct tests in 4.6.3.1 through 4.6.3.3. Test samples shall be taken at the same point specified in 4.6.2.2. Test samples shall be taken within the first minute after starting the canister and shall continue to be drawn at 10 minute intervals until completion of the test.

4.6.3.1 Breathable gas evolution at minus 22°F (minus 30°C). Each canister selected for test shall be thoroughly chilled to minus 22°F (± 5°F). One half of the sample canisters shall be selected and inserted into OBA and ABMS and initiated within a total of 60 seconds. Canisters shall be tested at normal demand (see 4.6.2.2). The other half of the test canisters shall have the caps removed and the protective foil punctured, inserted into a test apparatus, initiated within 60 seconds, and tested to show conformance to the time and volume requirements of 3.5.1.

4.6.3.2 Breathable gas evolution at 212°F (100°C). Each canister selected for test shall be thoroughly heated to plus 212°F (± 5°F). One half of the sample canisters shall be selected and inserted into the OBA and ABMS and initiated within a total of 60 seconds. Canisters shall be tested at normal demand (see 4.6.2.2). The other half of the test canisters shall have the caps removed and the protective foil punctured, inserted into a test apparatus, initiated within 60 seconds, and tested to show conformance to the time and volume requirements of 3.5.1.

Source: https://assist.dla.mil -- Downloaded: 20260-18T10:27Z
Check the source to verify that this is the current version before use.

4.6.3.3 Purity. The gas samples collected in performing tests specified in 4.6.3.1 and 4.6.3.2 shall be tested for purity as specified in 3.4.1. Carbon monoxide shall not exceed 0.02 percent by volume at any one time, as specified in 3.5.1.

4.6.4 Canister sparking. In conformance with 3.5.2, the canister breathable gas starting process shall not produce a spark. Samples shall be tested in a darkened area to allow any sparking to be observed during the activation process. Not more than one sample shall be tested at a time.

4.6.5 Salty spray test. To determine conformance to 3.5.3, sample canisters shall be exposed to a continuous 5 percent salt water spray, or equivalent, for 96 hours, rinsed with fresh water, and wiped dry. Failure of the normal demand performance test (see 4.6.2.2) after this conditioning shall be cause for rejection.

4.7 Packaging inspection. Sample packages and packs, and the inspection of the preservation, packing and marking for shipment and storage shall be in accordance with the requirements of section 5 and the documents specified therein.

5. PACKAGING

(The packaging requirements specified herein apply only for direct Government acquisition. For the extent of applicability of the packaging requirements of referenced documents listed in section 2, see 6.7.)

5.1 Preservation. Preservation shall be level A or C as specified (see 6.2).

5.1.1 Level A. Canisters shall be cleaned, dried, and unit-protected in accordance with method III of MIL-P-116, and as follows: Six canisters, placed in a vertical attitude with necks upward, shall be contained in a fiberboard box meeting the requirements of type CF, grade V3C of PPP-B-636, with style at the contractor's option. Each box shall be furnished with interior fiberboard partitions providing each canister with a separate cell. Canisters' necks shall be provided additional protection by use of fiberboard pads to prevent damage during handling, shipment, and storage. Box closure, waterproofing, and reinforcing shall be in accordance with method V of PPP-B-636.

5.1.2 Level C. Six canisters, cleaned and dried, shall be preserved in a single container in a manner which will afford protection against physical and mechanical damage during shipment and handling from the supply source to the first receiving activity for immediate use.

5.2 Packing. Packing shall be level B or C as specified (see 6.2).

5.2.1 Level B. Canisters preserved as specified shall be packed in containers conforming to the following specifications at the contractor's option.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

Specification	Container	Type or class
PPP-B-636	Fiberboard	Weather-resistant
PPP-B-640	Fiberboard corrugated, triple wall	Class 2

Fiberboard boxes shall be closed, waterproofed, and reinforced in accordance with the appendix to the applicable box specification, except that method V of the appendix shall apply for boxes conforming to PPP-B-636. Unit containers conforming to class weather-resistant of PPP-B-636, when closed, waterproofed, and reinforced as specified herein, and used as a shipping container, need not be overpacked.

5.2.2 Level C. Canisters preserved as specified shall be packed in containers conforming to the following specifications at the contractors' option.

Specification	Container	Type or class
PPP-B-636	Fiberboard	Class - domestic
PPP-B-640	Fiberboard-corrugated, triple wall	Class 1

Fiberboard boxes shall be closed in accordance with the appendix to the applicable box specification. Unit containers conforming to class weather resistant or domestic of PPP-B-636, closed, waterproofed, and reinforced, when required, and used as shipping containers, need not be overpacked.

5.3 Palletization. When specified (see 6.2), unit packages or shipping containers, as applicable, shall be palletized for shipment in accordance with MIL-STD-147.

5.4 Marking. In addition to any special marking required (see 3.3 and 6.2), canisters, unit packages, shipping containers, and palletized loads shall be marked for shipment in accordance with the requirements of MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The canister covered by this specification is intended to be used with the type A-4 oxygen breathing apparatus to supply breathable gas for use in shipboard fire fighting and rescue operations.

6.2 Acquisition requirements. Acquisition documents must specify the following:

(a) Title, number, and date of this specification.
(b) Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).
(c) When first article is required (see 3.1).
(d) Level A or C preservation as specified (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

(e) Packing level required (see 5.2).
(f) Palletization required (see 5.3).
(g) Marking required (see 5.4).

6.3 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DID's) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/ provided and that the DID's are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DoD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title	Suggested Tailoring
4.3	DI-T-4902	First article inspection report	----

The above DID's were those cleared as of the date of this specification. The current issue of DoD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

6.4 First article. When first article inspection is required, the canisters should be a first article sample or standard production items from the contractor's current inventory. The first article should consist of 100 units. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.5 Material safety data sheets. Contracting officers will identify those activities requiring copies of completed Material Safety Data Sheets prepared in accordance with FED-STD-313. The pertinent Government mailing addresses for submission of data are listed in FED-STD-313.

6.6 Sub-contracted material and parts. The packaging requirements of referenced documents listed in section 2 do not apply when material and parts are acquired by the contractor for incorporation into the equipment and lose their separate identity when the equipment is shipped.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

6.7 Subject term (key word) listing.

Oxygen equipment

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - EA
Navy - SH
Air Force - 99

Review activities:
Air Force - 84
DLA - GS

Preparing activity:
Navy - SH
(Project 4240-0548)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, *folded along the lines indicated, taped along the loose edge (DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SEA SYSTEMS COMMAND (SEA 55Z3)
DEPARTMENT OF THE NAVY
WASHINGTON, DC 20362-5101

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-17671F	CANISTER, OXYGEN BREATHING APPARATUS, FOR TYPE A-4

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:27Z
Check the source to verify that this is the current version before use.