MIL-F-17655C(NAVY)
4 February 1969

SUPERSEDING
MIL-F-17655B(SHIPS)
26 September 1960

MILITARY SPECIFICATION

FIELD CHANGES AND FIELD CHANGE KITS; GENERAL SPECIFICATION FOR

All interested commands of the Department of the Navy have concurred in the use of this specification.

1. SCOPE

1.1 *Scope.*—This specification covers the development and preparation of field changes and field change kits (evaluation and production), developed for the purpose of improving performance, operational characteristics, maintenance, reliability, and safety features of equipment for the Naval Ship Systems Command and Naval Electronic Systems Command.

1.2 *Classification.*—Field changes are classified as specified in 1.2.1 through 1.2.2.3 (see 6.3.1).

1.2.1 *Evaluation field change.*—An evaluation field change is used to determine either the military suitability of a preproduction field change or the adequacy of a production field change. An evaluation field change contains all parts, materials, and instructions required to accomplish and evaluate the change (see 6.3.2).

1.2.2 *Production field change.*—A production field change is a change that has been evaluated and approved for accomplishment. Production field changes are of the following types and classes:

1.2.2.1 *Types.*—The following type designations indicate the extent to which parts are supplied as part of the kit or required to be furnished by the installing activity to accomplish the change:

Type I.—A type I field change requires parts, all of which are included in a kit which consists of a publications package (see 3.6), all parts, materials, and special tools required to accomplish the change to one equipment and to revise existing equipment nameplates, publications, and charts.

Type II.—A type II field change requires parts, none of which are included with the field change. The type II field change may be either a kit consisting of a publications package (see 3.6) or articles for a publication (see 3.5) providing instructions for accomplishing the field change and for correcting related publications.

Type III.—A type III field change requires parts, of which some but not all, are included in a kit. The field change kit consists of a publications package (see 3.6) and some of the parts, materials, and special tools required to accomplish the field change to one equipment and to revise existing nameplates, publications, and charts. (Parts, test equipment, etc., not included in the kit are stocked onboard ship or should be requisitioned.)

Type IV.—A type IV field change does not require parts or the use of special tools. The type IV field change may be either a kit consisting of a publications package (see 3.6) or articles for a publication (see 3.5) providing instructions for accomplishing the field change and for correcting related publications.

FSC TMSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

1.2.2.2 *Classes.*—The following class designation indicates the funding and installation responsibility for accomplishment of the field change:

Class A.—A class A field change is approved for accomplishment by forces afloat or station personnel; no installation funding is required.

Class B.—A class B field change requires Fleet installation funding.

Class C.—A class C field change normally requires industrial assistance for installation and requires the appropriate Systems Command installation funding.

1.2.2.3 *Accomplishment priority.*—The following accomplishment priorities indicate the urgency of the accomplishment:

Emergency.—This priority is assigned to changes proposed for either of the following reasons:

(a) To effect a change in operational characteristics which if not accomplished without delay, may seriously compromise the national security.

(b) To correct a hazardous condition which may result in fatal or serious injury to personnel, extensive damage, or destruction of equipment.

Urgent.—This priority is assigned to changes for the following reasons:

(a) To effect a change in operational characteristics which if not accomplished expeditiously, may seriously compromise the mission effectiveness of deployed equipment.

(b) To correct a potentially hazardous condition which may result in serious injury to personnel or in damage to equipment. A potentially hazardous condition compromises safety and embodies risk but within reasonable limits, permits continued use of the affected equipment, provided the operator has been informed of the hazard and appropriate precautions have been defined and distributed to the user.

(c) To meet significant contractual requirements (e.g., when lead time will necessitate slipping approved production, activaiton, or construction schedules, if the changes are not incorporated).

(d) To effect an interface change which if delayed, will cause a schedule slippage or increased cost.

(e) To effect through value engineering or other cost reduction efforts, net life cycle savings to the Government of more than one hundred thousand dollars, where expedited processing of the change will be a major factor in realizing lower costs.

Routine.—This priority is assigned to proposed changes when "emergency" or "urgent" is not applicable.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS
MILITARY

MIL-D-1000/2	Drawings, Engineering and Associated Lists.
MIL-M-9868/1	Microfilming of Engineering Documents, (35mm) for Naval Ship Systems.
MIL-P-15024	Plates, Identification — Information and Marking for Identification of Electrical, Electronic and Mechanical Equipment.
MIL-M-15071	Manuals, Equipment and Systems.
MIL-S-15822	Sheets, Technical; Supply Data and Instruction.
MIL-E-16400	Electronic Equipment, Naval Ship and Shore; General Specification.
MIL-E-17362	Electronic Repair Parts, Requirements, Procedures for Provisioning Technical Documentation and Stock Numbering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

MIL-E-17555	Electronic and Electrical Equipment and Associated Repair Parts, Preparation for Delivery of.
MIL-C-17581	Charts, Operating Instructions, for Ship or Shore Electronic Equipment.
MIL-S-21740	Sheet, Technical Data, Performance Standards.
MIL-B-21741	Book, Technical, Maintenance Standards.
MIL-M-21742	Manual, Technical, Overhaul and Repair Instructions.
MIL-E-21981	Electronics Type Designations, Identification Plates and Markings; Requirements for.
MIL-D-23140	Drawings, Preliminary and Final, Electronic Equipment and Systems, Installation Control.
MIL-M-24100	Manuals, Orders and Other Technical Instructions, for Equipment and Systems.
MIL-M-38784	Manuals, Technical: General Requirements for Preparation of.
MIL-P-38790	Printing Production of Technical Manuals; General Requirements for.

STANDARDS
MILITARY

MIL-STD-12	Abbreviations for Use on Drawings, Specifications, Standards and in Technical Documents.
MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-415	Test Points and Test Facilities for Electronic Systems and Associated Equipment, Design Standard for.
MIL-STD-1326	Test Points, Test Point Selection and Interface Requirements for Equipments Monitored By Shipboard On-Line Automatic Test Equipment.

PUBLICATIONS
MILITARY

DOD 5220.22M	Industrial Security Manual for Safeguarding Classified Information.
OPNAV 43P2	Maintenance and Material Management (3-M) Manual.

NAVSHIPS

0969-019-7000	Electronic Test Equipment Application Guide.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 *Other publications.*—The following documents from a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 Jackson West Boulevard, Chicago, Illinois 60606.)

National Motor Freight Classes and Rules

(Application for copies should be addressed to the Issuing Officer, National Motor Freight, 1616 P Street, N.W., Washington, D.C. 20036.)

UNITED STATES OF AMERICA STANDARDS INSTITUTE (USAS)

Y14.15—Electrical and Electronics Diagrams.

Y32.2 —Electrical and Electronics Diagrams, Graphic Symbols for.

Y32.14—Logic Diagrams, Graphic Symbols for.

Y32.16—Electrical and Electronics Reference Designations.

(Application for copies should be addressed to the United States of America Standards Institute, 10 East 40th Street, New York, New York 10016.)

(Technical society and technical associa-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

tion specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 *General requirements.*

3.1.1 *Definitions.*—For the purposes of this specification, definitions as set forth in 6.3 shall apply.

3.1.2 *Security classification.*—The security classification shall be assigned by the command or agency concerned. Handling and production of all classified material shall be in accordance with DOD 5220.22M Industrial Security Manual for Safeguarding Classified Information.

3.1.3 *Safety.*—Safety requirements shall be in accordance with MIL-E-16400.

3.1.4 *Maintainability, reliability, operability and design.*—Maintainability, reliability, and operability guidelines shall be incorporated into the design to the extent practical, as follows:

(a) Provide adequate accessibility and work clearance.

(b) Limit the number and variety of parts, tools, accessories, and test equipment to those of the basic equipment.

(c) Provide for convenient maintenance accessibility. The removal of assemblies to effect maintenance shall be kept to a minimum. Maintenance aids provided in the basic equipment shall be included in the field changes.

(d) Design shall be in accordance with MIL-E-16400 and the detail field change specification.

3.1.5 *Test points and test features.*—Test points and test features shall be incorporated into equipments in accordance with MIL-STD-415 and, if applicable, with MIL-STD-1326 (to the extent the equipment is affected by the field change).

3.1.6 *Test equipment.*—Test equipment required shall be selected from NAVSHIPS 0969-019-7000.

3.1.7 *Nomenclature.*—When the field change does not apply to the entire equipment population, or when required by the contract or order, application shall be made for assignment of a new type designation (nomenclature) in accordance with MIL-E-21981.

3.1.8 *Provisioning documentation.* — Unless specified otherwise in the contract or order, provisioning documentation shall be supplied in accordance with MIL-E-17362.

3.1.9 *Drawings and data.*—When new major units are supplied or changes made to interconnection wiring or when physical/functional interface is affected, installation drawings and preliminary data sheet material shall be provided in accordance with MIL-D-23140 and MIL-S-15822. Microfilm of engineering (manufacturers) drawings prepared to MIL-D-1000/2 shall be provided in accordance with MIL-M-9868/1.

3.1.10 *Reference designations.* — Reference designations for electrical and electronic parts shall be in accordance with USAS Y32.16 and marked in accordance with MIL-E-16400.

3.1.11 *Abbreviations.*—The use of abbreviations shall be held to a minimum. Any abbreviations used shall be in accordance with MIL-STD-12.

3.1.12 *Symbols.* Symbols for electrical and electronic parts shall be in accordance with the distinctive shape series of USAS Y32.14 and standards USAS Y32.2 and USAS Y14.15.

3.1.13 *Notes, cautions, and warnings.*—Notes, cautions, and warnings shall be used to emphasize important, critical, and potentially dangerous instructions and shall be in accordance with MIL-M-38784 and MIL-M-15071.

3.1.14 *Procedural steps and listings.*—Steps of procedure, such as sequential steps of assembly or disassembly, shall be numbered in consecutive Arabic numerals, for example

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

1, 2, 3, etc. The same format shall be followed for lists of equipment or other lists forming part of the text.

3.1.15 *Illustrations.*—Illustrations shall be prepared in accordance with MIL–M–15071 and MIL–M–38784.

3.1.16 *Change of type classification.*—When the contract or order calls for a type of field change that does not conform to the type designation representing the parts-supplied category listed in 1.2, the contractor shall request permission to make the type designation agree with the correct designation.

3.1.17 *Manuscript copy.*—Upon approval of the evaluation field change test (see 3.2.2), four manuscript copies of the field change bulletin or article and publications correction material (including illustrations), shall be forwarded to the applicable command or agency for review and approval prior to printing (see 4.3 and MIL–M–38784.) Copies of manuscripts for field change bulletins shall have attached a completed and signed copy of the contractor's check list shown on figure 1. Manuscript copy of change pages shall be copies of the pages with changes inserted.

3.1.18 *Field change numbers.*—Field change numbers shall be obtained from the procuring activity and shall be requested when the manuscript copy (see 3.1.17) is submitted for approval.

3.1.19 *Federal stock numbers for field change kits.*—A Federal stock number is required for each production field change kit subject to requisition from stock. Federal stock numbers shall be requested from the procuring activity when the manuscript copy (see 3.1.17) is submitted for approval.

3.1.20 *Printing and binding.*—Printing and binding of field change bulletins may be in any method providing clear, legible copy. Self covers are permitted. Printing and binding of publication correction material shall conform to the requirements of MIL–M–15071, MIL–M–24100, MIL–M–38784, and MIL–P–38790, as applicable.

3.2 *Evaluation field change.*—An evaluation field change shall be supplied for each type of field change specified in the contract or order (see 4.2). The evaluation field change shall have available for the evaluation, all parts, material, special tools, and special test equipment required to accomplish the change. (All Government furnished material specified in the contract or detail specification shall be requested from the procuring activity in sufficient time to assure its availability at the time and place of the evaluation.) A brief report consisting of the following data shall be supplied for evaluation:

(a) Title (see 3.6.2.2).
(b) Purpose (see 3.6.2.6).
(c) Estimated man-hours (see 3.6.2.2).
(d) Prerequisite field changes (see 3.6.2.7).
(e) List of parts and material (see 3.6.2.10).
(f) Special tools and test equipment (see 3.6.2.11).
(g) Modification procedures (see 3.6.2.12).
(h) Check out procedures (see 3.6.2.12).

3.2.1 *Publication correction requirements interface effect report.*—If the contract or order involves only the purchase of an evaluation field change, the evaluation field change shall include a report containing the following:

(a) A list of existing publications, charts, and drawings pertaining to the equipment with an estimate of the work required to prepare publication changes.
(b) Extent to which the weight power requirements, heat dissipation, and other interface characteristics have been changed. When interfaces have not been changed, a statement to this effect shall be included.

3.2.2 *Evaluation.*—An evaluation test shall be performed in accordance with 4.2. Kits installed and approved as acceptable in equipment affected by the change, shall not be removed for packaging and shipment.

3.3 *Production field changes.*—All produc-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

tion field changes shall be evaluated in accordance with 3.2 and approved in accordance with 3.9.2 and 4.5.

3.3.1 *Type I.*—A type I field change (see 1.2.2.1) shall contain the following, as applicable:

(a) All parts (see 3.4) and material required to accomplish the field change to one equipment.
(b) All special tools, jigs, and instruments required to accomplish the field change.
(c) Identification plates (if the field change affects the equipment nomenclature) in accordance with MIL-P-15024.
(d) Publications package (see 3.6).

3.3.2 *Type II and type IV.*—A type II or type IV field change (see 1.2.2.1) shall consist of a publications package (see 3.6) or articles for publication (see 3.5), to be printed in such a document as the Electronic Information Bulletin (EIB).

3.3.3 *Type III.*—A type III field change (see 1.2.2.1) shall conform to 3.3.1 except for omission of any parts, material, special jigs, or instruments exempted by the contract or the order.

3.4 *Parts.*

3.4.1 *Field change kits supplied under equipment contracts.*—All parts of backfit kits supplied under equipment contracts shall be identical to those included in the equivalent production field change.

3.4.2 *Field change kits not supplied under equipment contracts.*—All parts of kits that are covered by detail field change specifications shall be in accordance with the detail specificatons; all parts of kits not covered by detail specifications shall be in accordance with MIL-E-16400.

3.4.3 *Stock numbers for parts.*—Stock numbers for parts not having a current Federal stock number shall be obtained in accordance with MIL-E-17362.

3.5 *Articles for publication.*—Articles for publication are acceptable only for relatively simple changes wherein the data with accompanying illustrations for (a) accomplishing the change to equipment and (b) accomplishing the revision to all existing manuals, charts, and other related publications, will not require more than one 8 by 10½ inch page when printed (approximately four double-spaced manuscript pages), (c) when the publications errata can be conveniently transcribed into the applicable publications, and (d) when approved by the procuring activity. Two kinds of publication articles shall be prepared, one containing field change instructions in accordance with 3.5.1 and the other containing publications correction material in accordance with 3.5.2. Separate publication correction articles shall be prepared for each technical manual or other publication, chart, reference standards book, performance standards sheet, etc., affected by the field change. Manuscript copy (see 3.1.17) of an article shall consist of an original and two copies. Illustrations shall be prepared as reproducible copy of suitable quality for offset reproduction. Articles shall include the applicable information as shown on figure 2.

3.5.1 *Field change instructions.*—Format for the preparation of a field change instruction (figures 3 and 4) shall include the following, as applicable:

(a) Field change number and nomenclature.
(b) Title.
(c) Type and class.
(d) Estimated man-hours.
(e) Equipment affected.
(f) Purpose.
(g) Prerequisite field changes.
(h) Identification of accomplishment.
(i) Material[1].
(j) Tools or test equipment required.
(k) Modification procedures.
(l) Routine instructions.

[1] Type II and type III field changes shall include the following statement: "Parts not available locally should be requisitioned in accordance with existing procedures."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

3.5.2 *Publications correction instructions.*—Publications correction instructions set forth in an article for publication, shall be prepared in the same manner as an interim change to the applicable publications in accordance with MIL-M-15701. A separate article shall be prepared for making revisions to each publication, chart, performance standard sheet, reference standards book, drawing, etc., affected by the field change. Format shall be in accordance with figure 2. (Whenever possible, the data shall be prepared for a paste-down so that the article can be cut out and secured in the publication being revised.)

3.6 *Publications package.*—The publications package shall consist of the following:

(a) Information sheet (see 3.6.1).

(b) Two copies of the field change bulletin (see 3.6.2).

(c) Two copies of technical manual correction material in accordance with 3.7.1.

(d) One copy of each other publications correction material in accordance with 3.7.

3.6.1 *Information sheet.*—The publications package shall have identifying and descriptive information equivalent to that shown on figure 5, as the first sheet of the publications package. The information may be on a separate sheet stapled to the upper left-hand corner of the publications material, reproduced on an envelope, or on a wrap-around band containing the publications material.

3.6.2 *Field change bulletin.*—The field change bulletin shall consist of descriptive data, illustrations, and step-by-step procedures for accomplishing the field change. Where lengthy procedures, schematic diagrams, or other data are included in the technical manual or publications correction material (see 3.7), it is not necessary to repeat this data in the bulletin. Reference shall be made in the bulletin to the technical manual or the correction material for the procedure or illustration. The field change bulletin shall contain the following information, as applicable, prepared in the format shown on figures 3 and 6.

3.6.2.1 *Running heads and running feet.*—Running heads and running feet shall appear on each page. Pages shall be numbered consecutively. The first page shall show the total number of pages, for example, (page 1 of 5); successive pages shall contain the page number only, for example, 2, 3, 4, 5, etc.

3.6.2.2 *Main heading.*—The main heading shall contain the following as shown on figures 3 and 6:

(a) Publication number as assigned by the approval letter.

(b) Security classification (see 3.1.2) of classified bulletins.

(c) Name and address of the cognizant command or agency.

(d) Field change number(s) (see 3.1.13).

(e) Federal stock numbers for field change kit, when required (see 3.1.19).

(f) Title shall consist of a brief statement of purpose and effect of change (such as, "Increases, Receiver Sensitivity, Modified Antenna Beam Pattern, Increase Range, etc.").

(g) Type of field change (see 1.2.2.1).

(h) Class of field change (see 1.2.2.2).

(i) Accomplishment priority (see 1.2.2.3).

(j) Estimated man-hours required to accomplish and checkout the field change.

(k) Operational or nonoperational change. The effect of the change on the operating characteristics of the basic equipment (a range increase is an operational change whereas a resistor replacement to increase reliability is a nonoperational change).

(l) Name and address of the contractor or Government preparing activity.

(m) Contract or project order number, where applicable.

(n) Security notice.—The security classification of unclassified field changes shall be marked "Unclassified" when the equipment is classified. Classified bulletins shall include the following security notice (see figures 3 and 6):

"This document contains informa-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

tion affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794. The transmission or revelation of which in any manner to an unauthorized person is prohibited by law."

(o) Distribution statement.—A statement shall be included to denote the conditions of availability for distribution, release, or disclosure of the bulletin. The distribution statement shall be requested when the manuscript is submitted for approval.

3.6.2.3 *Accomplishment responsibility notice.*—Unless specified otherwise in the contract or order, a statement equivalent to one of the following shall be included for the class of field change designated by the applicable command or agency:

(a) Class A.—(See 1.2.2.2.)
"This field change is within the technical capability of forces afloat and station personnel and is approved for accomplishment on equipment affected."

(b) Class B.—(See 1.2.2.2.)
"Naval shipyards, tenders, and repair facilities shall accomplish this field change on ship-installed equipment affected without reference to the Naval Ship Systems Command or Naval Electronic Systems Command, when authorized by the Type Commander."

(c) Class C.—(See 1.2.2.2.)
"Naval shipyards or repair facilities shall accomplish this field change without reference to the cognizant Systems Command when authorized by the Management Systems Command, or Type Commander."

3.6.2.4 *Accomplishment priority.*—A statement to agree with the accomplishment priority (see 1.2.2.3) shall be included to designate the action required for accomplishment of the change. This statement will be provided by the procuring activity and shall be requested when the manuscript is submitted for approval.

3.6.2.5 *Equipment affected.*—This item shall list the equipment affected by the field change and shall include, as applicable, the type, model, serial numbers, and conditions. (For example, AN/SRR-1, all serial numbers; AN/SRR-1A, serial numbers 1 through 52, all equipments operated under tropical conditions, all equipments ashore.) If all the equipment population is to be the same after the field change has been accomplished, a statement to this effect shall be included. If all the equipment population is not the same after applicable equipments have been modified by the field change, a statement to this effect shall be included.

3.6.2.6 *Purpose.*—This item shall be a technical elaboration of the title.

3.6.2.7 *Prerequisite field changes.*—This item shall list all field changes that must be completed before a particular field change can be accomplished. If there are none, enter the word "None".

3.6.2.8 *Effect on nomenclature.* This item shall state the effect of changes to the equipment nomenclature resulting from the field change; if nomenclature is not affected, enter the word "None".

3.6.2.9 *Indication of accomplishment.*—This item shall consist of a brief statement describing how to determine that the change has been accomplished.

3.6.2.10 *List of parts and material.*—This item shall list all parts and material required to accomplish the change. Separate the material supplied with the kit from the material to be supplied by the installing activity. Federal stock numbers shall be used for parts to be requisitioned from stock or listed for identification purposes. The list of parts and materials shall be prepared in tabular form (as shown on figure 3) and shall include the following:

(a) Item number.
(b) Reference designation.
(c) Quantity.
(d) Description (brief description of each item).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

(e) Federal stock number or publication number (see figure 3).

3.6.2.10.1 *Type II and type III field changes.* —For types II and III field changes that require requisitioning of parts, the following statement shall be included with the list of material:

"Parts required but not supplied, which are not available locally shall be requisitioned in accordance with existing procedures."

3.6.2.11 *Special tools and test equipment.*— This item shall list jigs, instruments, and test equipment (see 3.1.6) required to accomplish the field change and to test the equipment after the change has been accomplished. Identify tools and test equipment supplied with the field change kit and those furnished by the installing activity (see figure 3). Special tools are defined as those tools not listed in the Federal Supply Catalog (copies of this catalog may be consulted in the office of the Defense Contract Administration Service (DCAS)).

3.6.2.12 *Procedures.*—Procedural steps (see 3.1.14) and other information required to accomplish the change shall include the following information as applicable:

(a) Notes, cautions, and warnings (see 3.1.13) defining precautions and conditions involved to accomplish the field change when danger to life or damage to equipment may result.

(b) Complete detailed instructions for the construction and use of special tools or jigs required for accomplishing the field change.

(c) Appropriate steps in proper sequence of turn-off, turn-on procedures to insure that power is off and any other steps relating to safety.

(d) Detailed step-by-step procedures (including soldering sequence) required for accomplishing the field change (when disassembly varies from reassembly include both disassembly and reassembly instructions). Parts and material shall be clearly identified by name and item number. For check off purposes, open parenthesis shall be included in the left-hand margin for each step as shown on figure 3.

(e) All mechanical and electrical adjustments to be made after the installation of the field change.

(f) Illustrations, photographs, and diagrams not available in existing publications. When the change requires circuit modifications, a "before and after" partial schematic wiring diagram of the portion affected shall be provided. A series of "X" marks shall indicate the connections removed, and heavy solid lines shall show the new connections. When necessary for clarity, two separate diagrams shall be furnished. For relatively simple changes (replacement of a resistor or a capacitor, etc.) a partial wiring diagram need not be furnished if the replaced part or parts can be easily located on the existing diagrams. All changes affecting interunit connections shall be clearly described and illustrated.

(g) Remarks concerning circuit operation indicative of improper installation of the field change.

(h) Instructions for modifying or adding reference designations to the chassis.

(i) Check out procedures. Instructions for check out of proper field change installation.

3.6.2.13 *Routine instructions.* — Applicable statements, modified as necessary to reflect the field change (see figure 3), shall be included to cover the following subject matter in the order indicated:

(a) Corrections to publications and charts (see 3.6.2.13.1).

(b) Record of accomplishment (see 3.6.2.13.2).

(c) Disposition of replaced material (see 3.6.2.13.3).

(d) Disposition of field change bulletins (see 3.6.2.13.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

3.6.2.13.1 *Corrections to publications and charts.*—

(a) *Field change not requiring publications corrections.*—As applicable, enter the following:
"No publications or charts require revision because of this field change."

(b) *Field change requiring publications corrections.*—As applicable, enter the following (see figure 4):
"*Corrections to publications and charts.* — The applicable equipment technical manuals, performance standards sheets, reference standards books, overhaul and repair instructions, maintenance requirement cards, plans, charts, and nameplates shall be corrected or replaced in accordance with the following instructions: (Specific reference shall be made to the appropriate interim change, permanent change, or revised publication or chart)."

(c) In addition, one of the following statements shall follow the above statement, as applicable:

(1) Field changes applying to all equipments (except those covered by an equivalent factory change):
"Maintenance support activities shall correct their publications immediately, but keep the superseded data intact for support of equipments that have not been modified. Holders of equipments should not make the corrections until the field change has been accomplished."

(2) Field changes not applying to all equipments (see 3.6.2.5):
"Inasmuch as all equipments are not to be modified by this field change or an equivalent production change, the publications corrections cover the equipment both with and without the field change. Accordingly, all copies of the books should be corrected upon receipt."

3.6.2.13.2 *Record of accomplishment.* — As applicable, enter the following under this heading:

"Personnel accomplishing this field change shall record its completion on the Field Change Record Plate, FSN 0264–085–0000 and on the Record of Field Change Card NAVSHIPS 537, if Maintenance Data Collection System (MDCS) has not been implemented. If MDCS is implemented, record completion on the Field Change Record Plate and on appropriate Shipboard Maintenance Action form in accordance with OPNAV 43P2 using Equipment Identification Code (EIC) number_____."

3.6.2.13.3 *Disposition of replaced material.*—Material which is removed shall be returned to supply in accordance with current instructions (see figure 3).

3.6.2.13.4 *Disposition of field change bulletin.*—As applicable include the following statement:

"Maintenance support activities shall retain a library copy of this field change bulletin. Holders of equipment shall not destroy the field change bulletin until the field change has been accomplished, the equipment tested, and the applicable manuals, charts, and identification plates have been corrected or replaced."

3.7 *Publications correction material.*—Publications correction material consisting of interim changes, permanent changes, or revised manuals) shall be supplied for correcting all existing equipment documents, charts, and other publications affected by the field change. (See 3.5 for type II and type IV field changes promulgated by means of published articles.) Correction material shall be prepared in accordance with the requirements of MIL–M–15071, MIL–M–38784, MIL–S–15822 and MIL–D–1000/2.

3.7.1 *Technical manuals.*—Technical manual correction material shall conform to the requirements of MIL–M–38784 and MIL–M–15071, or MIL–M–24100, as applicable.

3.7.1.1 *Supplementary manuals.* — Supple-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

mentary technical manuals (which augment the technical manual) shall be supplied when specified in the contract or order. (Supplementary manuals are normally required when the field change includes new major units which do not apply to the entire population of equipments described in the basic technical manual.) Supplementary manuals shall be written in such a manner that when used with the manual for unmodified equipment, the contents of the two manuals will cover the modified equipment to the extent specified for a complete manual in accordance with MIL-M-38784.

3.7.2 *Operating instruction charts.*—When the field change alters the equipment operating instruction charts, new charts shall be provided in lieu of a change in accordance with MIL-C-17581.

3.7.3 *Performance standards sheets.*—Where the field change alters the performance standard sheet a new performance standard sheet shall be provided (in lieu of a change) in accordance with MIL-S-21740.

3.7.4 *Reference standards books.*—When the field change alters any reference standard, manual corrections or revisions shall be provided for the reference standards book in accordance with MIL-B-21741.

3.7.5 *Overhaul and repair instructions.*—When the field change alters any of the overhaul and repair instructions, the manual shall be corrected or revised in accordance with MIL-M-21742.

3.7.6 *Maintenance requirement cards.*—When specified in the contract or order, maintenance requirement cards shall be revised. If applicable, revised maintenance requirements cards (Planned Maintenance System (PMS)) shall be supplied in accordance with OPNAV 43P2.

3.7.7 *Engineering and installation control drawings.*—Corrections to engineering drawings, control installation drawings, and microfilm shall be supplied in accordance with 3.1.9.

3.8 *Approval.*—The field change shall be approved by the applicable Systems Command, its specified field activities, or representatives. (Approval is contingent upon the satisfactory completion of the following elements:

(a) Evaluation field change (see 3.2).
(b) Production field change (see 3.3).
  (1) Parts assembly and piece parts (see 3.4).
  (2) Publications correction material (see 3.1.17 and 3.7).
(c) Engineering and installation drawings (see 3.1.9 and 3.7.7.).

3.9 *Quantity.*—

3.9.1 *Evaluation field change kits.*—Unless otherwise specified in the contract or order, the evaluation field change kit (see 3.2) shall be included as one of the production field change kits.

3.9.2 *Production field change kits.*—Unless otherwise specified in the hardware contract or order, one field change kit shall be supplied for each equipment that does not include the equivalent factory change. For equipments not supplied under equipment contracts the quantity of field change kits shall be specified in the contract or order.

3.9.3 *Publications material.*—Unless otherwise specified in the contract or order, the contractor shall supply the following bulk quantities of publications material in addition to the publications material in each field change kit:

(a) 300 field change bulletins.
(b) 300 copies of correction matter for each publication requiring revision.
(c) 50 copies of each revised chart.

3.9.4 *Drawings.*—Unless otherwise specified in the contract or order, quantities of installation and engineering drawings shall be in accordance with 3.1.9.

3.9.5 *Replenishment material.*—The original artwork and one photolithographic negative (MIL-P-38790) of each half-tone illustration shall be included in each data item, together with two copies of the printed document and

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

adequate assembly instructions for purposes of reprinting. This material shall be forwarded as directed, with a covering letter advising that the material is for replenishment and updating purposes.

3.10 *Distribution.*—Distribution shall be as specified in the contract or order.

3.11 *Acceptance.*—Acceptance of the field change shall be subject to compliance with the requirements of approval (see 3.8), quality assurance provisions, and the provisions of the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 *Responsibility for inspection.* — Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 *Quality program requirements.* — The quality program shall be in accordance with the respective specification that applies to the parts and material of the field change and the data generated or corrected.

4.2 *Evaluation test.*—Except for reprocurement contracts, where an evaluation test of an identical field change has been successfully accomplished, one evaluation field change kit (see 3.2), shall be supplied for an evaluation test of the field change prior to production of the field change kits. The evaluation test shall be accomplished at the place of manufacture or at such other location as may be acceptable to the procuring activity. Unless otherwise specified in the contract or order, the evaluation test shall be performed by personnel of the same technical level as the personnel required to accomplish the production field change and shall be witnessed by a representative of the procuring activity. In performing the evaluation test, the detailed procedures specified in 3.6.2.12, as applicable, shall be followed. Any deviations or corrections necessary to accomplish a satisfactory test shall be recorded and the contractor shall correct or clarify the procedure, as necessary. If such deviations are extensive, the procuring activity concerned may require additional evaluation tests. When required by the contract or order, a report of the evaluation test shall be furnished to the procuring activity on or before submission of the manuscript of the publications material for approval. This report shall include information concerning action taken, results, recommendations, and statements including:

(a) Any change in weight of the equipment and the effect on over all equipment power requirements and heat dissipation.

(b) Any change in the performance standards or maintenance standards of the equipment.

(c) Changes in interface parameters.

4.3 *Publications material.*—Publications material (manuscripts) shall be validated by the supplier for technical and engineering accuracy and adequacy; and for conformance with the requirements of the technical content specifications and the applicable contract. Evidence of such validation shall be made available to the Government upon request, at the time the material furnished hereunder is submitted for approval.

4.4 *Hardware.*—Unless otherwise specified in the contract or order, the quality assurance program for hardware shall conform to the detail specification and MIL-E-16400.

4.5 *Production inspection.* — Field change kits shall be inspected to determine compliance with this specification and the requirements of the approval instructions of the command or agency concerned. Inspection of the material, parts, special tools, and special test equipment furnished with type I and

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

type III field changes, supplied on other than equipment contracts, shall be conducted as specified in the detail field change kit specification.

4.6 *Inspection of preparation for delivery.*—The packaging, packing, and marking shall be inspected for compliance with section 5 of this document.

5. PREPARATION FOR DELIVERY

5.1 *Preservation and packaging.*—Preservation and packaging shall be in accordance with the applicable level of MIL–E–17555 (see 6.3.1).

5.2 *Packing.*—Packing shall be accomplished in a manner which will insure acceptance by common carrier and will afford protection against physical or mechanical damage during direct shipment from the supply source to the using activity for early installation. The shipping containers or method of packing shall conform to the Uniform Freight Classification Rules, National Motor Freight Classes and Rules, or other carrier regulations, as applicable to the mode of transportation.

5.3 *Marking.*—Marking information shall be in accordance with MIL–STD–129. The information shall include the following:

(a) Field change number(s) _____
(b) Field change bulletin publication number _____
(c) Field change title _____
(d) Type and class _____
(e) Field change kit Federal stock number (if applicable) _____
(f) Contract number _____
(g) "DO NOT OPEN UNTIL REQUIRED" _____

5.4 *Bulk packaging of field change kits.*—Individually packaged field change kits may be grouped in packages for bulk shipment. Bulk shipment for type II kits shall have the field change bulletins and publications correction material packaged separately and forwarded to Receiving Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, Pennsylvania 19120, marked for COG–I stock.

6. NOTES

6.1 *Intended use.*—This specification covers the preparation and handling of field changes and field change kits for the Naval Ship Systems Command and Naval Electronic Systems Command.

6.2 *Ordering data.*—Procurement documents and detail specifications should specify the following:

6.2.1 *Procurement documents:*

(a) Title, number, and date of this specification.
(b) Equipment nomenclature.
(c) Interim change, permanent change or revised manual.
(d) Quantity, type, class, and priority (see 1.2).
(e) Bulk quantity of publications material.
(f) Title of field change.
(g) Installation drawings, if applicable.
(h) Engineering drawings and microfilm, if applicable.
(i) Applicable level of preservation and packaging required (see 5.1).
(j) Evaluation test report (see 4.2).
(k) Security classification (see 3.1.2).
(l) Configuration baseline.
(m) Publication baseline.
(n) Nomenclature (see 3.1.7).

6.2.2 *Detail specifications:*

(a) Equipment nameplate requirements.
(b) Technical requirements.
(c) Applicability to equipments.
(d) Weight and moment changes, if required.
(e) Evaluation test site.

6.3 *Definitions.*—

6.3.1 *Detail field change specification.*—The detail field change specification requirements pertaining to a specific procurement which forms part of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

6.3.2 *Evaluation field change kit.*—An evaluation field change kit is a kit developed to determine military suitability of a production field change or the extent the contractor has conformed to the required specification (see 3.2).

6.3.3 *Field change.*—A field change is any modification or alteration made to an electronic equipment after delivery to the Government.

6.3.4 *Field change bulletin.*—A field change bulletin is a publication which provides a list of the material supplied or required and detailed step-by-step instructions to accomplish a field change (see 3.6.2).

6.3.5 *Field change kit.*—A field change kit consists of a publications package and may or may not include parts (see 3.3).

6.3.6 *Interim change.*—An interim change is a temporary correction to a technical manual or other publication. It normally consists of published instructions for making minor pen-and-ink corrections (see 3.7). It may also include insert pages and artwork. Interim changes are assigned formal numbers and shall be superseded by the first permanent change following the interim change.

6.3.7 *Interim change article.*—A temporary change to a technical manual promulgated to manual holders by an article published in a publication such as the EIB. Interim change articles are normally promulgated to correct errors in a technical manual, but may be used for corrections for relatively simple field changes.

6.3.8 *Permanent change.* — A permanent change is a revision for permanent incorporation into a technical manual or other publication. It supersedes and incorporates interim changes which have not been previously covered by a permanent change. It consists of revised pages and may include instructions for making such pen-and-ink corrections as may be conveniently transcribed in the material (see 3.7) if specifically approved by the procuring activity.

6.3.9 *Production field change.*—A production field change is the material necessary to accomplish an approved modification to an electronic equipment and to correct related publications. A production field change is identified by an assigned field change number. As used herein, all authorized changes, except evaluation field changes, are production field changes irrespective as to whether parts are required or supplied (see 3.3).

6.3.10 *Published article.*—Field change instructions and/or publication correction instructions promulgated to equipment users by an article published in a publication such as the EIB.

6.3.11 *Publication correction material.*—Correction material consists of interim or permanent changes for correcting all equipment technical manuals and other support documents, charts, and other equipment publications affected by the field change (see 3.7).

6.3.12 *Publications material.* — Publications material is the instructional information required to accomplish a field change and the data required to correct applicable manuals, drawings, charts, and other equipment publications. This material may be a published article (see 3.5) or a publications package (see 3.6).

6.3.13 *Publications package.*—A publications package is a collection of publications material (see 6.3.5) in a single cover or envelope (see 3.6).

6.3.14 *Supplementary manual.*—A supplementary manual augments a technical manual so that both manuals jointly represent the equipment configuration and contains all information to install, operate, maintain, and repair basic equipment.

6.3.15 *Validation.*—The process by which the contractor assures the technical accuracy and adequacy of the field change.

6.3.16 *Verification.*—The process by which the Government assures the accuracy of the field change by actual comparison with hardware. This includes Government action to assure proper execution of validation by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

6.4 *Shipping instructions.* — Shipping instructions for field change kits and bulk publication material should be requested from the procuring activity at least one month prior to the scheduled date of the initial shipment. When approval of publication correction material has not been received, the contractor shall provide as much of the data as is available and make reference to the submission letter for information concerning the field change publications material and correction matter. The following should accompany the request:

(a) *Field change kits:*

(1) Field change number(s).

(2) Field change title.

(3) Contract (or order) number.

(4) Stock number of kits (if received).

(5) Quantity of field change kits.

(6) Approximate delivery schedule.

(7) Weight and dimensions of packaged field change kits.

(b) *Publications material:*

(1) Contract number.

(2) Title of each publication, including applicable publication numbers.

(3) Quantity to be shipped with field change kits.

(4) Quantity for bulk distribution.

(5) Replenishment material (a list of the original artwork, diagrams, drawings, photographs, etc., used in the production of the publication material).

(6) Government furnished material (GFM) shall be forwarded to the procuring activity.

6.5 *Liaison.*—In order to insure that suitable field change kits will be prepared, close liaison should be maintained with the procuring activity.

6.6 *Bidders considerations.*—

6.6.1 *Publications affected.*—Prospective bidders should check the number of publications likely to be affected by the field change and the extent to which they require correction.

6.6.2 *Quality program.*—A comprehensive quality assurance program is the only acceptable parameter to assure an adequate field change. The mission of a ship and the welfare of personnel aboard are directly dependent upon the availability and useability of the equipment. Therefore, it is of paramount importance that a comprehensive quality assurance program for planning, development, production, inspection, review, and validation be established and implemented.

6.6.2.1 *Validation plan.*—The validation plan shall reflect the supplier's procedure and scope of validation effect. The plan shall identify the baselines that will ensure timely delivery of the production field change. The plan must take into consideration changes and revisions of the technical manuals until the expiration of the supplier's responsibility.

6.6.2.2 *In-process inspections.* — In-process inspections are conducted by the supplier during the process of field change preparation. Conducting these inspections, following through with the correcting of discrepancies, and preventing discrepancy reoccurrence, is considered necessary to assure that the end product is of the requisite quality. In-process inspections may be conducted by the Government to assure that the field change is being prepared in accordance with specification requirements, at any time during the development of the field change.

6.6.2.3 *Validation.*—The contractor will be responsible for the technical adequacy and accuracy of all material furnished by the contractor. The demonstration by actual performance of instructions and procedures in each field change may be performed by a contractor at the equipment site. If performed by a subcontractor, this does not relieve the contractor of the responsibility for providing a correct and adequate product to the Government. Written information and drawings will be checked against actual equipment in accordance with the approved quality program (see 4.1.1) to insure that the informa-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

tion and drawings match the actual equipment in all details depicted on them.

6.6.2.4 *Verification.*—Verification is accomplished by the Government for the purpose of assuring that all publications material is compatible with the hardware and is adequate for the test, calibration, operation, troubleshooting, maintenance, and repair, and conforms with the content and production requirements of this specification and the contract.

Review activities:
Navy—EC

Preparing activity:
Navy—SH
(Project TMSS-NO14)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

CONTRACTOR'S CHECK LIST FOR FIELD CHANGE BULLETINS

FIELD CHANGE NO._____ FEDERAL STOCK NO._____ SECURITY CLASS._____

CONTRACT NO._____ CONTRACTOR_____

TYPE OF KIT_____ CLASSIFICATION_____ ACCOMPLISHMENT PRIORITY_____

TITLE OF PUBLICATIONS CORRECTED_____

NAVSHIPS PUBLICATION NO._____

TM_____ RSB(MSB)_____ OIC_____ PSS_____ CHARTS_____ MISC_____

PUBLICATIONS SPECIFICATIONS_____

TOTAL QTY BULLETINS_____
Kits sent direct (attach shipping list) ( )_____
Number of kits (sent to stock) ( )_____

BULLETIN REQUIREMENTS

		YES	NO	NOT APPLY
1.	Running heads and running feet include:			
a.	Assigned NAVSHIPS number in upper left-hand corner of each page.	( )	( )	
b.	On classified bulletins, the security classification is indicated at top and bottom center of all pages.	( )	( )	( )
c.	Command approval date in lower left-hand corner of each page.	( )	( )	
d.	Page number in lower right-hand corner of each page (see 3.6.2.1).	( )	( )	
2.	Main heading (figures 3 and 6) includes:			
a.	Publication number as assigned by the approval letter.	( )	( )	( )
b.	Security classification of all classified bulletins	( )	( )	( )
c.	Name and address of the cognizant command or agency.	( )	( )	
d.	Field change number(s) and AN/designation.	( )	( )	
e.	Federal stock numbers for field change kit, when required.	( )	( )	( )
f.	Title.	( )	( )	
g.	Type of field change.	( )	( )	
h.	Class of field change.	( )	( )	
i.	Estimated man-hours required to accomplish and check-out the field change.	( )	( )	
j.	Operational change.	( )	( )	
k.	Nonoperational change.	( )	( )	
3.	Body of bulletin provides for the following sub-heading in the order indicated:			
a.	Accomplishment responsibility notice.	( )	( )	
b.	Accomplishment priority.	( )	( )	
c.	Equipment affected.	( )	( )	
d.	Purpose.	( )	( )	
e.	Prerequisite field changes.	( )	( )	
f.	Effect on nomenclature.	( )	( )	
g.	Indication of accomplishment.	( )	( )	
h.	List of material.	( )	( )	( )
i.	List of tools and test equipment.	( )	( )	( )
j.	Procedures.	( )	( )	
k.	Routine instructions.	( )	( )	

Figure 1 - Sample contractor's check list for field change bulletins (Sheet 1 of 3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

BULLETIN REQUIREMENTS (Cont'd.)

	YES	NO	NOT APPLY
4. Accomplishment of responsibility notice:			
a. Requires statement for the following:			
(1) Class A field change.	( )	( )	
(2) Class B field change.	( )	( )	
(3) Class C field change.	( )	( )	
5. Accomplishment priority:	( )	( )	
a. Emergency.	( )	( )	
b. Urgent.	( )	( )	
c. Routine.	( )	( )	
6. Equipment affected:			
a. Type.	( )	( )	
b. Model.	( )	( )	
c. Serial numbers.	( )	( )	
d. Conditions.	( )	( )	
e. Equipment affected.	( )	( )	
f. Indicates extent to which all equipment of same nomenclature will be similar or dissimilar after field change.	( )	( )	
7. Purpose: An elaboration (from a technical standpoint) of the title.	( )	( )	
8. Prerequisite field changes: Includes reference to all changes which must be accomplished prior to accomplishment of this change; if none enter the word "None".	( )	( )	
9. Effect on nomenclature: The effect or changes to equipment nomenclature resulting from the field change; if nomenclature is not effected, enter the word "None".	( )	( )	
10. Indication of accomplishment: Includes a brief statement describing how to determine that the change has been accomplished.	( )	( )	
11. List of materials:			
a. Includes tabular itemized list as follows:			
(1) Item number of each part.	( )	( )	
(2) Reference designation.	( )	( )	
(3) Quantity, per item.	( )	( )	
(4) Name of each part required and brief description of elements.	( )	( )	
(5) Federal stock numbers.	( )	( )	
(6) All material (wire, solder, etc.) not included in the kit, required for accomplishing the change.	( )	( )	
(7) Publication material (list at the end of the table).	( )	( )	
12. Tools and test equipment:			
a. Includes list of all tools and test equipment and furnished to accomplish this field change.	( )	( )	( )
13. Procedure includes:			
a. Detailed instructions with step-by-step description for accomplishing the field change as follows:	( )	( )	( )
(1) Notes, cautions, and warnings.	( )	( )	( )
(2) Detailed instructions for the construction and use of special tools or jigs required.			

Figure 1 - Sample contractor's check list for field change bulletins (Sheet 2 of 3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

BULLETIN REQUIREMENTS (CONT'D.)

		YES	NO	NOT APPLY
(3)	Turn-off, turn-on procedures to insure that power is off and any other steps relating to safety.	( )	( )	
(4)	Step-by-step procedures (including soldering sequence) required when disassembly varies from reassembly. For check off purposes, open parenthesis shall be included in the left-hand margin for each step.	( )	( )	
(5)	All mechanical and electrical adjustments.	( )	( )	
(6)	Illustrations, photographs, and diagrams not available in existing publications.	( )	( )	
(7)	Remarks concerning circuit operation indicative of improper installation of the field change.	( )	( )	
(8)	Instructions for modifying or adding reference designations to the chassis.	( )	( )	
14.	Routine instructions:			
a.	Include the following:			
(1)	Corrections to publications and charts.	( )	( )	
(2)	Record of accomplishment.	( )	( )	
(3)	Disposition of replaced material.	( )	( )	
(4)	Disposition of field change bulletins.	( )	( )	
15.	Contractor's check lists for field change bulletins, temporary corrections and permanent changes accompany each field change bulletin manuscript submitted to the agency concerned for review.	( )	( )	
16.	Publication package cover or information sheet:	( )	( )	
a.	Include the following:			
(1)	NAVSHIPS number in upper left-hand corner (Type II field changes only)	( )	( )	
(2)	"PUBLICATION PACKAGE FOR FIELD CHANGE (Number and nomenclature)" is centered at top.	( )	( )	
(a)	Contents of package (specific publication material).	( )	( )	
(b)	Purpose of field change.			
(c)	Equipment affected and limitation of change.	( )	( )	
(d)	Prerequisite field changes.	( )	( )	
(e)	Time required to make the field change.	( )	( )	

I certify that the subject Field Change Bulletin conforms to the statements as checked above, has been revised in accordance with the comments in the marked-up bulletin, and meets the requirements of the approval letter and required specifications.

_____
Head Publications Department

_____
Date

Figure 1 - Sample contractor's check list for field change bulletins (Sheet 3 of 3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

PUBLICATION ARTICLE (See 3.5)

FIELD CHANGE 7 - AN/UPX-1, 8-AN/UPX-1A INTERROGATOR SETS
IMPROVEMENT OF I-F GAIN CONTROL; TYPE II, CLASS A;
ROUTINE ACTION: 2 MANHOURS

This field change applies to Interrogator Sets AN/UPX-1 and AN/UPX-1A in which field changes 4-AN/UPX-1 and 5-AN/UPX-1A have been accomplished.

The purpose of this field change is to modify the I-F gain circuit so that the gain control can be used when the set is in either the LOCAL or REMOTE mode of operation. (Field changes 4-AN/UPX-1 or 5-AN/UPX-1A enable the I-F gain control to be used in the LOCAL mode only.)

Field change 4-AN/UPX-1 or 5-AN/UPX-1A must be accomplished before installation of this field change. Equipment nomenclature is not affected.

This field change can be identified by noting that the I-F gain can be adjusted by R151 when LOCAL-REMOTE switch S108 is in the REMOTE position.

MATERIAL REQUIRED:

Item	Quantity	Description	FSN
1	24 in.	No. 22, orange, hook-up wire	1N6145-669-6703

Parts required but not supplied which are not available locally shall be requisitioned in accordance with existing procedures.

TOOLS REQUIRED:

Soldering iron, 100W
Solder, 60/40
Diagnonal cutting pliers
Wire stripper

PROCEDURES:

1. Remove all power from equipment. Extend AN/UPX-1/1A chassis from cabinet. If location prohibits access to underside of chassis, remove AN/UPX-1/1A from cabinet.

2. Remove yellow wire from R121.

3. Remove white wire for R151 and solder to terminal of R121 from which yellow wire was removed in step 2.

4. Unfasten E110 to gain access to C113.

5. Remove video processor assembly U402; this step exposes the LOCAL-REMOTE switch.

6. Place LOCAL-REMOTE switch in remote position.

7. Determine which of the three orange wires on C113 goes to the WIPER contact of LOCAL-REMOTE switch S108-A. (The remote position of S108-A will connect this wire to terminal 89 on E-101.)

8. Remove this wire from both C113 and the WIPER contact of S108-A. Clip both ends of this wire at the cable harness.

Figure 2 - Sample format of a publication article
(Sheet 1 of 2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

PROCEDURES: (CONTINUED)

9. Solder one end of the 2-foot length of the orange No. 22 hook-up wire (item 1) to the LOCAL-REMOTE switch wiper terminal from which the old orange wire was removed in step 8.

10. Route the new orange wire through the chassis to the terminal or R151 from which the white wire was removed in step 3. Cut off excess wire and solder to this terminal.

11. Solder yellow wire from R151 (removed from R121 in step 2) to the terminal of C113 from which the old orange wire was removed in step 8.

12. Replace E110, U402, and slide the AN/UPX-1/1A chassis back in the cabinet.

ROUTINE INSTRUCTIONS:

1. Make corrections to the technical manual for Interrogator Set AN/UPX-1/1A, NAVSHIPS 0967-051-4000, in accordance with instructions immediately following this article.

2. Personnel accomplishing this field change shall record its completion on the Field Change Record Plate, FSN I0264-085-0000, and on the Record of Field Change Card, NAVSHIPS 537, if MDCS has not been implemented. If MDCS is implemented, record completion on the Field Change Record Plate and on the appropriate Shipboard Maintenance Action Form, in accordance with OPNAV 43P2, using the following Equipment Identification Code (EIC):

Equipment	EIC
AN/UPX-1	DE30000
AN/UPX-1A	DE35000

AN/UPX-1, AN/UPX-1A, NAVSHIPS 0967-051-4000
TECHNICAL MANUAL CORRECTIONS

Make the following pen-and-ink corrections to the technical manual after accomplishment of field changes 7-AN/UPX-1 or 8-AN/UPX-1A.

1. Page 38, Receiver-Transmitter RT-194/UPX-1 (FCs 1-4) or RT-194A/UPX-1 (FCs 1-5) Blocked Text.

a. Near top center of page, delete arrow between S108-A and N-VD-5.

b. Near top center of page, add arrow from N-VD-4 to N-VD-5.

c. In N-VD-4 block, change description to read "provides means for local and remote I-F gain control".

2. Page 39, Receiver-Transmitter RT-194/UPX-1 (FCs 1-4) or RT-194A/UPX-1 (FCs 1-5) Bloc Schematic. Revise I-F gain circuit diagram, near top center of page, as shown on figure 6.

Record this action on the Title Page, page 1, and adjacent to each pen-and-ink correctic by inserting this EIB number.

Figure 2 - Sample format of a publication article (Sheet 2 of 2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

UNCLASSIFIED

NAVSHIPS XXX-XXX-XXXX

ELECTRONIC FIELD CHANGE BULLETIN NAVAL SHIP SYSTEMS COMMAND DEPARTMENT OF THE NAVY WASHINGTON, D.C. 20360	2-AN/SRR-1 1-AN/SRR-1A FSN-XXXX-XXX-XXXX
TITLE: Replace Power Transformer 1T14	
TYPE: (1), CLASS: (A) ROUTINE ACTION	OPERATIONAL CHANGE: ( )
ESTIMATED MANHOURS: (1)	NONOPERATIONAL CHANGE: (X)
PREPARED BY: Naval Ship Engineering Center Technical Data and Publications Section (SEC 6181C) Hyattsville, Maryland 20782	CONTRACT NO. PROJECT NO.
WARNING: *This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794. The transmission or relation of which in any manner to an unauthorized person is prohibited by law.	
DISTRIBUTION STATEMENT: Each transmittal of this document outside the Department of Defense must have prior approval of Naval Ship Engineering Center, SEC 6181C, Center Building, Prince George's Center, Hyattsville, Maryland 20782.	

ACCOMPLISHMENT RESPONSIBILITY: This field change is within the technical capability of forces afloat and station personnel and is approved for accomplishment on equipment affected.

ACCOMPLISHMENT PRIORITY: Routine.
This field change is approved for accomplishment effected at the earliest opportunity.

EQUIPMENT AFFECTED: AN/SRR-1: all serial numbers; AN/SRR-1A: serial numbers 1 through 652. (All other serials were corrected by an identical production change.)

PURPOSE: To replace power transformer 1T14 with an improved type to prevent failure because of overload.

PREREQUISITE FIELD CHANGES: No field changes need be accomplished before the installation of this field change.

EFFECT ON NOMENCLATURE: None.

INDICATION OF ACCOMPLISHMENT: The new transformer is gray with FSN9N5950-646-1282 stamped on top of housing. (See figure 5-14, NAVSHIPS XXXX-XXX-XXXX, for location.)

*(This classification shall appear on classified bulletins only.)

DATE:

UNCLASSIFIED

Figure 3 - Sample of a typical field change bulletin and temporary publication material (Sheet 1 of 4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

LIST OF PARTS AND MATERIALS REQUIRED:

LIST OF PARTS AND MATERIALS
SUPPLIED WITH FIELD CHANGE KITS

Item No.	Reference designation	Quantity	Description	FSN/ publication No.
1	1T14	1	Power transformer	
7	-	1	6-inch length #20 stranded hook-up wire, white and black	
2	-	2	Field change bulletin	
3	-	2	Interim change T-4 to NAVSHIPS xxxx-xxx-xxxx, technical manual for Radio Receiving Set AN/SRR-1 and AN/SRR-1A	See 3.6.2.10
4	-	1	Operator's instruction chart	
5	-	2	Performance standards sheet	
6	-	2	Interim change T-1 to NAVSHIPS xxxx-xxx-xxxx, Maintenance standards book for Radio Receiving Sets AN/SRR-1 and AN/SRR-1A	

(Type II and type III field changes: "Parts required but not supplied, which are not available locally shall be requisitioned in accordance with existing procedures.")

SPECIAL TOOLS AND TEST EQUIPMENT
REQUIRED BY INSTALLING ACTIVITY

Item	Description	Purpose	FSN/ if applicable
Soldering iron Solder Multimeter	100 watts 60/40 AN/SPM-4C		

PROCEDURES: Refer to figure 5-54, NAVSHIPS xxxx-xxx-xxxx. Check each step as completed.

NOTE

Observe All Safety Precautions

CHECK

( ) 1. Disconnect the power input cable, antenna plug, and audio output plug. Remove the receiver chassis from the cabinet and place on work bench.

( ) 2. Remove power transformer 1T14. Tag disconnected leads of the receiver for identification. Install new transformer 1T14, item 1, in same location of old transformer.

Figure 3 - Sample of typical field change bulletin and temporary publication material (Sheet 2 of 4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

PROCEDURES: (CONTINUED)

CHECK

( ) 3. Connect two of three high-voltage secondary leads, (3) and (9), respectively, on the new transformer. Lead (3) connects terminal 3 to prong 4 of socket 1XV11; lead (9) connects terminal 9 to prong 6 of socket 1XV11.

( ) 4. Connect one end of 6-inch white and black hook-up wire, item 7; lead (4); and the other high-voltage secondary lead (6) to terminal 6 of the new transformer. Connect the other end of the 6-inch hook up wire, item 7, to terminal 4 of the new transformer. Lead (6) connects terminals 4 and 6 to ground.

( ) 5. Connect the white wire (5) and white heater wire (5A) to transformer terminal 5. Lead (5) connects terminal 5 to prong 7 of socket 1XV9 lead (5A) connects terminal 5 to prong 7 of socket 1XV4.

( ) 6. Connect leads (7) and (8) to transformer terminals 7 and 8, respectively. Lead (7) connects terminal 7 to prong 2 of socket 1XV11, lead (8) connects terminal 8 to prong 7 of socket 1XV11.

( ) 7. Connect the 115-volt primary leads, (1) and (2), to transformer terminals 1 and 2.

( ) 8. Replace the receiver chassis in the cabinet and reconnect the power input cable, antenna plug, and audio output plug.

( ) 9. Apply power and check all new connections, using Multimeter AN/PSM-4 ( ).

( ) 10. Operate the equipment for a period of 1/2 hour in accordance with the instructions contained in technical manual for Radio Receiving Sets AN/SRR-1 and AN/SRR-1A, NAVSHIPS xxxx-xxx-xxxx.

ROUTINE INSTRUCTIONS:

1. Corrections to publications and charts: The applicable equipment technical manual, performance standards sheet, reference standards book, overhaul and repair instructions, plans, charts, and nameplates shall be corrected or replaced in accordance with the following instructions:

a. Maintenance Support Activities shall correct their publications immediately, but keep the superseded data intact for support of equipment that have not been modified. Holders of affected equipment shall not make the corrections until the field change has been accomplished.

b. Correct the technical manual for Radio Receiving Set AN/SRR-1, in accordance with interim change T-4 to NAVSHIPS xxxx-xxx-xxxx, item 3.

Figure 3 - Sample of a typical field change bulletin and temporary publication material (Sheet 3 of 4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

ROUTINE INSTRUCTIONS: (CONTINUED)

c. Substitute operator's instruction chart for Radio Receiving Set AN/SRR-1. (NAVSHIPS xxxx-xxx-xxxx), item 4, for the superseded sheet (NAVSHIPS xxxx-xxx-xxxx).

d. Substitute performance standards sheet for Radio Receiving Set AN/SRR-1 (NAVSHIPS xxxx-xxx-xxxx), item 5, for the superseded sheet (NAVSHIPS xxxx-xxx-xxxx).

e. Correct the reference standards book for Radio Receiving Set AN/SRR-1 as provided for an interim change T-1 to NAVSHIPS xxxx-xxx-xxxx, item 6.

f. This field change does not affect any other publications, plans, charts, or nameplates.

2. Record of accomplishement: Personnel making this field change shall record its completion on the Field Change Record Plate, FSN/I0264-085-0000, and on the Record of Field Change Card, (NAVSHIPS 537), if MDCS has been implemented, record completion on the Field Record Plate, and on the appropriate Shipboard Maintenance Action Form, in accordance with OPNAV 43P2, using the following equipment identification code (EIC):

Equipment	EIC
AN/SRR-1	xxxxxxx
AN/SRR-1A	xxxxxxx

3. Disposition of replaced material: The old transformer 1T14 describe in the following table shall be turned into the nearest supply activity for processing in accordance with current instructions.

Reference designation	Quantity	Name of part	FSN
1T14	1	Power transformer	9N5950-646-1280

4. Disposition of field change bulletin: Maintenance support activities shall maintain a library copy of this field change bulletin. Holders of equipment shall not destroy this field change bulletin until the field change has been accomplished, the equipment tested, and the applicable manuals, drawings, charts, and identification plates have been corrected or replaced.

Figure 3 - Sample of a typical field change bulletin and temporary publication material (Sheet 4 of 4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

UNCLASSIFIED

PUBLICATIONS CORRECTION MATERIAL (See 3.7)

CHANGE T-1
NAVSHIPS 0967-076-7012

TEMPORARY CHANGE T-1 to TECHNICAL MANUAL for Teletypewriter Set AN/UGC-16 NAVSHIPS 0967-076-7010 (Formerly NAVSHIPS 94104).

This temporary change revises the manual to reflect the equipment changes made by field changes 5-AN/UGC-16, -16A. When this change is included in the manual, the manual shall cover the equipment as though field changes NAVSHIPS 0967-062-6050, has been accomplished on the equipment. This changes does not supersede any other changes or corrections.

Maintenance support activities shall make this change in the technical manual immediately but shall keep the superseded data intact for support of equipments that have not been modified.

Holders of equipment accompanied by technical manuals shall not make this change in the manual until accomplishment of the field changes referenced above.

Insert this temporary change in the manual immediately after the front cover and preceding the title page or prior changes or temporary corrections in effect. Make pen-and-ink changes in the manual as follows:

1. Section 8, page 8-18, figure 8-8:

   a. Show logic element 02H01 to have an output to 12S00 (8-6, A13).

2. Section 8, page 8-16, figure 8-6:

   a. Show logic element 12S00 to have an input to pin 10 from 02H01 (8-8, A5).

CHANGE T-1

Figure 4 - Sample of publications correction material change for a technical manual, the result of a field change.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

INFORMATION SHEET (See 3.6.1)

NAVSHIPS XXXX-XXX-XXXX

PUBLICATION PACKAGE FOR FIELD CHANGE 3 - AN/SRR-1
CHANGE 1 - AN/SRR-1A

CONTENTS: Two field change bulletins, NAVSHIPS XXXX-XXX-XXXX
Two interim corrections, T-3 NAVSHIPS XXXX-XXX-XXXX

PURPOSE: This publication package contains the necessary publications for field change 3 - AN/SRR-1 and field change 1 - AN/SRR-1A which replaces power, transformer 1T14 with an improved type to prevent failure due to overload.

EQUIPMENTS AFFECTED: AN/SRR-1: All serial numbers; AN/SRR-1A: Serial numbers 1 through 652. All sets were corrected by an identical production change (see 3.6.2.5).

PREREQUISITE FIELD CHANGES: No field changes need be accomplished prior to the installation of this field change.

TIME REQUIRED: Approximately 1 manhour.

Figure 5 - Sample information sheet (typical of the type included with each publication package).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

SECURITY CLASSIFICATION

NAVSHIPS (Publication No.) (3.6.2.2)
ELECTRONIC FIELD CHANGE BULLETIN — FIELD CHANGE NO.
NAVAL SHIP SYSTEMS COMMAND
DEPARTMENT OF THE NAVY
WASHINGTON, D.C. 20360 (3.6.2.2) — FEDERAL STOCK NO.
TITLE (3.6.2.2)
TYPE: ( ), CLASS: ( ) — ACCOMPLISHMENT PRIORITY: (3.6.2.2 & 3.6.2.4) — OPERATIONAL CHANGE / NONOPERATIONAL CHANGE
ESTIMATED MANHOURS: ( )
PREPARED BY: — CONTRACT NO. / PROJECT NO.
NAVAL SHIP ENGINEERING CENTER
TECHNICAL DATA AND PUBLICATIONS SECTION (SEC 6181C)
HYATTSVILLE, MARYLAND 20782 (3.6.2.2)
WARNING:
See statement on figure 3.
(3.6.2.2)
DISTRIBUTION STATEMENT:
See statement on figure 3.
(3.6.2.2)

ACCOMPLISHMENT RESPONSIBILITY (3.6.2.3)

ACCOMPLISHMENT PRIORITY: (3.6.2.4)

EQUIPMENT AFFECTED: (3.6.2.5)

PURPOSE: (3.6.2.6)

PREREQUISITE FIELD CHANGES: (3.6.2.7)

EFFECT ON NOMENCLATURE: (3.6.2.8)

INDICATION OF ACCOMPLISHMENT: (3.6.2.9)

LIST OF PARTS AND MATERIALS: (3.6.2.10)

SPECIAL TOOLS AND TEST EQUIPMENT: (3.6.2.11)

PROCEDURES: (3.6.2.12)

ROUTINE INSTRUCTIONS: (3.6.2.13)
1. Corrections to publications and charts: (3.6.2.13.1)
2. Record of accomplishment: (3.6.2.13.2)
3. Disposition of replaced material: (3.6.2.13.3)
4. Dispositon of field change bulletin: (3.6.2.13.4)

VALIDATION PROCEDURES: (3.6.2.I2)

DATE — SECURITY CLASSIFICATION — PAGE __(of __)

Figure 6 - Format of field change bulletin with paragraph references, also see figure 3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

INDEX

	Paragraph	Page
Abbreviations	3.1.11	4
Acceptance	3.11	12
Accomplishment priority	1.2.2.3, 3.6.2.4, 3.6.2.9	2,8
Accomplishment, record of	3.6.2.13.2	10
Accomplishment responsibility	3.6.2.3	8
Applicable documents	2. 2	2
Approval	3.8	11
Articles	3.1.17, 3.5.1, 3.5.2	5,6,7
Articles, preparation of	3.5, 3.5.2	6,7
Articles for publication	3.5	6
Bidder's considerations	6.6	15
Binding	3.1.20	5
Bulk packaging	5.4	13
Bulletins, field change	3.6.2, 3.6.2.2	7
Charts	3.5	6
Classes	1.2.2.2	2
Classification	1.2	1
Classification, security	3.1.2	4
Cognizant Systems Command	3.6.2.2	7
Contractor's check list	3.1.17	5
Correction material	3.5, 3.6.2	6,7
Correction to charts	3.6.2.13.1	10
Corrections to publications	3.6.2.13.1	10
Covers	3.1.20	5
Data	3.1.9	4
Definitions	3.1.1, 6.3	4,13
Descriptive data	3.6.2	7
Designations	3.1.10	4
Detail specifications	6.2.2	13
Distribution	3.10	12
Drawings	3.1.9, 3.7.7, 3.9.4	4,11
Effect on nomenclature	3.6.2.8	8
Emergency priority	1.2.2.3	2
Engineering drawings	3.7.7	11
Equipment affected	3.5.1, 3.6.2.5	6,8
Equipment contracts	3.4.1, 3.4.2	6
Estimated man-hours	3.5.1, 3.6.2.2	6,7
Evaluation field change	1.2.1, 3.2, 3.9.1, 6.3.2	1,5,11,14
Evaluation test	3.2.2, 4.2	5,12
Federal stock numbers	3.1.19, 3.6.2.2	5,7
Field change	6.3.3	14
Instructions	3.5.1	6
Kit	3.1.19, 3.4.1, 3.4.2, 5.4, 6.3.2, 6.3.5	5,6,13,14
Numbers	3.1.18, 3.6.2.2	5,8
Prerequisite	3.5.1, 3.6.2.7	6,8
Report	3.2	5
Test	3.1.17	5
Type I	1.2.2.1, 3.3.1	1,6
Type II	1.2.2.1, 3.3.1	1,6
Type III	1.2.2.1, 3.3.3	1,6
Type IV	1.2.2.1, 3.3.2	1,6
Field change bulletins	3.1.20, 3.6.2, 6.3.4	5,7,14
Disposition	3.6.2.13.4	10
General requirements	3.1	4
Government furnished material	3.2	5
Hardware	4.4	12
Identification of accomplishment	3.5.1	6
Illustrations	3.1.15, 3.5, 3.6.2	5,6,7
In-process inspection	6.6.2.2	15
Indication of accomplishment	3.6.2.9	8

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

INDEX

	Paragraph	Page
Information sheet	3.6.1	7
Inspection of preparation for delivery	4.6	13
Installation drawings	3.7.7	11
Instruction charts	3.7.2	11
Intended use	6.1	13
Interconnection wiring	3.1.9	4
Interface	3.1.9	4
Interface effect report	3.2.1	5
Interim change	6.3.6	14
Lengthy procedures		
Liaison	6.5	15
List of material	3.3.1, 3.5.1, 3.6.2.10	6,8
List of procedures	3.1.14, 3.6.2.12	4,9
List of test equipment	3.2, 3.5.1, 3.6.2.11	5,6,9
Listings	3.1.14	4
Main heading	3.6.2.2	7
Maintainability	3.1.4	4
Maintenance requirement cards	3.7.6	11
Man-hours	3.5.1, 3.6.2.2	6,7
Manuscript copy	3.1.17, 3.1.18, 3.1.19, 3.5, 3.6.2.4	5,6,8
Marking	5.3	13
Microfilm	3.1.9	4
Modification procedures	3.5.1	6
Nomenclature	3.1.7, 3.6.2.8	4,8
Nonoperational change	3.6.2.2	7
Notes	3.1.13, 6.	4,13
Notices	3.6.2.2, 3.6.2.3	7,8
Operability	3.1.4	4
Operating instruction charts	3.7.2	11
Operational change	3.6.2.2	7
Ordering data	6.2	13
Other publications	2.2	3
Overhaul and repair instructions	3.7.5	11
Packing	5.2	13
Page numbering	3.6.2.1	7
Parts	3.1.12, 3.3.1, 3.4, 3.4.3, 3.6.2.10	4,6,8
Pen-and-ink changes	3.5.2	7
Performance standard sheets	3.5, 3.7.3	6,11
Permanent changes	6.3.11	14
Preliminary data sheets	3.1.9	4
Preparation for delivery	5.	13
Prerequisite field changes	3.5.1, 3.6.2.7	6,8
Preservation and packaging	5.1	13
Printing	3.1.20	5
Priority	1.2.2.3	2
Procedural steps and listings	3.1.14	4
Procedures	3.6.2.12	9
Procurement documents	6.2.1	13
Production field change	1.2.2, 3.3, 3.9.2, 6.3.4	1,5,11,14
Production inspection	4.5	12
Provisioning documentation	3.1.8	4
Publications affected	6.6.1	15
Publication articles	3.5, 3.5.1, 3.5.2	6,7
Publications correction instructions	3.5.2, 3.6.2, 3.7, 6.3.11	7,10,14
Publication material	3.9.3, 4.3, 6.3.12	11,12,14
Publication package	3.6, 3.6.1, 6.3.13	7,14
Purpose	3.5.1, 3.6.2.6	6,8

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

INDEX

	Paragraph	Page
Quality assurance provisions	4.	12
Quality program	6.6.2	15
Quality program requirements	4.1.1	12
Quantity	3.9	11
Record of accomplishment	3.6.2.13.2	10
Reference designations	3.1.10	4
Reference standard books	3.5, 3.7.4	6,11
Reliability	3.1.4	4
Replaced material	3.6.2.13.3	10
Replenishment material	3.9.5	11
Requirements	3.	4
Responsibility for inspection	4.1	12
Routine instructions	3.5.1, 3.6.2.13	6,9
Routine priority	1.2.2.3	2
Running heads and running feet	3.6.2.1	7
Safety	3.1.3	4
Schematic diagrams	3.6.2	7
Scope	1.1	1
Security classification	3.1.2	4
Security notice	3.6.2.2	7
Sequential steps	3.1.4	4
Shipping instructions	6.4	15
Special tools and test equipment	3.2, 3.5.1, 3.6.2.11	5,6,9
Standard books	3.5, 3.7.4	6,11
Step-by-step procedures	3.6.2	7
Stock numbers	3.4.3	6
Supplementary manuals	3.7.1.1	10
Symbols	3.1.12	4
Technical manuals	3.6.2, 3.7.1	7,10
Technical manual correction material	3.5.2, 3.6.2.13.1	7,10
Test equipment	3.1.6, 3.6.2.11	4,9
Test features	3.1.5	4
Test points	3.1.5	4
Title	3.5.1, 3.6.2.2	6,7
Tools and test equipment	3.2, 3.5.1, 3.6.2.11	5,6,9
Type classification	3.1.16	5
Type designation	3.1.16	5
Types/field changes	1.2.2.1	1
Type I	1.2.2.1, 3.3.1	1,6
Type II	1.2.2.1, 3.3.2	1,6
Type III	1.2.2.1, 3.3.3	1,6
Type IV	1.2.2.1, 3.3.2	1,6
Urgent priority	1.2.2.3	2
Validation	3.6.2.12, 6.6.2.3	9,15
Validation plan	6.6.2.1	15
Validation procedures	3.6.2.12	9
Verification	6.6.2.4	16
Warnings	3.1.13	4

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDER
NAVAL SHIP ENGINEERING CENTER
CENTER BUILDING - SEC 61247
PRINCE GEORGE;S CENTER
HYATTVILLE, MARYLAND 20782

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.