MIL-P-17639F(SH)
AMENDMENT 2
17 June 1987
SUPERSEDING
AMENDMENT 1
28 March 1986

MILITARY SPECIFICATION

PUMPS, CENTRIFUGAL, MISCELLANEOUS SERVICE, NAVAL SHIPBOARD USE

This amendment forms a part of MIL-P-17639F(SH), dated 18 February 1986, and is approved for use within the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, under "SPECIFICATION, MILITARY": Add "MIL-G-5514 - Gland Design; Packings, Hydraulic, General Requirements for."

PAGE 3

2.1.1, under "SPECIFICATION, MILITARY (Continued)": Add "MIL-P-25732 - Packing, Preformed, Petroleum Hydraulic Fluid Resistant, Limited Service at 275°F (132°C)."

PAGE 16

3.3.1.1.5: Delete and substitute:

"3.3.1.1.5 Pump casing joints shall be made up using compressed asbestos sheet gaskets, except circular joints which shall be sealed by O-rings as specified (see 6.2.1). O-rings may be used to seal casing joints in other applications when approved by the design review activity. O-ring gland design shall be in accordance with MIL-G-5514. For pumps with a design temperature of 250 degrees Fahrenheit (°F) or lower, O-rings shall be made of Nitrile rubber (BUNA-N) in accordance with MIL-P-25732. For pumps with a design temperature above 250°F, the O-ring material shall be justified to the design review activity."

AMSC N/A FSC 4330
DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.

3.3.1.2.5: Delete and substitute:

"3.3.1.2.5 Pump casing joints shall be made up using compressed asbestos sheet gaskets, except circular joints which shall be sealed by O-rings as specified (see 6.2.1). O-rings may be used to seal casing joints in other applications when approved by the design review activity. O-ring gland design shall be in accordance with MIL-G-5514. For pumps with a design temperature of 250°F or lower, O-rings shall be made of Nitrile rubber (BUNA-N) in accordance with MIL-P-25732. For pumps with a design temperature above 250°F, the O-ring material shall be justified to the design review activity."

PAGE 47

4.6.7.1.3: Delete and substitute:

* "4.6.7.1.3 Endurance test shall not be continuous but shall be interrupted by at least three rest periods of approximately 8 hours each. The number of starts specified in 4.6.7.1 at full line voltage shall be performed during the course of the test. During an early part of the endurance test, the pump shall be operated continuously for 24 hours at a capacity as near free delivery as possible at maximum rated speed and normal specified temperature, submergence, and suction conditions. During the latter part of the endurance test, the pump shall be operated as near shut-off as possible for 12 hours continuously. The remainder of the endurance test shall be run at maximum rated speed and within plus 20°F minus 0°F of maximum specified liquid temperature. The pump shall be operated at one-third, two-thirds, and rated capacity in approximately equal time intervals. Operations shall be at minimum specified net positive suction head available or maximum specified suction lift or vacuum, as applicable."

PAGE 53

6.2.1: Delete second item "(jj)" and substitute: "(kk)".

6.2.1: Add as new item: "(ll) Whether circular joints are required for casing joints (see 3.3.1.1.5 and 3.3.1.2.5)".

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 4330-N266)

Source: https://assist.dla.mil Downloaded: 2026-10-18T10:25Z
Check the source to verify that this is the current version before use.