GG-C-00447a
July 25, 1966
Interim Revision of
Fed. Spec. GG-C-447
October 26, 1950

INTERIM FEDERAL SPECIFICATION

CLOCK, ALARM (GENERAL PURPOSE)

This Interim Federal Specification was developed by General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim Federal specification as a valid exception to Federal Specification GG-C-447, dated October 26, 1950.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers general purpose alarm clocks of the shelf type, hand-wound, spring-driven.

1.2 Classification.

1.2.1 Type and grade. Clocks furnished under this specification shall be of one type and one grade.

1.2.2 Sizes. The general purpose alarm clock dials shall be of the following sizes, as specified (see 6.1):

Size 1: 2-1/2 inches
Size 2: 4 inches

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

Federal Specifications:
L-P-310 - Phenolic Molded Plastics
PPP-T-360 - Time measuring Instruments: Packaging of.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 6645

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

Military Standard:
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Design and construction. The design and construction of the clock shall be in accordance with the requirements specified hereinafter.

3.2 Materials. The materials used in the fabrication of the alarm clock shall be first-class in all respects suitable for this type of commodity.

3.3 Case. The case of the clock may be made of sheet metal or plastic. The metal cases shall have a durable corrosion-resistant finish. The molded plastic material shall be in accordance with any of the types II through VI of Federal Specification L-P-310 or equal, and shall be supplied in a standard finish. All cases shall have a clear glass or plastic crystal. The case shall be made dustproof insofar as is practical for this type of commodity so that there are no unnecessary openings in the case except those required for winding and resetting devices.

3.4 Movements.

3.4.1 General. All movements shall be first grade both as to material and workmanship. Gears shall be of clock brass, or of steel, nylon, aluminum alloy or laminated phenolic material of equal or superior wearing quality. Fiber gears will not be acceptable. All pivots shall be smoothly finished and free from burrs. All gears and pinions shall be cleancut and free from burrs. Gears and pinions shall have hubs or equivalent construction necessary to insure rigidity and shall be force fit on the staffs.

3.4.2 Operation.

3.4.2.1 The movement of the clock shall run without objectionable noise, and shall operate for not less than 32 hours on one complete winding.

3.4.2.2 Each clock shall be equipped with a regulator for rate adjustment. The regulator shall be so adjusted that the greatest change of daily rate shall be within 4 minutes fast or slow of mean time.

3.5 Gong. The clock shall have a loud alarm, and the movement shall be so constructed that the alarm will sound continuously or intermittently at the option of the contractor for at least 20 seconds. Tolerance between the alarm setting time and the striking of the gong shall be plus or minus 5 minutes at 6 o'clock. Manual turn-on, turn off, and setting mechanisms for the alarm, with an alarm time indicator, shall be incorporated in the clock.

3.6 Dial. The diameter of the dial (sight opening), shall be of the dimensions specified in 1.2.2 plus or minus 1/4 inch. The dial material shall be made of paper or other material suitable for the purpose. When the dial is of material other than metal it shall be securely fastened to a metal base in such a manner as to prevent warping, buckling or any irregularities in appearance or positive fit. The dial shall have arabic numerals and minute marks on a contrasting background for the purpose of indicating the time and the setting of the alarm. If luminous hands and numerals are required, it shall be so specified in the invitation for bids.

3.7 Identification marking. Each clock shall have stamped or marked thereon, in a location optional with the contractor, in appropriate sized characters, the name of the contractor or trade name of the manufacturer of such known character as to be easily identified with said manufacturer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

4.2 Sampling.

4.2.1 Visual and dimensional examination. Sampling for visual and dimensional examination shall be in accordance with MIL-STD-105, Inspection Level II, A.Q.L. 4.0.

4.2.2 Test. Sampling for test shall be in accordance with MIL-STD-105, Inspection Level S2, A.Q.L. 2.5.

4.3 Classification of defects. For inspection purposes, defects shall be classified as follows:

EXAMINE	DEFECT	Major	Minor
Clock, General	Not design specified	X	
	Case improperly finished	X	
	Burrs or undesirable projecting ridges at the dividing line of mold		X
	Any component cracked, fractured, broken or damaged	X	
	Clock operates with objectionable noise.	X	
	Clock will not run	X	
Case	Material used other than specified	X	
	Improper fit of case to dial and dial cover	X	
Dial	Any dial marking missing, illegible, incomplete, incorrect, or wrong material used to apply	X	
	Dial surface scratched, abraded, or otherwise damaged	X	
Hands	Any hand not securely mounted	X	
	Any hand bent, malformed, or otherwise damaged	X	
	Hand rubs against dial or dial cover, or hand obstructs movements of another hand	X	
Crystal	Crystal broken, poor quality, not clear, blisters, bubbles, scratch or scratches, coarse or open seeds, heavy seeds or feathers, or other defects which distort or impair vision	X	

4.4 Visual and dimensional examination. The clocks shall be examined to determine compliance with all requirements contained in sections 3 and 5 of this specification.

4.5 Test.

4.5.1 Movement. Wind the clock until completely wound and allow it to run in the normal operating position, with no change in the original adjustment, under the prevailing atmospheric conditions. Rewind completely at the end of each 32-hour period, and continue the test for 72 hours. Check the rate of the clock daily and at the end of the test period for conformance with 3.4.2.1 and 3.4.2.2.

4.5.2 Gong. Wind the alarm until completely wound. Set the alarm time indicator at 6 o'clock. Put the setting mechanism of the alarm on the "ON" position and test to determine compliance with all the requirements of paragraph 3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. Packaging, packing and marking shall be as specified in Federal Specification PPP-T-360, except that Group 4 packaging and packing requirements in lieu of Group 3 shall apply.

6. NOTES

6.1 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, symbol, and date of this specification.
(b) Size of dial and case material and finish (see 1.2.1 and 3.3).
(c) Luminous dial, if required (see 3.6).
(d) Inspection responsibility, if other than specified (4.1).
(e) Levels of packaging, packing, and marking for shipment (5.1).

6.2 The right is reserved to reject bids on products that have not been subjected to the required tests (4.4), or for which the supplier is unable to furnish authenticated records (4.4).

6.3 This specification does not include all types, classes, grades, sizes, etc., of the commodity indicated by the title of the specification, or which are commercially available, but is intended to cover the types, etc., which are normally procured to meet Federal Government requirements.

6.4 It is believed that this specification adequately describes the characteristics necessary to secure the desired material, and that normally no samples will be necessary prior to award to determine compliance with this specification. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitations for bids and the particular purpose to be served by the bid sample should be definitely stated, the specification to apply in all other respects.

FSA DC 87- 1807

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.