GG-C-447
AMENDMENT—3
April 17, 1963
SUPERSEDING
AMENDMENT—2
February 8, 1955

FEDERAL SPECIFICATION

CLOCK, ALARM (GENERAL PURPOSE)

This amendment, which forms a part of Federal Specification GG-C-447, dated October 26, 1950, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 1, delete paragraph 2.1 and parenthetical paragraph and substitute new paragraph 2.1 and parenthetical paragraph as follows:

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

Federal Specifications:

PPP-T-360—Time measuring Instruments: Packaging of.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Page 1, paragraph 3.3, lines 3 and 4. Delete "of proper thickness as specified in the invitation for bids".

Page 1, paragraph 3.5: Delete in its entirety and substitute:

3.5 **Gong.** The clock shall have a loud alarm, and the movement shall be so constructed that the alarm will sound continuously or intermittently at the option of the contractor for at least 20 seconds. Tolerance between the alarm setting time and the striking of the gong shall be plus or minus 5 minutes at 6 o'clock. Manual turn-on, turn off, and setting mechanisms for the alarm, with an alarm time indicator, shall be incorporated in the clock.

Page 2, section 5: Delete in its entirety and substitute:

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing, and marking. Packaging, packing, and marking shall be as specified for packaging group 3 in PPP-T-360.

Page 2, paragraph 6.1: In line 2, delete "thickness of case desired," and in line 5, delete "3.3,".

Page 2, following paragraph 6.2, add the following:

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:50Z
Check the source to verify that this is the current version before use.

6.3 **Transportation description.** Transportation descriptions and minimum weights applicable to this item are:

Rail:

Clocks, not otherwise indexed by name.
Carload minimum weight 16,000 pounds subject to Rule 34, Uniform Freight Classification.

Motor:

Clocks, not otherwise indexed.
Truckload minimum weight 16,000 pounds subject to Rule 115, National Motor Freight Classification.

Page 5, bottom of page: Delete "NAVY: MCShS".

Page 6, following paragraph 7.4.5, add:

MILITARY INTEREST:

Army—QT
Navy—Sh MC
Air Force

Page 6, bottom of page: Delete "For sale" statement and substitute:

Copies of this specification may be purchased for 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.