FEDERAL SPECIFICATION

CLOCK, ALARM (GENERAL PURPOSE)

This specification was approved on the above date by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. CLASSIFICATION

1.1 Type. — Alarm clocks covered by this specification shall be of the shelf type, hand-wound, spring-driven.

2. APPLICABLE SPECIFICATIONS

2.1 There are no other specifications applicable to this specification except those referenced in section 7 by individual departments.

(Copies of Federal specifications and the Federal Specifications Index may be obtained upon application, accompanied by postal note, money order, coupon, or cash, to the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Prices may be obtained from the Superintendent of Documents.)

3. REQUIREMENTS

3.1 Design and construction.—The design and construction of the clock shall be in accordance with the requirements specified hereinafter.

3.2 Materials.—The materials used in the fabrication of the alarm clock shall be first-class in all respects suitable for this type of commodity.

3.3 Case.—The case of the clock may be made of sheet metal or commercially proven material of proper thickness as specified in the invitation for bids, and designed to withstand reasonably hard usage. The case shall be made dustproof insofar as is practical for this type of commodity. All surfaces of the case shall have a durable corrosion-resistant finish.

3.4 Movement.—The movement of the clock shall be reasonably quiet in operation, and shall run for not less than 32 hours on one complete winding. Each clock shall be equipped with a regulator for rate adjustment and the regulator shall be capable of adjusting the movement either faster or slower in order to indicate mean time. The regulator shall be so adjusted that the greatest change of daily rate shall be within 4 minutes fast or slow of mean time.

3.5 Gong. — The clock shall have a loud alarm, and the movement shall be so constructed that the alarm will sound continuously or intermittently at the option of the contractor for at least 4 minutes. Tolerance between the alarm setting time and the striking of the gong shall be ± 5 minutes at 6 o'clock. Manual turn-on, turn-off, and setting mechanisms for the alarm, with an alarm time indicator, shall be incorporated in the clock.

3.6 Dial.—The dial of the clock shall be approximately 4 inches in diameter and shall be made of paper or other material suitable for the purpose. The dial shall have Arabic numerals and minute marks on a contrasting background for the purpose of indicating the time and the setting of the alarm. If luminous hands and numerals are required, it shall be so specified in the invitation for bids and contract or order.

3.7 Identification marking. — Each clock shall have stamped or marked thereon, in a location optional with the contractor, in appropriate sized characters, the name of the contractor or trade name of the manufacturer

901695—50—(81)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

of such known character as to be easily identified with said manufacturer.

3.8 **Workmanship.** — The finished clocks shall be clean, well made, and free from any defects which affect the appearance or which may affect the serviceability. The quality shall be known as firsts.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 **Sampling.**—Two clocks from each lot of 100 clocks, or fraction thereof, delivered shall be taken as representative of the lot for inspection and tests to determine compliance with this specification.

4.2 **Inspection.** — Each sample clock shall be visually inspected with respect to materials, size, workmanship, and finish. Inspection may be made throughout the entire process of manufacture, in which event every facility shall be afforded the inspectors by the manufacturer for the prosecution of their work. Final inspection of the finished clock shall be made either at the place of production or at the point of delivery, as designated in the contract or order of the procuring agency.

4.3 **Tests.**

4.3.1 *Movement.* — Wind the clock until completely wound and allow it to run in the normal operating position, with no change in the original adjustment, under the prevailing atmospheric conditions. Rewind completely at the end of each 32-hour period, and continue the test for 72 hours. Check the rate of the clock daily and at the end of the test period for conformance with 3.4.

4.3.2 *Gong.*—Tests shall be conducted on the alarm mechanism to determine compliance with the requirements of 3.5.

5. PREPARATION FOR DELIVERY

5.1 **Packaging.** — Unless otherwise specified, commercial packaging will be acceptable.

5.2 **Packing.**—The subject commodity shall be prepared for shipment to permit acceptance by carrier for transportation at the lowest applicable rate, and to afford maximum protection from normal hazards of transportation.

5.3 **Marking.**—Unless otherwise specified, shipping containers shall be marked with the name of the commodity as defined by the contract or order under which shipment is made, the quantity contained therein, the name of the contractor, and the number of the contract or order.

6. NOTES

6.1 **Ordering data.** — Purchasers should specify thickness of case desired, whether luminous hands and numerals are required, and should exercise any desired options offered herein. (See 3.3, 3.6, 5.1, 5.3, 7.4.3, and 7.4.4.)

6.2 If for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids, and the particular purpose to be served by the bid sample should be definitely stated, this specification to apply in all other respects.

Patent notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

7. DEPARTMENTAL REQUIREMENTS

7.1 The following specifications and other publications, of the issues in effect on date of invitations for bids, and special requirements, form a part of this specification for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

purchases made under this specification by the respective departments.

7.2 Army.

7.2.1 *Applicable specifications.*

Federal Specifications:

NN-B-591—Boxes; Wood-Cleated-Fiberboard.

NN-B-601—Boxes; Wood-Cleated-Plywood, for Domestic Shipment.

NN-B-621—Boxes; Wood, Nailed and Lock-Corner.

NN-B-631—Boxes; Wood, Wirebound, for Domestic Shipment.

LLL-B-631—Boxes; Fiber, Corrugated (for Domestic Shipment).

LLL-B-636—Boxes; Fiber, Solid (for Domestic Shipment).

Military Specifications:

JAN-P-103—Packaging and Packing for Overseas Shipment — Boxes; Wood Cleated; Solid Fiberboard.

JAN-P-105—Packaging and Packing for Overseas Shipment — Boxes, Wood, Cleated, Plywood.

JAN-P-106—Packaging and Packing for Overseas Shipment — Boxes; Wood, Nailed.

JAN-B-107—Boxes, Wood, Wirebound (Overseas Type).

JAN-P-125—Packaging and Packing for Overseas Shipment — Barrier-Materials, Waterproof, Flexible.

JAN-P-140—Packaging and Packing for Overseas Shipment — Adhesives, Water-Resistant, Case-Liner.

U. S. Army Specification:

100-2 —Standard Specification for Marking Shipment by Contractors (including Corps of Engineers Supplement).

(Copies of specifications required for Army purchases may be obtained upon application to the procuring agency. Both the title and identifying symbol or number should be stipulated when requesting copies.)

7.2.2 *Packaging.*—Each alarm clock shall be packaged in a full-telescope-design box constructed of corrugated or solid fiberboard and having a bursting strength of not less than 175 pounds per square inch. Boxes shall conform to Specification LLL-B-631 or LLL-B-636. The clock shall be positioned and cushioned within the box in such a manner that it does not contact any interior face of the container. This may be accomplished by the use of scored and folded corrugated fiberboard pads or other suitable cushioning material such as medium weight, flexible, single-faced corrugated material or cellulose wadding. Closure of the box shall be effected with 2-inch-wide kraft paper gummed tape; tape may be applied in short lengths over the opening of the box or girthwise around the box, overlapping approximately 2 inches. Tape requirements may be waived if box is of self-locking type.

7.2.3 *Packing.*

7.2.3.1 *For domestic shipment.*—Twenty-four alarm clocks, packaged as specified in 7.2.2 shall be packed in a style RSC corrugated or solid fiberboard box conforming to Specifications LLL-B-631 and LLL-B-636, respectively. All flaps of the fiberboard box shall be securely sealed with a good-quality adhesive applied thoroughout the entire area of contact between the flaps. Alternate domestic shipping containers conforming to Specification NN-B-591, style A or B; NN-B-601, style A or B; NN-B-621, style 2 or 4; or NN-B-631, style 1, 2, or 2A, may be used. Only one type and style container shall be used for any one contract.

7.2.3.2 *For overseas shipment.*—Twenty-four alarm clocks, packaged as specified in 7.2.2, shall be packed in a wood-cleated solid-fiberboard box, wood-cleated plywood box, nailed wood box, or wirebound wood box con-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

forming to the requirements of Specifications JAN–P–103, JAN–P–105, JAN–P–106, and JAN–B–107, respectively. Each overseas shipping container shall be provided with a sealed case-liner or prefabricated bag made of waterproof barrier-material in accordance with Specification JAN–P–125, type L–2, or M. All closures shall be sealed with a continuous seam, at least ¾ inch wide, of water-resistant adhesive complying with Specification JAN–P–140. The overseas shipping containers shall be constructed for type 1 load, and shall be strapped in accordance with the appendix to the applicable box specification. Only one type and style container shall be used for any one contract.

7.2.4 *Marking.*

7.2.4.1 *Packages.*—Individual alarm clock boxes shall have one end printed or labeled as follows:

Nomenclature
Stock number
Quantity
Name and address of contractor
Contract or order number

7.2.4.2 *Shipping containers.* — Shipping containers for the Army shall be marked in accordance with Specification 100–2, except that service color marking will not be required on domestic shipments.

7.3 Navy.

7.3.1 *Applicable specifications and other publications.*

Federal Specifications:

UU–C–843 —Cushioning Materials; Cellulosic.

NN–B–591 —Boxes; Wood-Cleated-Fiberboard.

NN–B–601 —Boxes; Wood-Cleated-Plywood, for Domestic Shipment.

NN–B–621 —Boxes; Wood, Nailed and Lock-Corner.

Military Specifications:

JAN–P–103—Packaging and Packing for Overseas Shipment — Boxes; Wood Cleated; Solid Fiberboard.

JAN–P–105—Packaging and Packing for Overseas Shipment — Boxes, Wood, Cleated, Plywood.

JAN–P–106—Packaging and Packing for Overseas Shipment — Boxes; Wood, Nailed.

JAN–P–116—Packaging and Packing for Overseas Shipment — Preservation, Methods of.

JAN–P–125—Packaging and Packing for Overseas Shipment — Barrier-Materials, Waterproof, Flexible.

JAN–P–133—Packaging and Packing for Overseas Shipment — Boxes, Set-Up, Paperboard.

JAN–P–140—Packaging and Packing for Overseas Shipment — Adhesives, Water-Resistant, Case-Liner.

Navy Department Specification:

General Specifications for Inspection of Material.

Bureau of Supplies and Accounts Publication:

Navy Shipment Marking Handbook.

(Copies of Federal and Military specifications required for Navy purchases, Navy Department specifications, and the Navy Shipment Marking Handbook may be obtained without cost upon application to the Bureau of Supplies and Accounts, Navy Department, Washington 25, D. C., except that activities of the Armed Forces should make application to the Naval Supply Center, Norfolk 11, Va. Commanding Officer. Both the title and identifying symbol or number should be stipulated when requesting copies of specifications.)

7.3.2 *Packaging.*

7.3.2.1 *For domestic shipment.* — Clocks shall be wrapped individually with creped cellulose wadding conforming to the requirements of Specification UU–C–843, or similar

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

suitable non-abrasive material, and then individually packaged in a set-up paperboard box conforming to type I of Military Specification JAN-P-133. The clock shall be so supported and cushioned within the box that it cannot directly contact any interior face or otherwise become damaged during shipment and storage.

7.3.2.2 *For overseas shipment.* — Clocks shall be packaged in accordance with method II, submethods IIb, IIc, or IIe, of Specification JAN-P-116.

7.3.3 *Packing.*

7.3.3.1 *For domestic shipment.* — Twelve clocks, packaged as specified in 7.3.2.1, shall be packed in a snug-fitting wood-cleated fiberboard box, wood-cleated plywood box, or nailed wood box conforming to Specifications NN-B-591, NN-B-601, and NN-B-621, respectively.

7.3.3.2 *For overseas shipment.* — Twelve clocks, packaged as specified in 7.3.2.2, shall be packed in a wood-cleated solid-fiberboard box, wood-cleated plywood box, or nailed wood box conforming to Specifications JAN-P-103, JAN-P-105, and JAN-P-106, respectively. Each box shall be lined with a sealed waterproof bag made from material conforming to Specification JAN-P-125. Seams and closures shall be sealed with adhesive conforming to Specification JAN-P-140.

7.3.4 *Marking.*—In addition to any special marking required by the contract or order, shipments for the Navy shall be marked in accordance with the Navy Shipment Marking Handbook.

7.3.5 *Ordering data.* — Requests, requisitions, schedules, and contracts or orders should specify whether the subject commodity is to be packaged, packed, and shipping containers marked for domestic or overseas shipment. (See 7.3.2, 7.3.3, and 7.3.4.)

NAVY: MCSbS

7.4 Air Force.

7.4.1 *Applicable standard and specification.*

Military Standard:

JAN-STD-105 — Sampling Inspection Tables for Inspection by Attributes.

U. S. Army Specification:

94-40645—Marking; Exterior, Domestic and Export Shipment, by Contractors.

(Copies of specifications required for Air Force purchases may be obtained from the Commanding General, Air Matériel Command, Wright-Patterson Air Force Base, Dayton 1, Ohio.)

7.4.2 *Sampling.*

7.4.2.1 *Sampling for qualification test.* — Qualification test samples shall consist of a minimum of three sample clocks. Samples shall be appropriately identified, and shall be forwarded to the agency designated in the letter of authorization.

7.4.2.2 *Sampling for acceptance.*

7.4.2.2.1 *Sampling for visual and dimensional inspection.* — Sampling to determine conformance with the visual and dimensional requirements of this specification shall be in accordance with JAN-STD-105.

7.4.2.2.2 *Sampling for functional tests.* — Sampling to determine conformance with the functional requirements of this specification shall be as follows: A sample of 10 clocks shall be taken at random from each lot and tested in accordance with 4.3.1. If one or more of the sample clocks fails to run for at least 32 hours on one winding, the lot shall be rejected. However, if all of the clocks run for at least 32 hours on one winding, but more than one unit fails to operate within the tolerance as prescribed in 3.4, the lot shall be rejected. Likewise, a sample of 10 clocks shall be taken for the test specified in 4.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

If any of the sample clocks fail to strike, the lot shall be rejected, however, if all the sample clocks strike but more than one does not strike within the tolerance prescribed in 3.5, the lot shall be rejected.

7.4.3 *Qualification test.*—Unless otherwise specified by the procuring agency, manufacturers' types of clocks which have not previously passed a qualification test shall satisfactorily pass a qualification test prior to acceptance of any clocks.

7.4.4 *Test procedures.*—Unless otherwise specified, contractors records of all inspection work and tests, giving the results of tests required to determine compliance with the requirements and tests specified herein, shall be kept complete and shall be available to the Government representative at all times. The tests shall be accomplished on articles to be supplied on the contract or order. The record or report of inspection and tests shall be signed or approved by a responsible person specifically assigned by the contractor.

7.4.4.1 *Inspection.* — The clocks shall be visually inspected with respect to materials, size, workmanship, and finish. Inspection may be made throughout the entire process of manufacture, in which event every facility shall be afforded inspectors by the manufacturer, for the prosecution of their work. Final inspection of the finished clocks shall be made at the point of production or at the point of delivery designated in the contract or purchase order of the procuring agency.

7.4.5 *Marking of shipping containers.* — Shipping containers for the Air Force shall be marked in accordance with the requirements of U. S. Army Specification 94–40645.

This specification is a part of Section IV, Part 5, of the Federal Standard Stock Catalog.

For sale by the Superintendent of Documents, Washington 25, D. C. Price 5 cents.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:50Z
Check the source to verify that this is the currentversion before use.