CG-D-458B
INT. AMENDMENT-2 (GSA-FSS)
July 3, 1969
SUPERSEDING
INT. AMENDMENT-1 (GSA-FSS)
March 25, 1969

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

DISPENSER, PRESSURE-SENSITIVE ADHESIVE TAPE

This interim amendment was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification CG-D-458B, dated April 2, 1962.

PAGE 2

After 3.1, add new paragraphs as follows:

3.1.1 Reels (Drums). The reels (drums) of the type V, classes 2, 3, 4, and 5 dispensers shall be plastic or metal of sufficient strength to withstand a pull load of 10 pounds without damage when tested in accordance with paragraph 4.5.1.2.

3.1.2 Base pads. The base of type V, classes 2, 3, 4, and 5 dispensers shall be covered with a soft, resilient pad, or pads to prevent damage to surfaces on which placed and to resist sliding during dispensing of tape. The pad or pads shall be firmly and smoothly attached to the bottom of the dispenser.

3.1.3 Tape cutoff blades. The tape cutoff of the type V, classes 2, 3, 4, and 5 dispensers shall be a serrated-edge, corrosion resistant metal blade. (See 3.2.5.2.3)

PAGE 3

Paragraph 3.2.5. Delete in its entirety and substitute:

3.2.5 Type V.

3.2.5.1 Class 1. Type V, class 1 dispenser shall be suitable for dispensing any type of pressure-sensitive tape in predetermined lengths. Tape shall be dispensed by setting indicator to the length desired and manually pulling and cutting the tape on a cutoff blade.

3.2.5.2 Classes 2, 3, 4, and 5. Type V, classes 2, 3, 4, and 5 dispensers shall be suitable for dispensing film and paper-backed pressure-sensitive tape. The dispenser body shall be open and the tape feed manual. The tape cutoff shall be manual, using a serrated-edge metal blade. Dispensers shall have sufficient space between the edge of a full roll of tape (see 3.3.6.1, 3.3.6.2, 3.3.6.3 or 3.3.6.4), the tape holding platform, the underside of tape, and the dispenser body, to permit insertion of a round rod, 5/8 inch in diameter.

3.2.5.2.1 Dimensions.

3.2.5.2.1.1 Class 2. Type V, class 2 dispenser shall be not less than 7 inches in length, 4 inches in width, and 3 inches in height, excluding roll of tape.

3.2.5.2.1.2 Class 3. Type V, class 3 dispensers shall be not less than 7 inches in length, 3 inches in width, and 3 inches in height, excluding roll of tape.

3.2.5.2.1.3 Class 4. Type V, class 4 dispensers shall be not less than 7 inches in length, 3 inches in width, and 3 inches in height, excluding roll or tape.

3.2.5.2.1.4 Class 5. Type V, class 5 dispensers shall be 6-3/4 ± 3/4 inches in length, 2-3/4 ± 1/2 inches in width at the widest point, and 2-3/4 ± 1/2 inches in height at the highest point, excluding roll of tape.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:50Z
Check the source to verify that this is the current version before use.

PAGE 3 (con

3.2.5.2.2 Weight. Over-all weight of the dispenser body and tape reel (drum) of the type V, class 5 dispenser shall be not less than 2 pounds or more than 4 pounds and shall be distributed to provide stability.

3.2.5.2.3 Cutoff blade. The serrated cutting edge shall contain not less than 22 and not more than 28 teeth per inch and shall be sufficiently sharp to permit cutting without causing tape to wrinkle or tear unevenly. The ends of the serrated cutting edge shall be shielded to prevent physical injury to the hands. (See 3.1.3.)

3.2.5.2.4 Reels (Drums). The shaft of the drum shall fit into slots that are free from burrs or obstructions which prevent easy insertion or free rotation of the drum. The slots shall be designed so the drum will not be displaced from dispenser body when dispensing tape. (See 3.1.1.)

PAGE 4

Paragraph 3.3.6 Delete and substitute:

3.3.6 Type V.

3.3.6.1 Class 1. Type V, class 1 dispensers shall accommodate rolls of tape up to 1 inch wide with a roll diameter up to 5 inches.

3.3.6.2. Class 2. Type V, class 2 dispensers shall accommodate rolls of tape up to 3 inches wide with a roll diameter up to 5 inches. Dispenser shall not slide or tip during tape dispensing operation before reaching a pull load of 4 pounds when tested in accordance with 4.5.1.1.

3.3.6.3 Class 3. Type V, class 3 dispensers shall accommodate rolls of tape up to 2 inches wide with a roll diameter up to 5 inches. Dispenser shall not slide or tip during tape dispensing operation before reaching a pull load of 3-1/2 pounds when tested in accordance with 4.5.1.1.

3.3.6.4 Class 4. Type V, class 4 dispensers shall accommodate rolls of tape up to 1 inch wide with a roll diameter up to 5 inches. Dispenser shall not slide or tip during tape dispensing operation before reaching a pull load of 3 pounds when tested in accordance with 4.5.1.1.

3.3.6.5 Class 5. Type V, class 5 dispensers shall accommodate rolls of tape up to 3/4 inch wide with a roll diameter up to 2-1/2 inches. Dispenser shall not slide or tip during tape dispensing operation before reaching a pull load of 1-3/4 pounds when tested in accordance with 4.5.1.1

PAGE 5

Paragraph 4.4 Delete and substitute:

4.4 Examination. Dispenser samples selected in accordance with 4.3.1 shall be inspected for the following defects to determine compliance with the applicable paragraphs, Acceptable Quality Level (AQL) 4.0 percent defective:

Defect	Applicable Paragraph
Material not as specified.	3.1, 3.1.1, 3.1.2, 3.1.3
Cutoff blade not as specified.	3.2.1, 3.2.2, 3.2.3.1, 3.2.5.1, 3.2.5.2.3, 3.2.6
Construction not as specified.	3.2
Capacity not as specified.	3.3
Dimensions	3.2.5.2.1
Weight	3.2.5.2.2
Identification marking missing	3.5
Workmanship.	3.6

After last sentence of paragraph 4.5.1 add:

A rod 5/8 inch in diameter shall be inserted as indicated in 3.2.5.3. The rod shall not touch the underside of the tape extended between roll and the holding platform.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

After 4.5.1 add new paragraph as follows:

4.5.1.1 Sliding and tipping test. Dispenser shall be placed on a smooth glass surface. Tape shall be dispensed to a length of 4 ± 1/2 inches, and firmly pressed against the tape holding platform without cutting the tape. The loose end of the tape will be fastened to a push pull gage of adequate capacity (Chatillon Model No. 719-20 or equal). Gage will then be pulled slowly outward, parallel to the test surface to determine compliance with the requirements of paragraph 3.3.6.2, 3.3.6.3, 3.3.6.4 and 3.3.6.5.

4.5.1.2 Reel (Drum) strength test. Dispenser shall be blocked to prevent forward movement. Pass tape 12 inches in length around reel and fasten both ends to a push pull gage of adequate capacity (Chatillon Model No. 719-20 or equal). Gage will be pulled slowly outward to determine compliance with 3.1.1

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:50Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.