GG-D-00458C(GSA-FSS)
August 7, 1970
Interim Revision of
Fed. Spec. GG-D-458b
April 2, 1962

INTERIM FEDERAL SPECIFICATION

DISPENSER, PRESSURE-SENSITIVE ADHESIVE TAPE

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification GG-D-458b dated April 2, 1962.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers requirements for manually operated pressure-sensitive adhesive-tape dispensers for dispensing tapes with pressure-sensitive adhesive on one side only.

1.2 Classification.

1.2.1 Types and classes. Pressure-sensitive adhesive-tape dispensers shall be of the following types and classes as specified (see 6.2):

Type I	Deleted (see 6.3)
Type II	Deleted (see 6.3)
Type III	Deleted (see 6.3)
Type IV	Deleted (see 6.3)
Type V	Desk and counter dispensers, hand operated.
Class 1	Deleted (see 6.3)
Class 2	For tapes up to 3 inches wide.
Class 3	For tapes up to 2 inches wide.
Class 4	For tapes up to 1 inch wide.
Class 5	For tapes up to 3/4 inch wide.
Type VI	Hand dispensers, hand operated, random lengths.
Class 1	For tapes up to 3/4 inch wide.
Class 2	For tapes up to 1/2 inch wide.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form part of this specification to the extent specified herein.

Federal Specifications:

L-T-90 - Tape, Pressure-Sensitive Adhesive (Cellophane and Cellulose Acetate).
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes; Paperboard, Metal Stayed (including Stay Material).
PPP-B-676 - Boxes, Set-up, Paperboard.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specification, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-B-10377 - Boxes; Wood-Cleated, Veneer, Paper Overlaid.
MIL-L-10547 - Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The material of the body for type V dispensers shall be metal not less than 1/32 inch thick. Type VI dispensers shall be light-weight durable plastic.

3.1.1 Reels (Drums). The reels (drums) of the type V, classes 2, 3, 4, and 5 dispensers shall be plastic or metal of sufficient strength to withstand a pull load of 10 pounds without damage when tested in accordance with 4.4.2.

3.1.2 Base pads. The base of type V, classes 2, 3, 4, and 5 dispensers shall be covered with a soft, resilient pad, or pads to prevent damage to surfaces on which placed and to resist sliding during dispensing of tape. The pad or pads shall be firmly and smoothly attached to the bottom of the dispenser.

3.1.3 Tape cutoff blade. The tape cutoff blade shall be a serrated corrosion resistant metal blade.

3.2 Design and construction.

3.2.1 Type V. Type V dispensers shall be sturdily constructed suitable for dispensing film and paper-backed pressure-sensitive tape. The dispenser body shall be open and the tape feed manual. The tape cutoff shall be manual, using a serrated metal blade. To provide ease in detachment of tape from the holding platform for dispensing the dispenser shall have sufficient space between the outer edge of a full roll of tape (see 3.3.1), the tape holding platform, the underside of tape, and the dispenser body to permit insertion of a round rod 5/8 inch in diameter (see 4.4.1).

3.2.1.1 Dimensions.

3.2.1.1.1 Class 2. Type V, class 2 dispensers shall be not less than 7 inches in length, 4 inches in width, and 3 inches in height, excluding roll of tape.

3.2.1.1.2 Class 3. Type V, class 3 dispensers shall be not less than 7 inches in length, 3 inches in width, and 3 inches in height, excluding roll of tape.

3.2.1.1.3 Class 4. Type V, class 4 dispensers shall be not less than 7 inches in length, 3 inches in width, and 3 inches in height, excluding roll or tape.

3.2.1.1.4 Class 5. Type V, class 5 dispensers shall be 6-3/4 ± 3/4 inches in length, 2-3/4 ± 1/2 inches in width at the widest point, and 2-3/4 ± 1/2 inches in height at the highest point, excluding roll of tape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

3.2.1.2 Weight. Over-all weight of the dispenser body and tape reel (drum) of the type V, class 5 dispenser shall be not less than 2 pounds or more than 4 pounds and shall be distributed to provide stability.

3.2.1.3 Cutoff blade. The serrated cutting edge shall contain not less than 22 and not more than 28 teeth per inch and shall be sufficiently sharp to permit cutting without causing tape to wrinkle or tear unevenly. The ends of the serrated cutting edge shall be shielded to prevent physical injury to the hands. (See 3.1.3.)

3.2.1.4 Reels (Drums). The shaft of the drum shall fit into slots that are free from burrs or obstructions which prevent easy insertion or free rotation of the drum. The slots shall be designed so the drum will not be displaced from dispenser body when dispensing tape.

3.2.2 Type VI. Type VI dispensers shall be suitable for dispensing film-backed pressure-sensitive tape. The dispensers shall consist of two mated halves of plastic that essentially enclose the roll of tape. The two parts shall fit with a friction fit but must be separable to allow insertion of new roll of tape. The spindle on which the roll of tape fits shall be an integral part of one half of the dispenser. Tape feed shall be manual. Tape cutoff shall be manual using a serrated metal blade.

3.3 Capacity and performance.

3.3.1 Type V.

3.3.1.1 Class 2. Type V, class 2 dispenser shall accommodate rolls of tape up tp 3 inches wide, with a roll diameter up to 5 inches and a 3 inch core. When specified, dispenser shall be equipped with three tape reels (drums) side by side permitting use of single or multiple rolls of tape in total width up to 3 inches (see 6.2). The tape shall dispense easily and shall not bind against any part of the dispenser. Dispenser shall not slide or tip before reaching a pull loads of 4 pounds when tested in accordance with 4.4.1.1.

3.3.1.2 Class 3. Type V, class 3 dispenser shall accommodate rolls of tape up to 2 inches wide, with a roll diameter of up to 5 inches and a 3 inch core. When specified, dispenser shall be equipped with two tape reels (drums) side by side permitting use of single or multiple rolls of tape in total width up to 2 inches (see 6.2). The tape shall dispense easily and shall not bind against any part of the dispenser. Dispenser shall not slide or tip before reaching a pull load of 3-1/2 pounds tip when tested in accordance with 4.4.1.1.

3.3.1.3 Class 4. Type V, class 4 dispenser shall accommodate rolls of tape up to 1 inch wide, with a roll diameter of up to 5 inches and a 3 inch core. The tape shall dispense easily and shall not bind against any part of the dispenser. Dispenser shall not slide or tip before reaching a pull load of 3 pounds when tested in accordance with 4.4.1.1.

3.3.1.4 Class 5. Type V, class 5 dispenser shall accommodate rolls of tape up to 3/4 inch wide, with a roll diameter of up to 2-1/2 inches and a 1 inch core. Tape shall dispense easily and shall not bind against any part of the dispenser. Dispenser shall not slide or tip before reaching a pull load of 1-3/4 pounds when tested in accordance with 4.4.1.1.

3.3.2 Type VI. Type VI, class 1 and 2 dispensers shall accommodate rolls of tape 3/4 inch and 1/2 inch wide, respectively. Dispensers shall accommodate rolls of tape containing up to 36 yards of cellulose tape.

3.4 Color. Any solid color representing the manufacturer's normal commercial production is acceptable.

3.5 Identification marking. Each dispenser shall be permanently marked with the manufacturer's name or trademark.

3.6 Workmanship. Tape dispensers shall be free from any defects that may affect serviceability or appearance, such as dents, nicks, burrs, rust, and sharp edges other than cutoff blades. Surfaces which accommodate tape reel shafts shall be free from burrs or rough surfaces which will damage the reel or shaft.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection of preparation for delivery requirements. The packaging, packing and marking of tape dispensers shall be subject to inspection by the inspector to determine compliance with the requirements of Section 5 of this specification.

4.2 Sampling.

4.2.1 Lot. A lot shall consist of all dispensers of the same type and class offered for inspection at one time.

4.2.2 Sampling of end item for visual examination. A random sample of dispensers shall be taken from each lot in accordance with MIL-STD-105, inspection level S-3. The acceptable quality level (AQL) shall not exceed 4.0 percent defective. The sample unit shall be one dispenser.

4.2.3 Sampling for end-item tests. Random sample of dispensers for each test shall be taken from each lot in accordance with MIL-STD-105, inspection level S-3. The acceptable quality level (AQL) shall not exceed 4.0 percent defective. The sample unit shall be one dispenser.

4.3 Visual examination of end item. Dispenser samples selected in accordance with 4.2.2 shall be examined for the defects listed in table I. Any sample containing one or more defects shall be rejected.

TABLE I.

Defect	Applicable Paragraph
Material not as specified	3.1, 3.1.1, 3.1.2, 3.1.3
Cutoff blade not as specified	3.2.1
Construction not as specified	3.2
Dimensions	3.2.1.1
Weight	3.2.1.1.4
Identification marking missing	3.5
Workmanship	3.6

4.4 Tests.

4.4.1 Capacity and performance. A roll of tape conforming to equal the maximum width and roll diameter specified for the respective type and class shall be inserted in the applicable dispenser. A rod 5/8 inch in diameter shall then be inserted between the holding platforms and tape roll for type V, class 2, 3, 4, and 5 to determine compliance with 3.2.1. A minimum of six lengths of tape shall be dispensed to determine ease of operation (see 3.3.1). Tape used for tests shall conform to L-T-90, type I.

4.4.1.1 Sliding and tipping test. Dispenser shall be placed on a smooth glass surface. Tape shall be dispensed to a length of 4 $\pm$ 1/2 inches, and firmly pressed against the tape holding platform without cutting the tape. The loose end of the tape will be fastened to a push pull gage of adequate capacity (Chatillon Model No. 719-20 or equal). Gage will then be pulled slowly outward, parallel to the test surface to determine compliance with the requirements of paragraph 3.3.6.2, 3.3.6.3, 3.3.6.4, and 3.3.6.5.

4.4.2 Reel (Drum) strength test. Dispenser shall be blocked to prevent forward movement. Pass tape 12 inches in length around reel and fasten both ends to a push pull gage of adequate capacity (Chatillon Model No. 719-20 or equal. Gage will be pulled slowly outward to determine compliance with 3.1.1.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Dispensers shall be preserved and packaged level A or C, as specified in the contract or order (see 6.2).

5.1.1 Level A. All uncoated and unpainted ferrous-metal surfaces shall be cleaned method C-1, thoroughly dried, and coated with P-7 type preservative in accordance with MIL-P-116. Preserved surfaces, subject to contact with packaging or packing materials, shall be covered or wrapped with greaseproof barrier material conforming to MIL-B-121, type II or III, grade A. The barrier material shall be secured in place with pressure-sensitive tape, minimum 2 inches in width, conforming to PPP-T-76. Dispensers, except type V, class 5 and type VI shall then be individually packaged in a fiberboard box conforming to PPP-B-636. When specified, the fiberboard box shall be constructed and sealed with tape

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

in accordance with V3c or V3s of PPP-B-636. The contents of each fiberboard box shall be adequately cushioned with fiberboard pads applied in a manner designed to prevent movement or damage while in transit or storage.

5.1.1.1 Type V, class 5 and type VI dispensers. Unless otherwise specified, type V, class 5 and type VI dispensers shall be packaged in quantities of 12 each in boxes conforming to PPP-B-566, PPP-B-665 or PPP-B-676.

5.1.2 Level C. Tape dispensers shall be packed in accordance with commercial practice.

5.2 Packing. Dispensers, packaged level A or C, shall be packed levels A, B, or C, as specified in the contract or order (see 6.2).

5.2.1 Level A. Dispensers, packaged as specified, shall be packed in overseas- type boxes conforming to any of the following: PPP-B-585, class 3; PPP-B-591; PPP-B-601; PPP-B-621; PPP-B-636; or MIL-B-10377. Gross weight of wood and wood-cleated boxes shall not exceed 200 pounds; of fiberboard boxes, 70 pounds. The bursting strength of fiberboard boxes shall be not less than 275 pounds. Box closures shall be in accordance with the appendix to the applicable specification. When specified, dispensers packaged in accordance with 5.1.1 shall require no overpacking.

5.2.3 Level C. Dispensers shall be packed in containers of the type, size and kind commonly used for the purpose, in a manner that will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply with the rules or regulations of carriers as applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking specified in the contract or order, each intermediate package and shipping container shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military requirements. In addition to any special marking required by the contract or order, all interior packages and shipping container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.

6.1.1 Type V.

6.1.1.1 Classes 2, 3, 4, and 5. Type V, classes 2, 3, 4, and 5 dispensers are intended for dispensing cellophane, acetate fiber, acetate, or paper tapes.

6.1.2 Type VI. Type VI dispensers are intended for dispensing cellulose pressure-sensitive tapes where predetermined measured lengths are not a factor.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type desired and class, if applicable (see 1.2).
(c) Whether three reels (drums) are required if type V, class 2 dispensers are ordered or two reels (drums) are required if type V class 3 dispensers oare ordered (see 3.3.1).

6.3 Former classification. Requirements for type I, II, III, IV, and type V, class have not been included in this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, and mail to: Gen. Services Admin., FSS (FMSO), Washington, D.C. 20406.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

GG-D-00458C(GSA-FSS) Dispenser, Pressure Sensitive Adhesive Tape

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

FORM GSA FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.