GG-D-459B
February 25, 1974
SUPERSEDING
Int. Fed. Spec. GG-D-00459A (GSA-FSS)
June 14, 1962

FEDERAL SPECIFICATION

DISPENSER, PRESSURE-SENSITIVE ADHESIVE TAPE (FOR FILAMENT-REINFORCED TAPE)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers metal or plastic manually-operated, pressure-sensitive adhesive tape dispensers for dispensing filament-reinforced tape, 1/4-inch to 1-inch wide, 3-inch inside diameter of core, 60-yard roll.

1.2 Classification.

1.2.1 Types.

Type I - Hand dispensers, metal, hand-operated.
Type II - Deleted (see 6.3).
Type III - Hand dispensers, plastic, hand-operated.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

L-P-1183 - Plastic Molding Material, Acrylonitrile-Butadiene-Styrene (ABS), Rigid.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Edged and Components.
PPP-B-676 - Boxes, Set-Up.
PPP-T-97 - Tape, Pressure-Sensitive Adhesive, Filament Reinforced.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information on the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:50Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The material of the body for type I dispensers shall be metal not less than 1/16-inch thick, cold-rolled steel. Type III dispensers shall be made of plastic material conforming to L-P-1183, type II or V. The blades shall be spring steel with a hardness of 89.0 to 90.5 Rockwell 15N Scale.

3.2 Design and construction.

3.2.1 Type I. Type I dispensers shall be sturdily constructed suitable for dispensing filament-reinforced pressure-sensitive adhesive tape. The tape cut-off shall be manual, using a serrated cutting blade.

3.2.2 Type III. Type III dispensers shall be constructed of a one-piece design and suitable for dispensing filament-reinforced pressure-sensitive adhesive tape. The tape cut-off shall be manual, using a serrated or plain cutting blade.

3.3 Capacity and performance. The dispensers shall accommodate a roll of tape with an outside diameter of up to 8 inches for the type I dispenser, and up to 6-1/2 inches for the type III dispenser. The tape shall dispense easily and shall not bind against any part of the dispenser. All dispensers, metal or plastic, shall provide a comfortable grip for the operator and be designed for ease of use. The dispensers shall provide for starting the tape by hand-pressure, sealing the tape by hand-pressure, and cutting off the tape with a serrated or plain cutting edge blade. The blade shall be replaceable with replacement blades available from manufacturer.

3.4 Finish. The type I dispenser shall be protected by plating, painting or equivalent finish. Exposed surfaces of the type III dispenser shall be smooth without sharp edges.

3.5 Color. The type III dispenser shall be any solid color representing the manufacturer's normal commercial production.

3.6 Identification marking. Each dispenser shall be permanently marked with the manufacturer's name or trademark.

3.7 Workmanship. Workmanship shall be first-class in every respect. Rivets, if used, shall be neatly set. All fasteners shall be firmly tightened so as to prevent their working loose under service conditions. All burrs and sharp edges shall be removed. The dispenser shall provide for ease in assembling the tape roll and ease in removing and cutting the tape. The dispenser shall be free from any defects that may affect its serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. A lot shall consist of all dispensers of the same type offered for inspection at one time.

4.2.2 Sampling of end item for visual examination. A random sample of dispensers shall be taken from each lot in accordance with MIL-STD-105, inspection level S-3. The acceptable quality level (AQL) shall not exceed 4.0 percent defective. The sample unit shall be one dispenser.

4.2.3 Sampling of end item tests. Random sample of dispensers for each test shall be taken from each lot in accordance with MIL-STD-105, inspection level S-3. The acceptable quality level (AQL) shall not exceed 4.0 percent defective. The sample unit shall be one dispenser.

4.3 Visual examination of end item. Dispenser samples selected in accordance with 4.2.2 shall be examined for the defects listed in table I. Any sample containing one or more defects shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

TABLE I.

Defects	Applicable Paragraph
Material not as specified	3.1
Construction not as specified	3.2
Finish	3.4
Identification marking missing	3.6
Workmanship	3.7

4.4 Tests.

4.4.1 Capacity and performance. A 60-yard roll of filament-reinforced pressure-sensitive adhesive tape, approximately 8 inches outside diameter and 1-inch wide, shall be inserted in the type I dispenser, or a roll 6-1/2 inches outside diameter and 1-inch wide shall be inserted in the type III dispenser. Various lengths of tape shall be applied around the corner of a box by manually dispensing each piece of tape, applying pressure as the tape is withdrawn from the dispenser, and cutting off the tape. A minimum of six lengths of tape shall be dispensed to determine ease of operation (see 3.3). Tape used for the test shall conform to PPP-T-97.

4.5 Inspection of preparation for delivery. An inspection shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table II. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be III and the acceptable quality level (AQL) shall be 6.5 defects expressed in defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect; illegible; or improper size, location; sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps; loose strapping, inadequate stapling; bulging or distortion of container.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B or C, as specified (see 6.2).

5.1.1 Level A or B. Each dispenser shall be packaged in a box conforming to PPP-B-566 or PPP-B-676. Cushioning material shall be utilized to prevent damage to the item during handling, shipment and storage.

5.1.2 Level C. Each dispenser shall be packaged to afford adequate protection against damage during known favorable conditions of shipment and storage from the supply source to the receiving activity. The supplier may use his standard practice when it meets this requirement.

5.1.3 Intermediate packaging. Ten packaged dispensers, of one type only, shall be intermediate packaged in a box conforming to PPP-B-566, PPP-B-665, PPP-B-676 or PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A. Dispensers, of one type only, shall be packed in a box conforming to PPP-B-636, class weather-resistant. The box shall be waterproof sealed and reinforced with bands of filament tape in accordance with the appendix to the box specification.

5.2.2 Level B. Six intermediate packages shall be packed in a box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.3 Level C. The box shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking. In addition to any special marking specified in the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable.

6. NOTES

6.1 Intended use. The intended use of each type dispenser covered by this specification is the hand application of filament-reinforced pressure-sensitive tape which is used to reinforce shipping containers in lieu of using steel strapping where the volume of work does not justify special automatic machinery.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of dispenser required (see 1.2).
(c) Level of packaging and packing (see 5.1 and 5.2).

6.3 Former classification. Requirements for type II of GG-D-00459A have been deleted by this revision.

MILITARY INTEREST:

Military coordinating activity:

Army - GL

Participating activities:

Navy - SA
Air Force - 84

DOD WAIVED COORDINATION

Preparing activity:

GSA-FSS

U. S. GOVERNMENT PRINTING OFFICE : 1974 O - 544-607/1541

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:50Z
Check the source to verify that this is the current version before use.