GG-I-550B
October 11, 1974
SUPERSEDING
Fed. Spec. GG-I-550a
November 30, 1960

FEDERAL SPECIFICATION

INKING PAD, OFFICE TYPE NUMBERING MACHINE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers uninked felt inking pads used in office-type numbering machines.

1.2 Classification.

1.2.1 Type and sizes. Pads covered by this specification shall be of one type and of the sizes shown in figures 1 and 2, as specified (see 3.6, 6.1, and 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-665 - Boxes: Paperboard, Metal Edged and Components.
PPP-B-676 - Boxes, Set-Up.
PPP-T-97 - Tape; Pressure-Sensitive Adhesive, Filament Reinforced.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).
Fed. Std. No. 191 - Textile Test Methods.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-P-116 - Preservation, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:51Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.

3. REQUIREMENTS

3.1 Material. The felt used for the pads shall be preshrunk, firmly felted, and uniform in appearance and structure.


3.2 Color. Pads shall be white in color.

3.3 Fiber content. Fiber content shall be not less than 95 percent virgin wool when tested as described in 4.5.2.1.1.

3.4 Weight. The weight of the felt shall be 32 ounces based upon a sheet 20 by 20 by 1/4 inches when weighed as described in 4.5.2.1.2. A tolerance of plus or minus 3 percent will be permitted.

3.5 Ash. The ash content shall be not more than 1.5 percent when tested as described in 4.5.2.1.3.

3.6 Dimensions. Dimensions of the inking pads shall be as indicated in figures 1 and 2 for the respective sizes (see 1.2.1). Unless otherwise indicated, commercial tolerance shall be held.




TOP VIEW




END VIEW

Size No.	Dimensions (Inches) A	B	C
1	1.094	0.406	0.250
2	1.250+.030 −.000	.406	.219
3	1.375	.468±.005	.234±.015
4	1.562	.468	.312
5	1.094	.469	.250

FIGURE 1



TOP VIEW



END VIEW

Size No.	Dimensions (Inches) A	B	C	D
6	1.437+.031 −.000	0.445	0.281	0.375

FIGURE 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

3.7 Workmanship. Inking pads shall have smooth surfaces, be symmetrically cut and be free from any defects which will affect appearance or serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection of preparation for delivery. An inspection shall be made to determine whether the preservation, packaging, packing, and marking comply with the requirements of section 5 of this specification. Defects shall be scored in accordance with table I. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

TABLE I. Classification of preparation for delivery defects.

Examine	Defects
Marking	Omitted; incorrect; illegible; improper size, location, sequence, or method of application
Material	Any component missing or damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, inadequate stapling,or distortion of container.
Contents	Quantity per container is more or less than specified. Gross weight exceeds requirements of the box specification.

4.2 Lot. All inking pads of the same size presented at one time for delivery shall be considered a lot for purposes of inspection and tests.

4.3 Sampling.

4.3.1 For examination. The samples shall be taken in accordance with MIL-STD-105.

4.3.2 For tests. Sufficient felt shall be taken to perform the tests specified in 4.5.2.1.

4.4 Examination. Each of the sample pads taken shall be visually and dimensionally examined to verify compliance with the requirements of this specification. Acceptable Quality Level (AQL) shall be 2.5 percent defective in accordance with MIL-STD-105.

4.5 Tests.

4.5.1 Certification. The following tests may be waived provided a certified mill report indicates that the felt is acceptable with respect to physical and chemical properties. (See 3.3, 3.4, and 3.5).

4.5.2 Acceptance tests. The sample felt taken in accordance with 4.3.2 shall be subjected to the following tests. Failure of any sample to meet the test requirements shall be cause for rejection of the lot.

4.5.2.1 Test procedures.

4.5.2.1.1 Fiber content. The fiber content shall be based on the wool content of the finished material as determined by method 2101 of Fed. Test Method Std. No. 191.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:51Z
Check the source to verify that this is the currentversion before use.

4.5.2.1.2 Weight. A felt sample shall be measured, placed in a weighing-bottle and dried in an oven at a temperature of 105 to 110 degrees C. (221 to 230 degrees F.) to constant weight (plus or minus 0.001 gram), cooled in a desiccator, and weighed.

4.5.2.1.3 Ash. Approximately 3 grams of the material shall be cut into pieces approximately 1/8 inch square, dried to a constant weight at 105 to 110 degrees C. (221 to 230 degrees F.) and allowed to cool in a desiccator. A 2-gram portion of the dried specimen shall be weighed quickly in a tared crucible. The crucible shall be placed in a muffle furnace and the temperature raised slowly to 800 to 1000 degrees C. (1472 to 1832 degrees F.), care being taken to avoid loss of ash by quick ignition, or by subjecting the specimen to strong drafts. When all the organic matter has been burned off, the crucible shall be placed in a desiccator, cooled, and weighed. The ignition and subsequent cooling in a desiccator shall be repeated to constant weight. The ash shall be reported as a percentage of the weight of the oven-dried material.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packaging. Twelve inking pads shall be packaged in accordance with MIL-P-116, method 1-C.

5.1.1.2 Intermediate packaging. Twelve unit packages (144 pads) shall be packed in a close-fitting box conforming to PPP-B-566, PPP-B-665, PPP-B-676 or to PPP-B-636. Closure of boxes shall be in accordance with the applicable box specification or appendix thereto.

5.1.2 Level B.

5.1.2.1 Unit packaging. Twelve inking pads shall be packaged in accordance with MIL-P-116, method III.

5.1.2.2 Intermediate packaging. Twelve unit packages (144 pads) shall be packed in a close-fitting box conforming to PPP-B-566, PPP-B-665, PPP-B-676 or to PPP-B-636. Closure of boxes shall be in accordance with the applicable box specification or appendix thereto.

5.1.3 Level C. The stamp pads shall be packaged to insure protection during shipment and safe delivery to destination.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Twelve intermediate packages (1728 pads) as described in 5.1 shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant, grade V3c minimum. Closure and waterproof sealing of the boxes shall be in accordance with the appendix to PPP-B-636. In lieu of steel strapping, boxes shall be reinforced with tape conforming to PPP-T-97, type IV, applied in accordance with the appendix thereto.

5.2.2 Level B. Twelve intermediate packages (1728 pads) as described in 5.1 shall be packed in a close-fitting box conforming to PPP-B-636, class-domestic. Closure of boxes shall be in accordance with method II of the appendix to PPP-B-636.

5.2.3 Level C. Stamp pads packaged as specified in 5.1 shall be packed to comply with the National Motor Freight Classification rules or the Uniform Freight Classification rules.

5.3 Marking. In addition to any special marking required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. Marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Inking pads covered by this specification are intended for use as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

Size No.	Numbering Machine
1	Roberts Nos. 37, 47, 48, 49, 50, and 64.
2	Bates, Jr.
3	American Visible, Models 21, 41, 71, and 5 in 1 Machines Models 110 and 111.
4	Roberts Nos. 90, 95, and 190.
5	Ajax Business Machine Model 150.
6	Bates Regular Models.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, (see 5.1.3, and 5.2.3) and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Size number required (see 3.6 and 6.1).
(c) Levels of packaging and packing required (see 5.1 and 5.2).
(d) Marking required (see 5.3).

6.3 Military standards. Items procured under this specification for military use are to be limited to the variety shown on the applicable military standards. Personnel of the military departments are requested to refer to these documents for guidance.

6.4 It is believed that this specification adequately describes the characteristics necessary to secure the desired material, and that normally no samples will be necessary prior to award to determine compliance with this specification. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids and the particular purpose to be served by the bid sample should be definitely stated, the specification to apply in all other respects.

COORDINATION WAIVED BY DOD

Preparing Activity:

GSA - FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specificat ion to obtain extra copies and other documents reference herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.