GG-M-565C
April 6, 1973
SUPERSEDING
Int. Fed. Spec. GG-M-00565B (GSA-FSS)
July 2, 1969 and
Fed. Spec. GG-M-565
December 15, 1955

FEDERAL SPECIFICATION

MOISTENERS, PAPER SEALING, WELL TYPE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers well-type paper sealing moisteners.

1.2 Classification. Moisteners covered by this specification shall be of the following types, as specified (see 6.2 and 6.3).

Type I. Brush (Nonadjustable).

Type II. Roller.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

UU-L-49 - Labels, Paper; Gummed (Water-Activated).
UU-P-121 - Paper, Bond and Writing, White and Colored.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-B-665 - Boxes: Paperboard, Metal Edged and Components.
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-P-116 - Preservation, Method of.
MIL-L-10547- Liners, Case, and Sheet, Overwrap, Water-vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by supplier in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bid or request for proposal shall apply.

National Motor Freight Traffic Association, Incorporated, Agent:

National Motor Freight Classification .

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street N. W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 Porcelain. Porcelain shall be uniformly glazed, except for the bottom of the cup, and one side of the roller for a distance of not more than 1/2 inch from the axle housing. The glaze shall be free from crazing, cracks, chips, and bare spots.

3.1.2 Metals. The cover with guide arm, and the brush ferrule for the type I moistener shall be fabricated from aluminum alloy, or corrosion-resisting steel. The cup of the type I moistener shall be fabricated from wrought aluminum alloy, corrosion-resisting steel, or shall be aluminum or zinc-base die casting. Corrosion-resisting steel shall be AISI 302, 304, or 430 types. Unless otherwise specified (see 6.2), the roller axle for the type II moistener shall be of any aluminum or copper zinc alloy.

3.1.2.1 Thickness. Thickness of cast parts shall be not less than 0.10 inch, and thickness of the brush ferrule shall be not less than 0.015 inch. Thickness of metals other than casting and brush

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

ferrule shall be not less than 0.025 inch. The diameter of the roller axle for the type II moistener shall be of sufficient thickness to support the roller and in accordance with commercial practice.

3.1.2.2 Finish. Finish of corrosion-resisting steel shall be No. 4 - general purpose polished finish, or No. 6 - dull satin finish. Finish of aluminum or zinc-base die casting shall be baked-on enamel. Unless otherwise specified (see 6.2), color of the enamel shall be gray. The hue, value, and chroma of the color shall be at the manufacturer's option, and in accordance with good commercial practice.

3.1.3 Brush filler. The brush filler for type I moistener shall be composed of at least 50 percent by weight of natural color hog bristle and the remainder natural color horsehair or other animal hair or bristle of similar character. Filler material shall be straightened and sterilized by a commercial accepted method and shall weigh 1/2 ounces, plus or minus 1/16 ounces when tested under standard textile testing conditions (see 4.1.1).

3.2 Design and Construction.

3.2.1 Type I. Type I moistener shall be of the nonadjustable (stationary) brush type. Moistener shall be sturdily constructed and suitable for the purpose intended. The moistener shall consist of a cup (water reservoir), brush unit, and a cover (lid) with guide arm. Moistener shall be constructed to permit the brush to extend within the cup containing water, and water shall be drawn up to the top of the brush by capillary action to moisten envelope flaps, gummed labels, and similar items requiring water for sealing purposes. Moistener shall be equipped with rubber, cork, or felt feet or base to prevent marring of furniture. When tested in accordance with 4.4.1, a sufficient amount of water shall be transferred to the labels for the labels to adhere and remain firmly fixed to the paper.

3.2.1.1 Cup. The cup shall be made of metal specified in 3.1.2. The cup shall have an inside length to accommodate the brush unit width, and shall have an inside depth to accommodate the brush unit length when the brush unit is positioned in the cup at not more than a 45-degree angle from the vertical. The cup shall have an inside width at the top of not less than 2-1/4 inches. The brush unit shall be supported at one height.

3.2.1.2 Brush unit. The filler material shall have a chiseled trim by cupping, forming or by machine chiseling. The filler shall be 70 percent top size with no more than 5 percent shorts (1 inch or less) (see 4.1.1). The filler extending out of the ferrule shall be 1-3/4 inches with a minus tolerance of 1/8 inch, and shall extend 3/8 inch, with a minus tolerance of 1/16 inch, from the edge of the guide arm. The over-all dimensions of the brush shall be not less than 2-7/8 inches wide and 5/16 inch thick at the top of the ferrule, and 2-1/4 inches long. Unless otherwise specified, the brush filler shall be set in pure rubber, synthetic rubber, or thermosetting resin base, and secured with a ferrule fabricated from metal specified in 3.1.2. The ferrule shall be not less than 1/2 inch wide, and shall be interlocked and soldered, lock-seamed and punched, soldered, welded, or held together with a minimum of three metal rivets.

3.2.1.2.1 Replacement brushes. Replacement brushes shall be furnished as specified in invitation for bids, contract or order (see 6.2).

3.2.1.3 Cover and guide arm. The cover and guide arm shall be made of metal specified in 3.1.2. The cover shall encompass the top of the cup, except for the exposed brush filler, and shall clip or snap on the cup (3.2.1.1). The guide arm shall be not less than 7/8 inch wide, and of sufficient length to equal the width of the exposed brush unit. The guide arm shall be constructed to guide items to be moistened for contact with the exposed brush area.

3.2.2 Type II. The type II moistener shall be of the roller type, sturdily constructed and suitable for the purpose intended. The moistener shall consist of a cup (water reservoir), and roller with a stationary (permanently affixed) axle. The moistener shall be constructed to permit the roller, on the roller axle, to revolve within the cup containing water, and water shall be drawn to the top of the roller for moistening envelope flaps, gummed labels, and similar items requiring water for sealing purposes. The moistener shall be equipped with rubber, cork, or felt feet or base to prevent marring of furniture. When tested in accordance with 4.4.1, a sufficient amount of water shall be transferred to the labels for the labels to adhere and remain firmly fixed to the paper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

3.2.2.1 Cup. The cup shall be made of porcelain specified in 3.1.1, and shall be of a size to accommodate the roller specified in 3.2.2.2. The cup shall have two recessed grooves to receive the roller axle, one centered on each side of the cup, with a depth equal to more than one-half the diameter of the roller axle ends (see 3.2.2.2).

3.2.2.2 Roller. The roller shall be made of porcelain specified in 3.1.1. The roller shall be 2 inches wide ± 1/8 inch, and 2-7/8 inches in diameter ± 1/8 inch. The roller shall be equipped with a fixed axle as related to the roller, and shall be secured within the roller by press-fit, or use of metal bushing(s) or shim(s). Soluble bushing or shim material is not acceptable. The ends of the roller axle shall be designed to fit the recessed grooves of the cup, and permit the roller to revolve freely.

3.3 Workmanship. The moisteners shall be free from any defects which affect serviceability or appearance.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and service conform to prescribed requirements.

4.1.1 Certification of compliance, type I brush. In accordance with 4.1, a certification of compliance shall be furnished by the contractor, accomplished by actual test and inspection report or other verifiable data, stating that the identification, sterilization, and weight of the brush filler conform to the requirements as specified in 3.1.3, and that the percent top size and shorts of the filler material in the brush unit conform to the requirements as specified in 3.2.1.2.

4.2 Sampling.

4.2.1 Lot. A lot shall consist of all moisteners of the same type and class offered for inspection at one time.

4.2.2 Sampling of end item for visual examination. A random sample of moisteners shall be taken from each lot in accordance with MIL-STD-105, inspection level S-4. The acceptable quality level (AQL) shall not exceed 4.0 percent defective. The sample unit shall be one moistener.

4.2.3 Sampling for preparation for delivery requirements. For examination of interior packaging the sample unit shallbe one shipping container fully prepared for delivery, selected at random just prior to the closing operation. Sampling shall be in accordance with MIL-STD-105. Closure defects shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

4.2.4 Sampling for test. A random sample of moisteners shall be taken from each lot in accordance with MIL-STD-105, inspection level S-1. The AQL shall not exceed 4.0 percent defective. The sample unit shall be one moistener.

4.3 Examination.

4.3.1 Visual examination of end item. Samples taken in accordance with 4.2.2 shall be examined for defects listed in table I. Any sample containing one or more defects shall be rejected. The Government reserves the right to classify as a defect any departurefrom the specifications not listed in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of moistener defects

Examine	Defect
GENERAL	Not type specified (1.2).
MATERIAL	
Type I	Not as specified (3.1.2). Not of thickness specified (3.1.2.1). Finish not as specified (3.1.2.2).
Type II	Not glazed as specified (3.1.1). Not free from crazing, cracks, chips, or bare spots (3.1.1). Unless alternate material specified, axle not aluminum or copper zinc alloy (3.1.2).
DESIGN AND CONSTRUCTION	
Type I	Brush not stationary (3.2.1). Not equipped with rubber, cork, or felt feet or base (3.2.1). Cup, including dimensions, not as specified (3.2.1.1). Brush unit, including dimensions, not as specified (3.2.1.2). Cover and guide arm, including dimensions, not as specified (3.2.1.3).
Type II	Not equipped with rubber, cork, or felt feet or base (3.2.2). Cup not of sufficient size to accommodate the roller (3.2.2.1). Cup does not have recessed grooves to receive the roller with axle (3.2.2.1). Recessed grooves of the cup do not equal more than one-half the diameter of the roller axle ends (3.2.2.1). Roller, including dimensions, not as specified (3.2.2.2). Roller axle not stationary, or not secured within the roller as specified (3.2.2.2).
WORKMANSHIP	Any defects which would affect serviceability or appearance (3.3).

4.3.2 Examination of preparation for delivery. Samples selected in accordance with 4.2.3 shall be examined to determine that the preservation, packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table II.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Material	Any component missing or damaged.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of preparation for delivery defects (continued)

Examine	Defects
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling, or distortion of container.
Contents	Number per container is more or less than required. Net weight exceeds requirements of the box specification.

4.4 Test. Sample moisteners selected in accordance with 4.2.4 shall be subjected to the following tests.

4.4.1 Moistening performance test. Labels used in this test shall conform to class A, Styles 2 or 4, of UU-L-49. Bond paper used in this test shall conform to type III of UU-P-121. The test shall be made as follows: Fill cup (water reservoir) two-thirds full or until roller or base end of brush is below level of water. Rotate roller several turns to moisten entire surface of the roller, or allow brush-type moistener to stand untouched for 30 minutes. Moisten five labels by applying gummed side against moistening surface of roller or brush, and then press labels against bond paper. Examine paper with labels for conformance with 3.2.1 or 3.2.2, as applicable.

5. PREPARATION FOR DELIVERY.

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Type I Moisteners. The moisteners shall be individually packaged in close-fitting box conforming to PPP-B-636, class weather-resistant, style optional; PPP-B-566, PPP-B-665, or PPP-B-676. Boxes conforming to PPP-B-636 shall be closed in accordance with the appendix therein. All other type boxes shall be waterproof sealed in accordance with MIL-P-116, method IC-2.

5.1.1.2 Type II Moisteners. The moisteners shall be individually packaged in close-fitting boxes conforming to PPP-B-636, class weather-resistant, style optional. Sufficient blocking and bracing shall be utilized between the water reservoir and the removable roller to prevent damage. Boxes shall be closed in accordance with the appendix to PPP-B-636.

5.1.1.3 Replacement Brushes for Type I Moisteners. Twelve brushes shall be packaged in a close-fitting box conforming to PPP-B-636, class weather-resistant, style optional. Boxes shall be closed in accordance with the appendix to PPP-B-636.

5.1.2 Level B.

5.1.2.1 Type I and II Moisteners. The moisteners shall be individually packaged in close-fitting boxes conforming to PPP-B-636, class domestic, style optional. Sufficient blocking and bracing shall be utilized with the type II moisteners between the reservoir and the removable roller to prevent damage. Boxes shall be closed in accordance with the appendix to PPP-B-636.

5.1.2.2 Replacement Brushes for Type I Moisteners. Twelve brushes shall be packaged in a close-fitting box conforming to PPP-B-636, class domestic, style optional. Boxes shall be closed in accordance with the appendix to PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

5.1.3 Level C. The moisteners and replacement brushes shall be packaged to insure protection during shipment and safe delivery to destination.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Moisteners packaged as specified in 5.1 and in the quantities specified (see 6.2), shall be packed in a close-fitting box conforming to any of the following:

PPP-B-585	Class 3
PPP-B-591	Class 1
PPP-B-601	Overseas type
PPP-B-621	Class 2
PPP-B-636	Class weather-resistant
PPP-B-640	Class 2

The gross weight of the wood boxes shall not exceed 200 pounds. The gross weight of the fiberboard boxes shall be subject to the weight limitations of the box specification. Each wooden box shall be provided with a sealed case liner conforming to MIL-L-10547. The fiberboard boxes shall be closed in accordance with the applicable specification or appendix thereto.

5.2.2 Level B. Twenty four unit packages of moisteners of like type or replacement brushes packaged as specified in 5.1 shall be packed in a close-fitting box conforming to PPP-B-636, class domestic, grade 275 minimum. Boxes shall be closed in accordance with method II of appendix to PPP-B-636.

5.2.3 Level C. The moisteners packaged as specified in 5.1, shall be packed to comply with the Uniform Freight Classification rules or the National Motor Freight Classification rules, as applicable.

5.3 Marking. In addition to any special markings required by the contract or order, all marking shall be in accordance with 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil Agencies. All marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military Agencies. All marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The moisteners are intended for use in moistening tape, envelope flaps, gummed labels, and other items requiring water for sealing purposes.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type of moistener required (see 1.2).
(c) Specify material when the roller axle for type II moistener can be other than aluminum or copper zinc alloy (3.1.2).
(d) Color of the type I moistener, if other than gray is desired (see 3.1.2.2).
(e) Replacement brushes, if required (see 3.2.1.2.1).
(f) Levels of packaging and packing and any special marking for shipment required (see 5.1, 5.2, and 5.3).
(g) Quantities required under Level A packing (see 5.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.

6.3 Cross reference data. Cross reference of classification changes between this specification and the preceding Interim Specification GG-M-00565B (GSA-FSS) dated July 2, 1969, and Federal Specification GG-M-565 dated December 15, 1955, are as follows:

GG-M-00565B/GG-M-565	GG-M-565C
Type I. Brush	Type I Brush (Nonadjustable).
Class 1. Nonadjustable.	None.
Class 2. Adjustable.	None.
Type II. Roller	Type II. Roller.

DOD WAIVED COORDINATION

User Interest:

Army-GL

Preparing activity:

GSA-FSS

U. S. GOVERNMENT PRINTING OFFICE : 1973 O - 514-179 (493)

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:51Z
Check the source to verify that this is the current version before use.