MILITARY SPECIFICATION SHEET

ELECTRON TUBE, GAS

TYPE 4B32

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Rectifier, half-wave

See figure 1

Mounting position: Any

Weight: 7.5-ounces (212.6 grams) nominal

ABSOLUTE RATINGS:

Parameter:	Ef	epx	ib	Io	TA	tk	F
Unit:	Vac	kv	a	Adc	°C	sec	Hz
Maximum:	5.25	10	5	1.25	70	---	150
Minimum:	4.75	---	---	---	-55	30	---
TEST CONDITIONS:	5.0	12	---	---	---	30	60

GENERAL:

Qualification - Required

Ⓑ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:49Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1								
1231	Peak emission	-	ib = 10 a	0.65	II	etd	---	16.0	v
1353	Operation of rectifiers	1	Io = 1.25 Adc (min); t = 120 sec (min)	0.65	II	---	---	---	---
1301	Filament current	-		0.65	II	If	6.25	8.00	Aac
	Quality conformance inspection, part 2								
(3) 1041	Shock	-	Accel = 30 G, 11 ±2 ms	---	---	---	---	---	---
	Quality conformance inspection, part 3								
---	Life test	-	Group D; Io = 125 Adc; epx = 10 kv; ib = 5.0 a; t = 500 hours	---	---	---	---	---	---
---	Life-test end point:								
1231	Peak emission	-		---	---	etd	---	20.0	v

NOTE:

1. This test shall be the first test performed at the conclusion of the holding period.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force -17, 80
DSA - ES


User activities:
Army - MU
Navy - AS, OS, MC, CG, SH
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5960-2943)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:49Z
Check the source to verify that this is the current version before use.



PIN CONNECTIONS	
Pin No.	Element
1	nc
2	f
3	nc
4	f
cap	a

Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
Quality conformance inspection, part 2		
A	7.600 (193.04)	8.500 (215.90)
B		2.320 (58.93)
(B) Quality conformance inspection, part 3 (see note)		
C	Cap: C1-5 (EIA)	
D	Base: A4-29 (EIA)	

NOTE:
This test shall be performed during the initial production and once each succeeding 12-calendar months in which there is production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of two. In the event of failure, the test will be made as a part of quality conformance inspection, part 2, code level D, with an AQL of 6.5. The regular "12-calendar month" double sampling plan shall be reinstated after three consecutive samples have been accepted.

FIGURE 1. Outline drawing of electron tube type 4B32.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:49Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:49Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 202610-15T13:49Z
Check the source to verify that this is the current version before use.