MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6197

This amendment forms a part of Military Specification Sheet MIL-E-1/904D, dated 7 February 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 3

Periodic-check test: Delete "Periodic check test" title heading.

Quality conformance inspection, part 3, Method 1031, Low-frequency vibration, under NOTES column: Add "10".

Page 4

Add new note 10 as follows:

"10. This test shall be performed during the initial production and once each succeeding 12-calendar months in which there is production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of one. In the event of failure, the test will be made as a part of quality conformance inspection, part 2, code level D, with an AQL of 6.5. The regular "12-calendar month" double sampling plan shall be reinstated after three consecutive samples have been accepted."

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - MI
Air Force - 99
DSA - ES

User activities:
Army - ME, WC, AV
Navy - AS, OS, MC, CG
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5960-3051)

☆U.S. GOVERNMENT PRINTING OFFICE: 1977—703-122/6556

Source: https://assist.dla.mil -- Downloaded: 202640-15T13:50Z
Check the source to verify that this is the current version before use.