MIL-E-1/959D
AMENDMENT 2
15 November 1978
SUPERSEDING
AMENDMENT 1
24 September 1976

MILITARY SPECIFICATION SHEET

ELECTRON TUBE, POWER

TYPE 576A

This amendment forms a part of Military Specification Sheet MIL-E-1/959D, dated 1 August 1975, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Quality conformance inspection, part 2, Method 1041, Shock, under Conditions column: Delete "Angle = 20°" and substitute "Accel = 30 G, 11 ±2 ms."

PAGE 4

* FIGURE 1, Dimension "E" under Minimum column: Delete ".370(9.40)" and substitute ".355(9.02)"; under Maximum column, delete ".380(9.65)" and substitute ".365(9.27)".

* NOTE: The margin of this amendment is marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 99, 17
DLA - ES

User activities:
Army - AR
Navy - AS, OS, MC, CG
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5960-3190)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:54Z
Check the source to verify that this is the current version before use.