MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6AU6WC

This amendment forms a part of Military Specification MIL-E-1/952G dated 17 February 1981, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Quality conformance inspection, part 3, method 1501, Intermittent life, Conditions column: Delete "TA = room", "(see note 9)", and "Group E" and substitute "(see notes 8 and 10)".

PAGE 4

Quality conformance inspection, part 3, method 1511, Cathode interface life, Conditions column: Add "(see note 10)".

PAGE 5

Add new note 10 as follows:

"10. The life-test sample shall consist of 20 tubes per lot and not more than 1 tube failure shall be permitted. In the event of rejection of the first sample due to failure of more than 1 tube, a second sample of 40 tubes shall be selected from the lot. Acceptance shall then be based on the combined first and second samples, and shall not exceed a total of three tube failures."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

User activities:
Army - AR, ME
Navy - AS, OS, MC, CG
Air Force - 11

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5960-3273)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T13:54Z
Check the source to verify that this is the current version before use.