MIL-C-14700A(PA)
Amendment 2
18 September 1975
SUPERSEDING
Amendment 1
11 April 1975

MILITARY SPECIFICATION

CHARGE, PROPELLING, M80 FOR 8 INCH
HOWITZER, M2 CANNON

This amendment forms a part of Military Specification MIL-C-14700A(PA), dated 20 November 1974 and is approved for use by all Departments and Agencies of the Department of Defense.

P. 3 - Para 3.7 - After "Proving ground", add the following:

The propelling charge, when fired with the M424 projectile shall comply with the following requirements when tested as specified in 4.5.4. The MK25 projectile may be used in lieu of the M424 when the MK25 is adjusted to a standard weight of 242 pounds, including fuze and must be inert.

P. 4 - Change Para 3.10.6 to Para 3.11: Change Para 3.11 to Para 3.12

P. 11 - Para 4.4.2.3, Major B Defect 131, Requirements Paragraph Column - Change 3.10.6 to 3.11

P. 12 - Para 4.4.2.4, Major B Defect 131, Requirement Paragraph Column - Change 3.10.6 to 3.11

P. 12 - Para 4.4.2.4, Major B Defect 134 - Delete "Weight of propellant correct" and substitute "Propellant correctly weighed and check weighed;" AQL or 100% Column, delete "Table II" and substitute "100%"

P. 13 - Para 4.4.2.5, Major B Defect 136 - Delete "Weight of propellant correct" and substitute "Propellant correctly weighed and check weighed"; AQL or 100% column, delete "Table II" and substitute "100%"

P. 17 - Para 4.5.4 - Delete entire paragraph and substitute:
Proving ground (see 3.7) - These tests shall be conducted at a Government Proving Ground in accordance with applicable proving ground acceptance test procedures. The sample charges shall be fired in an 8 Inch Howitzer, M2 Cannon, for which the charge is standard and observation shall be made for conformance to all applicable requirements. The charges shall be conditioned at 70 degrees fahrenheit

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:36Z
Check the source to verify that this is the current version before use.

± 5 degrees for 24 hours and fired at Zone 3 using M424 projectiles of the standard weight zone and dummy fuzes. When the MK25 projectile is used as a substitute for the M424, using the specified weight, it shall be conditioned at 70 degrees fahrenheit ± 5 degrees for 24 hours and fired at Zone 3.

Custodian
Army-PA

Preparing Activity
Army-PA

Project No. 1110-A052

☆ U.S. GOVERNMENT PRINTING OFFICE: 1976—603-766/4235

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:36Z
Check the source to verify that this is the current version before use.