MILITARY SPECIFICATION

FUZE, TIME, M84A1
METAL PARTS FOR

This amendment forms a part of Military Specification MIL-F-14715A (MU), dated 22 March 1971, and is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 12

4.3.2.11, add Majors 51 and 52 as follows:

"Major: 100 Percent Inspection
"51 Distance between ends of power groove...Gage...11051
52 True position of end of groove...Gage...11052"

Major 107, delete in its entirety and substitute:

"107 True position of outside diameter slot...Gage...11007"

Add Major 110 as follows:

"110 Presence of more than one keyway...Visual...11010"

Minor 206, delete in its entirety.

PAGE 13

4.3.2.12, Major 106, delete "Visual" and substitute "Gage"

PAGE 14

4.3.2.15, Minor 206, delete "Gage" and substitute "Visual"

4.3.2.16, Major 101, change "Location of guide projections with outside diameter" to "True position of outside diameter"

Add Major 103 as follows:

"103 True position of guide projections...Gage...16012"

AMSC N/A FSC 1390

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:37Z
Check the source to verify that this is the current version before use.

PAGE 16

4.3.3.3, AQL, delete "0.65 percent" and substitute "0.065 percent"

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A575)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:37Z
Check the source to verify that this is the current version before use.