MIL-F-14716A (AR)
AMENDMENT 2
16 June 1982
SUPERSEDING
AMENDMENT 1
9 June 1978

MILITARY SPECIFICATION

FUZE. TIME, M84A1
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-14716A (MU), dated 22 March 1971, and is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Specifications, Purchase Description-Delete in its entirety.

Specifications, Military-add the following:

MIL-T-48140 - Tungsten Powder (for Pyrotechnics)
MIL-C-48181 - Delay, Tungsten, Composition

PAGE 2

Drawings, Army, Delete and substitute:

"9232784 - Fuze, Time, M84A1
8865235 - Box, Fiber, Ammunition for Fuze, Time, M84 and M84A1 (Inner)
8865236 - Box, Fiber, Ammunition for Fuze, Time, M84 and M84A1 (Outer)
9275135 - Box, Packing, Ammunition for Fuze, Time, M84 or M84A1"

PAGE 13

* 4.2.2.11, delete major 101 and substitute major 101 as follows:

"101. Minimum breakaway torque when removing head ass'y (9205588) from body ass'y (9232789) shall not be less than 90 inch lb's test/gage 11003".

PAGE 14

Paragraph 4.2.2.13, Add "and dwg. 9275135".

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:37Z
Check the source to verify that this is the current version before use.

PAGE 17

Paragraph 4.2.3.8, Delete and substitute: "Torque on Adjustment Ring, Major defect, Code No. 11012 (see dwg. 9232784). The maximum torque (either breakaway or turning) at assembly necessary to turn the adjustment ring shall comply with the applicable requirement (65 to 90 inch-pounds). Inspection shall be 100% using test equipment in accordance with 4.2.4."

PAGE 18

Paragraph 4.3.3, Delete and substitute sentence three as follows: The torque applied to the test head adapter to seat the fuze rings shall be such that the maximum torque (either breakaway or turning) necessary to turn the adjustment ring shall be (65 inch-pounds (min.) to 90 inch-pounds (max).

PAGE 19

Paragraph 5.1.1, Add "and Level C:

Paragraph 4.2.1, Delete dwg. 8865236 and substitute dwg "9275135".

Add "5.2.2 Level C - The fiber container shall be packed as specified on dwg. 8865236".

Paragraph 5.3, Add "and 9275135".

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
ARMY-AR

Preparing activity:
ARMY-AR

(Project 1390-A351)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:37Z
Check the source to verify that this is the current version before use.