MILITARY SPECIFICATION

# RELAYS, HYBRID, ESTABLISHED RELIABILITY, GENERAL SPECIFICATION FOR

This supplement forms a part of
MIL-R-28776C, dated 18 July 1994.

## SPECIFICATION SHEETS

| | | |
|---|---|---|
| MIL-R-28776/1 | - | Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere (Transistor Driven) (Electromechanical Output). |
| MIL-R-28776/3 | - | Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere (Sensitive, Coil Operate Power at 25°C) (Transistor Driven) (Electromechanical Output) With Diode Coil Suppression. |
| MIL-R-28776/4 | - | Relays, Hybrid, Established Reliability, SPDT, Low Level to 1.0 Ampere (Sensitive, Coil Operate Power at 25°C) (Transistor Driven) (Electromechanical Output) With Diode Coil Suppression. |
| MIL-R-28776/5 | - | Relays, Hybrid, Established Reliability, SPDT, Low Level to 1.0 Ampere (Transistor Driven) (Electromechanical Output) With Diode Coil Suppression. |
| MIL-R-28776/6 | - | Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere, Internal MOSFET Drive With Zener Diode Gate Protection, (Electromechanical Output), Diode Coil Suppression and Terminals With 0.100 Grid Lead Spacing. |
| MIL-R-28776/7 | - | Relays, Hybrid, Established Reliability, DPDT, Low Level to 1.0 Ampere (Sensitive Coil Operate at 25°C), Internal MOSFET Driver With Zener Diode Gate Protection (Electromechanical Output), Diode Coil Suppression and Terminals With 0.100 Grid Lead Spacing. |

## CONCLUDING MATERIAL

Preparing activity:
DLA - ES

(Project 5945-0954)


DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:08Z
Check the source to verify that this is the current version before use.