INCH-POUND

MIL-PRF-28776/6D
AMENDMENT 1
30 April 1997

PERFORMANCE SPECIFICATION SHEET

RELAYS, HYBRID, ESTABLISHED RELIABILITY, DPDT, LOW LEVEL TO 1.0 AMPERE
INTERNAL MOSFET DRIVER WITH ZENER DIODE GATE PROTECTION
(ELECTROMECHANICAL OUTPUT)
DIODE COIL SUPPRESSION AND TERMINALS WITH 0.100 GRID LEAD SPACING

This amendment forms a part of MIL-PRF-28776/6D, dated 8 July 1996, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Electrical data, delete in its entirety and substitute:

"ELECTRICAL DATA:

"Insulation resistance: 10,000 MΩ minimum at 500 V dc, except the resistance between coil and case at high temperature shall be 1,000 MΩ minimum.

"Dielectric withstanding voltage:

"Sea level:

"Between case, frame or enclosure, and all contacts in the energized and deenergized positions: 500 V rms (60Hz).

"Between case, frame or enclosure, and coil: 500 V rms (60 Hz).

"Between all contacts and coil: 500 V rms (60 Hz).

"Between open contacts in the energized and deenergized positions: 500 V rms (60 Hz).

"Between contact poles in the energized and deenergized positions: 500 V rms (60 Hz).

"Post intermediate current life test:

"Between case, frame or enclosure, and all contacts in the energized and deenergized positions: 500 V rms (60 Hz).

"Between case, frame or enclosure, and coil: 500 V rms (60 Hz).

"Between all contacts and coil: 500 V rms (60 Hz).

"Between open contacts in the energized and deenergized positions: 375 V rms (60 Hz).

"Between contact poles in the energized and deenergized positions: 500 V rms (60 Hz).

"Altitude:

"Between all terminals to case: 125V rms (60 Hz)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:11Z
Check the source to verify that this is the current version before use.

Custodians:
Navy - EC
Air Force - 85

Preparing activity
DLA - CC

(Project 5945-1018)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:11Z
Check the source to verify that this is the current version before use.