INCH-POUND

MIL-PRF-28776/7E
AMENDMENT 1
30 April 1997

PERFORMANCE SPECIFICATION SHEET

RELAYS, HYBRID, ESTABLISHED RELIABILITY, DPDT, LOW LEVEL TO 1.0 AMPERE (SENSITIVE COIL OPERATE POWER AT 25°C), INTERNAL MOSFET DRIVER WITH ZENER DIODE GATE PROTECTION (ELECTROMECHANICAL OUTPUT) DIODE COIL SUPPRESSION AND TERMINALS WITH 0.100 GRID LEAD SPACING

This amendment forms a part of MIL-PRF-28776/7E, dated 8 July 1996 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Electrical data, delete in its entirety and substitute:

"ELECTRICAL DATA:

"Insulation resistance: 10,000 MΩ minimum at 500 V dc, except the resistance between coil and case at high temperature shall be 1,000 MΩ minimum.

"Dielectric withstanding voltage:

"Sea level:

"Between case, frame or enclosure, and all contacts in the energized and deenergized positions: 500 V rms (60Hz).

"Between case, frame or enclosure, and coil: 500 V rms (60 Hz).

"Between all contacts and coil: 500 V rms (60 Hz).

"Between open contacts in the energized and deenergized positions: 500 V rms (60 Hz).

"Between contact poles in the energized and deenergized positions: 500 V rms (60 Hz).

"Post intermediate current life test:

"Between case, frame or enclosure, and all contacts in the energized and deenergized positions: 500 V rms (60 Hz).

"Between case, frame or enclosure, and coil: 500 V rms (60 Hz).

"Between all contacts and coil: 500 V rms (60 Hz).

"Between open contacts in the energized and deenergized positions: 375 V rms (60 Hz).

"Between contact poles in the energized and deenergized positions: 500 V rms (60 Hz).

"Altitude:

"Between all terminals to case: 125V rms (60 Hz)."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:11Z
Check the source to verify that this is the current version before use.

Custodians:
Navy - EC
Air Force - 85

Preparing activity
DLA - CC

(Project 5945-1019)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:11Z
Check the source to verify that this is the current version before use.