INCH-POUND

MIL-PRF-28776/7E
AMENDMENT 2
19 July 1999
SUPERSEDING
AMENDMENT 1
30 April 1997

PERFORMANCE SPECIFICATION SHEET

RELAYS, HYBRID, ESTABLISHED RELIABILITY, DPDT, LOW LEVEL TO 1.0 AMPERE (SENSITIVE COIL OPERATE POWER AT 25°C), INTERNAL MOSFET DRIVER WITH ZENER DIODE GATE PROTECTION (ELECTROMECHANICAL OUTPUT) DIODE COIL SUPPRESSION AND TERMINALS WITH 0.100 GRID LEAD SPACING

This amendment forms a part of MIL-PRF-28776/7E, dated 8 July 1996 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Figure 1, bottom view, locating tab dimension, delete ".375" and substitute ".031 ± .003".

PAGE 2

* Figure 2, bottom view, locating tab dimension, delete ".375" and substitute ".031 ± .003".

PAGE 4

Electrical data, delete and substitute:

"ELECTRICAL DATA:

"Insulation resistance: 10,000 MΩ minimum at 500 V dc, except the resistance between coil and case at high temperature shall be 1,000 MΩ minimum.

"Dielectric withstanding voltage:

	Sea level V rms (60 Hz)	Post intermediate current life test Sea level V rms (60 Hz)	Altitude V rms (60 Hz)
Between case, frame or enclosure, and all contacts in the energized and deenergized positions: ----------	500	500	
Between case, frame or enclosure, and coil: ----------	500	500	125
Between all contacts and coil: ----------	500	500	All terminals to case
Between open contacts in the energized and deenergized positions: ----------	500	375	
Between contact poles in the energized and deenergized positions: ----------	500	500	

"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:11Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Navy - EC
Air Force - 11
DLA - CC

Preparing activity
DLA - CC

(Project 5945-1057-002)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T15:11Z
Check the source to verify that this is the current version before use.