MIL-T-13460(SigC)
Amendment No. 2
22 July 1955
Superseding
Preceding Amendment

MILITARY SPECIFICATION

TELEPHONE SET TA-263( )/PT

1. Paragraph 2.1:

a. Delete the following specifications:

FEDERAL

NN-B-591	Boxes, Fiberboard, Wood-Cleated (For Domestic Shipment)
UU-T-111	Tape, Paper, Gummed (Sealing and Securing)
PPP-B-601	Boxes; Wood-Cleated-Plywood

MILITARY

MIL-B-131	Barrier-Material; Water-Vaporproof, Flexible

U. S. ARMY

19-10	Filler, Interior Packaging, Fiberboard, Corrugated Single and Double Faced, For General Packing Purposes

b. Delete the following drawings:

SC-D-15914	Moisture Resistance Test Cycle for Ground Signal Equipment
SC-D-19999	Standard Extreme Temperature Cycle

c. Add the following specification:

FEDERAL

T-T-871	Twine; Cotton, Wrapping

d. Add the following Standards:

MIL-STD 169	Extreme Temperature Cycle
MIL-STD 170	Moisture Resistance Test Cycle for Ground Signal Equipment
MIL-STD-252	Wired Equipment, Classification of Visual and Mechanical Defects For

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:35Z
Check the source to verify that this is the current version before use.

2. Section 2 - Add the following:

2.2 Other publications. - The following documents form a part of this specification, unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

NATIONAL MOTOR FREIGHT CLASSIFICATION, RULES AND CONTAINER SPECIFICATIONS FOR TRUCK SHIPMENTS

(Application for copies should be addressed to the Issuing Officer, 1424 Sixteenth Street, N.W., Washington 6, D. C.)

UNIFORM FREIGHT CLASSIFICATION, RATINGS, RULES, AND REGULATIONS

(Application for copies should be addressed to the Association of American Railroads, Chicago, Illinois)

3. Paragraph 3.1.1 Telephone Set TA-263( )/PT. Add the following:

"In case of conflict between the drawings and specification, the specification shall govern."

4. Paragraph 3.1.2 Carrying Case. Replace with the following:

3.1.2 Case, Telephone Set CY-1717( )/PT. Construction of Case, Telephone Set CY-1717 ( )/PT shall conform to the procurement model.

5. Replace "3.6 Carrying Case" with "3.6 Telephone Set CY-1717( )/PT"

6. Figure 1: Replace "36db" with "20db."

7. Section 3 - Add the following:

3.13 In order to attach the filter assembly to the side of the die cast case of the TA-43/PT set, it will be necessary to drill six holes in the side of the case. Before this is done the hand generator shall be removed from the case. This will disturb the "0" ring water seal around the generator. In putting the generator back in place again, the following precautions shall be taken:

a. The generator clamping nut shall be tightened sufficiently to provide an adequate water seal and prevent generator vibration in its mounting. Excess tightening will destroy the generator part.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:35Z
Check the source to verify that this is the current version before use.

b. The ceramic discs in the generator spacer shall be protected against damage or clogging.

c. Metal filings or particles shall be kept away from the components on the back of the set panel and from the inside of the case.

d. The critical volume control on the buzzer shall be protected against damage or maladjustment.

e. Any strain on the leads attached to the generator terminal shall be avoided, to prevent these terminals from turning and grounding on the adjacent metal housing of the generator.

f. The panel of the set shall be put back on the case with care to avoid improper seating of the "O" ring and damage to the water seal.

g. Proper precautions shall be exercised to prevent metal filings and dirt from getting into the Telephone Set TA-43/PT housing during disassembly, drilling and assembly. No deleterious effects shall result from this processing.

3.14 Generator. - When cranking the generator by hand at approximately 200 rpm, the open voltage at the line terminals of the telephone shall be approximately 90 volts.

8. Table II Government group A inspection. Replace with the following:

Table II - Government group A inspection

Inspection	Rqt. Par.	Test Par.	AQL		
			Major	Minor	Control
Visual and Mechanical		4.2	1.5 dphu	6.5 dphu	25 dphu
Insertion loss	3.4.2	4.3	) 1.5	*	
Impedance	3.4.3	4.4	) dphu		
Whistles	3.5	4.5	) for		
Buzzer		4.12	) group		
Generator	3.14	4.13	)		
Talking		4.14	1%		

* All electrical defects are considered major.

9. Paragraph 4.2 Visual and Mechanical inspection. Replace with the following:

4.2 Visual and mechanical inspection Parts and equipment shall be examined for the defects listed in Standard MIL-STD-252.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:35Z
Check the source to verify that this is the current version before use.

10. Paragraph 4.5 Whistles Add the following

"An external 20 cycle per second, 75-90 volt ringing source shall be applied to Ringing Equipment EE-101-A for the test of Figure 1".

11. Paragraph 4.6 Temperature Replace "Drawing SC-D-19999" with Standard MIL-STD-169."

12 Paragraph 4.7.2(d):

a. In second sentence, replace "Drawing SC-D-15914" with "Standard MIL-STD-170".

b. In third sentence, replace "Drawing" with "standard"

13. Paragraph 4.10 Bounce test; equipment under 1000 pounds. In first sentence, replace "transit" with "carrying".

14. Section 4 Add the following:

4.12 Buzzer test. - With the volume control on the telephone turned to loud, the selector switch on "LB," the handset on the hookswitch, and a 20 cps ringing source applied to the line terminals, the buzzer shall operate on 31 volts and shall not operate on 25 volts. With the volume control turned to low, and 20 cps, 90 volts applied to the line terminals, the armature of the buzzer shall not strike the diaphragm.

4.13 Generator test. - The equipment shall be tested for compliance with 3.14.

4.14 Talking test. - Two Telephone Set TA-263( )/PT shall be connected through a 36 db, 600 ohm circuit and conversation shall be readily understood when talking at normal level.

15. Section 5 Replace with the following:

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. -

5.1.1 Level A- Military package. - Telephone Set TA-263( )/PT shall be preserved and packaged in accordance with the procedures specified for the designated methods as prescribed in Specification MIL-P-116 and described in the following paragraphs:

5.1.1.1 Technical literature. - Package each technical literature Method IC-3 as follows: Place each technical literature within a close-fitting, Type I, Grade A, Class b bag conforming to Specification JAN-P-117. Heat seal closure.

Source: https://assist.dla.mil -- Downloaded: 202640-18T00:35Z
Check the source to verify that this is the currentversion before use.

5.1.1.2 Carrying case. - Fold each carrying case into proportionate dimensions and tie with Type II, cotton twine conforming to Specification T-T-871.

5.1.1.3 Telephone Set TA-263( )/PT. Package each telephone set Method IC-5 as follows: Cushion each telephone set on all surfaces with cells or pads or both fabricated of double-faced, corrugated fiberboard with a 200 pound dry Mullen bursting strength conforming to the applicable provisions of Specification LL-B-631 and designed to absorb the shock of impact normally encountered in handling and transit. Place the cushioned equipment, along with the items packaged as specified in 5.1.1.1 and 5.1.1.2, within a close-fitting, RSC, CF, Grade 5 of fiberboard box conforming to Specification JAN-P-108. Box closure shall be made with adhesive specified in the appendix of the box specification and, in addition, corners and joints shall be sealed with water-resistant, pressure-sensitive tape, Type II, Grade A, Olive Drab, conforming to Specification JAN-P-127.

5.1.2 Level B. Limited military package. - Telephone Set-263( )/PT shall be packaged and preserved in accordance with the procedures specified in 5.1.1.

5.1.3 Level C- Minimum military package. - Telephone Set TA-263 ( )/PT shall be packaged in accordance with commercial practice and in a manner that will guarantee adequate protection against corrosion, deterioration and physical damage during direct shipment to the first receiving activity at lowest transportation rate.

5.2 Packing. -

5.2.1 Level A- Military pack. - Place a quantity of Telephone Sets TA-263 ( )/PT within a close-fitting, Style 4 nailed wood box conforming to Specification JAN-P-106. Closure shall be made in accordance with the appendix of the box specification. Gross weight of the shipping container shall not exceed 150 pounds.

5.2.1.1 Metal strapping. Shipping containers shall be strapped in conformance with the requirements of the appendix of the applicable container specification only for direct shipment to ports.

5.2.2 Level B- Limited military pack. Place a quantity of Telephone Sets TA-263( )/PT within a close-fitting, Style 4 nailed wood box conforming to Specification NN-B-621. Closure shall be made in accordance with the box specification. Gross weight of the shipping container shall not exceed 200 pounds.

5.2.3 Level C- Minimum military pack. Telephone Set TA-263( )/PT shall be packed for shipment in a manner conforming to the requirements of Uniform Freight Classification for rail shipment, National motor Freight Classification for truck shipment, Parcel Post Regulations and the regulations of other carriers as applicable to the mode of transportation employed.

5.3 Marking. - Interior packages and exterior shipping containers shall be marked in accordance with the applicable provisions of Military Standard MIL-STD 129.

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:35Z
Check the source to verify that this is the current version before use.