NN-H-106
AMENDMENT—3
OCTOBER 8, 1952

SUPERSEDING
AMENDMENT—2
October 28, 1944

FEDERAL STANDARD STOCK CATALOG

Section IV

(Part 5)

FEDERAL SPECIFICATION

FOR

HANDLES; WOOD, MISCELLANEOUS (FOR) TOOLS

This amendment, which forms a part of Federal Specification NN-H-106, dated January 9, 1934, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 4, paragraph H–1: Delete paragraph H–1 and substitute the following:

H–1. The following departmental specifications and standard, of the issues in effect on date of invitation for bids, and special requirements, form a part of this specification for purchases made under this specification by the respective departments:

H–2. Navy.

H–2a. *Applicable specifications and standard.*

Military specifications:

JAN-P-105—Packaging and Packing for Overseas Shipment—Boxes, Wood, Cleated, Plywood.

JAN-P-106—Packaging and Packing for Overseas Shipment—Boxes, Wood, Nailed.

MIL-B-107—Boxes, Wood, Wirebound (Overseas Type).

MIL-C-072—Compound, Rust-Preventive, Thin-Film (Polar Type).

Navy Department Specification:

General Specifications for Inspection of Material.

Military Standard:

MIL-STD-129—Marking of Shipments.

200431°—52—No. 6

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

H–2b. *Packaging.*[1]—Unless otherwise specified, all handles shall be completely immersed in kerosene for a period of at least 10 minutes and allowed to dry before being packed. All metal ferrules subject to corrosion shall be treated with a rust-preventive compound conforming to the requirements for grade 1 of Military Specification MIL-C-072. Handles shall be packaged in units of 12, 24, or 36 in a suitable folding or set-up box, or, in a style RSC corrugated or solid fiberboard box conforming to the following requirements:

Gross weight, maximum	Average bursting strength	Sum of inside dimensions, maximum
Pounds	*Pounds*	*Inches*
40	200	60
65	275	75
90	350	90

H–2b (1). All flaps shall be sealed by means of a suitable adhesive, metal stitched, or taped. If taped, kraft gummed tape of not less than 2½-inch width, 60-pound minimum basis weight shall be used.

H–2c. *Packing.*

H–2c (1). *For domestic shipment.*[1]

H–2c (1) a. Unless otherwise specified, the subject commodity packaged in folding or set-up boxes, as described in paragraph H–2b, shall be packed in fiberboard boxes, cleated plywood boxes, nailed wood boxes or wirebound boxes, as follows:

H–2c (1) a (1). Style RSC corrugated or solid fiberboard boxes shall conform to the requirements specified in paragraph H–2b.

H–2c (1) a (2). Cleated plywood boxes, nailed wood boxes, and wirebound boxes shall conform to the requirements of

[1] Packaging and packing requirements for domestic shipment apply only for direct Navy purchases. Unless otherwise specified, packaging and packing requirements for domestic shipments to subcontractors, contractors, or shipbuilders, may be in accordance with best commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:57Z
Check the source to verify that this is the current version before use.

Military Specifications JAN-P-105, JAN-P-106, and MIL-B-107, respectively, except that no strapping will be required. In cleated plywood boxes no water-resistant or toxic-treated plywood will be required. The gross weight shall not exceed approximately 150 pounds.

H-2c (1) b. Unless otherwise specified, the subject commodity packaged in style RSC corrugated or solid fiberboard boxes described in paragraph H-2b, will require no further packing.

H-2c (2). *For overseas shipment.*—Unless otherwise specified, the subject commodity packaged in folding or set-up boxes as described in paragraph H-2b, shall be packed in cleated plywood boxes, nailed wood boxes, or wirebound boxes conforming to the requirements of Military Specifications JAN-P-105, JAN-P-106, and MIL-B-107, respectively. Shipping containers shall be lined with a sealed waterproof bag or its equivalent made in conformance with the construction and tests of Military Specification JAN-P-125. The material used shall have a minimum water resistance of 24 hours. The seams and closures shall have strength and water-resistance equal to that of the body material. Shipping containers shall be strapped in conformance with the requirements of the appendix to the applicable box specification.

H-2c (3). *For domestic[1] or overseas shipment.*—Where practicable, shipping containers shall be of the same uniform size, and shall contain the identical number of items of one size and type. Containers shall be designed to fit the contents in a compact manner.

H-2d. *Marking.*

H-2d (1). *Packages.*—Unless otherwise specified, each package shall be plainly marked with the following information completed:

Article_____
Stock No_____
Size_____
Type_____
Quantity_____
Manufacturer_____
Contractor_____

[1] See footnote 1.

H-2d (2). *Shipping containers.*—Unless otherwise specified, each shipping container shall be plainly marked in black with the following information completed:

Article_____
Stock No_____
Size_____
Type_____
Quantity_____
Contractor_____
Contract No_____
Gross weight_____
Cube_____

H-2d (3). *Marking of handles.*—Handles shall be marked in a plain and permanent manner with the manufacturer's name, or trade-mark of such known character, that the source of manufacture may be readily determined.

H-2d (4). In addition to the foregoing, marking shall conform to the requirements of Military Standard MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:57Z
Check the source to verify that this is the current version before use.