INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

SANDERS, ELECTRIC, PORTABLE, BELT, DISK, AND OSCILLATING PAD

This interim amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification 00-S-90C, dated June 22, 1970.

PAGE 1

Paragraph 1.2.1, under "Type III - Sanders, oscillating pad": Delete and substitute:

"Style 1 - Orbital.
Style 2 - Reciprocating."

PAGE 3

Paragraph 3.3.1: Delete and substitute:

"3.3.1 Safety devices. Safety devices, guards, and ventilating openings shall be within the acceptable safety limits of UL 45. In addition, type I sanders, specifically, shall be equipped with guards at each nip point where the belt runs onto a pulley. These guards shall effectively prevent the operator's hands or fingers from coming in contact with these nip points. The unused run of the sanding belt shall be guarded against accidental contact."

PAGE 4

Paragraph 3.4.6: Delete last two sentences.

Paragraph 3.4.8.3: Delete and substitute:

"3.4.8.3 Wiring, cord, and plug cap. All wiring, the flexible cord, and the attachment plug cap shall be in accordance with UL 45. The cord shall have an attachment plug cap conforming to UL 498 requirements for 2 pole, 3 wire grounding devices rated 15 amperes at 125 volts and shall have a minimum free length of 6 feet measured from point of entry into the sander."

PAGE 5

Paragraph 3.4.8.4: Delete and substitute:

"3.4.8.4 Switch. Each type I and type II sander shall be provided with an AC/DC rated trigger switch safely and conveniently located. Current rating of all switches shall not be less than the rated load current of the tool. The trigger switches may have a lock-on mechanism, provided that actuation and turn-off can be accomplished by the same finger(s) that actuate the switch. Switches for the type III sanders may be of the positive on-off type."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

PAGE 8

Paragraph 3.9: Delete and substitute:

"3.9 Type III, sanders, oscillating pad. Type III oscillating pad sanders shall be of two styles. Style 1 shall have an orbital motion with no less than 4,000 cycles at no-load; style 2 shall have a reciprocating (straight line) motion with no less than 3,000 cycles at no-load. They shall conform to table III for the specified size and shall be similar to figure 3. When ordering, specify style and size desired (see 6.2)."

FIGURE 3: Delete "Style 1." and "Style 2." under figures.

PAGE 8

Paragraph 3.9.1: Delete and substitute:

"3.9.1 Components. Oscillating pad sanders shall consist essentially of housing, motor, switch, wiring, gears, shafts and bearings, backing pad, abrasive holding device, and handle(s), and shall conform to the specified requirements."

Paragraph 3.9.1.1: Delete in its entirety.

Paragraph 3.9.1.2: Renumber to "3.9.1.1".

PAGE 9

Paragraph 3.9.1.3: Renumber to "3.9.1.2".

Paragraph 3.9.1.4: Renumber to "3.9.1.3" and change title from "Standard equipment" to "Backing pad".

Paragraph 3.10: Delete (e) and (f) and substitute:

"(e) No-load surface feet per minute for type I sanders; no-load revolutions per minute for type II sanders; frequency in orbits per minute or cycles per minute for type III sanders."

Paragraph 3.12: Delete last sentence.

Paragraph 3.13: Delete and substitute:

"3.13 Workmanship. Sanders provided under this specification shall be of a neat and uniform appearance and shall be free from defects which may adversely affect the appearance, durability, or serviceability of the tool."

PAGE 12

Paragraph 6.2, (b): Delete and substitute:

"(b) Type, class, style, size, and grips (see 1.2, 3.7, 3.8, and 3.9)."

Paragraph 6.2, (d), (e), (i), and (j): Delete.

Paragraph 6.2: Reletter ordering data (a) through (g).

Add the following new paragraph:

"6.6 The sanders covered by this specification are in compliance with the requirements of the Occupational Safety and Health Administration (OSHA) standards published prior to the date of this document."

GSA DC 73-13484

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.