FED. SUP CLASS.
5935



For Detail Dimensions see Procurement Specification

MS PART NO.
MS24283-1

Dimensions in inches. Unless otherwise specified, tolerances. decimals ±.005

Concentricity, maximum indicator reading .002

Dimensions of gages for center contacts:	Pin A	0.188 O.D.
	Pin B	0.180 O.D.
Dimensions of gages for outer contacts	Ring A	0.794 I.D.
	Ring B	0.804 I.D.

Max. weight 7½ oz.
Coupling nut pull· 250 pounds

These values apply to tests on individual adapters:

VSWR 1.12 : 1 max. measured over the frequency range 30 to 5000 MC/sec in 50 MC increments.

Insertion loss 0.1 db max. at 5000 MC/sec.

Corona level. 7000 volts RMS min. at sea level
1700 volts RMS min at altitude

High potential 10000 volts RMS at sea level
2500 volts RMS at altitude
7500 volts RMS after moisture resistance test, vibration test and shock test

Power Handling Capability: 500 watts range 30 to 5000 MC/sec. at 70000 ft. and 203°F. (max. temperature rise not to exceed 20°F when tested for one hour at 70000 ft. altitude, 203°F and 5000 MC.)

THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN.

REFERENCED DOCUMENTS SHALL BE THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

THIS STANDARD HAS BEEN APPROVED BY THE DEPARTMENT OF THE AIR FORCE AND IS MANDATORY FOR USE BY THAT DEPARTMENT ALL OTHER MILITARY ACTIVITIES ARE REQUIRED TO EMPLOY THIS STANDARD WHERE SUITABLE.

APPROVED 5 Jan 60 REVISED

CUSTODIANS AIR FORCE	OTHER INT. A - N - AF -	MILITARY STANDARD CONNECTOR, PLUG, ELECTRICAL - 45° ADAPTER, LT SERIES	MS 24283 (USAF)
Procurement Specification MIL-C-26637	SUPERSEDES:		SHEET 1 OF 1

DD FORM 672
1 OCT 52

MVM CORP DAYTON OHIO
2/65 2300

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:51Z
Check the source to verify that this is the current version before use.