FED. SUP CLASS
2620

COLOR CODE TAPING OF AIRCRAFT TIRES FOR AGE IDENTIFICATION

1. ALL AIRCRAFT TIRES MANUFACTURED FOR THE U.S. AIR FORCE SHALL BE TAPED WITH A CIRCUMFERENTIAL BAND OF ONE INCH TAPE COMPLETELY AROUND AND APPROXIMATELY CENTERED ON THE TIRE TREAD. TIRES HAVING A GROOVE LOCATED ON THE CENTER LINE MAY HAVE THE TAPE APPLIED TO AN ADJACENT RIB.

2. THE TAPE SHALL BE OVERLAPPED UPON ITSELF APPROXIMATELY FOUR (4) INCHES. WHEN SPLICING PARTIALLY USED ROLLS OF TAPE, THE TAPE SHALL BE OVERLAPPED FOUR (4) INCHES SO AS TO ASSURE A STRONG JOINT.

3. CODING REQUIREMENTS:

A. NEW TIRES — NEW TIRES SHALL BE COLOR CODED WITH TAPE TO IDENTIFY THE YEAR THE TIRES WERE MANUFACTURED.

B. REBUILT TIRES — REBUILT TIRES SHALL BE COLOR CODED WITH TAPE TO IDENTIFY THE YEAR THE CARCASSES WERE REBUILT.

4. THE TAPE COLOR AND SHADE SHALL BE IN ACCORDANCE WI[TH] [FED]ERAL STANDARD 595 AS SPECIFIED IN THE TABLE SHOWN BELOW. THE COLOR CYCLE WILL REPEAT [EVERY] THREE (3) YEARS.

5. ALL TAPE PRODUCED FOR THE PURPOSE OF COLOR COD[ING] [UNI]TED STATES AIR FORCE AIRCRAFT TIRES SHALL HAVE IMPRINTED ON IT THE YEAR CORRESPONDIN[G] [TO] THE COLOR AS OUTLINED ON THE "COLOR CODE TABLE" OF THIS SPECIFICATION. THE YEAR SHALL BE [PRI]NTED IN A NEAT, LEGIBLE MANNER AND SHALL BE REPEATED CONTINUOUSLY FOR THE TOTAL LENGTH OF THE TAPE PER GIVEN ROLL WITH 3 INCH SPACINGS BETWEEN THE PRINTED DATES. YEAR DATE NUMBERS SHALL BE 3/4 INCH IN HEIGHT AND BLACK OR WHITE IN COLOR. SPACING BETWEEN THE LETTERING SHALL BE NO LESS THAN 1/8 INCH AND NO MORE THAN 1/4 INCH. THE PRINTING SHALL BE INSOLUBLE IN WATER AND RESISTANT TO ANY ABRASION RESULTING FROM NORMAL OPERATIONS. THE YEAR SHALL BE PLACED ON THE TAPE IN THE MANNER ILLUSTRATED BELOW.

CANCELED AFTER 7 JAN 1980. NO SUPERSEDING STANDARD.

6. THE TAPE MANUFACTURER SHALL SUBMIT TO OO-ALC (MME), HILL AFB, UTAH, A THIRTY (30) YARD MINIMUM LENGTH OF TAPE 1 INCH WIDE. A MANUFACTURER MUST RECEIVE APPROVAL FOR EACH PARTICULAR YEAR BY SUBMITTING A TAPE SAMPLE OF THE COLOR SPECIFIED FOR THAT YEAR TO DETERMINE CONFORMANCE WITH FED-STD-595. IF THE MANUFACTURING PROCESS IS CHANGED OR ALTERED, A NEW QUALIFICATION TEST REPORT (QTR) SHALL BE SUBMITTED TO OO-ALC (MME). FOR THE LISTING OF APPROVED TAPE MANUFACTURERS, CONTACT PROCUREMENT OFFICE (PPWF), HILL AIR FORCE BASE, UTAH 84056.

(B)

COLOR CODE

YEAR OF MANUFACTURE			FED-STD-595 CODE	
			COLOR	SHADE NO
1971	1974	1977	GREEN	14187
1972	1975	1978	BLUE	15123
1973	1976	1979	ORANGE	12246

NOTE: REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

(A) PARA 5 LINE 5 ADDED "BLACK OR WHITE" IN COLOR: PARA 6, LINE 1, ADDED "THE TAPE MANUFACTURER".

APPROVED AUG 19, 1971 REVISED (A) MAR. 07 1972 (B) 7 JAN 80

THIS MILITARY STANDARD IS APPROVED FOR USE BY CODE 99, (DEPARTMENT OF THE AIR FORCE) AND IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

P.A.99 Other Cust	TITLE COLOR CODING - AGE IDENTIFICATION ACFT TIRES	MILITARY STANDARD MS 27822(USAF),
PROCUREMENT SPECIFICATION	SUPERSEDES: AF61A32147	SHEET 1 OF 1

DD FORM 1 SEP 67 672-1 (Limited coordination) EDITION OF 1 SEP 67 MAY BE USED. ☆U.S. GOVERNMENT PRINTING OFFICE: 1980—603-121/528

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:52Z
Check the source to verify that this is the current version before use.