MILITARY SPECIFICATION

COVER, BATTERY BOX: FOR BB-626( )/U
BATTERY (WITH BLOWER ASSEMBLY)

1. SCOPE

1.1 This specification covers the requirements applicable to the design and fabrication of a battery box cover containing a blower assembly and including all electrical accessories needed for the proper operation of the BB-626( )/U Battery under loads in excess of 2 amperes(A). Hereafter the Cover, Battery Box shall be referred to as cover.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-571	-	Solder, Tin Alloy, Lead-tin Alloy And Lead Alloy.

MILITARY

MIL-T-152	-	Treatment, Moisture-And Fungus-resistant, Of Communications, Electronic, And Associated Electrical Equipment.
MIL-T-704	-	Treatment And Painting Of Material.
MIL-W-4088	-	Webbing, Textile, Woven Nylon.
MIL-F-14256	-	Flux, Soldering, Liquid (Rosin Base).
MIL-P-15024	-	Plate, Identification-information And Marking For Identification Of Electrical, Electronic And Mechanical Equipment.

FSC 6135

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

MIL-E-16400	-	Electronic Equipment, Naval Ship And Shore, General Specification.
MIL-E-17555	-	Electronic And Electrical Equipment, Accessories, And Repair Parts, Packaging And Packing Of.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures And Tables For Inspection By Attributes.
MIL-STD-129	-	Marking For Shipment And Storage.
MIL-STD-202	-	Test Methods For Electronic And Electrical Component Parts.
MIL-STD-461	-	Electromagnetic Interference Characteristics Requirements For Equipment.
MIL-STD-810	-	Environmental Test Methods.
MS3114	-	Connector, Receptacle, Electric, Solder Type, Rear Mounting Jam Nut, Bayonet Coupling.
MS27295	-	Cap, Electrical Connector Receptacle, Protective, Metal, Bayonet Coupling.

DRAWINGS

U.S. MARINE CORPS

695176C0000	-	BB-626( )/U Battery Box.
695176C0002	-	BB-626( )/U Cover Battery Box (With Blower Assembly).
695176C0003	-	BB-626( )/U Battery Box Female Connectors.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS

Handbook H28 - Screw Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.)

3. REQUIREMENTS

3.1 First article. The first article is defined as a cover which will be identical to the production items which the manufacturer will subsequently produce in fulfillment of the procurement contract. As soon as practicable after award of contract and prior to submission of any covers for final acceptance, the contractor shall furnish two first articles for examination and test to determine conformance to this specification. Examination and test shall be those specified herein. Approval of the first article by the activity concerned shall not relieve the contractor of his obligation to supply identical covers conforming to this specification. Any changes or deviations of covers from the first article shall be subject to the approval of the contracting officer.

3.2 Parts, materials and processes. Parts, materials and processes shall be as specified herein. The selection of class, grade or type shall be such that when mounted in the cover the part or material will perform its intended function under the service and storage conditions specified herein. The location of connectors shall be as shown on Drawing No. 695176C0002. Where applicable, requirements of MIL-E-16400 shall be followed. All parts, materials and processes used in the fabrication of the cover shall be of the proper grade for the purpose intended and shall not adversely affect the service life of the cover.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

3.2.1 Plastic. Where not machined, plastic materials and parts shall have the original smooth or polished surfaces. Surfaces which have been sawed, cut, punched or otherwise machined shall be as smooth as practicable in accordance with good manufacturing practice for the intended application.

3.2.2 Tropicalization. Tropicalization of the cover is not required. Wherever practicable, materials used in the equipment shall not, in themselves, be nutrients for fungi or susceptible to deterioration by moisture and fungi. If not practicable to use such materials for certain items used in the equipment, such items shall be given moisture fungus proofing treatment prior to assembly in the equipment or the areas in the equipment where such items are used shall be coated with a moisture and fungus resistant varnish in accordance with MIL-T-152 prior to shipment.

3.3 Design and construction. The cover shall be designed and constructed so that it will interface both mechanically and electrically with the battery box shown on Drawing No. 695176C0000 and conform to the dimensions specified on Drawing No. 695176C0002. The complete cover shall consist of a cover assembly designed to mate with the BB-626( )/U Battery and a blower assembly with ancillary electrical devices. The cover contains necessary electrical connectors to mate internally with the battery and also to provide external connection to the load. A current-sensitive blower control circuit is provided to automatically activate the blower when battery load exceeds a preset value. Power requirements will be 55 watts (maximum). Air volume is 5 cubic feet per minute (ft^3/min) (minimum). The cover shall be made of metal treated and painted to prevent rust or corrosion (see 3.9) or of oriented, glass filament epoxy of high impact strength. It shall be of unitized construction with sufficient space within to accommodate a blower assembly (see 3.3.2) and automatic blower control circuitry. The cover shall be equipped with two latch hooks so located and oriented that they are compatible with and align with the corresponding mating latches of the BB-626( )/U Battery as shown on Drawing No. 695176C0003. A pliable gasket shall be bonded to the inside of the cover to match the rim of the battery box to form an effective seal between the cover and the battery box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

3.3.1 Carrying strap. The cover shall be equipped with a webbed carrying strap recessed so as not to increase the overall height of the cover when not in use. The webbing shall be woven nylon conforming to type XVII of MIL-W-4088 and suitably impregnated. Color shall match Marine Corps green, No. 23 (see 6.3). The strap shall be securely attached to the cover to provide full support for the battery under all conditions.

3.3.2 Blower assembly. The blower used with the cover shall be a Globe Industries vane axial type, Part No. 19A 2057, or equal, with air volume of 5 ft^3/min.

3.3.2.1 Blower housing. The blower shall be securely mounted in the cover and provided with a screened opening 1 inch in diameter for admission of air to the blower wheel. The screen shall be metal no coarser than 30 mesh. The blower motor shall have inherent protection against damage due to water, dust or any other foreign material entering the housing. The blower shall discharge air into the battery case to provide equitable distribution of air to all battery cells.

3.3.2.2 Blower control. Operation of the blower shall be fully automatic. The blower control device shall sense the battery load and operate the blower when the current delivered by the battery to the load exceeds 2 $\pm$0.5 A. For system loads of less than 1.5 A, the blower shall be inoperative. The control device shall introduce no more than a 200-millivolt drop to the load circuit. The device shall draw no current from the battery when the battery is not in use.

3.3.2.3 Control enclosure. The blower control shall be enclosed and protected so that total immersion of the battery in water shall in no way impair function or operation of the device when it has been removed from the water. There shall be no requirement for the battery to be operated while submerged.

3.3.3 Connectors. The cover shall be equipped with an electrical connector mounted and positioned on the end of the cover opposite the location of the blower motor assembly (see 3.3.2.1). The connector shall conform to MS3114-E14-5S with a captive protective cap conforming to MS27295-3. The output from the battery shall be through terminals B and E, with B the negative terminal and E the positive terminal. Connection of the cover to the battery

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

shall be by two male plugs conforming to Drawing No. 695176C0002 and so positioned as to mate with the female receptacles mounted in the battery box and shown on Drawing No. 695176C0003.

3.3.4 Wiring. Wiring shall be neat and sturdy and in accordance with good manufacturing practice.

3.3.4.1 Slack. Wire and cables shall be as short as practical except that sufficient slack shall be provided for the following:

(a) To provide for at least two replacements of the part to which the wire is attached.

(b) To ensure freedom of motion of lugs or terminals normally intended to have some degree of movement.

(c) To facilitate field repair of broken or cut wires.

3.3.4.2 Routing. Wires shall be routed and secured in a manner to avoid contact with rough or irregular surfaces or sharp edges under service conditions specified herein. Wires shall not be bent sharply where they enter insulating material.

3.3.4.3 Splicing. Wires in continuous runs between two terminals shall not be spliced during manufacture.

3.3.5 Riveting. Thickness of countersunk metal which accepts the heads of flush rivets shall be not less than the height of the rivet heads. The distance from the centers of rivet holes to the edges of the material in which the holes are formed shall be at least one and one-half times the rivet diameter. After riveting, the joints shall be tight, the joined parts shall be undamaged and the rivet heads shall be properly seated and tight against their bearing surfaces.

3.3.6 Soldering. Solder shall conform to QQ-S-571. For soldering electrical connections, composition SN60, type AR or S, shall be used for general purpose; and composition SN62 or SN63, type AR or S for special purposes. When type S solder is used, the flux shall conform to MIL-F-14256.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

3.3.6.1 Acid or acid salts. No acid or acid salts shall be used in the preparation for, or the soldering of, any electrical connections. Exception is permitted for tinning or soldering of mechanical joints not used to complete electrical circuits. In all cases where acid or acid salt fluxes are used, the parts shall be thoroughly washed to remove all residue when soldering has been completed.

3.3.6.2 Process. There shall be no sharp points or rough surfaces resulting from insufficient heating during soldering. The solder shall feather out to a thin edge, indicating proper flowing and wetting action and shall not be crystallized, overheated or underheated. The minimum amount of flux and solder shall be used for electrical connections. Any means employed to remove excess flux shall not incur the risk of loose particles of flux, brush bristles or other foreign material remaining in the cover. Insulating material which has been subjected to heating during the soldering operation shall be undamaged and parts fastened thereto shall not have become loosened.

3.3.6.3 Protective coating. Solder joints used for wiring connections which may be exposed to electrolyte shall be completely protected with a coating of room temperature cure epoxy or other approved electrolyte resistant material.

3.3.7 Securing of parts. Brackets, lugs, flanges, inserts, bolts and other mounting arrangements shall retain items securely when subjected to the service and test conditions specified herein. Parts shall be so mounted that loosening, wear of mounting arrangements or permanent separation of parts shall not occur when the items in which they are used are subjected to the shock tests specified herein. Any permanent deformation resulting from a test shall not cause degradation of performance below full specification requirements. Parts shall be secured in such a manner that failure of a single rivet or screw shall not free the part completely. Threaded fasteners shall comply with H28.

3.3.8 Cleaning. After fabrication, all parts shall be cleaned in accordance with good commercial practice. Cleaning processes shall have no deleterious effect. All corrosive material shall be removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

3.4 Maintainability. The cover shall be so constructed that parts and wiring comprising the assembly are accessible for repair and replacement without destruction of any part or component.

3.5 Performance. The cover shall meet the following performance requirements.

3.5.1 Total operating life. The equipment shall have a minimum total operating life of 5,000 hours with reasonable servicing and replacement of parts.

3.5.2 Motor and control mean time between repair. The motor and control shall operate at battery loads in excess of 2.5 A for at least 1,000 hours without the necessity of repair or adjustment.

3.5.3 Service conditions. The equipment shall be capable of performing under the following service conditions imposed by field employment:

(a)	Temperature requirements:	
	(1) nonoperating	-65°C to +65°C.
	(2) operating	-40°C to +50°C.
(b)	Ambient humidity range	0 to 100 percent relative.
(c)	Vibration	In accordance with 4.7.1
(d)	Shock	In accordance with 4.7.2
(e)	Rain	In accordance with 4.7.3
(f)	Thermal shock	In accordance with 4.7.4
(g)	Immersion	In accordance with 4.7.5
(h)	Altitude	In accordance with 4.7.6
(i)	Salt fog	In accordance with 4.7.7
(j)	Dust	In accordance with 4.7.8

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

3.5.4 Storage conditions. The cover shall be capable of being stored under the following conditions, without subsequent impairment of performance:

(a) Ambient temperature range -65°C to +65°C.

(b) Altitude Sea level to 30,000 feet

3.5.5 Audio noise. The maximum sound pressure levels as measured 5 feet from the blower shall not exceed the following values:

Octave Band	Sound Pressure Level (dB ref. 0.0002 microbar)
75-150	64
150-300	48
300-600	39
600-1200	32
1200-2400	32
2400-4800	38
4800-9600	40

3.5.6 Immersion. The cover shall show no evidence of performance deterioration after being subjected to the immersion test specified in 4.7.5.

3.6 Interference. The equipment shall meet the design requirements and interference control limits of MIL-STD-461.

3.7 Dimensions. Overall dimensions of the cover shall be as shown on Drawing No. 6951760C0002.

3.8 Weight. The complete cover shall not weigh more than 1.5 pounds.

3.9 Treatment and painting. Treatment and painting of the battery box cover assembly shall conform to MIL-T-704, type A. Color shall match Marine Corps green, No. 23 (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

3.10 Identification labels. Each cover shall be provided with a permanently mounted label. Marking shall be in accordance with the requirements of MIL-P-15024. In addition, marking shall be insoluble in 1.400 ±0.015 sp. gr. potassium hydroxide. Identification labels shall contain the following data:

Nomenclature	Manufacturer's name
Order or Contract Number	Manufacturer's plant location
Date Code	Federal Stock Number

3.11 Government furnished material (GFM). The Government shall provide two BB-626( )/U Batteries for use as GFM during the life of the contract.

3.12 Workmanship. The equipment covered by this specification including all parts and accessories shall be manufactured and finished in accordance with MIL-E-16400.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).

(b) Initial production inspection (see 4.4).

(c) Quality conformance inspection (see 4.5).

(1) Individual cover inspection (see 4.5.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

(2) Sample cover inspection (see 4.5.2.2).

(d) Inspection comparison (see 4.6).

(e) Inspection of preparation for delivery (see 4.9).

4.3 First article inspection. Two covers shall be tested as specified in 4.7 and examined for defects listed in 4.8. Failure of the covers to pass any test or inspection shall be cause for rejection.

4.4 Initial production inspection. Unless otherwise specified (see 6.2), one or more initial production covers shall be selected at random by the Government from the first covers being produced from production tooling, will be subjected to tests of 4.7 and examined for defects listed in 4.8 to determine conformance to the requirements of this specification. The inspection will be performed by the Government at a site selected by the Government. Acceptance of the initial production covers shall not exclude the remaining covers from the quality conformance inspection and acceptance provisions herein. Failure of an initial production cover to meet any requirement specified herein during and as a result of the initial production inspection shall be cause for rejection of the initial production covers and shall be cause for refusal by the Government to continue acceptance of production covers until evidence has been provided by the supplier that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the supplier at no cost to the Government on covers previously accepted and produced under the contract. Any deficiencies found as a result of the initial production inspection will be considered evidence that all covers accepted prior to the completion of initial production inspection are similarly deficient unless evidence to the contrary is furnished by the supplier and such evidence is acceptable to the contracting officer.

4.5 Quality conformance inspection.

4.5.1 Sampling. Selection of samples shall be in accordance with MIL-STD-105 using the normal inspection levels.

4.5.2 Examination.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

4.5.2.1 Individual cover inspection. Each production cover shall be visually examined for compliance with requirements specified herein. In addition, each production cover shall be tested in accordance with 4.7.9.

4.5.2.2 Sample cover inspection. Samples selected in accordance with 4.5.1 shall be examined for defects listed in 4.8. Acceptable quality level shall be 2.5 percent defective for major defects and 10 percent for minor defects.

4.6 Inspection comparison. When initial production inspection is specified, the Government may select covers at any time during the contract production period and subject these covers to tests of 4.7 and examine for defects listed in 4.8 to determine that the quality of the selected cover is equal to the quality standards established during initial production inspection. The inspection will be performed by the Government at a site selected by the Government. Covers shall be selected at random from those which have been accepted by the Government and will not include the previously inspected first article or initial production covers. Failure of any cover to pass inspection comparison may be considered cause for refusal by the Government to continue acceptance of covers until object evidence furnished by the supplier reveals that corrective action has been taken to eliminate the conditions which caused the rejection.

4.7 Tests. The covers shall be tested under room ambient conditions between 20°C and 30°C and an altitude between sea level and 5,000 feet unless otherwise specified herein.

4.7.1 Vibration. With cover assembled to a sample battery, testing shall be performed in accordance with Test Method 201 of low frequency conditions and Test Method 204 Test Condition C, Part 2 only for the high frequency conditions of MIL-STD-202 and the following:

(a) Cover and battery may be vibrated in one direction through both low and high frequencies before being changed to the next direction on the vibration table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

(b) Low frequency vibration may be varied either uniformly or logarithmically between the limits of 10 and 55 hertz.

(c) Length of time for low frequency vibration in one direction shall be 90-100 minutes (270-300 minutes for the complete test).

(d) The blower shall be operated during the low and high frequency vibration tests.

(e) Upon completion of this test, the blower shall meet the test requirements of 4.7.9.

4.7.2 Shock. One cover mounted on a sample battery shall be subjected to a total of nine impact shocks, three shocks in each axis (bottom, one side, and one face). The value of each shock shall be 60 g's for a duration of 10 to 15 milliseconds. Following this test, covers shall show no adverse effects when tested in accordance with 4.7.9.

4.7.3 Rain. With the cover mounted on a sample battery, the battery and cover shall be tested in accordance with MIL-STD-810 for rainproof equipment. During the test, the covers shall be tested to determine compliance with 4.7.9.

4.7.4 Thermal shock. The cover, mounted on a sample battery, shall be tested in accordance with Test Method 107, Test Condition B of MIL-STD-202, except that the high temperature shall be limited to +65°C. Upon completion of this test, the cover shall meet the requirements of 4.7.9.

4.7.5 Immersion. With the cover mounted on a battery, the cover and battery shall be immersed to a minimum depth of 3 feet in salt water(3 percent Na Cl) for 15 minutes. After completion of the period of immersion, the battery and cover shall be removed from the water and wiped dry on external surfaces and subjected to the test of 4.7.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

4.7.6 Altitude. The cover shall be subjected to a pressure reduced to simulate 30,000 feet above sea level, nonoperating, for 2 hours. The cover shall be tested at a pressure reduced to simulate 15,000 feet above sea level at a temperature of +22°C. While under this condition, the cover shall meet the requirements of 4.7.9 except that air volume is not specified.

4.7.7 Salt fog. The cover, mounted on a sample battery, shall be subjected to a salt fog test in accordance with MIL-STD-810. During this test, the cover shall meet the requirements of 4.7.9.

4.7.8 Dust. With cover mounted on a sample battery, dust test shall be performed in accordance with MIL-STD-810. During this test, the cover shall meet the requirement of 4.7.9.

4.7.9 Electrical. Each cover shall be attached to a battery box containing an active battery or an equivalent power source. Provision shall be made to load the output circuit with a variable load and suitable instrumentation shall be provided to confirm compliance with the below specified requirements under the following conditions:

Test Step	Load	Blower conditions
1	No load	Inoperative
2	1.4 A	Inoperative
3	2.5 A	Operative
4	1.4 A	Inoperative

Transition from one load level to another shall be smooth, without interruption of current flow, so that true hysteresis characteristics of the control circuit may be established. During this test, verification of proper blower rotation shall be made. Air must enter the battery case at the top and discharge at the bottom. Air volume shall be 5 ft^3/min ±10 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

4.8 Classification of defects. Defects shall be classified as indicated below:

Major Defects

(a) Dimensions not as specified in 3.7.

(b) Components missing or not as specified in 3.3.

(c) Assembly incomplete or not as specified in 3.3.

(d) Material not as specified in 3.2.

(e) Direction of blower air flow not as specified in 3.3.2.1.

(f) Cover does not latch or unlatch easily from sample battery (see 3.3).

(g) Labels not as specified in 3.10.

(h) Weight not as specified in 3.8.

(i) External connector polarity not as specified in 3.3.3.

(j) Gasket and compression incorrect (see 3.3).

Minor Defects

(a) Treatment and painting not as specified in 3.9.

(b) Workmanship not as specified in 3.2.

4.9 Inspection of preparation for delivery. An examination shall be made to determine that packaging, packing and marking requirements of Section 5 are met. For the purpose of inspection, a cover prepared for shipment shall constitute a unit of product. Each cover shall be inspected to determine correctness of the items listed below. Presence of one or more defects shall be cause for rejection.

(a) Preservation and packaging.

(b) Packing.

(c) Markings correct and legible.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging and packing. The cover shall be preserved, packaged and packed for the level of protection specified in the contract or order in accordance with MIL-E-17555.

5.2 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The battery cover specified herein is designed to cover a BB-626( )/U Battery and to provide forced aspiration air for the operation of the battery cells during periods of heavy loading (greater than 2.0 A).

6.2 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

6.2.1 Procurement requirements.

(a) Title, number and date of this specification.

(b) Selections of applicable levels of preservation, packaging and packing shall be as specified (see 5.1 and 5.2).

(c) Data to be included on the identification labels (see 3.10).

(d) Whether initial production inspection is required and the number of covers to be furnished (see 4.4).

6.2.2 Contract data requirements. Data conforming to Data Item Descriptions A-12, C-01, C-03, C-04, E-04, E-13, E-14, H-01, H-06, H-09, V-11, and V-16 will usually be required for delivery in connection with this specification. When so required, such data will be specified for delivery on a DD Form 1423 included in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

6.3 Color. Color chips for Marine Corps green number 23 may be obtained from the Commandant of the Marine Corps, Headquarters U. S. Marine Corps, (Code CSY-10), Washington, D. C. 20380.

6.4 First article. The first article shall be examined and tested for approval, at the contractor's plant or at an independent commercial testing laboratory acceptable to the procuring activity. First article tests shall be witnessed by a Government representative of the procuring activity. Approval of the first article shall be by the contracting officer.

Preparing activity:
Navy - MC
Project No. 6135-N105

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commanding General (Code 840)
Marine Corps Supply Activity
1100 South Broad Street
Philadelphia, Pennsylvania 19146

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4063, MAY 61, WHICH IS OBSOLETE

Source: https://assist.dla.mil - Downloaded: 2026-03-20T12:01Z
Check the source to verify that this is the current version before use.