MIL-I-28964B(MC)
28 August 1984
SUPERSEDING
MIL-I-28964A(MC)
10 September 1971

MILITARY SPECIFICATION

INSIGNIA, GRADE: PLASTIC

This specification is approved for use by the U.S. Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for plastic grade insignia for enlisted personnel and junior reserve officers training corps.

* 1.2 Classification. Insignia shall be furnished in pairs in the following types and classes (see 6.2):

Type I - Enlisted Personnel

Class 1 - Sergeant Major of the Marine Corps
Class 2 - Sergeant Major
Class 3 - Master Gunnery Sergeant
Class 4 - First Sergeant
Class 5 - Master Sergeant
Class 6 - Gunnery Sergeant
Class 7 - Staff Sergeant
Class 8 - Sergeant
Class 9 - Corporal
Class 10 - Lance Corporal
Class 11 - Private First Class

Type II - Junior Reserve Officers Training Corps

Class 1 - Sergeant Major
Class 2 - First Sergeant
Class 3 - Gunnery Sergeant
Class 4 - Staff Sergeant
Class 5 - Sergeant
Class 6 - Corporal
Class 7 - Lance Corporal
Class 8 - Private First Class

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Commandant of the Marine Corps (LMA-1), Headquarters, U. S. Marine Corps, Washington, DC 20380, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

*2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

L-P-392	- Plastic Molding Material, Acetal, Injection And Extrusion.
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-B-676	- Boxes, Setup.

MILITARY

MIL-B-17757	- Boxes, Shipping, Fiberboard (Modular Sizes).

STANDARDS

FEDERAL

FED-STD-141	- Paint Varnish, Lacquer and Related Materials, Method of Inspection, Sampling and Testing.
FED-STD-406	- Plastic, Methods Of Testing.

MILITARY

MIL-STD-105	- Sampling Procedures And Tables For Inspection By Attributes.
MIL-STD-129	- Marking For Shipment And Storage.

DRAWINGS

MARINE CORPS

705002B0000	- Insignia, Grade, Enlisted Personnel: Plastic.
71C5005B0000	- Insignia, Grade, Marine Corps Junior Reserve Officers Training Corps: Plastic.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following Government documents, drawings, and publications form a part of this specification to the extent specified herein.

LAWS AND REGULATIONS

U. S. POSTAL SERVICE MANUAL

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington D. C. 20402.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issue of the documents which are indicated as DOD adopted shall be the issue listed in the current DODISS and the supplement thereto, if applicable.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P. Street, N. W., Washington, DC 20026.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS
(ASTM) PUBLICATIONS

D-789 - Standard Specification for Nylon Injection Molding and Extrusion Material.

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

*3.1 Standard sample. The standard sample is furnished solely for guidance and information to the supplier (see 6.3). Variation from this specification may appear in the sample, in which case the specification shall govern.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

3.2 First article. When specified (see 6.2), before production is commenced, the first article, consisting of the number of insignia specified by the procuring activity (see 6.2) shall be submitted, or made available to the contracting officer or his authorized representative for inspection. The approval of the first article authorizes the commencement of production, but does not relieve the contractor of responsibility for compliance with all provisions of this specification. The first article shall be manufactured by the contractor in the same facilities to be used for the manufacture of the production items.

3.3 Material.

3.3.1 Plastic. The insignia (including the attaching device) shall be molded from acetal homopolymer or polymer resin having a melting point of 162°C minimum and conforming to type I, class 2 of L-P-392, except that the electrical property requirements shall not apply. Clean, unburned plastic material in the form of imperfect parts, sprues, runners or other scraps of the same composition, produced in the molding operation, may be reground and mixed with the virgin material. The molding material may contain a surface lubricant.

3.3.1.1 Bending strength. The prongs shall not break or separate from the insignia when tested as specified in 4.6.2.

*3.3.1.2 Thickness. The thickness for all classes of the insignia shall be 0.050 ± 0.005 inch when tested as specified in 4.6.3.

3.3.1.3 Pressing. The plastic insignia shall show no evidence of scorching, distortion, crazing or melting when tested as specified in 4.6.4.

3.3.1.4 Cracking. The plastic portion of the insignia shall show no evidence of cracking, permanent deformation or separation of the anchored device when tested as specified in 4.6.5.

3.3.1.5 Accelerated weathering. The plastic insignia shall show no evidence of chalking or change in appearance when tested as specified in 4.6.6.

3.3.1.6 Color and finish. The color shall be a concentration of uniformly dispersed, high-color carbon black, having a nonglossy finish appearance on all surfaces except the back, and shall match the standard or approved sample. Coloration shall be made during formulation of the molding compound. The finish shall be produced as a result of the molding operation and not by application of any protective coating, lacquer or other materials.

*3.3.2 Attaching device (prongs and clutch fasteners). Each insignia shall be provided with two molded plastic prongs having a free length of 9/32 + 1/64 inch and two clutch fasteners conforming to Drawing Nos. 705002B0000 and 71C5005B0000. The plastic prongs, made of the base material specified in 3.3.1, shall be molded as an integral part of the insignia. The clutch fasteners shall be made from any type brass. Removal of the clutch from the

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

prong, by hand, shall not be possible without first depressing the release wings (see 4.6.1 for the required test).

3.4 Design. The insignia shall be the Marine Corps design shown on Drawing Nos. 705002B0000 and 71C5005B0000. The molded design of each type and class insignia shall reflect exactly the design of the applicable standard sample (see 3.1). Each pair of type I, class I insignia and all classes of type II insignia shall consist of a right and left insignia. The type I, class 1 and all of type II insignia shall be produced in such a manner that when a pair of these insignia is worn, the head of the eagle or the flame end of the lamp, as applicable, shall be towards the front.

*3.5 Construction. The insignia, including all center devices (i.e., Marine Corps emblem with stars, bursting bomb, single star, diamond, crossed rifles and lamp of knowledge), and plastic prongs shall be molded and devices shall be firmly secured to the basic insignia at points of contact. All edges of insignia shall be clean, smooth and free from burrs, roughness and raggedness. Finished insignia requiring trimming shall be accurately trimmed. The prongs shall be positioned on the back of the insignia at the location shown on Drawing Nos. 705002B0000 and 71C5005B0000. The prongs shall meet the bending strength requirements specified in 3.3.1.1. The front of the insignia shall show no signs of unevenness or distortion.

3.6 Finished measurement. The finished insignia shall conform to the measurements shown on Drawing Nos. 705002B0000 and 71C5005B0000.

3.7 Workmanship. The insignia shall be accurately made and shall be clean, well finished and free from cracks, sharp or uneven edges, or any defects which might affect the appearance or serviceability. The finished insignia shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels (AQL's).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. When a certificate of compliance is permitted, the Government reserves the right to check test such items and determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

a. First Article Inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.3 Inspection conditions. Unless otherwise specified, inspection shall be in accordance with MIL-STD-105.

4.4 First article inspection. When first article is required, inspection and testing shall be made on a completely fabricated insignia of each type and class for all provisions of this specification applicable to end product examination and tests.

4.5 Quality conformance inspections.

4.5.1 Component and material inspection. In addition to the quality assurance provisions of the subsidiary specifications and drawings, testing shall be performed on the acetal resin plastic for melting point as follows. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units (DHU).

Lot expressed in terms of	Characteristic	Rqmt. para.	Test method	Indiv. unit	Appl. Rqmt. lot avg.	No. to per sple. unit	Det. as	Results rpt. sple. unit
100 lbs.	Melting point 1/	3.3.1	ASTM D-789	X	-	1	to nearest 0.1°C	2/

4.5.2 Examination of end item. The end item shall be examined for the defects listed in 4.5.2.1 and 4.5.2.2. The sample unit shall be one pair of insignia of each type and class.

4.5.2.1 General defects. General defects shall be classified as follows:

1/ The melting point temperature shall be recorded as the first appearance of a transparent area in the middle of each specimen.

2/ The specimen may be a shaving from a molded specimen, approximately 1.6 milmeter (0.0625 inch) in diameter. Fine powdered plastic or shavings from plastic pellets may also be used. For Government verification testing, three molded insignia may be submitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT	CLASSIFICATION		
		MAJOR	MINOR	
			A	B
Color and finish	a. Detail altered or device does not conform to drawings.	X		
	b. Surfaces not smooth.	X		
	c. Discolored, stained, mottled, spotted, clearly noticeable.	X		
	d. Inclusion of foreign matter or segregations clearly noticeable.	X		
	e. Abraded, scuffed, scratched or otherwise damaged.	X		
	f. Paired insignia not matching in color, shade and finish (when applicable)		X	
Design	a. Detail altered or device does not conform to drawings.	X		
	b. Any warp, twist or distortion producing irregular surface contour or outline.		X	
	c. Paired insignia not matching (i.e., each pair consisting of one left and one right insignia).		X	
Material	Not fabricated of the specified material	X		
Construction and workmanship	a. Nick, gouge, scratch, crack or dent		X	
	b. Distorted, bent, malformed or otherwise impaired.	X		
	c. Surface not smooth where required, e.g., is pitted, porous or chipped.	X		
	d. Edge not clean or smooth, i.e., . fin, flash, chipped, rough, or ragged	X		
	e. Device is not centered or positioned as required.	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

EXAMINE	DEFECT	CLASSIFICATION		
		MAJOR	MINOR	
			A	B
	f. Device is incorrect design, missing, or not securely anchored.	X		
	g. Device not molded in one operation, as required.	X		
	h. Insignia not accurately trimmed		X	
Attaching device	a. Missing.	X		
	b. Defective, e.g., any part damaged or malformed, affecting use.		X	
	c. Not positioned as specified or not aligned perpendicular to the back.	X		
	d. Prong not adequately secured to the insignia body.	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

4.5.2.2 Examination of insignia for dimensions. Any dimension that is not within the tolerances specified on Drawing Nos. 705002B0000 and 71C5005B0000 shall be classified as a defect.

4.5.2.3 Inspection levels and AQL's. Inspection levels and AQL's expressed in DHU's shall be as follows:

4.5.2.1	
Inspection level II of MIL-STD-105	AQL's
Major	2.5 DHU
Total Major and Minor (combined)	15.0 DHU
4.2.3.2	
Inspection level S-2 of MIL-STD-105 One class	4.0 DHU

4.5.3 Testing of the end item. Testing of the completely fabricated insignia shall be performed in accordance with the following for the characteristics shown therein. There shall be one determination per sample unit and results shall be reported as pass or fail. The sample unit shall be seven completely fabricated insignia of each type and class. The requirements are applicable to the individual unit. For the bending strength test, the sample unit shall be one item and all prongs on that item will be tested. However, one defect will be scored regardless of how many prongs fail on the item. The inspection level shall be S-2 and the AQL shall be 10 DHU.

Characteristic	Requirement para.	Test method
Test for bending	3.3.1.1	4.6.2
Test for thickness	3.3.1.2	4.6.3
Test for pressing	3.3.1.3	4.6.4
Test for cracking	3.3.1.4	4.6.5
Test for accelerated weathering	3.3.1.5	4.6.6
Test for attaching device (clutches)	3.3.2	4.6.1

4.5.4 Examination of preparation for delivery requirements. An examination shall be made to determine compliance with packaging, packing and marking requirements of Section 5. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 DHU.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect illegible, of improper size, location, sequence or method of application.
Materials	Any component missing. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of case liners, container flaps, loose strapping, inadequate strapping. Unit package not properly sealed. Bulging or distortion of containers.
Weight or content (exterior and interior)	Number or intermediate containers is more or less than required; gross/net weight exceeds requirements.

4.5.4.1 Examination for count of insignia in intermediate containers. Insignia packaged for shipment shall be examined to determine conformance with package markings and specified quantity. The sample unit for this examination shall be one box (interior package). Any box containing less than the specified or marked quantity of insignia shall be classified as a defect. The inspection level shall be S-2 and the AQL shall be 2.5 DHU. The lot size shall be the number of intermediate containers.

4.6 Tests.

4.6.1 Test for clutches. The clutch shall be removed and replaced ten times from the prong. An attempt shall then be made to remove the clutch by hand without first depressing the release wings, during which time the clutch and prong shall be inspected to determine compliance with 3.3.2.

*4.6.2 Test for bending strength. The prongs shall be bent five times through a 90° angle, 45° on each side of the prongs perpendicular position. Bending of the prongs shall be performed slowly, and each bending action shall take 10 seconds.

*4.6.3 Test for thickness. The test shall be performed in accordance with Method 1011 of FED-STD-406. The test shall be performed to determine compliance with 3.3.1.2.

4.6.4 Resistance to pressing heat. A household flat iron, heated to a temperature of 275°F to 300°F, shall be applied to the insignia for 12 pressing motions, not to exceed a total of 1 minute. The sole temperature of the iron shall be checked with a surface pyrometer. The insignia shall be attached to cloth for testing. The insiginia shall be examined to determine compliance with 3.3.1.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

*4.6.5 Cracking. The insignia, face side, shall be placed over a 1/2-inch mandrel, and bent in approximately 1 minute. The insignia shall be examined to determine compliance with 3.3.1.4.

*4.6.6 Accelerated weathering. The test shall be performed in accordance with Method 6152 of FED-STD-141, except that the exposure cycle shall be for 240 hours. The insignia shall be examined to determine compliance with 3.3.1.5.

5. PACKAGING

*5.1 Packaging. Packaging shall be level A or commercial as specified (see 6.2).

*5.1.1 Level A. One pair of insignia, with clutch fasteners assembled, shall be mounted on a cardboard having a minimum thickness of 0.011 inch and measuring 2-1/2 inches square and shall be wrapped in tissue paper. Each mounted pair of type I, class 1 and type II insignia shall consist of a right and left insignia. As an alternate to the tissue wrap, each pair of mounted insignia shall be packaged in a snug fitting transparent polyethylene bag having a minimum film thickness of 0.002 inch. All seams and closures shall be effected by heat sealing. Prior to or during heat sealing closure operations, excess air within the bag shall be expelled. Sixty cards (insignia of one type and class only shall be packaged in a paperboard inner container having outside dimensions 7 inches long, 5-5/8 inches wide, and 2-1/2 inches high. The container shall conform to type I, variety 1, class A, style 4 of PPP-B-676 or style RSC, type CF or SF, class domestic of PPP-B-636. The thickness of the paperboard shall be 0.040 inch, minimum.

*5.1.2 Commercial. Insignia shall be packaged in accordance with manufacturer's commercial practice.

*5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2).

5.2.1 Level A.

*5.2.1.1 Method 1. Twelve intermediate containers, of one type and class only, packaged as specified in 5.1.1 shall be packed in a fiberboard shipping container with liner, conforming to type CF class weather resistant, style CSSC-L size No. 1A, grade 275 of MIL-B-17757 and assembled, closed, and reinforced in accordance with the appendix thereto. Toward the end of the contract or when there is less than the required amount per container of the same type and class, mixed classes of the same type may be packed within the same container (see 5.3.1).

*5.2.1.2 Method 2. When specified (see 6.2), 12 shipping containers conforming to size 1A, grade 275 of MIL-B-17757, containing 12 intermediate containers packaged as specified in 5.1.1, shall be packed in a fiberboard shipping container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Twelve intermediate containers, of one type and class only, packaged as specified in 5.1.1 shall be packed in a fiberboard shipping container with liner, conforming to type CF, class domestic, style CSSC-L, size No. 1A of MIL-B-17757 and assembled, closed and reinforced in accordance with the appendix thereto. The fiberboard used in fabricating the box shall be grade 275. Toward the end of the contract, or when there is less than the required amount per container of the same type and class, mixed classes of the same type may be packed within the same container (see 5.3.1).

*5.2.3 Commercial. Insignia, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules, National Motor Freight Classification and U. S. Postal Service Manual, or as applicable.

*5.3 Marking. In addition to any special marking required by the contract or order, intermediate and shipping containers shall be marked in accordance with the requirements of MIL-STD-129. The individual units, packaged as specified in 5.1.1, shall be marked for purposes of identification by legibly printing or stamping the item nomenclature and National Stock Number (NSN) in black lettering on either the mounting card or paper label. When a paper label is used it shall measure approximately 1 inch by 1 inch and shall be placed in each transparent bag with the lettering facing out.

5.3.1 Mixed classes. Each shipping container packed with mixed classes shall have securely attached to the end and side, directly under the printing or stenciling, a white paper label 5 by 4 inches with the words "MIXED CLASSES" plainly stamped or printed thereon, and under these words shall be legibly printed the correct quantity of each contained therein.

6. NOTES

6.1 Intended use. Insignia covered by this specification are intended for use as follows:

Type I - To be attached to the collar of uniforms worn by enlisted men and women.

Type II - To be attached to the collar of uniforms worn by high school student members of Marine Corps Junior Reserve Officer's Corps.

*6.2 Ordering data

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) Type and class required (see 1.2).
(c) Whether first article is required (see 3.2).
(d) Number of insignia required for first article (see 3.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

(e) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
(f) When level A, method 2, packing is required (see 5.2.1.2).

6.2.2 Contract data requirements. When this specification is used in an acquisitionwhich incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph No.	Data requirement title	Applicable DID No.	Option
4	Inspection System Program Plan	DI-R-4803	-
4.3	First Article Inspection Procedure	DI-T-4901	-
4.3	First Article Inspection Report	DI-T-4902	-
4.5	Failure Report	DI-R-4805	-
4.6	Reports, Test	DI-R-2072	-

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5000.19L., Vol. II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

*6.3 Standard sample. The standard sample may be obtained from the procuring activity or as directed by the contracting officer.

6.4 First article. Examinations, test and approval shall be as specified by the contracting officer (see 3.2).

6.5 Changes from previous issues. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing activity:
Navy - MC
Project No. 8455-N056

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-I-28964B(MC)	INSIGNIA, GRADE PLASTIC

3a NAME OF SUBMITTING ORGANIZATION

b ADDRESS *(Street City State ZIP Code)*

4 TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)* _____

5 PROBLEM AREAS

a Paragraph Number and Wording

b Recommended Wording

c Reason/Rationale for Recommendation

6 REMARKS

7a NAME OF SUBMITTER *(Last First MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street City State ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements All users of military standardization documents are invited to provide suggestions This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems Enter in block 6 any remarks not related to a specific paragraph of the document If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commandant of the Marine Corps
Headquarters, U S Marine Corps
(Code IMA-1)
Washington, D C. 20380

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:08Z
Check the source to verify that this is the current version before use.