MILITARY SPECIFICATION

INSIGNIA, GRADE, MARINE CORPS JUNIOR RESERVE OFFICERS TRAINING CORPS: (EMBROIDERED)

This specification is approved for use by U. S. Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers requirements for Schiffli embroidered grade insignia stitched with rayon yarn on woolen cloth.

1.2 Classification. Grade insignia shall be of one type in the following classes as specified (see 6.2).

Class A - Sergeant Major
Class B - First Sergeant
Class C - Gunnery Sergeant
Class D - Staff Sergeant
Class E - Sergeant
Class F - Corporal
Class G - Private First Class

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Commandant of the Marine Corps (LMA-1), Headquarters, U. S. Marine Corps, Washington, D. C. 20380, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202640-20T21:00Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

UU-P-268	- Paper, Kraft, Wrapping.

MILITARY

MIL-B-17757	- Box, Shipping, Fiberboard, (Modular Sizes).
MIL-B-82252	- Cloth, Broadcloth, Wool and Wool Synthetic. (moth-proofed).

STANDARDS

FEDERAL

FED-STD-191	- Textile Test Methods.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

DRAWING

MARINE CORPS

695180A0000	- Insignia, Grade; Marine Corps Junior Reserve Officers Training Corps (Embroidered).

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 202610-20T21:00Z
Check the source to verify that this is the current version before use.

LAWS AND REGULATIONS

U. S. POSTAL SERVICE MANUAL

(Copies of the manual may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402).

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P. Street, N. W., Washington, D. C. 20026.)

3. REQUIREMENTS

3.1 Standard sample. Standard samples are furnished solely for guidance and information to the contractor (see 6.3). Variation from this specification may appear in the sample, in which case the specification shall govern.

3.2 First article. Unless otherwise specified (see 6.2), before production is commenced, a finished insignia shall be submitted or made ready for the contracting officer or his authorized representative for inspection as specified in 4.4. The approval of the first article authorizes the commencement of production but does not relieve the contractor of responsibility for compliance with all applicable provisions of this specification. The first article shall be manufactured by the contractor in the same facilities to be used for the manufacture of the production items.

3.3 Materials

Source: https://assist.dla.mil -- Downloaded: 202610-20T21:00Z
Check the source to verify that this is the current version before use.

3.3.1 Basic fabric. The basic fabric shall be cloth, wool, broadcloth, scarlet shade 2501, 16.5 ounce per linear yard of 54 inch width, conforming to type I, class 4 of MIL-C-82252 except the color shall be produced by stock dying and the finished cloth shall show fair fastness to crocking, perspiration, wet-dry cleaning and light.

3.3.2 Buckram. The buckram for backing the insignia shall be a light, open weave, single ply fabric weighing 2.5 ounces minimum per square yard, having a minimum thread count per inch of 40 in the warp and 20 in the filling, and having a minimum breaking strength of 30 pounds in the warp direction and 20 pounds in the filling direction when tested as specified in Section 4, Table II.

3.3.3 Embroidery yarn. The embroidery yarn shall be first quality continuous filament, regenerated cellulose type of rayon twisted into 75/2 denier Schiffli yarn.

3.3.3.1 Color and colorfastness. The yarn shall be dyed with vat or napthol colors to match the approved standard shade Gold (HF) Cable #67016. The colors shall show good fastness to wet (dry) cleaning and light for all insignia when tested as specified in Section 4, Table III.

3.3.3.1.1 Matching. The color shall match the approved standard shade under natural (north sky) daylight or artificial daylight having a color temperature of 7,500 ° Kelvin, and shall be a good approximation to the approved standard shade under incandescent lamplight at 2,800° Kelvin.

3.3.4 Bobbin yarn. Bobbin yarn shall be continuous filament nylon yarn or two-ply cotton yarn. The yarn shall be undyed, bleached or unbleached.

3.4 Design. Each class of insignia shall conform in all respects to the design of an approved sample and Drawing No. 695180A0000.

3.5 Construction.

3.5.1 Embroidering. The insignia shall be embroidered on Schiffli-type embroidery machines on the base cloth specified and in accordance with the approved sample. The embroidery stitches shall be not more than 4/32 inch in length. Care shall be exercised in embroidering the lamp device on the insignia so that in the finished insignia, the lamp device shall be horizontally level and the tip of the flame and handle of the lamp shall be equidistant from the lower edge of bottom bar. The insignia shall be produced in pairs consisting of a right and left hand insignia. The lamp device shall be embroidered in such a manner that when a pair is worn, the flame end of the lamp shall be towards the front.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:00Z
Check the source to verify that this is the current version before use.

3.5.2 Stiele stitches. The Stiele stitches shall be sufficiently and properly underlaid on all edges of the embroidered devices to show a well raised and rounded effect equal to the approved sample, and shall be tightly drawn and well executed to produce a clear, sharp edging. The spacing between the rows of Stiele stitches in the arcs and bars shall be uniformly 2/32 inch, and these areas, as well as the center device, shall be well raised and rounded with sufficient and properly inserted underlay stitches to produce the fullness and depth shown in the approved sample. The Stiele stitches shall be not more than 1/32 inch in length.

3.5.3 Number of embroidery stitches. The minimum number of embroidery stitches including the lamp device, shall be as follows:

Class	No. Stitches
A	6830
B	7730
C	6580
D	5370
E	4220
F	3130
G	1890

3.5.4 Backing. The insignia shall be backed with the buckram specified in 3.3.2.

3.5.5 Cutting. The background cloth shall be clean cut to form sharp, smooth, uniform edges and well defined corners and points.

3.6 Finished measurements. The finished insignia shall conform to the measurements shown on Drawing No. 695180A0000.

3.7 Government-loaned property. Unless otherwise specified (see 6.2), cartoons for use in construction and examination of insignia shall be loaned to the contractor.

3.8 Workmanship. The finished insignia shall show a clear cut execution and shall be clean, neatly made, with full tension on the thread, shall show no broken stitches, nor any stitches out of proper alignment. The insignia shall conform to the quality and grade of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:00Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First Article Inspection (see 4.4)
2. Quality Conformance Inspection (see 4.5)

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be in accordance with the provisions set forth in MIL-STD-105.

4.4 First article inspections. When first article is required, inspection shall be made of a completed pair of insignia for all provisions of this specification.

4.5 Quality conformance inspections.

4.5.1 Testing of components. Components and materials shall be tested as specified in Table II. The methods of testing in FED-STD-191, as specified herein shall be followed. The sample size for each characteristic of each component shall be as follows:

Lot Size (Unit)	Sample Size
800 or less	2
801 to 22,000	3
22,001 and over	5

The lot shall be unacceptable if one or more units of any component fail to meet the requirements in Table II. The lot size shall be expressed as follows:

Component	Unit
Buckram	1 linear yard
Embroidery yarn	1 pound
Bobbin yarn	1 pound

The unit of product shall be as follows:

Component	Unit of Product
Buckram	1 linear yard
Embroidery yarn	1 bobbin
Bobbin yarn	1 bobbin

4.5.2 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:00Z
Check the source to verify that this is the current version before use.

TABLE II
Testing of Components

Component	Characteristic	Reqt paragraph	Test method	No. of determinations unit of product	Results reported as
Buckram	Material identification	3.3.2	1200 1/	1	Pass or fail
	Weight	3.3.2	5041	5	To the nearest 0.1 oz.
	Yarns/inch				
	- warp	3.3.2	5050	5	To the nearest whole number
	- filling	3.3.2	5050	5	
	Breaking Strength				
	- warp	3.3.2	5100	5	To the nearest 1.0 lb.
	- filling	3.3.2	5100	5	
Emboidery Yarn	Material identification	3.3.3	1500/1520 1/	1	Pass or fail
	Denier	3.3.3	4021	1	To nearest denier
	Ply	3.3.3	Visual	1	Pass or fail
Bobbin Yarn	Material identification	3.3.4	1200/1530 1/	1	Pass or fail
	Ply (cotton yarn)	3.3.4	Visual	1	Pass or fail

1/ Unless otherwise specified, a contractor's certificate of compliance may be accepted as evidence of conformance.

4.5.3.1 Examination of the end item. The end item shall be examined for defects listed in 4.5.3.1 and 4.5.3.1. All defects shall be counted, except when two or more classifications are applicable to a single local condition, in which case the more serious condition shall be scored. the lot size shall be expressed in units of one insignia each. The sample size shall be in accordance with inspection level II. The acceptable

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:00Z
Check the source to verify that this is the current version before use.

quality levels (AQL) shall be 2.5 major defects per 100 units (DHU) and 10.0 total DHU units (Major , Minor A and Minor B).

4.5.3.1 General defects. General defects shall be classified as follows:

Examine	Defect	Classification		
		Major	Minor	
			A	B
Basic fabric	Other than specified:			
	-Noticeable at first glance	X		
	-Requires scrutiny to note		X	
	-Requires comparison with standard sample, drawing or cartoon to note.			X
	Any thickening resulting in improperly raised stitches clearly visible at normal inspection distance (arm's length) on face 1/.		X	
	Any splice, cut, hole or tear.	X		
	Color not as specified (wrong color).	X		
	Basecloth frayed, not uniformly trimmed.	X		
	Borders not uniform in width (clearly visible at normal inspection distance (arm's length).	X		
	Corners or points not well defined.	X		
Backing (buckram) not fully covered by embroidered design	Protrudes more than 1/32 inch beyond finish insignia.		X	
	Any smash, float, broken or missing yarn clearly visible at normal inspection distance (arm's length) on face 1/	X		
	Any hitchback, open place, misweave.		X	
	Slub, 3 or more times normal yarn diameter, oversize knot.		X	

1/ The term "face" as used herein denotes entire face of insignia as viewed when the item is sewn to a uniform.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:00Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification		
		Major	Minor	
			A	B
	Heavy or thin place, abraded surface clearly visible at normal inspection distance (arm's length)		X	
	Embroidered on wrong side (not face)			X
Embroidered face 1/	Device not as specified.	X		
Back	Bobbin yarn not as specified.		X	
Design.	Any departure from cartoon, drawing or standard sample.	X		
	Device incomplete.	X		
	Device poorly defined, sharp outline lacking:			
	-Noticeable at first glance.	X		
	-Requires scrutiny to note.		X	
	-Requires comparison with standard sample, drawing or cartoon to note.			X
	Distorted or misshaped overall form or outline, clearly visible at normal inspection distance (arm's length)	X		
	Shift; device or outlines mis-shaped, misplaced or overlapped incorrectly:			
	-Noticeable at first glance	X		
	-Requires scrutiny to note		X	
	-Requires comparison with standard sample, drawing or cartoon to note			X

1/ The term "face" as used herein denotes entire face of insignia as viewed when the item is sewn to a uniform.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:00Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification		
		Major	Minor	
			A	B
	Device flat:			
	-Underlay missing where underlay is specified or indicated by standard sample.	X		
	-Not well rounded or prominent, underlay insufficient.		X	
	Device inadequately covered (thin or uneven stitch density):			
	-Basecloth, background or underlay showing through.	X		
	-Showing thinness of detail only.		X	
Device	-Tip of flame and handle of lamp not equidistant from lower edge of bottom bar.		X	
	-Not horizontally level (clearly visible at normal inspection distance (arm's length))		X	
Construction (Stitches)	Tight tension:			
	-Distortion of surface (face side). 1/	X		
	-Speckles of unrelated colors or yarn breaking through surface.		X	
	Loose tension - loopy surface clearly visible at normal inspection distance (arm's length)	X		
	Broken or missing stitches in embroidery:			
	-Noticeable at first glance	X		
	-Requires scrutiny to note		X	
	Nonuniform embroidery stitch density clearly visible at normal inspection distance (arm's length)		X	

1/ The term "face" as used herein denotes entire face of insignia as viewed when the item is sewn to a uniform.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:00Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification		
		Major	Minor	
			A	B
Background	Not interlocked in evenly spaced rows:			
	-Noticeable at first glance	X		
	-Requires scrutiny to note		X	
	Rows not properly formed. (Clearly visible at normal inspection distance (arm's length))		X	
	Any rows omitted from proper sequence.			
	-Noticeable at first glance	X		
	-Requires scrutiny to note		X	
	Number of visible rows fewer than specified in applicable cartoon or standard sample.		X	
	Background stitches not in specified direction.		X	
Stieles	Not firmly drawn to produce clearly defined rows or edges.		X	
	Stiele stitches in areas, bars or center devices more than 1/32 inch.			X
	Background between Stiele stitches not uniform 2/32 inch.			X
Device Stitches	Spacing of rows not in accordance with applicable standard sample or cartoon.		X	
	Curvatures or design features fuzzy, not clearly outlined.			
	-Noticeable at first glance		X	
	-Requires scrutiny to note.			X

Source: https://assist.dla.mil -- Downloaded: 202610-20T21:00Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification		
		Major	Minor	
			A	B
Workmanship	Kinked, bunched, tangled yarn clearly visible at normal inspection distance (arm's length) on face. 1/		X	
	Broken, scuffed or cut yarns on face. 1/			
	-Noticeable at first glance.	X		
	-Requires scrutiny to note.		X	
	Spots, stains, foreign matter on face. 1/			
	-Noticeable at first glance	X		
	-Requires scrutiny to note		X	
	Spots, stains, foreign matter on back.			X
	Two threads untrimmed.			X
	Three or more threads untrimmed.		X	
	Creased or folded - will not flatten by manual pressure.		X	

1/ The term "face" as used herein denotes entire face of insignia as viewed when the item is sewn to a uniform.

4.5.3.2 Examination for dimensions. Measurements shall be taken of all points, lines, area, curves, radii, and spaces for which dimensions are specified in Drawing No. 695180A0000 including:

Overall length	Overall width
Diameter of radii	Angle (degrees)
Border width	
Device location	Device dimension

Spaces and distances between intermediate points.

Source: https://assist.dla.mil -- Downloaded: 202640-20T21:00Z
Check the source to verify that this is the current version before use.

The acceptable quality level shall be 4.0 defects per hundred units. The inspection level shall be level S-3. The sample shall be selected at random from among the units selected for visual examination. The tolerances provided in Drawing No. 695180A0000 shall be applied. Where no tolerance is cited (except where specifically ruled-out) one-half of the distance to the next higher or next lower value of the same measurement unit shall be allowed as tolerance (e.g., if measurement is given in 1/4-inch multiples, tolerance would be ± 1/8 inch).

4.5.3.3 Testing of end item. The end item shall be tested as specified in Table III. The lot size shall be expressed in units of one insignia. The unit of product shall be eight insignia. The lot shall be unacceptable if one or more units fail to meet the requirements referenced in Table III. The sample size shall be as follows:

Lot size (each)	Sample size
22,000 or less	2
22,001 and over	3

TABLE III - END ITEM TESTS

Characteristics	Reqt Paragraph	Test method	Number of determinations per unit of product	Results reported as
Colorfastness embroidery yarns to:				
-wet dry cleaning	3.3.3.1	5622	1	Good, fair or poor
-light	3.3.3.1	5660 1/	1	Good, fair or poor

1/ In the event of dispute resulting from the test with method 5660 or a result of anomalous behavior of certain dye types or formulations, the contracting officer may authorize the exposure of natural light in accordance with method 5662.

4.5.4 Examination of packaging. An examination shall be made to determine that the packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception it

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:00Z
Check the source to verify that this is the current version before use.

need not be sealed. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 DHU.

Examine	Defects
Markings (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as, incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling. Bulging or distortion of containers.
Weight	Net weight exceeds requirements.
Preservation (when applicable)	Omitted or not uniformly distributed in container.

5. PACKAGING

5.1 Preservation and packaging. Preservation and packaging shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. A matched pair of insignia (1 right and 1 left) shall be inserted into a commercial grade polyethylene bag. The bag shall be closed by stapling or taping to prevent accidental loss of contents. Ten pair of individually bagged insignia of one class only shall be put-up in bundles and securely cross-tied with cotton twine or tape.

5.1.2 Commercial. Commercial packaging shall afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The contractor may use his standard practice provided it meets the requirements specified for commercial packing.

Source: https://assist.dla.mil -- Downloaded: 202610-20T21:00Z
Check the source to verify that this is the currentversion before use.

5.1.3 Preservation. Except where the insignia are made from moth-repellent cloth, not less than 2 ounces of napthalene flakes or other equivalent moth repellent shall be uniformly distributed throughout the contents of each shipping container.

5.2 Packing. Packing shall be level B, or commercial as specified (see 6.2).

5.2.1 Level B. Insignia of one class only, packaged as specified in 5.1.1, shall be packed inquantities specified below in a fiberboard shipping container conforming to type CF, class-domestic, style CSSC, size No. 1, grade 275 of MIL-B-17757 and assembled and closed in accordance with appendix thereto. In addition, each container shall have the contents completely covered on the top and bottom with a sheet of 60-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Towards the end of the contract or when there is less than the required amount per container of the same class, mixed classes may be packed within the same container.

Class	Number of Bundles
A	50
B	50
C	60
D	80
E	80
F	96
G	120

5.2.2 Commercial. Insignia shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules, National Motor Freight Classification Rule and U. S. Postal Service Manual or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract shipping containers shall be marked in accordance with MIL-STD-129.

5.3.1 Label. Each shipping container packed with mixed classes shall have securely attached to the end and side directly under the printing or stenciling, a white paper label 5 by 4 inches with the words designating the combination plainly stamped or printed thereon, and under these words shall be legibly printed the correct quantity of each contained therein.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:00Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Insignia fabricated under the requirements of this specification are for wear by Marine Corps Junior Reserve Officer's Training Corps personnel on the dress blue uniform.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Class required (1.2).
(c) Whether first article is required (3.2).
(d) Whether cartoons are required as Government loaned property (see 3.7).
(e) Packaging and packing required (5.1 and 5.2).

6.3 Standard sample. For information regarding the availability of samples of the insignia and the standard shades specified, address inquiry to the procuring activity issuing the invitation for bids.

6.4 First article. Examination, tests and approval shall be as specified by the contracting officer (see 3.2).

6.5 Marginal notations. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Preparing activity

Navy - MC

Project No. 8445-N873

Source: https://assist.dla.mil -- Downloaded: 202610-20T21:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22-R255

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity

DOCUMENT IDENTIFIER AND TITLE Insignia, Grade, Marine Corps Junior Reserve Officers Training Crops. (Embroidered) MIL-I-28934A(MC)

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S N 0102-LF-014-1802

Source: https://assist.dla.mil -- Downloaded: 202610-20T21:00Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
HEADQUARTERS, U.S. MARINE CORPS
WASHINGTON, D.C. 20380

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
Department of the Navy
DOD -317



Commandant of the Marine Corps
Headquarters, U.S. Marine Corps
(LMA-1)
Washington, D.C. 20380

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-20T21:00Z
Check the source to verify that this is the current version before use.