MILITARY SPECIFICATION

POLE, BEACH, PANEL MARKER: METAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements for one type of beach pole.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-T-830	- Tube, Steel, (Carbon, Mechanical, Seamless And Welded).
RR-W-410	- Wire Rope And Strand.
TT-E-527	- Enamel, Alkyd, Lustreless.
PPP-C-650	- Crate, Wood, Open And Covered.
PPP-T-60	- Tape, Pressure sensitive Adhesive, Waterproof, For Packaging.

MILITARY

MIL-R-1223	- Rivets And Rivet Steel Bars.
MIL-C-16173	- Corrosion Preventive Compound, Solvent Cutback, Cold -application.

STANDARDS

FEDERAL

FED-STD-66	- Steel, Chemical Composition And Hardenability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:14Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105	- Sampling Procedures And Tables For Inspection By Attributes.
MIL-STD-129	- Marking For Shipment And Storage.

DRAWINGS

MARINE CORPS

71C5045A0000	- Pole, Beach, Panel Marker: Metal; Assembly And Details.
71C5045A0001	- Pole, Beach, Panel Marker: Metal; Details

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publication. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Samples. Samples are furnished solely for guidance and information to the supplier (6.3). Variation from this specification may appear in the sample, in which case the specification shall govern.

3.2 First article. Unless otherwise specified (see 6.2) before production is commenced, a finished beach pole with components shall be submitted, or made available to the contracting officer or his authorized representative for approval. The approval of the first article authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with applicable provisions of the specification. The first article shall be manufactured by the supplier in the same facilities to be used for the manufacture of the production items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:14Z
Check the source to verify that this is the current version before use.

3.3 Materials.

3.3.1 Tubing. The upper and lower pole sections shall be made from steel, mechanical, welded, round, cold-drawn conforming to QQ-T-830 and Drawing No. 71C5045A0000. Two sections of tubing are required for the beach pole.

3.3.2 Cap-clamp. The cap-clamp shall be made of steel-strip, mild, No. 16 gage (0.065) conforming to the requirements on Drawing No. 71C5045A0001. One cap-clamp is required for the beach pole.

3.3.3 Eye-bolt collar. The collar for the eye-bolt shall be made from steel, mechanical tubing, seamless, round, and cold-drawn conforming to QQ-T-830, and the requirements on Drawing No. 71C5045A0001. One collar for the eye-bolt is required for the beach pole.

3.3.4 Bushing. The bushing shall be made from steel, round, cold finished, AISI-C1018 conforming to FED-STD-66, and the requirements on Drawing No. 71C5045A0001. One bushing is required for the beach pole.

3.3.5 Hinge bar (upper and lower). The hinge bar for the lower, and upper sections of the pole shall be made from steel, round, cold finished, AISI-C1018 conforming to FED-STD-66 and the requirements on Drawing No. 71C5045A0001. One lower and one upper hinge bar is required for the beach pole.

3.3.6 Hinge-strip. The hinge-strip connecting the upper hinge bar to the lower hinge bar shall be made from steel strip, hot rolled conforming to the requirements on Drawing No. 71C5045A0001. One hinge strip is required for the beach pole.

3.3.7 Adjustable clamps. The adjustable clamps shall be made from steel strip, mild, No. 16 gage (0.065) conforming to the requirements on Drawing No. 71C5045A0001. Five adjustable clamps are required for the beach pole.

3.3.8 Stud. The stud shall be made from steel, round, cold finished AISI-C1018 conforming to FED-STD-66 and the requirements on Drawing No. 71C5045A0000. One stud is required for the beach pole.

3.3.9 Saddle plate. The saddle plate shall be made from steel, mild conforming to the requirements on Drawing No. 71C5045A0000. One saddle plate is required for the beach pole.

Source: https://assist.dla.mil -- Downloaded: 202640-20T21:14Z
Check the source to verify that this is the current version before use.

3.3.10 Stake. The stakes shall be made from steel, hot rolled AISI-C1015 conforming to FED-STD-66 and the requirements on Drawing No. 71C5045A0000. Three stakes are required for the beach pole (one short stake welded to the saddle plate and two longer stakes for supporting the pole).

3.3.11 Snap, hook, swivel eye. The hooks shall be made from steel, galvanized finish, conforming to requirements on Drawing No. 71C5045A0000. Six snap hooks are required for the beach pole.

3.3.12 Eye bolt with square nut. The eye bolt and square nut shall be made from steel, galvanized finish, conforming to requirements on Drawing No. 71C5045A0001. One eye bolt with square nut is required for the beach pole.

3.3.13 Screw with square nut. The machine screw with square nut shall be made from steel, galvanized finish conforming to requirements on Drawing No. 71C5045A0001. Five screws with square nuts are required for the beach pole.

3.3.14 Rivets.

3.3.14.1 Rivet, countersunk head. The countersunk head rivet shall be made from steel, 3/16 inch diameter, conforming to type C-1 of MIL-R-1223 and the requirements on Drawing No. 71C5045A0000. One countersunk head rivet is required for the beach pole.

3.3.14.2 Rivet, round head. The round head rivet shall be made from steel, 3/16 inch diameter, conforming to type B-1 of MIL-R-1223 and the requirements on Drawing No. 71C5045A0000. One round head rivet is required for the beach pole.

3.3.15 Wire rope. The preformed wire rope shall be made from steel, galvanized finish having 6 strands of 7 wires laid around a fiber core conforming to type I, class 1 of RR-W-410 and the requirements on Drawing No. 71C5045A0000, except the diameter shall be 1/8 inch. Two 17-foot lengths are required for the beach pole.

3.3.16 Clamps. The clamps for the wire rope shall be made from steel, galvanized finish, 1/8 inch diameter conforming to requirements on Drawing No. 71C5045A0000. Two clamps are required for the beach pole.

3.3.17 Connectors. The connectors for the wire rope shall be made from steel, having a galvanized finish similar or equal to the "Stanley (pull tite clamp)" as illustrated on Drawing No. 71C5045A0000. The connectors, when assembled to the wire rope, shall withstand, without failure or damage, a load equal to the breaking strength of the wire rope. Two connectors are required for the beach pole.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:14Z
Check the source to verify that this is the current version before use.

3.3.18 Chain. The machine chain for attaching to the stakes and connectors shall be made from steel wire, 1/8 inch diameter, machine tooled, having a galvanized finish and containing 12 twisted links conforming to requirements on Drawing No. 71C5045A0000. Two lengths (approximately 6 inches) are required for the beach pole.

3.3.19 Link. The link for attaching the chain to the stake shall be made from steel, 3/16 inch round, AISI-C1018 conforming to FED-STD-66. The ends, when set in place, shall be peened and welded as illustrated on Drawing No. 71C5045A0000. One link is required for each long stake.

3.4 Design. The beach pole shall be the U. S. Marine Corps design shown on Drawing Nos. 71C5045A0000 and 71C5045A0001. The pole shall be collapsible, equipped with cap collar, clamps, guy lines, hooks etc., for attaching the panel marker and erecting the pole but does not include the panel marker.

3.5 Construction. The construction of all components and the assembly of the beach pole covered herein shall conform to the requirements of this specification and requirements shown on Drawing Nos. 71C5045A0000 and 71C5045A0001.

3.6 Finish. The hinge strip and hinge bars shall have a cadmium plated finish; the wire ropes shall be steel with a galvanized finish; wire rope clamps, eye bolt with nut and machine screw with nut shall be cadmium or zinc coated and not enameled finish. All other steel parts shall have a bonderized, or equal, undercoating and a finish coat of enamel conforming to TT-E-527; color shall match Marine Corps green No. 23 (see 6.5).

3.7 Workmanship. The finished and assembled beach pole shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels (AQL).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:14Z
Check the source to verify that this is the current version before use.

Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. When certificates of compliance are permitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Inspection. Sampling for inspection shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

4.2.1 First article inspection. When first article is required, inspection shall be performed on a completely fabricated beach pole with components for conformance to all provisions of this specification.

4.2.2 Component and material inspection. In accordance with 4.1 above, components and materials shall be tested in accordance with all requirements of referenced specifications, drawings and standards, unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase documents. The supplier shall furnish a certificate of compliance for the material and finish requirements described in this specification.

4.2.2.1 In-process inspection. Inspection shall be made during the manufacture of the end item to ascertain that the following operation is performed as specified herein. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection has indicated nonconformance.

Operation or assembly	Requirement paragraph
Treatment of metal parts prior to painting	3.6

4.2.3 Examination of the end item. The end item shall be examined for the defects listed in 4.2.3.1 and 4.2.3.2. The sample unit shall be one completely fabricated beach pole and components.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:14Z
Check the source to verify that this is the current version before use.

4.2.3.1 General defects. General defects shall be classified as follows:

Examine	Defect	Classification Major	Minor
Finish	a. Not enameled where required.	X	
	b. Color of enamel not a close match to Marine Corps Green No. 23.	X	
	c. Enamel is blistered, peeling or flaking.		X
	d. Finish is scratched, scuffed or is otherwise impaired.		X
	e. Foreign matter imbedded.		X
	f. Touchup not neatly accomplished.		X
	g. Hinge strip or bar not cadmium plated.	X	
	h. Wire rope not galvanized.	X	
	i. Attachment hardware not plated as specified.	X	
Material	Component not rabricated of the specified material.	X	
Design	Any characteristic not in accordance with the specified requirements.	X	
Construction & Workmanship	a. Component missing, broken, split or otherwise impaired.	X	
	b. Any component that will not function as intended.	X	
	c. Burr or sharp edge.		X
Riveting	a. Riveting poorly accomplished.		X
	b. Rivet not secure.		X
	c. Rivet not flush where required.		X
Welding	a. Any weld missing.	X	
	b. Weld not type specified.		X
	c. Weld incomplete, porous, cracked or otherwise unsound.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:14Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Assembly	a. Not assembled as specified.	X	
	b. Any component not secure.	X	
	c. Adjustable clamps not located per Drawing No. 71C5045A0000.		X

4.2.3.2 Examination for dimensions. Examination shall be made of a complete pole assembly to determine compliance with the dimensions specified in the specification and on the Drawing Nos. 71C5045A0000 and 71C5045A0001. Any dimension not within the specified tolerance shall be classified as a defect.

4.2.3.3 Inspection levels and AQL's. The inspection levels and AQL's expressed in defects per hundred units(DHU) shall be as follows:

For 4.2.3.1	AQL	Inspection level
Major	4.0 DHU	II of MIL-STD-105
Minor	10.0 DHU	
For 4.2.3.2		
One class	4.0 DHU	S-2

4.2.4 Examination of preparation for delivery requirements. An examination shall be made to determine compliance with packaging, packing and marking requirements of Section 5 of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery, except that it need not be sealed. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 and the AQL shall be 4.0 DHU.

Examine	Defect
Marking	Omitted; incorrect; illegible; of improper size, location or method of application.
Materials	Any component missing. Any component damaged.
Workmanship	Inadequate application of components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:14Z
Check the source to verify that this is the current version before use.

Examine	Defect
Contents	Number per container is more or less than required.
Weight	Gross/net weight exceeds requirements.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. All uncoated metal surfaces of the pole and components shall be coated with a thin film, hard drying preservative conforming to grade 1 of MIL-C-16173. Components shall be secured to the pole, in a manner designed to restrict movement, by use of reinforced pressure sensitive tape conforming to PPP-T-60.

5.1.2 Level C. Beach poles shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level B or C as specified (see 6.2).

5.2.1 Level B. Twenty-four (24) beach poles and components packaged as specified in 5.1 shall be placed in a wooden crate conforming to type II, style A of PPP-C-650. Blocking and bracing of the contents and closure of crate shall be in accordance with the appendix to the crate specification.

5.2.3 Level C. Beach poles and components packaged as specified in 5.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, the interior and exterior containers shall be marked in accordance with the requirements of MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:14Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 68 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

S/N-0102-014-1801 C-25254

Source: https://assist.dla.mil -- Downloaded: 202640-20T21:14Z
Check the source to verify that this is the current version before use.