MIL-S-28982A(MC)
6 MARCH 1991
SUPERSEDING
MIL-S-28982(MC)
14 February 1972

MILITARY SPECIFICATION

STAND, FLAGSTAFF: WOOD

This specification is approved for use by the U.S. Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for one type of flagstaff stand.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

TT-V-121	-	Varnish, Spar, Water resisting
MMM-A-188	-	Adhesive, Urea-resin type (Liquid And Powder)
PPP-B-636	-	Box, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to the Commanding General (PSE-C), Marine Corps Research, Development, and Acquisition Command, Washington, DC 20380, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC-NA FSC 8345

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:13Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures And Tables For Inspection By Attributes.
MIL-STD-129	- Marking For Shipment And Storage

DRAWINGS

MARINE CORPS

71C5035A0000	- Stand, Flagstaff: Wood

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robins Avenue, Philadelphia, PA 19111-5094)

2.1.2 Other Government documents and publications. The following other Government documents and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

LAWS AND REGULATIONS
U.S. Postal Service Manual

(Application for copies of the manual should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.)

2.2 Non-government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

UNIFORM CLASSIFICATION COMMITTEE, AGENT
Uniform Freight Classification Rules

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT
National Motor Freight Classification

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:13Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P. Street, N.W., Washington, D. C. 20026.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard samples. Standard samples are furnished solely for guidance and information to the contractor (see 6.3). Variation from this specification may appear in the standard sample, in which case, the specification shall govern.

3.2 First article. Unless otherwise specified (see 6.2), before production is commenced, a finished stand shall be submitted, or made available to the contracting officer or his authorized representative for approval. The approval of the first article authorizes the commencement of production but does not relieve the contractor of responsibility for compliance with all applicable provisions of the specification. The first article shall be manufactured by the contractor in the same facilities to be used for the manufacture of the production items.

3.3 Materials.

3.3.1 Wood. All wood used for the stand shall be plain sawed hardwood oak, dried to moisture content of 6 to 10 percent at time of assembly. The wood pieces shall be sound, free from knots, decay, checks and cross grain, or any other fabricating defects affecting strength, wear or finish.

3.3.2 Adhesive. The adhesive shall conform to type III of MMM-A-188.

3.3.3 Varnish. The varnish shall conform to TT-V-121.

3.4 Design. The stand shall be the U. S. Marine Corps design shown on Drawing No. 71C5035A0000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:13Z
Check the source to verify that this is the current version before use.

3.5 Construction. The construction shall conform in all respects to Drawing No. 71C5035A0000 and as specified herein.

3.5.1 Fabrication. The stand shall be fabricated of hardwood specified in 3.3.1. Each wood piece shall be completely machined including properly fitted mortise and tenon; exposed wood shall be sanded smooth and sharp edges shall be broken.

3.5.2 Gluing. All gluing shall be done with the adhesive specified in 3.3.2. Adhesive shall be applied to the mating surface in an adequate and uniform manner as recommended by the glue manufacturer. Assembly periods and clamping or pressing time shall be in accordance with the glue manufacturer's instructions.

3.5.3 Finish. All exposed surfaces of the stand shall have two coats of varnish conforming to 3.3.3. The first coat of varnish shall be thoroughly dried and lightly sanded before application of the second coat of varnish.

3.6 Finished measurements. The finished flagstaff stand shall conform to the measurements shown in Drawing No. 71C5035A0000.

3.7 Marking. Each stand shall have an adhesive label placed on the side of one leg containing the following information:

NSN_____
Contractor_____
Contract No._____

3.8 Workmanship. The finished stands shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels (AQL).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all

Source: https://assist.dla.mil -- Downloaded: 202610-20T21:13Z
Check the source to verify that this is the currentversion before use.

requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Certificate of compliance. Where certificates of compliance are permitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.3 Inspection conditions. Unless otherwise specified all inspections shall be in accordance with the provisions set forth in MIL-STD-105.

4.4 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.5.3.2 and 4.5.3.3. The presence of any defect or failure to pass any test shall be cause for rejection of the first article. The number of units to be inspected shall be specified by the contracting officer (see 6.4).

4.5 Quality Conformance Inspection.

4.5.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be tested in accordance with all requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document. The following component may be accepted on the basis of a contractor's certification of compliance for requirements specified.

Source: https://assist.dla.mil -- Downloaded: 20260-20T21:13Z
Check the source to verify that this is the current version before use.

Component	Characteristic	Requirement paragraph
Adhesive	Assembly, gluing period, clamping, pressing and pressure	3.5.2

4.5.1.1 In-process inspection. Inspection shall be made during the manufacturing process for conformance to the following processes. Whenever nonconformance is noted, correction shall be made to affected items and process. The Government reserves the right to exclude from consideration for acceptance any material for which in-process inspection has indicated nonconformance.

Process	Requirement paragraph
Proper fitting of mortise and tenon	3.5.1
Sanding before application of second coat of varnish	3.5.3

4.5.2 Intermediate testing. Testing of the partially fabricated stand shall be performed in accordance with Table I for the characteristic shown therein. The sample unit shall be one of each component after all milling operations are completed, prior to gluing and varnishing. The requirement is applicable to the individual unit. The inspection level shall be S-1 (see 6.5).

Table I Test Method

Characteristic	Rqmt para	Test method	No. Determinations per sample unit	Results reported as
Moisture content	3.3.1	Std. Comm'l	3	Avg of 3 determinations to nearest 1%

4.5.3 Examination of end item. The end item shall be examined for defects listed in 4.5.3.2 and 4.5.3.3. The sample unit shall be one stand. The inspection level shall be II (see 6.5).

4.5.3.1 Classification of defects. All defects shall be classified as indicated below except those numbered 1 thru 8 in the classification column which shall be classified as:

Major defect - When seriously affecting appearance or serviceability.

Minor defect - When affecting appearance or serviceability, but not seriously.

4.5.3.2 General defects. General defects shall be classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:13Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Critical	Major	Minor
Finish	Not finished or finish is not clear varnish.		101	
	Finish not level and uniform, e.g., contains runs, drop, Sag, or check.	1		
	Varnish not adherent, e.g., is blistered, flaking or peeling.	2		
	Area of no film.		102	
	Area of thin film.			201
	Foreign matter embedded.	3		
	Scratch, gouge or dig.	4		
	Surface not sanded smooth.			202
Quality of wood	Not species specified.		103	
	Not plainsawed or flat grained.			203
	Any loose, unsound knot or hole (except where specified).		104	
	Sound tight knot more than 1/2 inch in greatest dimension		105	
	Sound tight knot 1/2 inch or less in greatest dimension.			204
	Decay or rot, split, check, compression wood, loosened grain, cross break, collapse, gum pocket, or other imperfection.		106	
	Irregularity of grain (cross grain) except birdseye, sound burl or swirl.	5		

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:13Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Critical	Major	Minor
	Any nonpermissible defect filled with plastic wood or other filler material.		107	
Construction and workmanship	Not specified design.		108	
	Direction of grain not as specified.	6		
	Evidence that hole is not counter-bored.		109	
	Machine mark.	7		
	Glue joint open more than 1/16 inch.		110	
	Glue joint open less than 1/16 inch.			205
	Excess glue on outside surface.	8		
	Sharp edge or corner not broken.			206
	Bearing surface not level e.g., stand rocks more than 1/32 inch when placed on a flat surface.	9		
	Splinter.			207

4.5.3.3 Examination of stand for defects in dimensions. Any dimension that is not within the tolerance specified in Drawing No. 71C5035A0000 shall be classified as a defect. The inspection level shall be S-3 (see 6.5).

4.5.4 Examination of preparation for delivery requirements. An examination shall be made to determine compliance with packaging, packing, and marking requirements of Section 5 of this specification. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection

Source: https://assist.dla.mil -- Downloaded: 2026l0-20T21:13Z
Check the source to verify that this is the currentversion before use.

lot. The inspection level shall be S-2 (see 6.5).

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, or improper size, location, sequence or method of application.
Materials	Any component missing, any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of case liners, container flaps, loose strapping, inadequate stapling. Bulging or distortion of containers.
Weight or content	Number per container is more or less than required; gross/net weight exceeds requirements.

5. PACKAGING

5.1 Packaging. Packaging shall be level A, B, or Commercial as specified (see 6.2).

5.1.1 Level A. Each stand shall be suitably cushioned and individually packaged in a snug fitting fiberboard box conforming to style RSC, grade V3C or V35, class weather-resistant of PPP-B-636; closure shall be in accordance with the appendix thereto.

5.1.2 Level B. Each stand shall be suitably cushioned and individually packaged in a snug fitting fiberboard box conforming to style RSC, type CF or SF, class domestic, grade 275 of PPP-B-636; closure shall be in accordance with the appendix thereto.

5.1.3 Commercial. Stand shall be packaged in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.2 Packing. No packing required.

5.3 Marking. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:13Z
Check the source to verify that this is the current version before use.

6. NOTES
(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The stand is intended for use as a flagstaff support.

6.2 Acquisition requirements.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number and date of this specification.
(b) Whether first article is required (see 3.2).
(c) Number of stands in first article (see 3.2).
(d) Selection of applicable levels of packaging (see 5.1).
(e) Acceptance criteria (see 6.5).

6.3 Standard samples. For information regarding the availability of sample of the stand specified, address inquiry to the acquisition activity issuing the invitation for bids (see 3.1).

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.5 Acceptance criteria. The acceptance criteria below are recommended for use. The acceptance criteria as specified in the contract or purchase order shall be binding. Unless otherwise specified, the following acceptance criteria are in accordance with MIL-STD-105.

6.5.1 For end item visual examination. An AQL, expressed in terms of defects per hundred units, of 2.5 for major defects and 10.0 for total (major and minor combined) defects is recommended.

6.5.2 For end item dimensional examination. An AQL, expressed in terms of defects per hundred units, of 4.0 is recommended.

6.5.3 For packaging examination. An AQL, expressed in terms of defects per hundred units, of 4.0 is recommended.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:13Z
Check the source to verify that this is the current version before use.

6.5.4 For intermediate testing. An AQL, expressed in terms of defects per hundred units, of 6.5 is recommended.

6.6 Subject (key word) listing.
Flag
Holder

6.7 Changes from previous issue. Asterisk are not used in this revision to identify changes with respect to the previous issue, due to extensive changes.

Preparing activity:
Navy - MC
Project No. 8345-N190

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T21:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-S-28982A(MC)	6 MARCH 1991

3. DOCUMENT TITLE

STAND, FLAGSTAFF: WOOD

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	e. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
Commanding General, Marine Corps Research, Development, and Acquisition Command (PSE-C)	(1) Commercial (202) 696-1186/87/88	(2) AUTOVON 226-1186/87/88
ADDRESS (Include Zip Code) Washington, DC 20380-0001	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026\10-20T21:13Z
Check the source to verify that this is the current version before use.