MILITARY SPECIFICATION

DETONATION, SIMULATOR, EXPLOSIVE, M80 LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not covered by t e drawings and provides quality assurance provisions for the fabrication of parts, assembly and packing for M80 Explosive Detonation Simulator.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes

FSC 1370

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests For

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.5)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

PRODUCT PACKAGING DRAWINGS

9234991 - Detonation Simulator, Explosive, M80
8853677 - Box, Paperboard, Packing Ammunition for Detonation Simulator, Explosive, M80
8853678 - Box, packing, Ammunition for Detonation Simulator, Explosive, M80

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assembly. The assembly shall comply with all requirements specified on Drawing (dwg.) 9234991 and with all requirements specified on applicable specifications.

3.3 Moisture content.

3.3.1 Charge composition. The moisture content of the charge composition at the loading station at the time of loading the assembly shall not be more than 0.50 percent when tested in accordance with paragraph 4.4.3.1.

3.3.2 Paper and paper products. The moisture content of the paper and paper products at the loading station at the time of loading shall be not more than 6.0 percent.

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:56Z
Check the source to verify that this is the current version before use.

3.4 Functioning. The assembly shall function and comply with the following requirements.

3.4.1 Premature. The assembly shall not function in less than three (3) seconds after initiation of the fuse.

3.4.2 Sound level intensity. The assembly shall produce a peak sound level intensity of 105 decibels minimum (min.).

3.5 Sensitivity. The assembly shall show no evidence of ignition or detonation when subjected to a weight of not less than five (5) pounds dropped from a height of two (2) feet, min. when tested as specified in 4.5.3.

3.6 Jumble test. The assembly shall show no evidence of loose powder and shall comply with the requirements of MIL-STD-331, Test 102.

3.7 Quick leak test. The packed box sealed in the barrier bag shall show no evidence of air or water leakage when tested as specified in 4.5.6.

3.8 First article inspection. This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.9 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of tears, fractures and foreign matter. All required markings shall be neat and sharply defined. All parts shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the sample quantities as indicated in Table 1..

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-20505D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Detonation, Simulator, Explosive, M80				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Tube, Outer (Dwg. 9234994)				
	Examination for defects	50		3.2	4.4.2.1
	Tube, Inner (Dwg. 9234995)				
	Examination for defects	50		3.2	4.4.2.2
	Body Assembly (Dwg. 9234993)				
	Examination for defects	50		3.2	4.4.2.3
	Assembly (Dwg. 9234991)				
	Examination for defects	50		3.2	4.4.2.4
	Sensitivity	5		3.5	4.4.3.3
	Jumble	5 Box		3.6	4.4.3.4
	Functioning	45	1-2	3.4	4.4.3.5

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-20505D(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
	Detonation, Simulator, Explosive, M80				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Box, Prior to Packing into Barrier Bag (Dwg. 8853677)				
	Examination for defects			3.2	4.4.2.5
	Sealed Packed Barrier Bag, Prior to Packing into Box (Dwg. 8853677)				
	Examination for defects			3.2	4.4.2.6
	Sealed Wooden Packing Box (Dwg. 8853678)				
	Examination for defects			3.2	4.4.2.7

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-01-19T07:56Z
Check the source to verify that this is the current version before use.

4. Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-20505D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9234995
4.4.2.1	Inner Tube				NEXT HIGHER ASSEMBLY 9234993
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Outside diameter		0.40%	3.2	Gage
Minor					
201	Inside diameter		0.65%	3.2	Gage
202	Total length		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 20260-19T07:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-20505D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Tube, Outer				9234994
					NEXT HIGHER ASSEMBLY
					9234993
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Total length		0.65%	3.2	Gage
203	Evidence of poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-10-19T07:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-20505D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Body Assembly				9234993
					NEXT HIGHER ASSEMBLY
					9234991
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length		0.40%	3.2	Gage
Minor					
201	Crimp length		0.65%	3.2	Gage
202	Parts missing or not in place		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil - Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-20505D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Assembly				9234991
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Charge on exterior surface, charge leaking or opening through which charge may leak		100%	3.2	Visual
Major					
101	Any opening in assembly that is leaking or may leak		0.40%	3.2	Visual/Manual
102	Disc not sealed 360 degrees		0.40%	3.2	Visual
103	Fuse not sealed 360 degrees		0.40%	3.2	Visual
Minor					
201	Length, max.		0.65%	3.2	Gage
202	Assembly crushed or otherwise damaged		0.65%	3.2	Visual
203	Marking misleading or unidentifiable		0.65%	3.2	Visual
204	Fuse improperly positioned		0.65%	3.2	Visual
205	Fuse not completely sealed (can be moved by light finger pressure)		0.65%	3.2	Visual/Manual
206	Evidence of poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 20202610-19T07:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-20505D(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.5	Box, Prior to Packing Into Barrier Bag	1	1	8853677
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box punctured, cut or torn in any area		0.40%	3.2	Visual
102	Box filler or simulator obviously wet or damp		0.40%	3.2	Visual
Minor					
201	Any packing material missing		0.65%	3.2	Visual
202	Incorrect number of assemblies in box		0.65%	3.2	Visual
203	Corners not blunted		0.65%	3.2	Visual
204	Marking of box missing or unidentifiable		0.65%	3.2	Visual
205	Evidence of poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil - Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-20505D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Sealed Packed Barrier Bag, Prior to Packing Into Box				8853677
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Waterproofness of bag destroyed by rupture, puncture or separation of heat seal		0.40%	3.2	Visual
102	Bag contains excess air		0.40%	3.2	Visual/Manual
Minor					
201	Heat seal of bag located so that two subsequent seals cannot be applied		0.65%	3.2	Visual
202	Marking of bag misleading or unidentifiable		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2024-10-19T07:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-20505D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Sealed Wooden Packing Box				8853678
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged to extent that contents are exposed or liable to become exposed		0.40%	3.2	Visual
102	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
103	DOT symbol misleading or unidentifiable		0.40%	3.2	Visual
Minor					
201	Hardware improperly engaged		0.65%	3.2	Visual
202	Strapping improperly assembled		0.65%	3.2	Visual
203	Car seal unsealed or incorrectly positioned		0.65%	3.2	Visual
204	Marking misleading or unidentifiable		0.65%	3.2	Visual
205	Contents loose		0.65%	3.2	Manual
206	Fillers missing between bag and box		0.65%	3.2	Visual
207	Evidence of poor workmanship		1.0%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. The jumble test and functioning tests specified herein shall be performed at an authorized test facility.

PRECAUTION. The composition charge is extremely sensitive to initiation by friction, impact and static electricity. Take appropriate precautions in all handling, processing and storage involving this composition.

4.4.3.1 Moisture content.

4.4.3.1.1 Charge composition. (See 3.3.1) Major Defect - Paper and Paper Products (see 3.3.2) Major Defect. The contractor shall provide adequate controls to assure that the materials comply with the applicable requirements. For verification, the contractor shall select and subject to test one sample of each material from each eight (8) hours production. A composite sample shall not be used. If the moisture content of a sample exceeds the requirements and loading has not begun, the material represented by the sample shall be rrejected. If components have been loaded with a material containing excessive moisture, the loaded components shall be rejected. The determination shall be as specified in 4.5.1.1. Since blending of the charge composition is accomplished in the simulator, a sample of sufficient size shall be taken from a “dummy” body used in conjunction with the loading of the simulators for determination of moisture.

4.4.3.1.2 Complete assembly. (See Dwg. 9234991) - Major Defect. A sample of 50 assemblies shall be selected from each lot for this determination. If one or more assemblies fail to comply with the requirement specified, the lot shall be rejected. The determination shall be as specified in 4.5.1.3.

4.4.3.2 Charge composition analysis. (See Dwg. 9234992) - Major Defect. This determination shall be conducted on the same sample selected for determination of moisture content. If the sample fails to comply with the requirements specified, the lot shall be rejected. The determination shall be as specified in 4.5.2.

4.4.3.3 Sensitivity. (See 3.5) - Major Defect. A sample of five (5) assemblies shall be selected from each lot for this test. If any assembly fails to comply with the requirement specified, the lot shall be rejected. The test shall be performed as specified in 4.5.3.

4.4.3.4 Jumble test. (See 3.6) - Critical Defect. A sample of five (5) boxes of 50 each simulators, packed and sealed in accordance with the instructions detailed on Dwg. 8853677, shall be selected for this test and each sealed package of 50 simulators tested individually. Following testing, each carton shall be opened and the contents examined. The lot shall be rejected if any simulator fails to comply with the requirements. The test shall be performed as specified in 4.5.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

4.4.3.5 Functioning. The simulator assemblies shall be observed for any evidence of failures to comply with the requirements as classified in Table II.

TABLE II

Defect	Classification
Premature (see 3.4.1)	Critical
Sound Level Intensity (see 3.4.2)	Major
Fuse Burning Time of less than four but more than three seconds (see dwg. 9234991)	Major
Fuse Burning Time of more than seven seconds (see dwg. 9234991)	Major

4.4.3.5.1 First three lots. Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, 125 assemblies-shall be selected from each lot for this test. If, during the test, any assembly exhibits a Critical defect or four (4) or more Major Defects are encountered, the lot shall be rejected. The test shall be performed as specified in 4.5.5.

4.4.3.5.2 After three consecutive lots. After three consecutive lots have complied with the criteria of 4.4.3.5.1, a sample of 50 assemblies shall be selected from each lot for this test. If, during the test, any assembly exhibits a Critical Defect or three (3) or more Major Defects are encountered, the lot shall be rejected.

4.4.3.6 Quick leak test of sealed barrier bag. Major Defect. Ten (10) boxes in sealed barrier bags shall be selected from each lot for this test. If two or more packages show evidence of air leakage during test or water leakage when package is opened, the lot shall be rejected. The test shall be performed as specified in 4.5.6.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the “Method of Inspection” headings in 4.4.2 and in the procedures in 4.5 (see 6.3).

4.5 Method of inspection.

4.5.1 Moisture content.

4.5.1.1 Moisture content of charge composition. An accurately weighed portion of three (3) grams (g.) of the charge composition shall be transferred to a tared moisture dish, The moisture dish and

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

contents shall be placed in a drying oven at 110 ± 5° Centigrade (C) for one hour, cooled in a desiccator and weighed. The Percentage of moisture in the sample shall be calculated as follows:

$$\text{Percentage of Moisture} = \frac{100A}{W}$$

where:
A = Loss in weight of moisture dish and contents.
w = Weight of sample, g.

4.5.1.2 Paper, paper products and carton packing material. Determine moisture content in accordance with Method 102.1 of Standard MIL-STD-1234 except that a ten (10) gram sample shall be used and the drying time shall be two (2) hours.

4.5.1.3 Moisture content of complete assembly. The complete assembly shall be accurately weighed. After weighing, the assembly shall be placed in a drying oven at 100 ± 5°C for three (3) hours, cooled in a desiccator and reweighed. The percentage of moisture in the assembly shall be calculated as follows:

$$\text{Percentage of Moisture} = \frac{100A}{W}$$

where:
A = Loss in weight of assembly, g.
w = Weight of sample, go

4.5.2 Charge composition analysis

4.5.2.1 Sulfur. The sample from the moisture determination shall be quantitatively transferred to a 250 milliliter (mL.) beaker, with the aid of 50 mL. of carbon disulfide. The solvent mixture shall be boiled and decanted through a tared filtering crucible leaving as much residue as possible in the beaker. The extraction shall be repeated twice, using 50 mL. of fresh solvent each time. On the third extraction, the residue shall be quantitatively transferred to the filtering crucible. Suction shall be applied for 15 minutes at 60°C ± 5° then cooled in a desiccator and weighed. The loss in weight shall be calculated as the percentage of sulfur in the sample.

4.5.2.2 Potassium perchlorate. The residue in the crucible from the sulfur determination shall be extracted with 100 mL. of boiling distilled water in small 20 mL. portions. The water shall stand in the crucible for approximately one minute before applying suction. The extraction shall be repeated until the filtrate shows no trace of perchlorates. Test for complete extraction of potassium perchlorate shall be accomplished by treating a few drops of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

filtrate on a white spot plate with a few drops of a one percent diphenylamine solution in concentrated sulfuric acid. If the filtrate on spot plate turns blue, perchlorates are present and additional washings are required. The crucible shall be dried for one hour at 100 ± 5°C, cooled in a desiccator and weighed. The loss in weight shall be calculated as the percentage of potassium perchlorate in the sample.

4.5.2.3 Aluminum. The aluminum in the sample shall be calculated by difference as follows:

$$\text{Percent Aluminum} = 100 - (P + S)$$

where:
S = Percentage of sulfur in sample
P = Percentage of potassium perchlorate in sample

4.5.3 Sensitivity. The simulator shall be placed on its side on a solid support. A suitable weight weighing not less than five (5) pounds shall be dropped a minimum distance of two (2) feet in such a manner that the weight shall be flat and shall be of such proportions that an edge does not strike the simulator. If any simulator fails to conform to the applicable requirement, it shall be classed defective. (Destructive test).

4.5.4 Jumble test. Each sealed package of 50 simulators shall be tested separately, and testing shall be in accordance with MIL-STD-331 except that the duration of test shall be 20 minutes. There shall be no bracing or blocking of the sealed package within the woodlined jumble box during test, i.e., nothing but the sealed package of 50 simulators shall be inside the jumble box during testing. Observation shall be made for conformance with the applicable requirement. (Destructive test).

4.5.5 Functioning. The simulator assembly shall be placed on a solid support and the fuse ignited. Observation shall be made for compliance with the requirements specified. The instrument used to measure the sound level intensity shall be located 75 ± .5 feet from the simulator support. Burning time from initiation to explosion of simulator shall be measured from the first spit of the fuse to the explosion.

4.5.6 Quick leak test (Vacuum Differential Method). The filled and sealed packages, after conditioning at ambient temperature (70 ± 5°F) for at least four (4) hours, shall be tested for leakage by submerging in water contained in a vacuum vessel. A vacuum differential of 216MM (8 1/2 inches) of mercury from ambient conditions shall be drawn and held for 30 seconds (min.) while observing for leakage of air. A steady stream or recurring

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

succession of bubbles from any surface or seam shall be cause for rejection. Where there is no emission of bubbles observed, the package shall be dried, opened and inspected. Evidence of water within the barrier, or on the box, shall also be cause for rejection. (Non-destructive test).

5. PACKAGING

5.1 Preservation and Packaging

5.1.1 Level A. The detonation simulator assemblies shall be preserved and packaged in accordance with dwg. 8853677.

5.2 Packing

5.2.1 Level A. The detonation simulator assemblies shall be packed in accordance with dwg. 8853678.

5.3 Marking. Marking shall be as specified on dwg. 8853677 and 8853678.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the Detonation, Simulator, Explosive, M80.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required, to Commander, US Army Armament Research and Development Center, ATTN: DRSMC-QAT-I, Dover, New Jersey 07801.

6.4 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, US Army Armament Research and Development Center, ATTN: DRSMC-QAT-M, Dover, New Jersey 07801.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, or ARRADCOM drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

6.6 Lot Acceptance Test Summary

PRODUCTION LOTS

Tests	First Three Consecutive Acceptable	Remaining	Requirements
Jumble	250		See 3.6
Functioning	125		See 3.4

6.7 Changes from Previous Issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1370-A159)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research &
Development Center
ATTN: DRSMC-QA
Dover, NJ 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-20505D (AR)	Detonation, Simulator, Explosive M80 LAP

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202640-19T07:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:56Z
Check the source to verify that this is the current version before use.