INCH-POUND

MIL-DTL-25708/2C
28 May 2008
SUPERSEDING
MIL-DTL-25708/2B (USAF)
23 July 1999

DETAIL SPECIFICATION SHEET

ANTENNA, BLADE, AS-2685/A

This specification is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the antenna described herein shall consist of this document and the latest issue of MIL-DTL-25708.



FIGURE 1. Outline drawing antenna AS-2685/A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:07Z
Check the source to verify that this is the current version before use.

Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A	.480	.500	12.19	12.90
B	.970	.990	24.64	25.15
C	.84	.90	21.3	22.9
D	1.72	1.78	43.7	45.2
E	1.78	1.82	45.2	46.2
F	2.59	2.65	65.8	67.3
G	3.590	3.610	91.19	91.69
H	5.22	5.28	132.6	134.1
J	.06 R ref		1.5 R ref	
K	.190 DIA	.202 DIA	4.83 DIA	5.13 DIA
L	---	2.00	---	50.8
M	---	1.00	---	25.4
N	.31 R ref		7.9 R ref	
P	---	3.32	---	84.3
Q	.06 R	.09 R	1.5 R	2.3 R
R	---	.534	---	13.56
S	.414	---	10.52	---
T	---	.598	---	15.19
U	1.11	1.15	28.2	29.2
V	---	1.75	---	44.4
W	---	3.75	---	95.25
X	---	.60	---	15.2
Y	.35	---	8.9	---
Z	---	.22	---	5.6
AA	---	.44	---	11.2
AB	.50 R ref		12.7 R ref	
AC	.120	.150	3.05	3.81

NOTES:

1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are upon 1 inch = 25.4 mm.
3. Unless otherwise specified tolerances on two place decimals are ± .01 inch and tolerances on three place decimals are ± .005 inch.

FIGURE 1. Outline drawing antenna AS-2685/A - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:07Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Materials:

Base: Aluminum alloy in accordance with ASTM B85, alloy SC84B.

Cover: Metal or other suitable material.

Temperature operating range: -55°C to 250°C.

Side loading: 10.5 psig (100 pounds).

Frequency: 960 to 1,220 MHz.

Impedance: 50 ohms nominal.

VSWR:

Antenna: 1.4:1 maximum from 960 to 1,220 MHz.
1.3:1 maximum from 1,000 to 1,100 MHz.

Sampling probe: 1.5:1 maximum from 960 to 1,220 MHz.

Power: 4 kW peak, 100 watts average.

Weight: 8 ounces.

Part or Identifying Number (PIN): M25708/2-02.

Data list: A data list shall accompany each antenna with VSWR measurement.
Values made at 960, 1,100, and 1,200 MHz.

Intended for use on F-4 aircraft.

Referenced documents. In addition to MIL-DTL-25708, this document references the following:
ASTM B85

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - AV
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Air Force - 99

(Project 5985-2008-019)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil/

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T07:07Z
Check the source to verify that this is the current version before use.